

Detectable Warning Tape Product Specifications

Product Type

Detectable Warning Tape

Description

Detectable warning tape provides for easy buried pipeline detection and below ground identification and warning. The tape can be located below ground with a non-ferrous metal locator/detector when buried at the proper depths. We recommend bury depths

•	Tape Width	<u>2"</u>	<u>3"</u>	<u>6"</u>
	Burial Depth	6" - 18"	6" - 28"	6" - 36"

Standard Widths

• 2", 3", 6", 12"

Standard Length

• 1000'

Physical Properties

Elongation: 80% MD and 135% TD

.0020 aluminum core adhered to 2.55 polyethylene backing

Tape color and legend combination are in accordance with APWA requirements

Tensile Strength: 7,800 PSI

Made in USA

Tape printing beneath top protective layer

Thickness: 5 mil nominal

Ultra high molecular weight

100% virgin polyethylene

Alkaline and corrosion resistant

Heavy metal free

APWA color coded

Packaging

2" - 12 rolls per case

3" - 8 rolls per case

6" – 4 rolls per case

12"- 2 rolls per case

Legends

•	Blue	Caution Buried Water Line Below	
•	Blue	Caution Buried Geothermal Line Below	
•	Brown	Caution Buried Non-Potable Water Line Belov	
•	Green	Caution Buried Sewer Line Below	
•	Orange	Caution Buried Fiber Optic Line Below	
•	Orange	Caution Buried Telephone Line Below	
•	Red	Caution Buried Electric Line Below	
•	Red	Caution Buried High Voltage Cable Below	
•	Yellow	Caution Buried Gas Line Below	
•	Purple	Caution Buried Reclaimed Water Line Below	