



Continental Copper Tracer Wire




Our Continental tracer wire brand is designed to perform in harsh environments where protection from sharp, abrasive, and corrosive soil conditions is important. Our solid copper tracer wire is manufactured from a soft drawn copper conductor in **12 or 10 AWG** with a **HMWPE .045 mil jacket**. This solid copper construction offers the ease of workability while combining the strength of a quality HMWPE jacket. Further, our solid copper wire performs reliably in field applications where signal strength and locating accuracy are critical. Choose the Continental tracer wire brand for your tracer wire needs!

Features

- Meets UL 1581 and ASTM D-1248
- Highest copper tracer wire break load available.
- Superior tracing performance.
- Available in **500'** and **2500'** spools.
- Made in America

CONDUCTOR SIZE	12 AWG Copper	10 AWG Copper
ITEM NUMBER	33-7728-00	33-7943-01
STRANDING	Solid	Solid
INSULATING MATERIAL	HMWPE	HMWPE
INSULATING THICKNESS	0.045" Nominal	0.045" Nominal
FINISHED O.D.	0.172" Nominal	0.194" Nominal
WEIGHT (PER 1000 FT.)	26.97 lbs./1000	39.95 lbs/1000
TEMPERATURE RATING	-20°C to 80°C	-20°C to 80°C
OPERATING VOLTAGE	600v	600v
INSULATION COLOR	Yellow-Gas	Yellow-Gas

Other insulating colors are available; Blue, Red and Green.



The Ultimate Connection



1-800-558-1373 or FAX 1-800-788-1668 • Visit www.conind.com