

RESIDENTIAL LOTS = 148

FISCHER GARDENS UNIT 2 BEXAR COUNTY, TX STREET, DRAINAGE, WATER, SANITARY SEWER, AND UTILITY IMPROVEMENTS



LOCATION MAP NOT-TO-SCALE

SA GIVEN TO FLY, LLC 6812 WEST AVENUE, SUITE 100 SAN ANTONIO, TX 78213 PHONE: 210-701-8337

COVER SI
OVERALL
OVERALL
MASTERI
OVERALI
OVERALI
DRAIN C
BALSA GA
ASH GARI
WILLOW F
MAPLE LI
CHERRY F
TYPICAL S
CONCRET
WHEELCH
TXDOT PE
TRAFFIC S
ACCESS F
TRAFFIC S
ACCESS F
TRAFFIC S
PLANS DE
SANITARY
PLANS DE SANITARY OVERALL
PLANS DE SANITARY OVERALL OVERALL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'G' PL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'G' PL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'G' PL LINE 'H' PL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'G' PL LINE 'I' PL
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'I' PL LINE 'I' PL SANITARY
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'I' PL LINE 'I' PL SANITARY
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'I' PL LINE 'I' PL SANITARY WATER IN
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'I' PL LINE 'I' PL SANITARY WATER IM WATER D
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'I' PL LINE 'I' PL SANITARY WATER IM WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY WATER IM WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER IN WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI
PLAINS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'H' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI STORMW/ PLAN (SH
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI STORMWA PLAN (SH
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI STORMWA PLAN (SHI STORMWA
PLANS DE SANITARY OVERALL OVERALL LINE 'F' PL LINE 'F' PL LINE 'I' PL SANITARY SANITARY WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI WATER DI STORMWA PLAN (SH STORMWA PLAN (SH

INDEX	
SHEET TITLE	SHEET NUMBER
EET	1.1
ITILITY PLAN (SHEET 1 OF 2)	2.1
ITILITY PLAN (SHEET 2 OF 2)	2.2
RAINAGE PLAN	3.1
GRADING PLAN (SHEET 1 OF 2)	4.1
GRADING PLAN (SHEET 2 OF 2)	4.2
PLAN AND PROFILE	5.1
PLAN AND PROFILE	5.2
PLAN AND PROFILE	5.3
RDENS PLAN & PROFILE	6.1
ENS PLAN & PROFILE	6.2
ATS PLAN & PROFILE	6.3
Y PLAN & PROFILE	6.4
OSE PLAN & PROFILE	6.5
TREET DETAILS	6.6
E DRIVEWAY DETAILS	6.7
NR RAMP DETAILS	6.8
D-18 DETAILS	6.9
GNAGE AND PEDESTRIAN	6.10
LAN (SHEET 1 OF 2)	
GNAGE AND PEDESTRIAN LAN (SHEET 2 OF 2)	6.11
GNAGE & PEDESTRIAN ACCESS TAILS	6.12
SEWER COVER SHEET	7.1
SEWER PLAN (SHEET 1 OF 2)	7.2
SEWER PLAN (SHEET 2 OF 2)	7.3
AN & PROFILE	7.4
AN & PROFILE	7.5
AN & PROFILE	7.6
N & PROFILE (SHEET 1 OF 2)	7.7
N & PROFILE (SHEET 2 OF 2)	7.8
SEWER NOTES	7.9
SEWER DETAILS	7.10
PROVEMENTS COVER SHEET	8.1
TRIBUTION PLAN (SHEET 1 OF 2)	8.2
TRIBUTION PLAN (SHEET 2 OF 2)	8.3
TAILS (SHEET 1 OF 5)	8.4
TAILS (SHEET 2 OF 5)	8.5
TAILS (SHEET 3 OF 5)	8.6
TAILS (SHEET 4 OF 5)	8.7
TAILS (SHEET 5 OF 5)	8.8
<i>TER POLLUTION PREVENTION ET 1 OF 2)</i>	9.1
TER POLLUTION PREVENTION ET 2 OF 2)	9.2
TER POLLUTION PROTECTION	9.3

	olliers							
Engi & [www.colliers	neering Design sengineering.com							
Copyright © 2024. Colliers Enginee and all the information contained he whom the services were contracted be copied, reused, disclosed, distr without the express written of	ring & Design All Rights Reserved. This drawing erein is authorized for use only by the party for or to whom it is certified. This drawing may not ibuted or relied upon for any other purpose consent of Colliers Engineering & Design.							
Formerly Known as								
Testinenspore	PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE							
FOR STATE SPECIFIC VISIT: WW	CORECT PHONE NUMBERS							
BY DESCRIPTION								
DRAWN								
DATE								
L L L L L L L L L L L L L L L L L L L								
CLAYTO CLAYTO T CLAYTO T CLAYTO CLAYTO TEXAS LICENSED P LICENSE N COLLIERS ENGIN TBPE Firm#: F-14909	DN J. LINNEY 11543 CENSE ^D NAL NAL NAL NOT NAL NOT NOT NOT NOT NOT NOT NOT NOT							
PREL	IMINARY FOR							
FISCHER UI PLAT #2	R GARDENS NIT 2 4-11800144							
SAN A BEXAR T	ANTONIO R COUNTY EXAS							
Colliers Engineering & Design	SAN ANTONIO (KFW) 3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 TBPLS Firm#: 10194550							
SCALE: DATE: PROJECT NUMBER: DR.	DRAWN BY: CHECKED BY: MS CG AWING NAME:							
SHEET TITLE:	ER SHEET							
SHEET NUMBER:	1.1							



KFW

1020

3421 Paesanos

Parkway

TBPE Firm#: F-14909 TBPLS Firm#: 10194550

HECKED BY

RAWN BY:

MS



* SEPARATION DISTANCE TO AND 290.44(e)

///PROPOSED SANITARY SEWER LINE ______



Colli Enginee & Des	ers ering ign									
www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.										
Formerly Known as										
EOR STATE SPECIFIC DIREC	PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE									
VISIT: WWW.CAI	LB11.COM									
DATE DRAWN BY DESCRIPTION Image:										
REV										
CLAYTON J. CLAYTON J. 11154 CCENS CCENS CONAL CCENS CONAL SICENSE COLLIENSED PROFES LICENSE NUMBE COLLIERS ENGINEERIN TBPE Firm#: F-14909 - T	LINNEY 3 9 10 10 10 10 10 10 10 10 10 10 10 10 10									
PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144 SAN ANTONIO										
	AS									
Colliers Engineering & Design SCALE:	N ANTONIO (KFW) 3421 Paesanos Parkway a Antonio, TX 78231 hone: 210.979.8444 S ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 TBPLS Firm#: 10194550 AWN BY: CHECKED PY:									
PROJECT NUMBER: DRAWING 1	MS CG									
314-60-01 OU314600 SHEET TITLE: OVERALL UTI (SHEET 2	LITY PLAN OF 2)									
SHEET NUMBER:										

Ultimate Cond	litions:												\ \ 	
Study Point	AREA	(Acres)	С	T _{ovrl} (min)	Carryover	T _{sc} (min)	T _{ch} (min)	T _{tot} (min)	l₅(in/hr)	I ₂₅ (in/hr)	I ₁₀₀ (in/hr)	Q_5 (ft ³ /s)	$Q_{25}(ft^{3}/s)$	Q ₁₀₀
OS-1	OS-1, OS-2	20.16	0.70	13.00	-	11.00	5.00	29	3.765	5.189	6.425	53.13	73.23	90
OS-2	OS-2	0.20	0.70	9.00		0.00	0.00	9	6.542	9.166	11.494	0.92	1.28	1
1	DA-1	1.27	0.80	10.00		1.00	2.00	13	5.662	7.888	9.854	5.77	8.04	10
2	DA-2	1.32	0.81	10.00		0.00	2.00	12	5.864	8.186	10.238	6.23	8.70	10
2A	DA-1, DA-2	2.59	0.80	10.00	PT.1	1.00	3.00	14	5.468	7.600	9.480	11.39	15.83	19
3	DA-3	0.22	0.84	7.00		0.00	0.00	7	7.105	9.955	12.488	1.31	1.83	2
ЗA	DA-1, DA-2, DA-3	2.81	0.81	10.00	PT.1	1.00	3.00	14	5.468	7.600	9.480	12.39	17.22	21
4	DA-4	5.14	0.77	10.00		0.00	3.00	13	5.662	7.888	9.854	22.41	31.22	39
5	DA-5	0.06	0.77	5.00		0.00	0.00	5	7.884	11.004	13.785	0.36	0.51	0
5A	DA-4, DA-5	5.20	0.77	10.00	PT.4	0.00	3.00	13	5.662	7.888	9.854	22.67	31.59	39
6	DA-6	7.40	0.77	10.00		1.00	3.00	14	5.468	7.600	9.480	31.16	43.31	54
7	DA-7	0.06	0.77	5.00		0.00	0.00	5	7.884	11.004	13.785	0.36	0.51	0
7A	DA-6, DA-7	7.46	0.77	10.00	PT.6	1.00	3.00	14	5.468	7.600	9.480	31.41	43.66	54
8	DA-8	7.83	0.77	10.00		1.00	3.00	14	5.468	7.600	9.480	32.97	45.82	57
9	DA-10	9.45	0.77	10.00		1.00	3.00	14	5.468	7.600	9.480	39.79	55.30	68
10	DA-10	7.32	0.77	10.00		0.00	3.00	13	5.662	7.888	9.854	31.91	44.46	55
11	DA-11	4.81	0.77	10.00		1.00	3.00	14	5.468	7.600	9.480	20.25	28.15	35
12	DA-12	4.97	0.77	10.00		2.00	1.00	13	5.662	7.888	9.854	21.67	30.19	37
13	DA-13	5.46	0.77	10.00		1.00	2.00	13	5.662	7.888	9.854	23.80	33.16	42
14	DA-14	0.04	0.77	5.00		0.00	0.00	5	7.884	11.004	13.785	0.24	0.34	0
14A	DA-13, DA-14	5.50	0.77	10.00	PT.14	1.00	2.00	13	5.662	7.888	9.854	23.98	33.41	42
15	DA-15	0.07	0.77	5.00		0.00	0.00	5	7.884	11.004	13.785	0.42	0.59	0
15A	DA-12, DA-15	5.04	0.77	10.00	PT.14	2.00	2.00	14	5.468	7.600	9.480	21.22	29.50	36
16	DA-16	0.05	0.77	5.00		0.00	0.00	5	7.884	11.004	13.785	0.30	0.42	0
16A	DA-10, DA-16	7.37	0.77	10.00	Pt.12	1.00	3.00	14	5.468	7.600	9.480	31.03	43.13	53
					/							1	· / /	



3421 Paesanos

Parkway

Phone: 210.979.8444

HECKED BY:

RAWN BY:

MS













Colliers								
Engineering & Design www.colliersengineering.com								
Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.								
Formerly Known as ENGINEERS + SURVEYING PROTECT YOURSELF								
ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSO PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM	N							
CRIPTION								
WN BY								
ATE DRA								
Lev								
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CENSE INTEGRAT INTEGR	0							
PRELIMINARY								
FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144								
SAN ANTONIO BEXAR COUNTY TEXAS								
ColliersEngineering & Design& DesignSAN ANTONIO (KFW)3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 TBPLS Firm#: 10194550	-							
SCALE: DATE: DRAWN BY: CHECKED BY: MS CG PROJECT NUMBER: DRAWING NAME: 314-60-01 GR3146001								
SHEET TITLE: OVERALL GRADING PLAN (SHEET 1 OF 2)								
SHEET NUMBER: 4.1	ſ							





PARKWAY SLOPE SETBACK SETBACK LAB EXPOSURE FOUNDATION F.F. ROPOSEL 8" MIN. SLAB EXPOSURE FINISHED ROUND FOUNDATION F.F. SPOT GRADE PROPOSED -FINISHED GROUND SPOT GRADE

TYPICAL SIDE YARD GRADING N.T.S.

GENERAL NOTES:

- 1. ELEVATION SHOWN ON FOUNDATION IS FOR FINISHED FLOOR. 2. CONTRACTOR SHALL PROVIDE OWNER ALL NECESSARY DENSITY TESTS FOR FILL LOTS AS REQUIRED BY HUD
- SPECIFICATIONS. 3. HOME BUILDER SHALL REFER TO THE APPROVED SUBDIVISION PLAT TO CONFIRM ALL BUILDING SETBACKS PRIOR TO ANY FOUNDATION WORK.
- 4. AS SOON AS PRACTICAL HOME BUILDER SHALL ESTABLISH VEGETATION (HYDROMULCH, SEEDING, SODDING, ETC...) TO PREVENT EROSION FROM OCCURRING.
- 5. CONTRACTOR SHALL CONTACT ENGINEER REGARDING ANY QUESTIONS ON THE INTENT OF THIS PLAN. 6. POSITIVE DRAINAGE SHALL BE MAINTAINED ON ALL SURFACE
- AREAS WITHIN THE SCOPE OF THIS PROJECT. DRAINAGE SHALL BE DIRECTED AWAY FROM ALL BUILDING FOUNDATIONS AND TOWARDS THE PROPER DRAINAGE EASEMENT OR STREET RIGHT OF WAY ACCORDING TO THE MASTER DRAINAGE PLAN FOR THE PROJECT. CONTRACTOR SHOULD TAKE PRECAUTIONS NOT TO ALLOW PONDING OF WATER.
- 7. ALL ELEVATIONS AND CONTOURS SHOWN ON THIS GRADING PLAN REFLECT FINISHED GRADES. THE THICKNESS OF PAVEMENT, CURBS, AND SIDEWALKS MUST BE SUBTRACTED TO OBTAIN SUBGRADE ELEVATIONS.
- 8. GRADING PLAN IS INTENDED FOR USE IN LOT GRADING ONLY. CONTRACTOR SHOULD REFER TO CONSTRUCTION DRAWINGS FOR ALL OTHER GRADES, INCLUDING, BUT NOT LIMITED TO, CHANNELS, ROADS, AND DETENTION PONDS.
- 9. CONTRACTOR SHALL ENSURE POSITIVE DRAINAGE ALL SWALES.







- E, G, T, & TV. E. = GAS, ELECTRIC, TELEPHONE, CABLE T.V. EASEMENT
 - = FLOW ARROW
 - = LOT GRADE TYPE
 - = PROPOSED DRIVEWAY LOCATION
 - H.P. = HIGH POINT



LOCATION MAP NOT-TO-SCALE

	Ē										
				C	0	11 i	er	S	ļ		
X		Engineering & Design									
	Copyria and all whom be cop	ght © 20 the info the serv bied, reu without	024. Co ormation ices we used, di t the exp	colli Iliers Er n contai re contr isclosed press wr	iers ngineerin ned her acted or , distrib ritten co	eng ag & Des ein is au to who uted or nsent of	inee ign All R ithorized m it is ce relied Colliers	Rights Re d for use ertified. upon fo Enginee	g.co eserved. e only by This dra r any o ering & D	This dra the par wing ma ther put esign.	awing ty for ny not rpose
	For	mer	ly K	now	n as	5	ENG	NEERS +		G	
		8		ŀ	ALL EXCAV PRE SL	PRC STATES ATORS PARING	DTEC 5 REQU 5, DESIG 6 TO 1 5 ANYW	T YOU JIRE NO GNERS DISTUR /HERE	URSE DTIFICA , OR AN B THE IN ANY	LF ATION NY PER EARTH (STATE	OF ISON I'S
	FC	Call L DR ST	ATE V	SPEC ISIT:	IFIC WWV	DIRE(V.CAI	CT PH _L811	HONE I .COM	i nun M	ИBER	s
	DATE DRAWN BY DESCRIPTION										
	REV										
	CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CENSE ONAL CONAL ONAL CONSE ONAL CENSE ONAL CLAYTON J. LINNEY 111543 CONAL CENSE ONAL CLAY CENSE ONAL CONSE ONAL CLAY CENSE ONAL CONSE ONAL CLAY CONSE ONAL CONSE CONS										
			I	PRE	ELI	MI	NA	RY	7		
	FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144										
	SAN ANTONIO BEXAR COUNTY TEXAS										
	E	Col ngin & D	l lie neer esig	rs ing gn	(SAI Sar Ph	N AN 3421 P n Ante none: TBPE TBPLS	ITON 1 Pae Parkw onio, 2 210. 2 210. NEERIN Firm#: Firm#:	IIO (I sano /ay TX 7 979.8 IG & DE F-1490 101945	KFW) s 8231 3444 sign, i 9 50	NC.
	SCALE: DATE: DRAWN BY: CHECKE MS C PROJECT NUMBER: DRAWING NAME: 314-60-01 GR3146001										BY:
	SHEET	P	OV PLA	ER N (ALI (SH	l G	RA T 2	DIN OI	NG F 2))	
	SHEET	NUME	BER:		2	4.2					



NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

CKED B

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS. PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS. PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

CAUTION!!:

THE CONTRACTOR SHALL BE REQUIRED TO LOCATE ALL PUBLIC OR PRIVATE UTILITIES INCLUDING BUT NOT LIMITED TO: WATER, SEWER, TELEPHONE AND FIBER OPTIC LINES, SITE LIGHTING ELECTRIC. SECONDARY ELECTRIC. PRIMARY ELECTRICAL DUCT BANKS. LANDSCAPE IRRIGATION FACILITIES, AND GAS LINES. ANY UTILITY CONFLICTS THAT ARISE SHOULD BE COMMUNICATED TO THE ENGINEER IMMEDIATELY AND PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL CONTACT 1-800-DIG-TESS A MINIMUM OF 48 HOURS PRIOR TO THE START OF CONSTRUCTION. ANY DAMAGE TO EXISTING UTILITIES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND THE REPAIR SHALL BE AT CONTRACTOR'S SOLE EXPENSE WHETHER

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

CKED BY

CG

IN AND AROUND TRENCH EXCAVATION.

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS. PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING

IN AND AROUND TRENCH EXCAVATION.

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING

IN AND AROUND TRENCH EXCAVATION.

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS. PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING

CKED BY

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

BEXAR COUNTY R.O.W. NOTE: A BEXAR COUNTY PERMIT MUST BE OBTAINED BEFORE WORKING IN THE BEXAR COUNTY RIGHT OF WAY.

TRENCH EXCAVATION SAFETY PROTECTION

CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT

PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS,

CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN

ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH

EXCAVATION.

CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE

GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR

PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH

EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM. OSHA

STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY

ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND

24	25	26	27	28	29	30	31	32	33	34	35	36	37
		BI-, RE LO PE — — — —	 DIRECTIONAL BL FLECTIVE PAVEI CATED ON ROAL RPENDICULAR T 	 .UE RAISED MENT MARKER D CENTERLINE TO F.H. LOCATION 		10' E.G.	 . <i>T.TV.E.</i> 					BI-I RE LO PE	 DIRECTIONAL FLECTIVE PA' CATED ON RC RPENDICULAI
			I		MAPLE LILY		i NGA tarak at beinterte bi	t Nice of Sectors		l Ling of the fail of the			ten an
 		······································			(50' R.O.W.)	e na da come de Aug		1					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	++	X 4 — — — — —				10' E.G.	.T.TV.E.				+	X	
5	6	7	8	9	10	11	12	13	14	15	16	17	MAPL
				BLOCK 10									STO
				MA1	CH LINE "A	A - A"	-						18

 	•	BI-DI REFL LOCA PERF	RECTIONAL BLUE LECTIVE PAVEME ATED ON ROAD C PENDICULAR TO	E RAISED ENT MARKER CENTERLINE F.H. LOCATION	·		T.TV.E.					BI Ri LC Pi	-DIRECTIONAL EFLECTIVE PA DCATED ON RC ERPENDICULA
					WILLOV (VARIABL	V FLATS E R.O.W.)						- <u></u>	
5	6	7	8	9 BLOCK 9	10	10' E.G.	т.тv.е. 12	13			16	17	ASH G WILLON
24	25	26	27	28	29	30	31	32	33	34	35	36	37

			FIS (CONCL	CHER GARDE JRRENT PLAT	NS, UNIT 1 #22-1180024	8)							
5	6	7	8	9	10	11	12	13	14	15	16	17	18
				BLOCK 8									
				BLOCK 8									
24	25	26 BI-DI REFI LOCA PERI	27 IRECTIONAL BLU LECTIVE PAVEM ATED ON ROAD PENDICULAR TO	28 E RAISED ENT MARKER CENTERLINE F.H. LOCATION	29	30	31 T.TV.E.	32	33	34	35	36 BI- RE LO PE	37 DIRECTIONA FLECTIVE P. CATED ON F RPENDICUL

LEC	ΞE	ND
C.B	=	COUNTY
E.G.T.C.E.	=	GAS, ELE CABLE E
V.N.A.E.	=	VEHICUL
(I)	=	WHEELCI SEE SHEI
SDWCR	=	SINGLE D SEE SHE
DDWCR	=	DOUBLE SEE SHE
[]/]]//]]]	=	SIDEWAL BY DEVE
	=	SIDEWAL OF HOME
	=	PROPOSI

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

RESIDENTIAL LOTS = 148

C.B	=	С
E.G.T.C.E.	=	Ċ
V.N.A.E.	=	۱
(I)	=	V S
SDWCR	=	S S
DDWCR	=	D S
TV:////////////////////////////////////	=	S B
e Kraske al	=	S C
anna anna anna anna anna anna anna ann		_

Colliers
Engineering & Design
www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.
Formerly Known as
PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF ECALVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM
WN BY DESCRIPTION Image: Im
DRAV
DATE
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CONAL CENSE ONAL
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CENSE ONAL ONAL ONAL ONAL ONAL ONAL ONAL ONAL
CLAYTON J. LINNEY III543 CLAYTON J. LINNEY III543 CENSE ONALF III543 CENSE ONALF III543 CLAYTON J. LINNEY III543 ONALF IIII543 ONALF III543 III543
CLAYTON J. LINNEY 111543 CENSE CLAYTON J. LINNEY 111543 CENSE ONAL CENSE CENSE ONAL CENSE ONAL CENSE ONAL CENSE
CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CENSE ONAL CLAYTON J. LINNEY 111543 COLUERS ENSIDE LICENSE PROFESSIONAL ENGINEER LICENSE NUMBER: 111543 COLUERS ENGINEERING & DESIGN, INC. TBPE FIRM#: F-14909 - TBPLS FIRM#: 10194550 PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144 SAN ANTONIO BEXAR COUNTY TEXAS COLUERS Engineering & Design COLUERS ENGINEERING & DESIGN, INC. TBPE FIRM#: F-14909 San ANTONIO (KFW) 3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 COLUERS ENGINEERING & DESIGN, INC. TBPE FIRM#: F-14999 TEXAS
CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CENSED CLAYTON J. LINNEY 111543 COLUENSED PROFESSIONAL ENGINEER LICENSE DUMBER: 111543 COLLERS ENGINEERING & DESIGN, INC. TEPE FIRM#: F-14909 - TEPLS FIRM#: 10194550 PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144 SAN ANTONIO BEXAR COUNTY TEXAS COLLERS Engineering & Design SCALE PROJECT NUMBER: DRAWING NAME: COLLERS COLLE
CLAYTON J. LINNEY 111543 CENSEP CLAYTON J. LINNEY 111543 CENSEP CLAYTON J. LINNEY 111543 CENSEP CLAYTON J. LINNEY TEXAS LICENSED PROFESSIONAL ENGINEER LICENSE NUMBER: 111543 COLLIERS ENGINEERING & DESIGN, INC. TBPE FIRM#: F.14909 - TBPLS FIRM#: 10194550 PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144 SAN ANTONIO BEXAR COUNTY TEXAS COLLIERS Engineering & Design SAN ANTONIO (KFW) 3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 COLLIES ENGINEERING & DESIGN, INC. TBLS FIRM#: 10194550 SCALE: DATE: DRAWN BY: CHECKED BY: MS CG PROJECT NUMBER: 314-60-01 SHEET TITLE TRAFFIC SIGNAGE AND PEDESTRIAN ACCESS PLAN (SHEET 2 OF 2)

	ĺ	C Eng	i n		eri	s ng			
Copyri and al whom be co	www. ght © 2024. C I the informatic the services w bied, reused, c without the ex-	colliers Engon contain rere contradisclosed, spress wri	erso gineerin hed here acted or distribu itten cor	engi g & Des ein is au to whor uted or isent of	ign All F thorizec n it is ce relied Colliers	ering tights Re for use ertified. upon fo Enginee	g.co eserved. e only by This dra r any o rring & D	This dra the par wing ma ther pu esign.	twing ty for y not rpose
For	merly K	ínow	n as	;	ENG	NEERS +	SURVEYIN	G	
F	BIT CONSTATE	SPEC	ALL S EXCAV PREI SU	PRC STATES ATORS PARING RFACE	DTEC REQU , DESIG G TO L ANYW	T YOI IIRE NG GNERS DISTUR (HERE	URSE DTIFICA , OR AT B THE IN ANY	LF ATION VY PER EARTH STATE	OF SON I'S S
			~~~~	V.CAL	L8 I	.cor			Ħ
KEV DATE DRAWN BY DESCRIPTION									
RE									
	The second secon		TTO 11 500	OF NJ. 154 VAL				Y Veer	
твр	CLA TEXAS LIC L COLLIEI E Firm#:	YT CENSE LICENS RS ENO F-1490	D PR SE NU GINE 09	OFES JMBE ERIN - T	SION R: 1 G & I BPLS	IAL E 1543 DESIC Firm	3 GN, IN n#: 1(	VC. )1945	550
ТВР	CLLA TEXAS LIC L COLLIEI E Firm#:	YT CENSE LICENS RS ENG F-1490	D PR SE NU GINE D9	OFES JMBE ERIN - T	SION ER: 11 G & I BPLS	IAL E I1543 DESIC Firm	3 5N, IN 1#: 10	VC. )1945	550
TBP	CLLA TEXAS LIC COLLIEI E Firm#:	PRE		MI GOR GOR GII GOR		IAL E I154: DESIC Firm	³ 5N, IN #: 10 <b>DET</b> <b>01</b>	NS	, +
	CLA TEXAS LIC COLLIEI E Firm#: ] FISC PLA B	PRE CHI SAN SAN SAN		MI FOR G MI MI FOR MI COR CXA	NA C 2 118 C 2 C 2 C 2 C 2 C 2 C 2 C 2 C 2	IAL E I154: DESIC Firm RD SO	³ 5 ^N , IN ##: 10 <b>DE</b> <b>D</b> <b>O</b> <b>O</b> <b>U</b> <b>V</b>	NS	550 •
	COLLIER COLLIER E Firm#: PISC PLA B Collie B B Collie & Desi	PRE CHI SAN F-1490 PRE			SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION SION	AL E I154: DESIC Firm RY RD SO SO SO SO SO SO SO SO SO SO SO SO SO	3 5N, IN ##: 10 PET 01 0 Y UIO (I sano (ay TX 7 979.8 G & DE F-1490 0 Y	NS VS (FW) s 8231 3444 ssign, I 9 50	550 
TBP TBP E SCALE PROJE	COLLIEI COLLIEI E Firm#: FISC PLA B Collie & Desi	PRE CHI C # SAN SAN SAN SAN SAN SAN SAN SAN			SION SION SION SION SION SION SION Gall Sale Sale Sale Sale Sale Sale Sale S	JAL E I154: DESIC Firm RY RY RD SO SO SO SO SO SO SO SO SO SO SO SO SO	3 50, IN H#: 10 PEN O1 O1 V Y UIO (I sano V Y UIO (I sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I Sano (I (I Sano (I Sano (I Sano (I S (I S (I ) (I S (I Sano (I S (I S (I S (I S (I S (I S (I S (I	NC. 1945 NS 42 (FW) 5 8231 3444 SIGN, I 50 CG	550 NC.
TBP [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [	COLLIEN COLLIEN E Firm#: FISC PLA Collie B Collie B Collie B Collie B Collie B Collie B Collie B Collie B	PRE CHI SAN SAN SAN SAN SAN SAN SAN SAN SAN SAN			INA INA INA INA INA INA INA INA	ALLE INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERING INTERINA INTERINA INTERINA INTERINA INTERINA INTERINA INTERINA INTERIN	3 50, IN ##: 10 PET 01 01 01 01 01 01 01 01 01 01	VC. 1949 VS 444 (FW) 5 8231 3444 cG	550 NC.

![](_page_21_Figure_0.jpeg)

# FISCHER GARDENS UNIT 2 BEXAR COUNTY, TX SANITARY SEWER IMPROVEMENTS

![](_page_21_Figure_6.jpeg)

# LOCATION MAP NOT-TO-SCALE

SA GIVEN TO FLY, LLC 6812 WEST AVENUE, SUITE 100 SAN ANTONIO, TX 78213 PHONE: 210-701-8337

![](_page_21_Picture_9.jpeg)

SAN ANTONIO RIVER AUTHORITY

100 E. GUENTHER STREET P.O. BOX 839980 SAN ANTONIO, TEXAS 78283-9980

			F	C	<b>Co</b>		er	s ng	Γ		
	Copyrig and all whom be cop	ght © 2 the info the serv bied, rec withou	024. Co prmatior rices wer used, di t the exr	colli lliers Er contai re contra sclosed	ierso	engi g & Des ein is au to whor uted or sent of	inee	tights Re for use ertified. upon for	<b>g.CO</b> eserved. e only by This dra r any o ring & D	<b>m</b> This dra the par wing ma ther pur esign	wing ty for y not rpose
	For	mer	ly Ki	now	n as		K	F			$\vec{1}$
			Ţ		ALL S EXCAV. PRE SU	PRC STATES ATORS PARING RFACE	DTEC REQU , DESIG G TO E ANYW	T YOI IIRE NG GNERS DISTUF /HERE	URSE DTIFIC/ , OR AI B THE IN ANY	LF ATION NY PER EARTH ( STATE	OF SON I'S
	FC	OR ST	ATE	SPEC ISIT:	CIFIC I WWV	DIREC	CT PH _L811	IONE .COI	NUN M	ИBER	s
	ON										
	Y DESCRIPTIC										
	DRAWN E										
	DATE										
	REV										
	TBP	C TEXA: COI E Firr	LLIER m#: F	CLA CLA S ENSE CCEN S ENSE S ENSE S ENSE S ENSE		OF NJ. 154 ENSI NAL		IEY IEY IAL E I154: DESIC	NGIN 3 ##: 10	Y NEER NC. 01945	550
	] F	FIS PL	F SC AT	PRI H] J	ELI ER UN	MI FOR G II II II II	NA AF [ 2 118	RY RD 80	) E 1 01	NS .42	, F
			B	SAI EX	N A AR TE	N'I CC EXA	'ON DUI AS	JIC NT	) Y		
	E	Col ngir & D	l <b>lie</b> n neer esig	rs ing gn	С	SAN Sar Ph OLLIER	N AN 3421 P n Ante none: s ENGI TBPE TBPLS I	Firm#:	IIO (I sano /ay TX 7 979.8 IG & DE F-1490 101945	KFW) s 8231 8444 ssign, i 9 50	NC.
P	ROJE	CT NUI 314-6	MBER: 0-01	ATÉ:	DRAV SSC\	VING N /3146	MS MS NAME: 001	5 5	CHE	CG	or:
	HEET	TITLE	SA	ANI CO	TA VE	RY R S	SE' HE	WE ET	R		
	SHEET	NUM	BER:		_	7.1					

SHEET INDEX	
SHEET TITLE	SHEET NO.
SANITARY SEWER COVER SHEET	7.1
OVERALL SEWER PLAN (SHEET 1 OF 2)	7.2
OVERALL SEWER PLAN (SHEET 2 OF 2)	7.3
LINE 'F' PLAN & PROFILE	7.4
LINE 'G' PLAN & PROFILE	7.5
LINE 'H' PLAN & PROFILE	7.6
LINE 'I' PLAN & PROFILE (SHEET 1 OF 2)	7.7
LINE 'I' PLAN & PROFILE (SHEET 2 OF 2)	7.8
SANITARY SEWER NOTES	7.9
SANITARY SEWER DETAILS	7.10

![](_page_22_Figure_0.jpeg)

PROPOSED WATER MAIN	=	-
PROPOSED WATER SERVICE & METER BOX	=	
PROPOSED WATER 3/4" IRRIGATION SERVICE & METER BOX	=	
PROPOSED FIRE HYDRANT	=	
PROPOSED WATER VALVE	=	
PROPOSED 100W STREETLIGHT	=	
PROPOSED SANITARY SEWER MAIN	=	-
PROPOSED SANITARY SEWER MANHOLE	=	-
PROPOSED SANITARY SEWER LATERAL	=	•
PROPOSED ELECTRIC, GAS, TELEPHONE, & CABLE TV EASEMENT	=	E
EXISTING WATER MAIN	=	_
EXISTING FIRE HYDRANT	=	
EXISTING WATER VALVE	=	
EXISTING SANITARY SEWER MAIN	=	_
EXISTING SANITARY SEWER MANHOLE	=	_
EXISTING OVERHEAD ELECTRIC W/POWER POLE	=	_

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.

![](_page_23_Figure_0.jpeg)

1. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF THIS CONTRACT SHALL BE IN ACCORDANCE WITH THE SAN ANTONIO RIVER AUTHORITY (S.A.R.A.) STANDARD SPECIFICATION. 2. SEWER PIPE WHERE WATER LINE CROSSES SHALL BE MEET THE REQUIREMENTS OF ASTM D2241. CONTRACTOR SHALL CENTER A 20 FOOT JOINT OF 160 P.S.I. PRESSURE RATED P.V.C. AT THE PROPOSED WATER CROSSING (NO SEPARATE PAY ITEM). PIPE TYPE DESIGNATIONS ARE SDR 26. 4. SEE THIS SHEET FOR TYPICAL SANITARY SEWER / WATER CROSSING DETAIL. 5. ALL MANHOLES SHALL HAVE CONCRETE RING ENCASEMENT AND A WATER TIGHT RING

## LEGEND

PROPOSED WATER MAIN PROPOSED WATER SERVICE & METER -C^s BOX PROPOSED WATER 3/4" IRRIGATION

SERVICE & METER BOX PROPOSED FIRE HYDRANT =

PROPOSED WATER VALVE PROPOSED 100W STREETLIGHT

PROPOSED SANITARY SEWER MAIN PROPOSED SANITARY SEWER MANHOLE =

PROPOSED ELECTRIC, GAS, TELEPHONE, = E. G. T. TV. E & CABLE TV EASEMENT EXISTING WATER MAIN

EXISTING FIRE HYDRANT

EXISTING WATER VALVE

EXISTING SANITARY SEWER MAIN EXISTING SANITARY SEWER MANHOLE EXISTING OVERHEAD ELECTRIC W/POWER POLE

EXISTING GUY WIRE/OVERHEAD ELECTRIC

			MATCH SEE	H LINE "A - A" SHEET 8.2				
			BLOCK 10	CB 4021				
24	25	26 27	28	29 30	31 / 32	33	34 35	36 37
		STA	A: 6+88.35 LINE "H" I. "H2"		E.G.T.TV.E.	DLINE "H" M.H. "H1"	10' E.G.T.TV.E	SEWER / V REFERENCE
8"SS + 8"SS -		7+00	8″SS ► (-6+(		5+00	4+00		50 8"SS I
	s	s			E.G.T.TV.E.		s	STA: 10
5	6	7 8	9	10 11		14	15 / 16	17   1
			BLOCK 11	CB 4021				
LOT 30' SANITARY IRE EASEMENT TO PRPORATION INTO	SEWER EASEME DEXPIRE UPON PLATTED STREE	ENT. ET R.O.W.)						
So AC. PERMEABLE	4+00	STA: 3+80.00 LIN M.H. "I1"	/E "/"					
ω <u> </u>	3+00			15.35 (DOC# 2021 OWNER: LONEST	5 ACRES 0360204 O.P.R.) FAR GRAYTOWN LLC			
0.P.R.) TOWN LLC   ∽ <del>−</del> - — — — — — —	8"SS + LINE				``			
o	2+00	STA: 1+00	0.00 CTOR TO TIE PROP 8	3"				
— م		SANITAR EXIST. M. BEGIN LI	Y SEWER MAIN TO ANHOLE NE "I"	RY SEWER EASEMENT				
0		5+00 +	(VOL. 13624, 	PG. 277 O.P.R.)	 	580 	9	
s + 00	551							

![](_page_23_Figure_17.jpeg)

![](_page_23_Figure_18.jpeg)

7.3

TRENCH EXCAVATION SAFETY PROTECTION CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

![](_page_24_Figure_2.jpeg)

![](_page_24_Figure_3.jpeg)

TRENCH EXCAVATION SAFETY PROTECTION CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

![](_page_25_Figure_2.jpeg)

![](_page_25_Figure_3.jpeg)

TRENCH EXCAVATION SAFETY PROTECTION CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR

STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

![](_page_26_Figure_3.jpeg)

![](_page_26_Figure_4.jpeg)

TRENCH EXCAVATION SAFETY PROTECTION CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR

STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

![](_page_27_Picture_3.jpeg)

TRENCH EXCAVATION SAFETY PROTECTION CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR

STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

![](_page_28_Figure_3.jpeg)

![](_page_28_Figure_4.jpeg)

GENERAL NOTES:

- 1 SAN ANTONIO RIVER AUTHORITY (RIVER AUTHORITY) STANDARD SPECIFICATIONS AND STANDARD DETAILS ARE PROVIDED FOR DESIGN AND CONSTRUCTION OF SEWER COLLECTION SYSTEMS MANAGED AND CONTRACTED BY THE RIVER AUTHORITY
- 2. AT ANY TIME, THESE STANDARD SPECIFICATIONS AND DETAILS MAY BE ALTERED OR SUPERSEDED BY THE GENERAL CONDITIONS, SUPPLEMENTAL CONDITIONS PLANS OR PROJECT SPECIFICATIONS WITHIN THE CONTRACT DOCUMENT PER DIRECTION FROM THE RIVER AUTHORITY
- 3. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE 9. OF THIS CONTRACT SHALL BE APPROVED BY RIVER AUTHORITY AND COMPLY WITH THE CONTRACT DOCUMENTS AND THE FOLLOWING AS APPLICABLE:
- 3.1. CURRENT TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) "DESIGN CRITERIA FOR DOMESTIC WASTEWATER SYSTEM" TEXAS ADMINISTRATIVE CODE (TAC) TITLE 30, PART 1, CHAPTER 217.
- CURRENT TEXAS DEPARTMENT OF 3.2. TRANSPORTATION (TXDOT), "STANDARD SPECIFICATIONS FOR CONSTRUCTION OF HIGHWAYS, STREETS AND DRAINAGE".
- 3.3. CURRENT RIVER AUTHORITY "STANDARD SPECIFICATIONS FOR SANITARY SEWER CONSTRUCTION".
- 3.4. CURRENT CITY OF SAN ANTONIO "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION" CURRENT CITY OF SAN ANTONIO "UTILITY EXCAVATION CRITERIA MANUAL".
- 4. THE CONTRACTOR IS TO NOTIFY AND MAKE ARRANGEMENTS WITH THE RIVER AUTHORITY INSPECTIONS DIVISION AT (210) 302-4200 FORTY EIGHT (48) HOURS PRIOR TO ANY EXCAVATION. CONTRACTOR SHALL ALSO PROVIDE PROCEDURES THAT WILL BE USED TO NOTIFY AFFECTED RESIDENTS AND/OR PROPERTY OWNERS 48 HOURS PRIOR TO ANY EXCAVATION OR CONSTRUCTION. A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD BEFORE ANY EXCAVATION OR START OF PROJECT
- 5. WORK SHALL NOT BE PERFORMED ON SATURDAYS, SUNDAYS, FEDERAL HOLIDAYS, RIVER AUTHORITY HOLIDAYS, BEFORE 7:30 AM, OR AFTER 4:30 PM, UNLESS PRIOR APPROVAL IS GRANTED BY THE RIVER AUTHORITY ENGINEER. REQUEST TO PERFORM WORK DURING THESE TIMES MUST BE EMAILED 48 HOURS IN ADVANCE TO UTILITIESDEVELOPMENT@SARIVERAUTHORITY.ORG.
- 6. NO EXTRA PAYMENT SHALL BE ALLOWED FOR WORK CALLED FOR IN THE PLANS BUT NOT INCLUDED IN THE BID SCHEDULE. THIS INCIDENTAL WORK WILL BE REQUIRED AND SHALL BE INCLUDED UNDER THE PAY ITEM WHICH IT RELATES TO
- WORK COMPLETED BY CONTRACTOR WHICH HAS NOT RECEIVED A WORK ORDER OR THE CONSENT OF RIVER AUTHORITY WILL BE SUBJECT TO REMOVAL AND REPLACEMENT AT THE EXPENSE OF THE CONTRACTOR
- 8. LOCATIONS AND DEPTHS OF EXISTING UTILITIES AND SERVICE LATERALS SHOWN ON THE PLANS ARE UNDERSTOOD TO BE APPROXIMATE ACTUAL LOCATIONS AND DEPTHS MUST BE FIELD VERIFIED BY THE CONTRACTOR AT LEAST 48 HOURS PRIOR TO CONSTRUCTION REGARDLESS OF ILLUSTRATION ON THE PLANS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO LOCATE UTILITY SERVICE LINES AS REQUIRED FOR CONSTRUCTION AND TO PROTECT THEM DURING CONSTRUCTION AT NO COST TO RIVER AUTHORITY. CONTRACTOR WILL BE RESPONSIBLE FOR ANY DAMAGES TO EXISTING UTILITIES AND REPAIRS WILL BE AT CONTRACTOR'S EXPENSE.

## THE FOLLOWING CONTACT INFORMATION IS SUPPLIED FOR VERIFICATION PURPOSES:

EAST CENTRAL SPECIAL UTILITY DISTRICT CITY OF SAN ANTONIO DRAINAGE CITY PUBLIC SERVICE (CPS) CITY OF CONVERSE (PUBLIC WORKS) TIME WARNER VALERO ENERGY CO. RIVER AUTHORITY INSPECTIONS TFXAS 811

SAN ANTONIO WATER SYSTEM (SAWS)

210-649-2383 210-207-5048 210-973-3500 210-659-9513 210-352-4872 210-349-7555 210-302-4200 800-344-8377 210-233-3500

- CERTAIN PORTIONS OF THE PROJECT MAY PARALLEL AND/OR CROSS EXISTING UTILITIES, AND CONTRACTOR IS REQUIRED TO PROTECT THESE UTILITIES. ADDITIONAL SUPPORTIVE SHORING MAY BE REQUIRED. IT IS THE CONTRACTOR'S RESPONSIBILITY TO PROTECT HIS WORKERS, EXISTING UTILITIES, AND FINISHED WORK THROUGHOUT THE PROJECT CONTRACTOR WILL BE RESPONSIBLE FOR ANY DAMAGES AND REPAIRS WILL BE AT CONTRACTORS EXPENSE.
- 10. WHERE WATER LINES AND NEW SEWER LINES ARE INSTALLED WITH A SEPARATION DISTANCE | ESS THAN 9 FEET (LE WATER | INES CROSSING WASTEWATER LINES WATER LINES PARALLELING WASTEWATER LINES OR WATER LINES NEXT TO MANHOLES), THE INSTALLATION MUST MEET THE REQUIREMENTS OF 30 TAC 217 AND 30 TAC 290.
- 11. DUE TO FEDERAL REGULATIONS TITLE 49. PART 192.161. CPS MUST MAINTAIN ACCESS TO GAS VALVES AT ALL TIMES. THE CONTRACTOR MUST PROTECT AND WORK AROUND VALVES THAT ARE IN THE PROJECT AREAS
- AN APPROPRIATELY SAFE OVERHEAD CLEARANCE MUST BE MAINTAINED BETWEEN ALL OVERHEAD EQUIPMENT AND PERSONNEL. THE CONTRACTOR SHALL NOTIFY CPS AT LEAST 48 HOURS PRIOR TO ANY CONSTRUCTION IN THE VICINITY OF CPS OVERHEAD LINES. CONTRACTOR SHALL MAINTAIN CPS RECOMMENDED CLEARANCE REQUIREMENTS.
- 13. ALL WORK IN THE TEXAS DEPARTMENT OF TRANSPORTATION (TXDOT) RIGHT-OF-WAY SHALL PROCEED DURING WORKING HOURS AGREED UPON BY RIVER AUTHORITY AND TXDOT INSPECTORS.
- 14. BEFORE THE START OF ANY CONSTRUCTION, THE PROJECT SITE MUST BE VIDEO RECORDED BY THE CONTRACTOR WITH ONE COPY SUBMITTED TO RIVER AUTHORITY. THE PRE-CON SITE VIDEO WILL PROVIDE ACCURATE DOCUMENTATION OF EXISTING CONDITIONS.
- 15. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING EXISTING FENCES, CURBS, STREETS, DRIVEWAYS, SIDEWALKS, LANDSCAPING AND STRUCTURES TO ORIGINAL OR BETTER CONDITION AS A RESULT OF DAMAGE DONE DURING THE PROJECT CONSTRUCTION.
- 16. ANY AND ALL FENCING, INCLUDING ELECTRIC FENCE, WHETHER OR NOT IDENTIFIED ON THE PLANS, MUST BE MAINTAINED AT ALL TIMES. ANY AND ALL DAMAGES DIRECTLY ATTRIBUTED TO THE CONTRACTOR MUST BE REPLACED TO EQUAL OR BETTER CONDITIONS AT THE CONTRACTOR'S EXPENSE AND AS APPROVED BY THE RIVER AUTHORITY INSPECTOR. GAPS IN THE FENCING MUST BE PROVIDED AT ALL LOCATIONS WHERE THE SEWER LINE EASEMENT CROSSES FENCING. FENCING REQUIRED TO MAINTAIN LIVESTOCK MUST BE MAINTAINED AT ALL TIMES.

- LANDOWNER.
- SECTION 2166.303 UNIFORM TRENCH SAFETY CONDITIONS.
- 21. NO TREES SHALL BE REMOVED AS PART OF THIS PROJECT UNLESS OTHERWISE SPECIFIED IN THE PLANS.
- UNACCEPTABLE BY RIVER AUTHORITY. UNDER THREATENING FLOODPLAIN.
- PLACED WITHIN THE LIMITS OF EXISTING FLOODPLAIN.
- ENCOUNTERED DURING CONSTRUCTION THE CONTRACTOR SHALL

## SANITARY SEWER PIPING:

- 52. THE TYPE AND DESCRIPTION OF THE PIPE CONDUIT IS SHOWN ON THE PLANS. REFER TO RIVER AUTHORITY SPECIFICATIONS FOR MATERIALS, STIFFNESS, AND TYPE.
- 53. THE USE OF ASBESTOS CEMENT PIPE WILL BE PROHIBITED UNDER THIS CONTRACT.
- 54. ALL DUCTILE IRON PIPE USED IN THIS SYSTEM SHALL BE CORROSION PROTECTED ON BOTH THE INTERIOR AND EXTERIOR SURFACES. ALL CORROSION PROTECTION SHALL BE APPLIED AND INSTALLED IN SUCH A MANNER AS TO MAINTAIN A CONTINUOUSLY PROTECTED SURFACE AFTER FINAL PIPE INSTALLATION.
- 55. SEE SPECIFICATIONS FOR PVC SEWER PIPE WITH OVER 14 FEET OF COVER.
- 56. ALL SEWER PIPES SHALL HAVE COMPRESSION OR MECHANICAL JOINTS.
- 57. SEWER PIPE CONNECTIONS TO PRECAST MANHOLES SHALL BE APPROVED BY THE RIVER AUTHORITY. THIS CONNECTION SHALL USE A FLEXIBLE "BOOT" TYPE CONNECTOR SUCH AS THE PSX POSITIVE SEAL SYSTEM OR ENGINEER APPROVED EQUAL AND COMPLY WITH ASTM C-923. SEWER PIPE CONNECTIONS TO MONOLITHIC MANHOLES WILL BE AS SHOWN ON THE STANDARD DETAIL SHEET. ANY CHANGES IN THESE METHODS MUST BE APPROVED BY RIVER AUTHORITY ENGINEER.
- 58. ALL PIPE TRENCHING. BEDDING AND BACKFILL SHALL BE CONDUCTED IN ACCORDANCE WITH RIVER AUTHORITY SPECIFICATIONS. COMPACTION SHALL BE 98% DENSITY; TESTING WILL BE REQUIRED PER LIFT EVERY 400 FEET.
- 59. SAND MIGRATION PREVENTION COLLAR WHEN CHANGING THE INITIAL BACKFILL FROM SELECT INITIAL BACKFILL TO OPTIONAL SELECT INITIAL BACKFILL. A TWO (2) FOOT LONG CLASS B CONCRETE ENCASEMENT OF FIRMLY COMPACTED. CONSOLIDATED CLAY ENCASEMENT BETWEEN THE TWO SHALL BE PROVIDED FOR THE ENTIRE HEIGHT OF THE INITIAL BACKFILL, EVERY 180 FEET ALONG PIPE AND 20 FEET FROM WALL OF MANHOLE IN EACH DIRECTION.

SEWER LINE LOCATION:

- 60. SEWER LINES SHALL BE SIZED AND EXTENDED THROUGH THE LIMITS OF A DEVELOPMENT TO SERVE ADJACENT PROPERTY, WITH MANHOLE AND STUB-OUT AT END OF SEWER LINE.
- 61. IN PHASED CONSTRUCTION OF THOROUGHFARES, THE SEWER LINE SHALL BE EXTENDED THE ENTIRE LENGTH OF PROPOSED THOROUGHFARE.
- 62. NO PUBLIC SEWER LINE SHALL BE LOCATED NEARER THAN FIVE (5) FEET FROM ANY TREE
- 63. SIZES AND GRADES FOR SANITARY SEWER SHALL BE AS REQUIRED BY THE RIVER AUTHORITY ENGINEER AND CONSIDERATION SHALL BE GIVEN AS TO POSSIBLE EXTENSIONS FOR FUTURE DEVELOPMENT. NO SANITARY SEWERS, OTHER THAN LATERALS AND FORCE MAINS, SHALL BE LESS THAN EIGHT (8) INCH IN DIAMETER.
- SEWER SERVICE LATERALS
- 64. WHEN SEWER LATERALS ARE TO BE CONNECTED TO EXISTING SEWER MAINS AND NO STUB-OUT HAS BEEN EARLIER PROVIDED, THE CONNECTION MUST BE MADE WITH AN APPROVED SERVICE SADDLE AS PER 31 TAC 313.5(C) (7). NEW INVERT TO BE BUILT, SMOOTH CHANNEL FOR NEW PIPE/SLOPE AT 2 % FLOW.
- 65. INSERTA-TEE TYPE FITTINGS WILL BE ALLOWABLE. THE MANUFACTURER SHALL COMPLY WITH THOSE IN THE RIVER AUTHORITY APPROVED PRODUCTS LIST.
- 66. ALL RESIDENTIAL SERVICE LATERALS SHALL BE SDR 26 PVC WITH RATING OF 115 PSI. BE EXTENDED TO THE PROPERTY LINE AT (6 x 6) CAPPED AND SEALED. ATTACH SEWER BURIAL TAPE TO THE END OF ALL SEWER LATERALS AND BRING UP TO THE GROUND LEVEL FOR MARKER (GREEN). (SEE HOUSE LATERALS DETAILS).

- THE SIZES AND LOCATIONS OF LATERALS SHALL BE DESIGNATED AS FOLLOWS UNLESS OTHERWISE DIRECTED BY THE RIVER AUTHORITY ENGINEER:
- 67. IN GENERAL, FOR SINGLE FAMILY DWELLING, THE LATERAL SIZE SHALL BE A FOUR (4) INCH MINIMUM. HOUSE LATERALS SHALL BE INSTALLED CENTER OF THE LOT AND SHALL HAVE A TEN (10) FOOT SEPARATION FROM THE WATER SERVICE THE SERVICE SHALL THEN BE EXTENDED AT A FORTY-FIVE (45) DEGREE ANGLE TO FOUR (4) FEET ABOVE THE FINISHED GRADE AND CAPPED. USE SEWER BURIAL TAPE TO MARK ALL SEWER SERVICE LATERALS.
- 68. MULTIPLE UNITS, APARTMENTS, LOCAL RETAIL AND COMMERCIAL SIX (6) INCH MINIMUM, MANUFACTURING AND INDUSTRIAL - EIGHT (8) INCH MINIMUM OR LARGER AS REQUIRED

TRAPS AND INTERCEPTORS (FOG - TECQ)

INSPECTIONS DEPARTMENT. ALL COMMERCIAL BUILINGS WILL HAVE TRAPS (FOG -TECQ). OIL SEPARATORS

69. UNIFORM PLUMBING CODE, CITY OF SAN ANTONIO BUILDING

70. WHICH INCLUDE OIL SEPARATOR- GASOLINE SERVICE STATIONS, CAR WASHES, GARAGES, DRY CLEANERS, CHEMICAL PLANTS, GAS PLANTS, HIDE PROCESSORS, TESTING LABORATORIES, OR ANY PLACE WHERE OIL OR SOLVENTS MAY BE INTRODUCED INTO THE SANITARY SEWER SYSTEM.THE SIZING CRITERIA FOR OIL SEPARATORS SHALL BE BASED ON THE G.P.M. RATE OF ALL FIXTURES, APPLIANCE OR APPURTENANCE, DRAINING INTO SEWER SYSTEM.

SAND INTERCEPTORS

71. SAND INTERCEPTORS SHALL BE INSTALLED IN THE SEWER SYSTEM OF THE FOLLOWING ESTABLISHMENTS. GARAGES. CAR WASHES. SERVICE STATIONS, OR ANY PLACE OF BUSINESS WHERE HEAVY SOLIDS MAY BE INTRODUCED INTO THE SANITARY SEWER SYSTEM. THE SIZING CRITERIA FOR A SAND INTERCEPTOR SHALL BE BASED ON THE REQUIRED G.P.M. x 12 MINUTE RETENTION TIMES TO OBTAIN THE TANK SIZE IN GALLONS CAPACITY.

AUTOMATIC CAR WASHES

72. WITH HIGH PRESSURE SPRAYS AND /OR BRUSHES INSTALL A 50 G.P.M. INTERCEPTOR.MINIMUM, FOR A 4-BAY VEHICLE WASH. THE SIZE OF THE INTERCEPTOR SHALL INCREASE 10 G.P.M. FOR EACH ADDITIONAL WASH BAY OVER 4. SINGLE BAY OR PORTABLE WASHER TYPE VEHICLE WASHES SHALL INSTALL A 20 GPM INTERCEPTOR MINIMUM.

NEUTRALIZING DEVICES

73. IN NO CASE SHALL CORROSIVE LIQUIDS, SPENT ACIDS, OR OTHER HARMFUL CHEMICALS WHICH MIGHT DESTROY OR INJURE A DRAIN. SEWER, SOIL, OR WASTE PIPE, OR WHICH MIGHT CREATE NOXIOUS OR TOXIC FUMES, DISCHARGE INTO THE SANITARY SEWER SYSTEM WITHOUT BEING THOROUGHLY NEUTRALIZED BY PASSING THROUGH A PROPERLY CONSTRUCTED AND ACCEPTABLE NEUTRALIZING DEVICE. SUCH DEVICE SHALL BE PROVIDED WITH A SUFFICIENT INTAKE OF NEUTRALIZING MEDIUM, CONSISTING OF LIMESTONE OR MARBLE CHIPS, SO AS TO MAKE ITS CONTENTS NON-INJURIOUS BEFORE BEING DISCHARGED INTO THE SANITARY SEWER SYSTEM.

LINT TRAPS

74. PUBLIC AND PRIVATE WASHATERIAS AND COMMERCIAL LAUNDRIES SHALL INSTALL A LINT TRAP EQUIPPED WITH A CONVENIENTLY LOCATED AND EASILY REMOVABLE WIRE BASKET OR OTHER SIMILAR DEVICE THAT WILL PREVENT THE STRINGS, RAGS, BUTTONS, OR OTHER PROHIBITED MATERIAL FROM ENTERING THE SANITARY SEWER SYSTEM. THE BASKET OR OTHER SIMILAR DEVICE SHALL PREVENT PASSAGE TO THE SANITARY SEWER SYSTEM OF SOLIDS GREATER THAN 1/2" INCH IN DIAMETER. THE LINT TRAP SIZE SHALL BE BASED ON THE TOTAL G.P.M. OF ALL FIXTURES, APPLIANCES AND APPURTENANCES DRAINING TO IT IN LIEU OF A LINT TRAP A LINT

75. SILVER RECOVERY UNITS SHALL BE INSTALLED IN WASTE LINE(S) LEADING FROM X- RAY PROCESSING, PHOTOGRAPHIC PROCESSING, AND /OR ANY PROCEDURES IN ESTABLISHMENT SUCH AS MEDICAL LABS. DENTAL LABS. PHOTO FINISHERS. PRINTERS. GRAPHIC ARTS PRODUCTION FACILITIES HOSPITAL FACILITIES VETERINARY HOSPITALS, OR OTHER ESTABLISHMENTS WHERE SILVER MAY BE INTRODUCED INTO THE SANITARY SEWER SYSTEM.

76. SOLIDS INTERCEPTORS SHALL BE INSTALLED WHEN PRE-TREATMENT OF WASTE STREAMS IS NECESSARY TO PREVENT SOLIDS GREATER THAN ½" IN DIAMTER, WHICH MAY CAUSE LINE STOPPAGE FROM ENTERING THE SANITARY SEWER SYSTEM.

SOLIDS INTERCEPTORS

**INTERCEPTORS** 77. INTERCEPTORS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE DESIGN APPROVED BY THE SAN ANTONIO RIVER AUTHORITY

- DESIGNED FOR GREASE RETENTION AND PROVIDE FOR A MINIMUM OF TWELVE (12) MINUTES RETENTION. 78. THERE SHALL BE AN ADEQUATE NUMBER OF MANHOLES TO PROVIDE ACCESS FOR CLEANING ALL AREAS OF AN INTERCEPTOR, ONE MANHOLE PER TRAP COMPARTMENT. MANHOLE COVERS SHALL BE
- GAS TIGHT IN CONSTRUCTION HAVING A MINIMUM OPENING DIMENSION OF 20 INCH INCHES (0.5 M).
- DESIGNED TO HAVE ADEQUATE REINFORCMENT AND COVER.
- 80. ALL INTERCEPTORS SHALL HAVE THE SIZE OF THE INTERCEPTOR (IN GALLON PER MINUTE OR GALLON CAPACITY) PERMANENTLY AFFIXED TO THE DEVICE.
- 81. ALL CONCRETE UTILIZED IN THE CONSTRUCTION OF INTERCEPTOR SHALL HAVE A MINIMUM STRENGTH OF 3000 PSI.
- 82. AN EFFLUENT SAMPLING WELL ON ALL INTERCEPTORS SHALL BE REQUIRED. THE SAMPLE WELL SHALL HAVE A RISER A MINIMUM OF 6" INCHES IN DIAMETER AND SHALL BE INSTALLED AFTER THE CONFLUENCE OF ALL WASTE STREAMS FROM THE FACILITY AND PRIOR TO DISCHARGING INTO SANITARY SEWER COLLECTION SYSTEM. THE WELL SHALL BE PERPENDICULAR TO THE EFFLUENT LATERAL TO ALLOW VISUAL OBSERVATION OF THE FLOW STREAM AND PROVIDE

FOR SAMPLING OF WASTEWATER.

### 17. CONTRACTOR MUST AVOID DAMAGE TO ADJACENT LAND OUTSIDE THE IDENTIFIED CONSTRUCTION LIMITS ANY CLAIMS DIRECTLY ATTRIBUTED. TO THE CONTRACTOR RESULTING FROM HIS STRAYING BEYOND THE CONSTRUCTION LIMITS MUST BE SETTLED BY THE CONTRACTOR TO THE SATISFACTION OF RIVER AUTHORITY AND THE APPROPRIATE

### 18. CONTRACTOR MUST MAINTAIN ACCESS FOR PRIVATE INDIVIDUALS AND BUSINESSES AT ALL TIMES. IF NORMAL ACCESS IS DAMAGED DURING CONSTRUCTION THE CONTRACTOR MUST REPLACE THE ACCESS TO EQUAL OR BETTER CONDITION AT THE CONTRACTOR'S EXPENSE AND AS APPROVED BY RIVER AUTHORITY.

19. CONTRACTOR MUST COMPLY WITH TEXAS GOVERNMENT CODE

20. CONTRACTOR SHALL BACKFILL ALL OPEN TRENCHES AT THE END OF THE DAY CONTRACTOR SHALL NOT INSTALL MORE PIPE THAN CAN BE COVERED NO OPEN TRENCHES WILL BE PERMITTED OVERNIGHT, ALL ENDS OF OPEN PIPE SHALL BE PLUGGED OVERNIGHT.

22. FOR PORTIONS OF THE CONSTRUCTION THAT ARE WITHIN THE LIMITS OF THE 100-YEAR FLOODPLAIN, THE CONTRACTOR IS REQUIRED TO KEEP THE CHANNEL CLEAR OF POTENTIAL OBSTRUCTIONS TO FLOOD FLOWS POTENTIAL OBSTRUCTIONS INCLUDE HEAVY CONSTRUCTION EQUIPMENT. TEMPORARY ROADS ACROSS CHANNEL. EXCAVATED MATERIAL, STOCKPILED DEBRIS, AND ALL OTHER ITEMS DEEMED

WEATHER CONDITIONS AND WHERE FLOODING IS LIKELY OBSTRUCTIONS SHALL BE IMMEDIATELY REMOVED BY THE CONTRACTOR AT NO ADDITIONAL COST TO RIVER AUTHORITY. THE CONTRACTOR ASSUMES ALL RISK FOR UNFINISHED WORK. NO EQUIPMENT OR MATERIALS SHALL BE STOCKPILED IN THE 100-YEAR

### 23. NO WASTE MATERIAL SHALL BE PLACED IN EXISTING DRAINAGE LOWS THAT WILL BLOCK OR ALTER FLOW LIMITS, NATURAL DRAINAGE, OR

## 24. IF A THREATENED OR ENDANGERED PLANT OR ANIMAL SPECIES AND/OR CULTURAL/ARCHAEOLOGICAL RESOURCES ARE

STOP WORK IMMEDIATELY AND NOTIFY THE APPROPRIATE PERSONNEL

INTERCEPTOR MAY BE INSTALLED. THE INTERCEPTOR SHALL BE SIZED

CONSISTING OF A MINIMUM OF TWO COMPARTMENTS WITH FITTINGS

79. IN AREAS WHERE TRAFFIC MAY EXIST THE INTERCEPTOR SHALL BE

## SEWER NOTES:

- 25. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT NO SANITARY SEWER OVERFLOW (SSO) OCCURS AS A RESULT OF THE WORK. ALL PERSONNEL RESPONSIBLE FOR SSO PREVENTION AND CONTROL SHALL BE TRAINED ON THE PROPER RESPONSE. SHOULD AN SSO OCCUR, THE
- CONTRACTOR SHALL:
- 25.1. IDENTIFY THE SOURCE OF THE SSO AND ATTEMPT TO ELIMINATE ANY ADDITIONAL SPILLAGE. 25.2. NOTIFY RIVER AUTHORITY CONSTRUCTION INSPECTIONS DIVISION
- AT 210-302-4216 OR 210-219-0130. 25.3. ATTEMPT TO ELIMINATE THE SOURCE OF THE SSO. 25.4. CONTAIN SEWAGE FROM THE SSO TO PREVENT CONTAMINATION OF
- WATERWAYS 25.5. CLEAN UP THE SPILL SITE AND REMOVE CONTAMINATED MATERIALS.
- 25.6. DISINFECT THE AREA OF THE SPILL WITH A MIXTURE OF HTH CHI ORINE AND WATER 25.7. CLEAN THE AFFECTED SEWER LINE AND REMOVE ANY DEBRIS.
- 25.8. IDENTIFY AND TRAIN PERSONNEL RESPONSIBLE FOR SPILLAGE PREVENTION AND CONTROL.
- 25.9. NO SEPARATE MEASUREMENT OR PAYMENT SHALL BE MADE FOR THIS WORK. ALL WORK SHALL BE DONE ACCORDING TO GUIDELINES SET BY THE TCEQ AND RIVER AUTHORITY.
- 26. TIE-INS OR SHUTDOWNS OF EXISTING FORCE MAINS OF ANY SIZE MUST BE COORDINATED WITH THE RIVER AUTHORITY INSPECTOR AT LEAST ONE WEEK IN ADVANCE OF THE SHUTDOWN CONTRACTOR SHALL PROVIDE A SEQUENCE OF WORK AS RELATED TO TIE-INS AT NO ADDITIONAL COST TO RIVER AUTHORITY OR THE PROJECT.
- 27. ELEVATIONS OF THE TOP OF MANHOLES AND INVERTS ARE FOR REFERENCE ONLY. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO MAKE ALLOWANCES AND ADJUSTMENTS FOR THE TOPS OF MANHOLES AND INVERTS TO MATCH THE FINISHED GRADE OF THE PROJECT IMPROVEMENTS (NSPI).
- 28. THE CONTRACTOR SHALL PROVIDE BYPASS PUMPING OF SEWAGE AROUND EACH SEGMENT OF PIPE TO BE REPLACED. CONTRACTOR SHALL HAVE STANDBY PUMPS AVAILABLE TO BYPASS FLOW IN CASE PRIMARY PLIMP FAILS. THE CONTRACTOR SHALL PROVIDE A SEQUENCE OF BYPASS PUMPING FOR REVIEW AND APPROVAL BY RIVER AUTHORITY THE CONTRACTOR SHALL ALSO PROVIDE A DETAILED SKETCH SHOWING THE LOCATION OF BYPASS PUMPING: SPECIFICATIONS FOR THE PUMPING EQUIPMENT; AND TYPE, SIZE, CAPACITY AND NUMBER OF PUMPS REQUIRED TO HANDLE THE PEAK WET WEATHER FLOW.
- 29. CONTRACTOR WILL MAINTAIN SERVICE TO ALL EXISTING SANITARY SEWERS AT ALL TIMES DURING CONSTRUCTION. CONTRACTOR WILL CLEAN ALL DEBRIS GRAVEL DIRT ETC. OUT OF MANHOLES AND FIX ANY STOPPAGES CAUSED BY DEBRIS DURING CONSTRUCTION AT CONTRACTOR'S EXPENSE. ANY DAMAGE TO EXISTING MANHOLES OR SEWER MAIN WILL BE CORRECTED AT CONTRACTOR'S EXPENSE. CONTRACTOR SHALL TAKE ALL NECESSARY MEASURES TO PREVENT DAMAGE TO EXISTING OR NEW RINGS, COVERS, OR CONES FROM EQUIPMENT AND MATERIALS USED OR TAKEN THROUGH THE WORK AREA. IF AN EXISTING OR NEW MANHOLE COVER, RING, OR CONE IS DAMAGED BY THE CONTRACTOR. IT SHALL BE REPLACED AS DIRECTED BY THE RIVER AUTHORITY INSPECTOR. MANHOLES WILL NEED TO BE RESEALED WITH RIVER AUTHORITY APPROVED SEALANT. IF SEAL COATING IS COMPROMISED, CONTRACTOR WILL HAVE MANHOLE RECOATED. CONTRACTOR SHALL RESEAL ALL LEAKS AT CONTRACTOR FXPENSE
- 30. CONTRACTOR TO ENSURE ALL PLUGS USED TO PLUG SEWER LINES WHILE TESTING THE PROJECT (SUCH AS AIR PLUGS, SCREW TYPE PLUGS, FTC) ARE LABELED MARKED OR TAGGED THE CONTRACTOR SHALL RECORD HOW MANY PLUGS ARE BEING USED, AS WELL AS THE LOCATION AND IDENTIFICATION OF EACH PLUG. CONTRACTOR WILL REPORT TO PROJECT INSPECTOR OF ANY LOST OR UNRESTRAINED PLUGS.
- 31. CONTRACTOR WILL BE HELD LIABLE FOR ANY DAMAGE TO SEWER COLLECTION SYSTEM, STOPPAGES, OVER-FLOWS, OR BACKUPS INTO HOMES CAUSED BY LOST OR RUNAWAY SEWER PLUGS.

### 32. CONTRACTOR WILL BE HELD RESPONSIBLE FOR ANY DAMAG WASTEWATER TREATMENT EQUIPMENT CAUSED BY LOST OF SEWER PLUGS. CONTRACTOR WILL BE HELD LIABLE FOR REA

33. RIVER AUTHORITY IS NOT RESPONSIBLE FOR ANY ABNORMALITIES ON STUB OUT. INVERT. GRADE OR SLOPE FOR ANY EXISTING MANHOLE TIE-IN OR SERVICE LATERAL

MANHOLE NOTES:

- 34. THERE SHALL BE 400 FEET MAXIMUM SPACE BETWEEN MANHOLES TO PROVIDE ACCESS FOR CLEANING. A 16-FOOT WIDE GATE WITH A LOCK SHALL ALSO BE SUPPLIED AND INSTALLED BY THE CONTRACTOR FOR ACCESSING THE SANITARY SEWER LINE.
- 35. ALL MANHOLES SHALL BE CONSTRUCTED SO THAT THE TOP OF THE RING IS AT LEAST FOUR (4) INCHES ABOVE THE FINISHED GRADE OF THE SURROUNDING GROUND IN UNPAVED AREAS. IN PAVED AREAS. THE MANHOLE RING SHALL BE FLUSH WITH THE PAVEMENT.
- 36. EVERY THIRD MANHOLE COVER WILL HAVE A 1" HOLE FOR A VENT.
- 37. EACH MANHOLE SHALL HAVE TWO LOCKS INSTALLED TO PREVENT REMOVAL.
- 38. ALL MANHOLES SHALL HAVE A 30" OPENING, WATERTIGHT RINGS AND COVERS, WITH THE RIVER AUTHORITY LOGO AND I/I BARRIER.
- 39. NEW MANHOLE PROTECTIVE COATING LINER MUST BE APPLIED TO ALL MANHOLES. APPLICATION PROCEDURES SHALL BE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATION AND PER THE FOLLOWING SPECIFICATIONS:
- 39.1. CONTRACTOR WILL BE RESPONSIBLE FOR MANHOLE SAFETY AND CONFINED SPACE ENTRY SET BY OCCUPATIONAL SAFETY AND HEALTH STANDARDS, 29 CFR 1910.146 APP. E. 39.2. THE CONTRACTOR SHALL NOTIFY THE RIVER AUTHORITY UTILITIES
- INSPECTIONS DEPARTMENT A MINIMUM OF 48 HOURS IN ADVANCE OF THE START OF ANY FIELD SURFACE PREPARATION WORK. 39.3. ALL NEW MANHOLES AND THE EXISTING MANHOLE THAT THE
- PROPOSED SEWER LINE WILL TIE-IN TO SHALL HAVE THE INTERIOR WALL PREPPED AS PER MANUFACTURER'S RECOMMENDATIONS AND COATED WITH A RIVER AUTHORITY APPROVED PRODUCT. 39.4. FOR ALL MANHOLES, APPLY THE CEMENTITIOUS COATING FIRST, FOLLOWED BY THE EPOXY COATING. LAFARGE SEWPERCOAT 200 HR
- PRODUCT IS THE ONLY APPROVED PRODUCT WHICH COMBINES THE CEMENTITIOUS AND EPOXY COATINGS, UNLESS OTHERWISE LISTED IN THE APPROVED PRODUCT LIST. 39.5. CEMENTITIOUS COATING WITH REQUIRED ONE-INCH-THICK APPLICATION SEE RIVER AUTHORITY APPROVED PRODUCT SHEET.
- 39.6. EPOXY COATING: WITH SPECIFIED THICKNESS APPLICATION: SEE RIVER AUTHORITY APPROVED PRODUCT SHEET.
- 39.7. SPRAY WALL POLYURETHANE SYSTEM REQUIRED THICKNESS 150 MILS
- 39.8. CONTRACTOR SHALL SUBMIT WARRANTY LETTER ON MANHOLE PROTECTIVE COATING FOR 10 YEARS AFTER FINAL ACCEPTANCE OF PROTECTIVE COATINGS.
- 40 ANY CONNECTIONS TO EXISTING MANHOI ES WILL REQUIRE A CRADLE TO SUPPORT THE INCOMING PIPE. A RUBBER GASKET WILL ALSO BE REQUIRED (CENTERED AT MANHOLE WALL) WITH GROUTING AT INTERIOR AND EXTERIOR PENETRATIONS.
- 41. PENETRATION INTO THE MANHOLE WILL BE CORE DRILLED. ANY DAMAGE TO EXISTING MANHOLE WILL BE REPAIRED AT CONTRACTOR'S EXPENSE. IF EXISTING SEWER MANHOLE SEAL COATING IS COMPROMISED, ALL OF THE MANHOLE WILL BE RESEALED.
- 42. IF ANY EXISTING MANHOLES CONNECTED WITH THIS PROJECT LEAK, THEY SHALL BE SEALED BY THE CONTRACTOR.
- 43. MANHOLES WITH STUB-OUTS 8-INCH OR LARGER MUST BE LOCATED AT THE END OF ALL SEWER LINES THAT MAY BE EXTENDED IN THE FUTURE. STUB-OUTS SHALL BE PLUGGED.
- 44. MANHOLE COVER INSERTS ARE SHOWN IN RIVER AUTHORITY APPROVED

## WATERTIGHT TESTING (24 HOURS):

- 83. ALL INTERCEPTORS SHALL BE WATER TESTED OUT AT JOB SITE AFTER BEING INSTALLED (PLUG BOTH ENDS AND FILL TO TOP OF INTERCEPTOR). INTERCEPTOR SHALL SHOW NO LEAKAGE FROM SECTION SEAMS, PINHOLES, OR OTHER IMPERFECTIONS. ANY LEAKAGE IS CAUSE FOR REJECTION WHEN I FAKAGE OCCURS ADDITIONAL WATER TESTING SHALL BE MADE. AFTER CORRECTING MEASURE TEST, REPORTS SHALL SHOW TOTAL NUMBER OF INTERCEPTERS TESTED. WHEN LEAKAGE OCCURS, CORRECTIVE MEASURES TAKEN SHALL BE REPORTED BY THE RIVER AUTHORITY INSPECTORS. RIVER AUTHORITY INSPECTORS SHALL RECORD IN DAILY LOG WITH PROJECT NAME, DATE IT WAS TESTED AND COMPLETED.
- 83.1. MANHOLES WILL BE REQUIRED ON SIX (6) INCH AND LARGER
- LATERALS WHERE THEY CONNECT TO THE MAIN 83.2. LATERALS WILL NOT BE ATTACHED TO SEWER MAINS THAT ARE DEEPER THAN TWELVE (12) FEET.
- 83.3. FITTINGS ARE NOT PERMITTED ON LATERALS BETWEEN THE WYE AND THE PROPERTY LINE. 83.4. DEEP CUT OR DROP CONNECTIONS SHALL NOT BE PERMITTED.
- 83.5. A MINIMUM OF ONE (1) LATERAL PER BUILDING SHALL BE REQUIRED. ALSO, A MINIMUM OF ONE (1) LATERAL PER RESIDENTIAL LOT SHALL BE REQUIRED. DUPLEXES SHALL HAVE TWO (2) LATERALS THAT SHALL BE INDEPENDENTLY ATTACHED TO
- THE MAIN. 83.6. ALL SEWER LATERAL CROSSING WATER MAINS SHALL CONFORM TO THE REQUIREMENTS OF THE TCEQ CHAPTER 317 (DESIGN CRITERIA FOR SEWERAGE SYSTEMS) LATEST REVISION, SDR 26 150 PSI, OR DUCT IRON PIPE, CONCRETE ENCASMENT.
- 84. WHERE REQUIRED CONCRETE ENCASEMENT SHALL BE PLACED FOR FULL WIDTH OF THE TRENCH TO A PLAIN SIX (6) INCHES ABOVE THE TOP OF THE PIPE WITH PAY UNITS AS SHOWN ON THE STANDARD DETAIL SHEET.
- 85. A MINIMUM OF FOUR (4) FEET OF COVER IS TO BE MAINTAINED OVER THE SANITARY SEWER MAIN AND LATERALS AT GRADE, OTHERWISE CONCRETE ENCASEMENT IS REQUIRED.
- 86. WHERE POROUS MATERIAL INCLUDING "SUBGRADE FILLER" IS USED FOR BACKFLL IN THE BEDDING AND INITIAL BACKFILL ZONES. SEEPAGE RETAINERS ARE REQUIRED AT AN APPROXIMATE OF 180 FEET. RETAINERS SHALL CONSIST OF CLASS "D" CONCRETE ENCASEMENT OR FIRMLY COMPACTED. CONSOLIDATED CLAY ENCASEMENT, THE RETAINERS SHALL EXTEND FROM THE BOTTOM OF THE TRENCH TO THE TOP OF THE GRANULAR MATERIAL FOR THE ENTIRE TRENCH WIDTH. ENCASEMENT SHALL BE 24 INCHES LONG. NO EXTRA PAY ITEM.

BLASTING

- 87. BLASTING SHALL NOT BE ACCEPTABLE.
- 88. TESTING SHALL NOT BE CONDUCTED UNTIL ALL OTHER UTILITIES WITHIN THE VICINITY OF THE SANTIARY SEWER ARE FULLY INSTALLED.

## THE FOLLOWING SEQUENCE WILL BE STRICTLY ADHERED TO:

- A. PULL MANDREL AFTER 30 DAYS OF INSTALLATION
- B. PERFORM AIR TEST C. PULL WIPER (AFTER STREET HAS BEEN ASPHALTED), AS APPLICABLE
- VACUUM TEST ALL MANHOLES WITHIN THE PROJECT
- E. CCTV- ALL OF THE NEW LINES AND PAN/TILT ALL SERVICE LATERALS

AT END OF PROJECT. CONTRACTOR SHALL SUBMIT FIELD COPY PLAN

AND PROFILES SHOWING AS-BUILT WORK, CCTV DVD, AND COMPACTION DENSITY REPORTS FOR MAIN SEWER LINES AND ALL SERVICE LATERALS CONTRACTOR SHALL ALSO ISSUE WARRANTY LETTERS FOR MATERIAL AND WORKMANSHIP FOR 12 MONTHS AFTER FINAL ACCEPTANCE.

- 89. ALL SEWER LINES MUST BE TESTED IN ACCORDANCE WITH THE FOLLOWING:
- A. 317.2(A)(5)(B); DEFLECTION TEST FOR FLEXIBLE AND SEMI-RIGID PIPE CONDUCTED AFTER FINAL BACKFILL HAS BEEN IN PLACED AT LEAST 30 DAYS.
- B. 317.2(A)(4)(A) & (B) OR RIVER AUTHORITY SPECIFICATIONS INFILTRATION AND OR EXFILTRATION AND OR LOW-PRESSURE AIR TEST
- C. 313.5(C)(10)(C) OR RIVER AUTHORITY SPECIFICATIONS: ALL MANHOLES AND WET WELLS MUST BE TESTED SEPARATELY AND INDEPENDENTLY OF THE COLLECTION LINES.
- D. IN THE EVENT THAT TESTING REQUIREMENTS CONFLICT, THE LATEST TCEQ DESIGN CRITERIA SHALL BE USED.
- 90. SEWER LINES SHALL BE TESTED FROM MANHOLE TO MANHOLE.
- 91. SANITARY SEWER CONNECTIONS MADE DIRECTLY TO EXISTING MANHOLES WHICH REQUIRE PENETRATION INTO THE MANHOLE WILL BE CORE DRILLED. ANY DAMAGE TO EXISTING MANHOLE WILL BE REPLACED AT CONTRACTOR'S EXPENSE AND WILL REQUIRE SUCCESSFUL TESTING OF THE EXISTING MANHOLE IN ACCORDANCE WITH THE RIVER AUTHORITY SPECIFICATIONS. THEY MUST HAVE A PROTECTIVE COATING SPECIFIED IN THE RIVER AUTHORITY APPROVED PRODUCTS LIST. COATING WILL BE MINIMUM OF 200 MILS THICKNESS DEPENDING ON EXISTING CONDITIONS, TO PREVENT INFRASTRUCTURE INFILTRATION, FOLLOW MANUFACTURER'S RECOMMENDATION ON PROTECTIVE COATING.
- 92. AFTER CONSTRUCTION, TESTING WILL BE DONE BY PAN/TILT TV CAMERA BY THE CONTRACTOR AND OBSERVED BY THE INSPECTOR, WASTEWATER ENGINEERING PERSONNEL AND CONTRACTOR AS CAMERA IS RUN THROUGH THE LINES. PAN/TILT ALL 6" SERVICE LATERALS TO 6"X6" STUB-OUT, VIDEOS MUST INCLUDE SUBDIVISION NAME, MANHOLE NUMBER, SERVICE LATERAL STATION NUMBER, FLOW DIRECTION, LOCATION ANY ABNORMALITIES, SUCH AS BROKEN PIPE OR MISALIGNED, JOINT, GRAVEL, DIRT, MUST BE CLEANED OUT. REPLACE AT CONTRACTOR'S EXPENSE. NEW SEWER SYSTEM WILL BE FLOODED WITH H2O BEFORE BEING TV. ALL SEWER LINES MUST BE PRESSURE CLEANED TO INCLUDE SERVICE LATERALS 6" INCH TO STUB-OUT. ALL VIDEOS SHALL BE SUBMITTED IN DVD FORMAT WITH WRITTEN REPORTS.
- 93. A COPY OF ALL TESTING REPORTS INCLUDING BACKFILL COMPACTION TESTS SHALL BE FORWARDED TO THE RIVER AUTHORITY.
- 94. DENSITY TEST WILL BE REQUIRED ON ALL SANITARY SEWER TRENCHES INCLUDING SERVICE LATERALS. SERVICE LATERALS TO BE CHOSEN RANDOMLY BY FIELD INSPECTOR. DENSITIES ON SERVICE LATERAL SHALL NOT EXCEED 25% OF TOTAL NUMBER OF SERVICE.
- EXCAVATION
- 95. CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED

E TO	
RUNAWAY	
PAIRS.	

TO 6"X6" CLEAN OUT. CONTRACTOR SHALL FLOOD ALL LINES BEFORE

PRODUCT SHEET. INSERTS SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING THE NECESSARY FIELD MEASUREMENTS FOR THE MANUFACTURER PRIOR TO PRODUCTION.

- 45. BEFORE BACK FILLING/COMPACTION/CONCRETE ENCASEMENT, ALL MANHOLE JOINT SECTION RISERS, CONE SECTIONS AND GRADE RING SHALL BE WRAPPED WITH INFI-SHIELD GATOR WRAP SEALING SYSTEMS, BUTYL ADHESIVE SEALANT WITH A MINIMUM THICKNESS OF 30 MILS JOINT SEALANT MUST MEET ASTM C923. MASTIC MUST MEETS ASTM C 990 OR BE APPROVED BY THE RIVER AUTHORITY ENGINEER.
- 46. IF CONCRETE THROAT RINGS ARE TO BE INSTALLED THEY MUST BE USED IN CONJUNCTION WITH A UV STABILIZED POLYETHYLENE LINER AND I/I BARRIER. I/I BARRIER MUST MEET THE FOLLOWING ASTM STANDARDS: ASTM D-790/1505 DENSITY OF POLYETHYLENE MATERIALS. ASTM D-1238 MELT FLOW INDEX, ASTM 638 TENSILE STRENGTH@, YIELD (50 mm/mm), ASTM 790 FLEXURAL MODULUS ASTM 648 HEAT DEFLECTION TEMPERATURE @IGEPAL, ASTM 1693 EsCR, 100% IGEPAL /10% IGEPAL.
- 47. A MINIMUM OF TWO AND A MAXIMUM OF FOUR THROAT RINGS WILL BE USED AT EACH MANHOLE FOR ADJUSTMENT.
- 48. DROP MANHOLES SHALL BE REQUIRED WHEN THE INFLOW ELEVATION IS MORE THAN 24 INCHES ABOVE THE OUTFLOW ELEVATION. DROP SHALL BE LOCATED OUTSIDE THE MANHOLE WITH THE FLOWLINE ELEVATION LOCATED BETWEEN THE CENTER LINE AND TOP OF SEWER LINE.
- 49. THERE SHALL BE CONCRETE ENCASEMENT 18 INCHES AROUND MANHOLE RING, AND 28 INCHES AROUND THE GATOR WRAP SEALING SYSTEM. CONCRETE ENCASEMENT SHALL BE CIRCULAR. FORMED LEVEL. AND HAVE A SMOOTH OR BROOM FINISH. SEE SPECIFICATIONS.
- 50. SEWER PIPE CONNECTIONS TO PRECAST MANHOLES SHALL BE APPROVED BY RIVER AUTHORITY. THIS CONNECTION SHALL USE A FI FXIBI F "BOOT" TYPE CONNECTOR SUCH AS THE PSX POSITIVE SEAL SYSTEM OR ENGINEER APPROVED EQUAL AND COMPLY WITH ASTM C-923. SEWER PIPE CONNECTIONS TO MONOLITHIC MANHOLES WILL BE AS SHOWN ON THE STANDARD DETAIL SHEET. ANY CHANGES IN THESE METHODS MUST BE APPROVED BY RIVER AUTHORITY ENGINEER.
- 51. ALL PIPE TRENCHING, BEDDING AND BACKFILL SHALL BE DONE IN ACCORDANCE WITH APPROPRIATE ASTM/ANSI SPECIFICATIONS IREFERENCE 31 TAC 317.2(A)(5)(A): ASTM C-12 (ANSI A106.2) OR ASTM D-2321 (ANSI K65.171)]. ALL COMPACTION SHALL BE TO 98% DENSITY. THERE SHALL BE ONE RANDOM DENSITY TEST PER LIFT FOR EVERY 400 FEET. ALL TESTING SHALL BE IN COMPLIANCE WITH CURRENT TXDOT SPECIFICATIONS
- 52. A SAND MIGRATION PREVENTION COLLAR SHALL BE INSTALLED WHEN TRANSITIONING FROM SELECT INITIAL BACKFILL TO OPTIONAL SELECT INITIAL BACKFILL. A 2-FOOT LONG CLASS B CONCRETE ENCASEMENT BETWEEN THE TWO SHALL BE PROVIDED FOR THE ENTIRE HEIGHT OF THE INITIAL BACKFILL EVERY 180 FEET ALONG PIPE AND 20 FEET FROM WALL OF MANHOLE IN EACH DIRECTION

EMPLOYEE OR STRUCTURAL DESIGN/ GEOTECHNICAL/ SAFETY/ EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTORS TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THE SYSTEMS. PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIALLY, CONTRACTOR AND/OR CONTRACTORS INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

96. CONTRACTOR IS RESPONSIBLE FOR REMOVAL OF ALL WASTE MATERIALS UPON PROJECT COMPLETION. THE CONTRACTOR SHALL NOT PERMANENTLY PLACE ANY

 <u> </u>									
		C	<b>`o</b> ]		er	s			
	E	Eng &	gin D	es	eri igi	ng n	•		
Copyrig and all t whom tl be copie	www. at © 2024. Co he information he services we ed, reused, d without the exp	colli Iliers Eng n contain re contra isclosed, press wri	erse gineerin ned here acted or distribu tten con	g & Desi in is au to whon ited or sent of (	nee gn All R thorized n it is ce relied u Colliers	ights Re for use rtified. 1 upon fo Enginee	served. only by This dra r any o ring & D	This dra the part wing ma ther pur esign.	wing ty for y not rpose
Form	nerly K	now	n as		<b>K</b> ENG	NEERS + S		G	Ē
FO	R STATE	SPEC	ALL S EXCAV/ PREF SU	PRC TATES TORS PARINO RFACE	REQU DESIG TO D ANYW	IRE NO GNERS, DISTUR HERE	URSE DTIFICA OR AN B THE IN ANY	LF ATION ( NY PER EARTH STATE	OF SON 'S :
	V	ISIT: \	WWW	/.CAL	L811	.CON	Λ	/ Dc	
NO									
DESCRIPTIC									
DRAWN BY									
/ DATE									
REV			وموم	<b>201</b>	· ) ) ]				Ę
		CLAN					M M M	Y	
T	EXAS LIC L COLLIER Firm#: F	ENSE ICENS S EN( -149(	D PR SE NL GINE 09	OFES IMBE ERINO	SION R: 11 G & C BPLS	IAL E 1543 DESIC Firm	NGIN 3 5N, IN 1#: 10	I NEER NC. 01945	550
	I	PRE	LI	MI	NA	RY	<del>,</del>		Ĭ
E	FISC	HI J	F ER JN	OR G	AF	RD	EI	٧S	
P	LAT	. #	2/	, ,	118	30	01	44	F
	B	SAN EX	J A AR TE	NT CC XA	ON DUI AS	JIO NT	Y		
	Collie Igineer & Desig	<b>rs</b> ing gn	C	SAN San Ph OLLIER	J AN 3421 P Anto one: s engli TBPE TBPLS F	TON Pae arkw onio, 210. NEERIN Firm#:	IIO (I sano ay TX 7 979.8 G & DE F-1490 101945	KFW) s 8231 3444 50	NC.
SCALE: PROJEC	T NUMBER:	DATE:	DRAV	DR /ING N 3146	AWN E MS IAME: 001	3Y:	CHE	CKED I CG	ЗY:
SHEET		AR	YS	EN	/EF	R N	OT	ËS	
SHEET	NUMBER:			7.9					Ī

![](_page_30_Figure_0.jpeg)

<b>Colliers</b> Engineering
& Design www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.
Formerly Known as
PROTECT YOURSELF         All STATES REQUIRE NOTIFICATION OF         Excavators, Designers, or any person         Preparing to Disturb the Earth's         Surface Anywhere in any state         For state specific Direct Phone NUMBERS         VISIT: WWW.CALL811.COM
v       Date       Drawn By       Description         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v         v       v       v       v
See
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CCENSED ONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONAL CONA
PRELIMINARY
FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144
SAN ANTONIO BEXAR COUNTY TEXAS
ColliersSAN ANTONIO (KFW)3421 Paesanos3421 PaesanosParkwaySan Antonio, TX 78231Phone: 210.979.8444Colliers ENGINEERING & DESIGN, INC.TBPE Firm#: F14909TBPLS Firm#: 10194550
SCALE:     DATE:     DRAWN BY:     CHECKED BY:       MS     CG       PROJECT NUMBER:     DRAWING NAME:       314-60-01     SSDT3146001
SHEET TITLE: SANITARY SEWER DETAILS
SHEET NUMBER:

# FISCHER GARDENS UNIT 2 BEXAR COUNTY, TX WATER IMPROVEMENTS

![](_page_31_Figure_1.jpeg)

RESIDENTIAL LOTS = 148

![](_page_31_Figure_5.jpeg)

HEET NUMBER
8.1
8.2
8.3
8.4
8.5
8.6
8.7
8.8

## LOCATION MAP NOT-TO-SCALE

SA GIVEN TO FLY, LLC 6812 WEST AVENUE, SUITE 100 SAN ANTONIO, TX 78213 PHONE: 210-701-8337

<b>Colliers</b> Engineering & Design	
www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This draw and all the information contained herein is authorized for use only by the party whom the services were contracted or to whom it is certified. This drawing may be copied, reused, disclosed, distributed or relied upon for any other purp without the express written consent of Colliers Engineering & Design.	ring for not ose
PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSO PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM	F ON;
NOLINA NOLINA NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NAME NA	
PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24–11800144	
SAN ANTONIO BEXAR COUNTY TEXAS	
SAN ANTONIO (KFW)         3421 Paesanos         Parkway         San Antonio, TX 78231         Phone: 210.979.8444         Colliers & Design         Scale:         Date:         Drawn BY:         CHECKED BY         MS         CG	с. Y:
PROJECT NUMBER: 314-60-01 DRAWING NAME: OWCV3146001 SHEET TITLE: WATER IMPROVEMENTS COVER SHEET	
SHEET NUMBER: 8.1	

CAUTION!!: THE CONTRACTOR SHALL BE REQUIRED TO LOCATE ALL PUBLIC OR PRIVATE UTILITIES INCLUDING BUT NOT LIMITED TO: WATER, SEWER, TELEPHONE AND FIBER OPTIC LINES, SITE LIGHTING ELECTRIC, SECONDARY ELECTRIC, PRIMARY ELECTRICAL DUCTBANKS, LANDSCAPE IRRIGATION FACILITIES, AND GAS LINES. ANY UTILITY CONFLICTS THAT ARISE SHOULD BE COMMUNICATED TO THE ENGINEER IMMEDIATELY AND PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL CONTACT 1-800-DIG-TESS A MINIMUM OF 48 HOURS PRIOR TO THE START OF CONSTRUCTION. ANY DAMAGE TO EXISTING UTILITIES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND THE REPAIR SHALL BE AT CONTRACTOR'S SOLE EXPENSE WHETHER THE UTILITY IS SHOWN ON THESE PLANS OR NOT.

## PRESSURE REDUCING VALVE (PRV) NOTE:

ELEVATION OF 895 FEET WHERE THE STATIC PRESSURE WILL NORMALLY EXCEED 80 PSI. AT ALL SUCH LOCATIONS WHERE THE GROUND LEVEL IS BELOW 895 FEET, THE DEVELOPER OR BUILDER SHALL INSTALL AT EACH LOT, ON THE CUSTOMER'S SIDE OF THE METER, AN APPROVED TYPE PRESSURE REGULATOR IN CONFORMANCE WITH THE PLUMBING CODE OF THE CITY OF SAN ANTONIO. NO DUAL SERVICES ALLOWED FOR ANY LOT(S) IF *PRV IS / ARE REQUIRED FOR SUCH LOT(S), ONLY SINGLE SERVICE CONNECTIONS SHALL BE ALLOWED. WATER SERVICES WHERE PRV'S REQUIRED ARE DESIGNATED BY AN ASTERISK (*).

*NOTE: A PRESSURE REGULATOR IS ALSO KNOWN AS A PRESSURE REDUCING VALVE(PRV)

## FIRE FLOW NOTE

IN AN EFFORT TO MEET THE CITY OF SAN ANTONIO'S FIRE FLOW REQUIREMENTS FOR THE PROPOSED RESIDENTIAL DEVELOPMENT, THE PUBLIC WATER MAIN SYSTEM HAS BEEN DESIGNED FOR A MINIMUM FIRE FLOW DEMAND OF 1 500 GPM AT 25 PSI RESIDUAL PRESSURE THE FIRE FLOW REQUIREMENTS FOR INDIVIDUAL STRUCTURES WILL BE REVIEWED DURING THE BUILDING PERMIT PROCESS IN ACCORDANCE WITH THE PROCEDURES SET FORTH BY THE CITY OF SAN ANTONIO DIRECTOR OF DEVELOPMENT SERVICES DEPARTMENT AND THE SAN ANTONIO FIRE DEPARTMENT FIRE MARSHAL.

![](_page_32_Figure_11.jpeg)

![](_page_32_Figure_12.jpeg)

![](_page_32_Figure_13.jpeg)

CAUTION!!: THE CONTRACTOR SHALL BE REQUIRED TO LOCATE ALL PUBLIC OR PRIVATE UTILITIES INCLUDING BUT NOT LIMITED TO: WATER, SEWER, TELEPHONE AND FIBER OPTIC LINES, SITE LIGHTING ELECTRIC, SECONDARY ELECTRIC, PRIMARY ELECTRICAL DUCTBANKS, LANDSCAPE IRRIGATION FACILITIES, AND GAS LINES. ANY UTILITY CONFLICTS THAT ARISE SHOULD BE COMMUNICATED TO THE ENGINEER IMMEDIATELY AND PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL CONTACT 1-800-DIG-TESS A MINIMUM OF 48 HOURS PRIOR TO THE START OF CONSTRUCTION. ANY DAMAGE TO EXISTING UTILITIES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND THE REPAIR SHALL BE AT CONTRACTOR'S SOLE EXPENSE WHETHER THE UTILITY IS SHOWN ON THESE PLANS OR NOT.

## PRESSURE REDUCING VALVE (PRV) NOTE:

ELEVATION OF 895 FEET WHERE THE STATIC PRESSURE WILL NORMALLY EXCEED 80 PSI. AT ALL SUCH LOCATIONS WHERE THE GROUND LEVEL IS BELOW 895 FEET, THE DEVELOPER OR BUILDER SHALL INSTALL AT EACH LOT, ON THE CUSTOMER'S SIDE OF THE METER, AN APPROVED TYPE PRESSURE REGULATOR IN CONFORMANCE WITH THE PLUMBING CODE OF THE CITY OF SAN ANTONIO. NO DUAL SERVICES ALLOWED FOR ANY LOT(S) IF *PRV IS / ARE REQUIRED FOR SUCH LOT(S), ONLY SINGLE SERVICE CONNECTIONS SHALL BE ALLOWED. WATER SERVICES WHERE PRV'S REQUIRED ARE DESIGNATED BY

*NOTE: A PRESSURE REGULATOR IS ALSO KNOWN AS A PRESSURE REDUCING VALVE(PRV)

## FIRE FLOW NOTE

REQUIREMENTS FOR THE PROPOSED RESIDENTIAL DEVELOPMENT, THE PUBLIC WATER MAIN SYSTEM HAS BEEN DESIGNED FOR A MINIMUM FIRE FLOW DEMAND OF 1,500 GPM AT 25 PSI RESIDUAL PRESSURE. THE FIRE FLOW REQUIREMENTS FOR INDIVIDUAL STRUCTURES WILL BE REVIEWED DURING THE BUILDING PERMIT PROCESS IN ACCORDANCE WITH THE PROCEDURES SET FORTH BY THE CITY OF SAN ANTONIO DIRECTOR OF DEVELOPMENT SERVICES DEPARTMENT AND THE SAN ANTONIO FIRE DEPARTMENT FIRE MARSHAL.

![](_page_33_Figure_12.jpeg)

![](_page_33_Figure_13.jpeg)

![](_page_33_Figure_15.jpeg)

![](_page_34_Picture_0.jpeg)

![](_page_34_Picture_1.jpeg)

## Series 2000PV:

for mechanical joints.

Mechanical Joint Restraint Gland for use With AWWA C900 or IPS Outside Diameter PVC Pipe in the fastest and most economical method of karaining PVC pipe to mechanical joints. Now the need for costly concrete thrust blocks and corrodible steel tie rods is eliminated. It can be used in straight UL Listed in the four through twelve inch sizes for alignment or at the preset deflection recommended

The 2000PV was the first PVC joint restraint to be tested to UNI-B-13, Underwriters Laboratories, and Factory Mutual.

![](_page_34_Picture_5.jpeg)

## The 2000PV MEGALUG Concept

EBAA Iron started manufacturing joint restraint products for PVC pipe in the early 1980s. The testing pipe. of early prototypes of various configurations of restraints on large diameter PVC pipe indicated that a The design of the 2000PV incorporates the gripping restraint device must be capable of consistently and mechanism into the design of the mechanical reliably gripping the pipe. If not, the restraint can slip joint gland and utilizes a simple two part assembly refer pressure, resulting in a sudden impact, and process. The first step involves assembling the couse the pipe to burst. Armed with this background joint the same as any standard mechanical joint. knowledge and an appreciation for the capabilities of The assembly procedure we recommend is that

in the industry once considered to be the 'only' way to actuation of the restraint. grip PVC pipe. This led to development of the Series

The 2000PV MEGALUG Mechanical Joint Restraint Tested to and meets the requirements of ASTM F 1674-96 'Standard' Test Method for joint restraint products use with PVC pipe through 24 inch size.

> joining UL Listed ductile iron fittings to UL Listed, Class 150 PVC pressure pipe. The maximum allowable joint deflection is five degrees.

> Factory Mutual approved for use on DR18 PVC pipe in four through twelve inch sizes.

![](_page_34_Picture_12.jpeg)

![](_page_34_Picture_13.jpeg)

2000PV MEGALUG Mechanical Joint Restraint for PVC

PVC pipe, EBAA purposefully deviated from what many established in AWWA C600. The second is the

![](_page_34_Picture_17.jpeg)

Fabricated fitting configurations may vary. CALL FOR OTHER SIZES, CONFIGURATIONS & GASKET MATERIALS

![](_page_34_Picture_19.jpeg)

THE HARRINGTON CORPORATION

HARCO DUCTILE IRON IPS GASKETED FITTINGS

isolate the lubrication chamber Thrust Washers We thrust washers are used. One is located Fusion-Bonded Epoxy These thrust washers provide easy operation the interior and the exterior. The fusion-bonded Factory Mutual Research Corp Listed-FM Approved  $\bigcirc$ 

FEATURES

and backflow control systems.

Triple O-ring Stem Seals

- Seat Tested at 375 p s Shell Tested at 500 p.s. g.
- Fusion-Bonded Epoxy Coating Complies With ANSI/AWWA C550
- CL250# Raised Face Flanges Available 250 p.s. g AWWA UL and FM
- Pressure Rating Fully Rubber-Encapsulated Wedge

## SPECIFICATIONS

The valve shall also be Listed by Underwriters Two of the O-rings shall reside above the thrust of the pressure energized O-ring style design Laboratories, incorporated, and Approved by collar The O-rings shall be replaceable under full. All internal and external ferrous surfaces of or cast gray-iron bodies are not acceptable collar for reduction of operating torque Certified to ANSI/NSF Standard 61 The valve shall have a smooth and oversize All exterior valve body bolting shall be type All valves shall be the AMERICAN Flow

944 -

The AMERICAN Series 2500 Ductile from Ductile Iron Construction

is designed for use in drinking water, sewage provide strength and a pressure rating that are fully epoxy coated and fire protection systems as well as impation meets or exceeds the requirements of AWWA C515 The tensile strength of ductile ion O-ring Style Gaskets ductile iron valve

- The Series 2500 Ductile Iron Resilient Wedge Gate Valve has these standard features:
  - Triple O-ring Stem Seals
  - Thrust Washers Smooth larger than nominal Waterway
  - 100% Leak-Tight Closure • 4" and larger sizes Certified to NSF/
  - ANSI standard 61 Complies with AWWA C515
  - Ductile Iron Body Bonnet Wedge Operating Nut and Stuffing Box

Quetile Iron cast on onto the body. The valve hexagonal heads, with dimensions conforming Wedge Gate Valves,

250 p.s. g AWWA Resilent Wedge Gate Valve The ductile ron body bonnet and wedge bolt holes and body-to-bonnet flange surfaces

epoxy coating is applied prior to assembly. The

FEATURES/SPECIFICATIONS

2" – 12" SERIES 2500 RESILIENT WEDGE GATE VALVE

is more than twice that of cast iron. This The body-to-bonnet and stuffing box cover added strength makes the Series 2500 more seals are pressure-energized O-lings. This Sealing the lubrication chamber is a series durable and rated at 250 p s g. This strength reduces the need for excessive bolt loading. of three O-ring stem seals The O-rings help to and higher pressure rating is provided in a which is required by designs that use flat compact lightweight and easy-to-handle gaskets. The O-rings are reusable which reduces downtime during any needed repair. The Series 2500 Resilient Wedge Gate Valve is furnished in configurations that are Listed by above and one is located below the thrust collar. The Series 2500 valve is epoxy coated on Underwriters Laboratories. Inc. and Approved by

Valves 2 12 in size shall be of a rest ent wedge shall be constructed of ductile iron and to ANSI B18.2.1. Metric size and/or socket wedge design. The valve shall have a cold provided with protective wedge guide covers in head cap screws or bolts are not allowed water rated working pressure of 250 p.s.l.g. sizes 4"-12". All wedges 3" and smaller shall The operating nut shall be 2" square and All cast ferrous components shall be ductile be constructed of bronze. All wedges shall be shall be constructed of ductile iron fitted to a Firon and shall be manufactured in compliance fully encapsulated with EPDM rubber square tapered stem to help ensure even valve with the latest edition of AWWA/ANSI C515. Valve stems shall be sealed by three O-rings operating input torque. All body gaskets shall be

Factory Mutual in applicable configurations working pressure and with the valve in the full the valve body and bonnet shall have a fusion The valve design shall be lightweight easy to open position O-rings set in a cartridge shall not bonded epoxy coating, complying with AWWA/ handle, and constructed with wall thickness per be allowed. The valve shall also be equipped with ANSI C550. The coating shall be electro-Table 2, of AWWA/ANS_C515. Heavy wall and/ thrust washers above and below the stem thrust statically applied prior to assembly and shall be

waterway and have the marking OL or 304 stainless stee and shall be provided with Control Series 2500 or 2500-1 Resilient

THE RIGHT WAY

121 [S

![](_page_34_Figure_49.jpeg)

0. BOX 10335 • LYNCHBURG VIRGINIA 24506 • PLANT 3721 COHEN PLACE • LYNCHBURG VIRGINIA 24501 PHONE: (434) 845-7094 • FAX: (434) 845-8562 • E-mail: sales@harcofittings.com Form XXX - 12/03/2003 - 3

				SATE VA	LVE	D			
" - 12" SERIES	5 2500 RE	SILIENT	WEDGE (		••• 				
S 2500 STANDARI	D NRS DIMENSI	DNS				Q		8"	(12)
					DC with 2" So			ead Oper N	1
	THE AD				RS with Handw IS & Y IRS with Enclos	heel ( Actuat ed Miter Gearin Parallel to Wate	Post Indicator  ror (Check One)  g prway	Valve (PN)	
					Sq. Oper. Nut landwheel Perp	Perpendicular ( endicular to Wa	o Waterway terway	5	
		O		Ope Ste	m Matenal	El Bronze	Left (C.C.W) Standard) C	C Right IC W.	
LAY LENSTH	1.2522	SHOWN NI			I Connections:	<u> 18</u> –			
END TO END		nya: on		UL.	Listed, FM App	roved C			
				Oth	ner Requiremen	ts (list on a sep	parate sheet		
DINENCION				Se	e notes at bot	tom of page			
		2	Series 2500 2-1/2 11:03	3 [®]	4	6	Series 2500-1 8 20,47	10 24.06	12* 27_59
B End to End – M	J/M <b>J</b>	10.22 8.25	12.00 N/A	N/A 8.62	N/A 10,00	N/A 10.50	N/A 11.50	N/A 12/50	N/A 13/50
Lay Length – M End to End – FL/FL	J/MJ Class 125	3 25 7 00	N/A 7:50	3 62 8 00	5 00 9 00	5,50 10,50	6.50 11.50	7,50 13,00	8.50 14.00 19.75
End to End – FL/FL End to End – T Fnd to End – FL/MJ	Y/TY (Class 125)		N/A N/A	N/A 8,31	13,00 9,50	15.88 10.50	17 <u>50</u> 12 <u>3</u> 8	18 75 13 62	19.75 14.38
End to End FL/TY End to End PV	Class 125	NA 1075	N/A 11.12	N/A 11_38	11,00 13,00	13.19 15:88	14,50 17,50	15.88 N/A	16.88
End to End – Th Handwheel Dia	readed	<u>6 25</u> <u>8 06</u> 9	8,00	7.38	10.00	12-00	14,00	15,50	15,50
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones through 12 valves through 12 valves usion-bonded epoxy coati anged ends are in accord neaded ends are in accord <b>THE RIGHT</b>	t or exceed requirem may be ordered in co- line and Approved b 250 p s ig AWWA have 250 p s ig UL ing meets or exceeds tance with ANSI/AWP wrdance with ASME B WAY	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w s requirements c WA C110/A214 116.4 Class 125	WWA C5 15 hich are issted by al Research versure vorking pressure of ASME/AWWA C2 0 (ASME B16 1, C 3)	550 kass 125)	14 Mechanical join Tyton " ends ar on cast iron 10 0 PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3	20 Intends are in accord dipush-on ends a size ductile iron suitable for use or E: Each valve sho in This should be arculation or other is recommended	26 ordance with ANSI are in accordance pipe. In steel (IPS) sizes of auld be operated th done on a time sch deposits that could this be done once	J 32 VAWWA C111/A21 with ANSVAWWA ( of PVC or steel pipe arough a ful cycle i hedule that is desk id render the valve a year	38 C111/A21 11 and returned t ined to prever inoperable or
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratories, through 12 valves have -1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord readed ends are in accord THE RIGHT SUBMI Angle Ball	t or exceed requirem may be ordered in co- inc and Approved b 2 500 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW rdance with ANSI/AWW rdance with ASME B WAY	ents of ANSVAW onfigurations wh ny Factory Mutua and FM rated working p and FM rated w %A C110/A214 116 4 Class 125	WWA C5 15 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C3 CASME B16 C C3 CASME B16 C C3 CASME B16 C C3 CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME CASME C	550 Hass 125) ON BFA43->	14 Mechanical join Tyton" ends ar or cast iron C PVC ends are s MAINTENANC normal position buildup of tube tight shutoff it 3	20 Intends are in acc and push-on ends a size ductile iron suitable for use or E: Each valve sho This should be arculation or other is recommended <b>- Style</b> )	26 ordance with ANSI are in accordance pipe in steel (IPS) sizes of uild be operated th done on a time sci deposits that could this be done once	J 32 VAWWA C111 A21 with ANSVAWWA ( of PVC or steel pipe inough a full cycle a hedule that is desk id render the valve r a year.	38 C111/A21 11 and returned t inoperable or
through 12" valves mee 1/2" through 12" valves inderwriter's Laboratories, through 12" valves have -1/2" through 12" valves usion-bonded epoxy coath anged ends are in accord readed ends are in accord readed ends are in accord THE RIGHT SUBMIT Angle Ball PACK	t or exceed requirem may be ordered in co- inc and Approved b 250 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW rdance with ANSI/AWW rdance with ASME B WAY TTAL II Flange M	ents of ANSVAW onfigurations wh ny Factory Mutua rated working p and FM rated w is requirements of WA C1 10/A21 116 4 Class 125 NFOR Meter Va COPPER	WWA C515 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C CASME B16 C C C C C C C C C C C C C C	550 Hass 125) ON BFA43->	14 Mechanical join Tyton" ends ar on cast iron (C 0 PVC ends are st MAINTENANC normal position buildup of tube tight shutoff it 3 3	20 Intends are in accord dipush-on ends a size ducille iron suitable for use or E: Each valve sho This should be arculation or other is recommended <b>. style</b>	26 ordance with ANSI are in accordance pipe in steel (IPS) sizes of uild be operated th done on a time sci deposits that could this be done once	J 32 VAWWA C111 A21 with ANSVAWWA ( of PVC or steel pipe inough a full cycle a hedule that is desk id render the valve a year.	38 11 C111/A21 11 and returned to inoperable or C111/A21 11
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coall anged ends are in accord threaded ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Stun are of	t or exceed requirem may be ordered in co- inc and Approved b 250 p s ig AWWA have 250 p s ig UL ing meets or exceed dance with ANSI/AWW rdance with ANSI/AWW rdance with ANSI/AWW rdance with ANSI/AWW rdance with ASME B WAY TTAL II Flange M JOINT FOR d one piece tee- dy stops allow S	ents of ANSVAW onfigurations whi ny Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116 4 Class 125 NFOR Meter Va COPPER head and sto 20° motion all otected.	WWA C5 15 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C ASME B16 C C C C C C C C C C C C C C	550 Hass 125) DN BFA43-)	14 Mechanical join Tyton "ends ar on cast iron (C O PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCCVV-NLL G (CTS) IN	20 It ends are in acc id push-on ends a size ductile iron suitable for use or E: Each valve sho 1 This shoud be arculation or other is recommended <b>.</b> Style) ILET BY M	26 ordance with ANSI are in accordance pipe. In steel (IPS) sizes of uld be operated th done on a time sci deposits that coul this be done once	AWWA C111/A21 with ANSVAWWA ( of PVC or steel pipe inough a full cycle in hedule that is desk id render the valve a year.	38 11 11 11 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 11 14 14
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coall anged ends are in accord threaded ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Stum are d EPD	t or exceed requirem may be ordered in co- inc and Approved b 2 500 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW rdance with ANSI/	ents of ANSVAW onfigurations whi ny Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116 4 Class 125 NFOR Meter Va COPPER head and sto 20° motion an rotected.	WWA C5 15 hich are usted by al Research ressure of ASME/AWWA C2 0 (ASME B16 C C C C C C C C C C C C C C	550 lass 125) DN BFA43->	14 Mechanical join Tyton" ends ar or cast iron (C 0 PVC ends are t MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCCVV-NL G (CTS) IN	20 It ends are in acc id push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended <b>.</b> Style) ILET BY M	26 ordance with ANSI are in accordance pipe in steel (IPS) sizes of uild be operated th done on a time sch deposits that could this be done once <b>IETER FLA</b> Pau A s into be and be and be accordent the second second second pipe and be accordent and accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent accordent	AWWA C111 A21 with ANSVAWWA C111 A21 with ANSVAWWA C of PVC or steel pipe incugh a full cycle a hedule that is desk d render the valve a year.	38 11 11 11 14 14 14 14 14 14 14
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coall anged ends are in accord threaded ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Stun are d EPD Fluo bras	t or exceed requirem may be ordered in co- inc and Approved b 2 500 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW rdance with ANSI/	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116 4 Class 125 NFOR Meter Va COPPER thead and str 0° motion a rotected. e stem	WWA C5 15 hich are usted by al Research ressure of ASME/AWWA C2 0 (ASME B16 C C C C C C C C C C C C C C	550 lass 125) DN BFA43-> IC TUBIN	14 Mechanical join Tyton" ends ar or cast iron (C 0 PVC ends are to MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCCVV-NL G (CTS) IN	20 It ends are in acc id push-on ends a size ductile iron suitable for use or E: Each valve sho 1 This should be arculation or other is recommended <b>J</b> <b>J</b> <b>LET BY M</b>	26 ordance with ANSI are in accordance pipe. In steel (IPS) sizes of uld be operated th done on a time sci deposits that coul this be done once <b>IETER FLA</b> Par A is into Mo sea Met	AWWA C111/A21 with ANSVAWWA C111/A21 with ANSVAWWA C of PVC or steel pipe inough a full cycle a hedule that is desk d render the valve a year.	38 11 11 11 14 14 14 14 14 14 14
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coall anged ends are in accord treaded ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Sturn are d EPD Fluo brass Bevy gasi seal	t or exceed requirem may be ordered in co- inc and Approved b 2 500 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW redance with AN	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A21 116 4 Class 125 NFOR NECOPPER thead and str O° motion avoidected. e stem	WWA C5 15 hich are isted by al Research ressure of ASME/AWWA C2 0 (ASME B16 C C C C C C C C C C C C C C	550 lass 125) DN 3FA43-> IC TUBIN	14 Mechanical join Tyton ends ar on cast iron (C D PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3	20 It ends are in acc id push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended <b>JLET BY M</b>	26 ordance with ANSI are in accordance pipe. In steel (IPS) sizes of uld be operated th done on a time sci deposits that coul this be done once this be done once <b>IETER FLA</b> Pa A s into Mo seea Met	AWWA C111/A21 with ANSVAWWA C111/A21 with ANSVAWWA C of PVC or steel pipe inough a full cycle in hedule that is desk id render the valve in a year.	38 C111/A21 11 and returned t inoperable or Inoperable or ET The stem he valve bber ball
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Sturn are d EPD Fluo brass Bev gas seal Anti-	tor exceed requirem may be ordered in co- inc and Approved b 250 p s ig AWWA have 250 p s ig UL ing meets or exceed tance with ANSI/AWW redance with ANSI/	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A21 116 4 Class 125 NFOR Meter Va COPPER thead and str 0° motion a rotected. e stem	WWA C5 15 hich are usted by al Research ressure of ASME/AWWA C2 0 (ASME B16 C C C C C C C C C C C C C C	550 lass 125) DN BFA43->	14 Mechanical join Tyton ends ar on cast iron (C 0 PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCCVM-NLL G (CTS) IN	20 It ends are in acc di push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be a arculation or other is recommended <b>JLET BY M</b>	26 ordance with ANSI are in accordance pipe. In steel (IPS) sizes of uld be operated th done on a time sci deposits that could this be done once this be done once <b>IETER FLA</b> <b>Pau</b> <b>A se</b> into <b>Seea</b> Meri <b>Height</b>	AWWA C111 A21 with ANSVAWWA C111 A21 with ANSVAWWA C of PVC or steel pipe inough a full cycle in hedule that is desk id render the valve is a year.	
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord inreaded ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> Solid Sturn are of EPD Fluo brass Bevy gast seal Anti- Integ mac	tor exceed requirem may be ordered in co- line and Approved b 2 500 p si g AWWA have 250 p si g UU ing meets or exceed dance with ANSI/AWP redance with AN	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w s requirements o WA C110/A21 1 16 4 Class 125 NFOR Meter Va COPPER thead and str O° motion au rotected. e stem	WWA C5 15 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C C C C C C C C C C C C C	500 kass 125) DN BFA43-> IC TUBIN	14 Mechanical joi Tyton ends ar or cast iron (C PVC ends are it MAINTENANC normal positio buildup of tube tight shutoff it 3	20 It ends are in acc d push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended ILET BY M	IETER FLA	AWWA C111 A21 with ANSVAWWA C111 A21 with ANSVAWWA C of PVC or steel pipe inough a full cycle in hedule that is deak id render the valve r a year.	
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord inreaded ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> . Solid Sturn are of EPD Fluo brass Bevy gast sean Anti- Integrade Bevy gast sean Anti- Integrade Ball Anti- Solid Stair	tor exceed requirem may be ordered in co- line and Approved b 2 500 p si g AWWA have 250 p si g UU ing meets or exceeds dance with ANSI/AWW redance with A	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116.4 Class 125 NFOR Vieter Va COPPER thead and sto O° motion au rotected. e stem	WWA C5 15 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C C C C C C C C C C C C C	50 13 13 13 15 15 12 12 12 12 12 12 12 12 12 12	14 Mechanical joi Tyton ends ar or cast iron (C PVC ends are it MAINTENANC normal positio buildup of tube tight shutoff it 3	20 It ends are in acc id push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended ILET BY M	ETER FLA	AWWA C111 A21 with ANSVAWWA C111 A21 with ANSVAWWA C of PVC or steel pipe inough a full cycle in hedule that is desk id render the valve r a year.	
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord inreaded ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> . Solid Sturn are of EPD Fluo brass Bevy gast sean Anti- Integrade Pack	tor exceed requirem may be ordered in co- line and Approved b 2 500 p si g AWWA have 250 p si g UU ing meets or exceeds dance with ANSI/AWW redance with A	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116.4 Class 125 NFOR Vieter Va COPPER thead and str O° motion a rotected. e stem	WWA C5 15 hich are Listed by al Research ressure of ASME/AWWA C3 0 (ASME B16 C C ASME B16 C C C C C C C C C C C C C C	500 kass 125) DN BFA43-) IC TUBIN	14 Mechanical joi Tyton ends ar or cast iron (C PVC ends are it MAINTENANC normal positio buildup of tube tight shutoff it 3	20 Intends are in accord dipush-on ends a size ductile iron suitable for use or E: Each valve sho in This shoud be arculation or other is recommended ILET BY M Ou Ou	ETER FLA	J 32 VAWWA C111 A21 with ANSVAWWA ( of PVC or steel pipe inough a fuil cycle in hedule that is desk id render the valve r a year.	
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord threaded ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> Solid Sturn are of EPD Fluo brass Bevy gast sean Anti- Integrace axia Pack Stain Valve Size 1-1/2" 2"	tor exceed requirem may be ordered in co- line and Approved b 250 p sig AWWA have 250 p sig UL ing meets or exceeds tance with ANSI/AWW redance with ANSI/	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116.4 Class 125 NFOR Vector Va COPPER -head and stu 0° motion an otected. e stem ber fraulic ains for w activates of Meter can ains	RMATIC alves - (2 OR PLAST em nd Size Len 2 -2-13	500 133 133 150 150 150 150 150 150 150 150	14 Mechanical joi Tyton" ends ar or cast iron (C PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCXVV-NLL G (CTS) IN COCXVV-NLL G (CTS) IN COCXVV-NLL G (CTS) IN COCXVV-NLL G (CTS) IN COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL COCXVV-NLL	20 Intends are in account of push-on ends a size duchle iron suitable for use or E: Each valve sho in This should be arculation or other is recommended <b>JEET BY M</b> <b>JLET BY M</b> Out DX. B BFA: B BFA: B BFA:	PART NUMBER 43-666V-NL 43-777V-NL	J 32 VAWWA C111 A21 with ANSVAWWA C of PVC or steel pipe inough a fuil cycle in hedule that is desk id render the valve a year.	_ET
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> . Solid Sturn are of EPD Fluo brass Bevy gast seat Anti- Integrit mac axia Pack Stair Valve Size 1-1/2" 2" Note: Ford rec	tor exceed requirem may be ordered in co- line and Approved b 250 p s ig AWWA have 250 p s ig UL ing meets or exceeds dance with ANSI/AWP redance with ANS	ents of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116.4 Class 125 NFOR Veter Va COPPER thead and str Oo* motion a rotected. e stem ber fraulic ains for w activates of Meter stiffer	AND CS 15 inch are listed by al Research ressure of ASME/AWWA CC 0 (ASME B16 1 CO COR PLAST em nd Size Len Size Len Size Len Size Len Size Len Size Len Size Len Size Len	500 133 1425 125) 10 10 10 10 10 10 10 10 10 10	14 Mechanical joi Tyton "ends ar or cast iron (C 0 PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCX VV-N/L G (CTS) IN COCX VV-N/L G (CTS) IN COCX VV-N/L G (CTS) IN COCX VV-N/L G (CTS) IN COCX VV-N/L COCX VV-N/L	20 Intends are in acc of push-on ends a size duchle iron suitable for use or E: Each valve sho in This shoud be arculation or other is recommended <b>JEET BY M</b> <b>JLET BY M</b> Ou Divide a star <b>BFA</b>	PART NUMBER 43-777/V-NL	J       32         VAWWA C111 A21         with ANSVAWWA C111 A21         of PVC or steel pipo         irough a full cycle in         hedule that is deak         dirender the valve         a year         NGE OUTIL         dlock Wing         map ring locks         o the body of the         Ided EPDM runt         the supports the         ter Flange	38 11 11 11 11 14 11 14 14 14 14
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> . Solid Stain are of EPD Fluo brass Bevy gast sean Anti Integrad Read Stain Valve Size 1-1/2" 2" Note: Ford record All brass that The product Certified tor Brass comp (ASTM B62 Padlock Value Stain Anti Integrad Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack Stain Pack S	tor exceed requirem may be ordered in co- line and Approved b 250 p sig AWWA have 250 p sig UU ing meets or exceed tance with ANSI/AW we are so exceed to an epiece tee- dy stops allow S enclosed and pr the order of the so one piece tee- dy stops allow S enclosed and pr the order of the so one piece tee- dy stops allow S enclosed and pr the order of the so one piece tee- dy stops allow S enclosed and pr the order of the so one piece tee- dy stops allow S enclosed and pr the so provides hype the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and pr the so one piece tee- dy stops allow S enclosed and p	Antipartic of ANSVAW onfigurations whi y Factory Mutua rated working p and FM rated w is requirements of WA C110/A214 116 4 Class 125 Antipartic of ANSVAW WA C110/A214 116 4 Class 125 Antipartic of ANSVAW ACTIO/A214 116 4 Class 125 Antipartic of ANSVAW ACTIO/A214 116 4 Class 125 Antipartic of ANSVAW ACTIO/A214 Infe A Class 125 Antipartic of Antipartic of Antiparti	WWA CS 15 inch are usted by all Research ressure of ASME Assure of ASME/AWWA CC 0 (ASME B16 10 COR PLAST em alves - (A OR PLAST em nd Size Lew 2 ^r 2-1 and NSF/ mage in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes with plast th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- th potable w ast into the 1 and NSF/ mes in contact S No. C8366 closed posi- ded in the ta- second ta- S No. C8366 closed posi- ded in the ta- second ta- S No. C8366 closed posi- ded in the ta- second ta- S No. C8366 closed posi- ded in the ta- S No. C8366 closed posi- ded in the ta- S No. C8366 closed posi- ded in the ta- second ta- S No. C8366 closed posi- ded in the ta- S	SOU ANSI Stan t with pote ON FEATUR ANSI Stan t with pote ON FEATUR ANSI Stan t with pote ON SFA43-2 C TUBIN C TUBIN C C C C C C C C C C C C C	14 Mechanical joi Tyton "ends ar or cast iron (C PVC ends are is MAINTENANC normal position buildup of tube tight shutoff it 3 3 COXVV-NL G (CTS) IN COXVV-NL G (CTS) IN Appendix 10.6 BT Appendix 10.6 BT	20 It ends are in acc d push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended <b>JET BY M</b> <b>JLET BY M</b> <b>VA Standa</b> ee identificat there applic conform to PSI 1/2" Flange er. Example	PART NUMBER 43-666W-NL 43-777W-NL Trd C800 (U able AWWVA Star	A SUBMITI I SUBMITI	ET the stem he valve bber ball 7ED 2833)
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord <b>THE RIGHT</b> <b>SUBMI</b> <b>Angle Ball</b> <b>PACK</b> . Solid Solid <b>PACK</b> . Solid Stain are of EPD Fluo brass Bevy gast sean Anti Integrad Stain Valve Size 1-1/2" 2" Note: Ford record All brass that The product Certified to Brass comp (ASTM B62 Padlock Value Stain Anti Integrad Stain Valve Size 1-1/2" 2" Note: Ford record All brass that The product Certified to Brass comp (ASTM B62 Padlock Value Stain Anti Includes EFF Suitable for Slotted hole <b>Optional:</b>	tor exceed requirem may be ordered in co- line and Approved b 250 p sig AWWA have 250 p sig WWA have 250 p sig WWA ing meets or exceeds tance with ANSI/AWW redance with ANSI/AW	A ctitudes of ANSVAW onfigurations while rated working p and FM rated w is requirements of WA C110/A21 116 4 Class 125 A ctitude class 125 A ctitu	WWA CS 15 inch are usted by all Research ressure of ASME Passure of ASME/AWWA CS 0 (ASME B16 10 0 (ASME B16 10 0 ASME B16 10 ASME B16 10 ASM	SON SFA43-> CTUBIN SFA43-> CTUBIN SFA43-> CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBIN CTUBI	14 Mechanical joi Tyton "ends ar or cast iron (C PVC ends are it MAINTENANC normal position buildup of tube tight shutoff it 3 3 COCVV-NL G (CTS) IN G (CTS) IN COCV-NL G (CTS) IN COCV-NL G (CTS) IN COCV-NL G (CTS) IN COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL COCV-NL	20 It ends are in acc d push-on ends a size duchle iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended <b>JET BY M</b> <b>JLET BY M</b> <b>VA Standa</b> ee identificat there applic conform to PSI 1/2" Flange er. Example ber	PART NumBER Meter con PART NumBER A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A3-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-777W-NL A4-	AWWA C111A21 with ANSVAWWA C111A21 with ANSVAWWA C111A21 with ANSVAWWA C of PVC or steel pips incude that is desk dirender the valve a year.	TED
through 12 valves mee 1/2 through 12 valves inderwriter's Laboratones. through 12 valves have 1/2 through 12 valves usion-bonded epoxy coat anged ends are in accord readed ends are in accord THE RIGHT SUBMIT Angle Ball PACK . Solid Sturn are d EPD Fluo brass Bevy gasl seal Anti- integ mac axia Pacl Stain Valve Size 1-1/2" 2" Note: Ford record All brass that The product Certified to Brass comp (ASTM B62 Padlock Witt Hole for attat 300 PSI wo Includes EF Suitable for Slotted hole Optional: Integ Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace Pace	tor exceed requirem may be ordered in co- line and Approved b 250 p sig AWWA have 250 p sig UU ing meets or exceed dance with ANSI/AWW redance with ASME B WAY TTTAL II Flange N JOINT FOR d one piece tee- dy stops allow S enclosed and pr M O-rings in the rocarbon-coated s ball eled EPDM rubic ket provides hyd friction washer- gral clamp conta hined grooves for restraint k Joint Nut ness steel screw SERVICE LINE SERVICE LINE SERVIC	ents of ANSVAW onfigurations whi y Factory Mutuar rated working p and FM rated w is requirements of WA C110/A21 116 4 Class 125 NFOR Meter Va COPPER thead and stu Oo motion and otected. e stem traulic contact wite ers "NL" ca tandard 6 do not com B584, UNS g valve in e is provid re style meter de shut offi rhead rotatiffer contact wite ers the inform o change with er Roc 2	WWA CS 15 inch are usted by all Research ressure of ASME ASME PRESSURE of ASME/AWWA CS 0 (ASME B16 10 COR PLAST em alves - (A OR PLAST em adves - (A A A A A A A A A A A A A A	SON SFA43-> TC TUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FEATUBIN FE	14 Mechanical joi Tyton "ends ar or cast iron (C PVC ends are it MAINTENANC normal position buildup of tube ught shutoff it 3 3 COCVV-NL G (CTS) IN G (CTS) IN COCV-NL G (CTS) IN Appendix In the second of the secon	20 Intends are in acc of push-on ends a size ductile iron suitable for use or E: Each valve sho This shoud be arculation or other is recommended a. Style) ILET BY M A. BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: BFA: B	PART NUMBER 43-666VV-NL 43-777V-NL rd C800 (U ation sea Meter con cof publication. n is current.	A SUBMIT ANS NO. C88 Indard C800 A SUBMIT ITEM(S) A SUBMIT ITEM(	38         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         11         12         13         14         15         15         16         16         17         18         18         19         11         11         12         12         13

Engineering & Design						
www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.						
Formerly Known as						
PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF ECCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM						
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CENSE ONAL CENSE ONAL CENSE ONAL CENSE ONAL CENSE ONAL CENSE ONAL CENSE ONAL CENSE COLLICENSED PROFESSIONAL ENGINEER LICENSE DPROFESSIONAL ENGINEER LICENSE NUMBER: 111543 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 - TBPLS Firm#: 10194550						
PRELIMINARY FOR FISCHER GARDENS UNIT 2 PLAT #24-11800144 SAN ANTONIO						

![](_page_35_Figure_0.jpeg)

And and a second	SIZE	AWWA C515 WORKING PRESSURE	UL WORKING PRESSURE	FM WORKING PRESSURE
147	14"-16"	250	250	250
	18"-24"	250	175*	
	30"-48"	250	•	
<b>1</b>	54	250†	-	

![](_page_35_Figure_3.jpeg)

Colliers						
Engineering & Design						
www.colliersengineering.com Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not						
be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.						
PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF						
FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM						
z						
DESCRIPTI						
DRAWN BY						
DATE						
REV						
CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CENSEO ONAL CENSEO ONAL CENSEO ONAL COLLENSED PROFESSIONAL ENGINEER LICENSED PROFESSIONAL ENGINEER LICENSED PROFESSIONAL ENGINEER LICENSE NUMBER: 111543 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 - TBPLS Firm#: 10194550						
PRELIMINARY						
FOR FISCHER GARDENS						
UNIT 2 PI_AT #2%_118001//						
1 LAI #24 11000144						
SAN ANTONIO BEXAR COUNTY TEXAS						
ColliersEngineering & Design& DesignSAN ANTONIO (KFW)3421 Paesanos Parkway San Antonio, TX 78231Phone: 210.979.8444 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 TBPLS Firm#: 10194550						
SCALE: DATE: DRAWN BY: CHECKED BY: MS CG PROJECT NUMBER: DRAWING NAME:						
314-60-01 OWDT3146001 SHEET TITLE: WATER DETAILS (SHEET 2 OF						
SHEET NUMBER:						
8.5						

![](_page_36_Picture_0.jpeg)

AVERAGE

O.D. (IN)

6.90

9.05

11,10

13.20

Call and all and and and all the

ANSI/AWWA C909

ASTM F477_

UL1285 6"12" PC 235

ANSI/NSF Standard 61

UL1285 6"-12" PC 235

JM Eagle[™] Installation Guide

20 feet laying length

AWWA C605

ASTM D1784 Cells Class 12454

MIN. T.

0.221

0.290

0.356

0.423

20.05 17.40 0.395 16.56 9½

O.D.

(IN)

APPROX.

ID (IN)

6.43

8.44

10.35

12.31

Pressure Class 235*

Pressure Class 165

SUBMITTAL AND DATA SHEET

PIPE SIZE

(IN)

6

8

10

12

16

* Check for availability.

UL 1285 Listed - 6"-12" PC 235

Product Standard:

Pipe Compound:

Certifications.

Pipe Length:

nstallation:

Gasket:

APPROX.

BELL O.D.

(IN)

8.53

10.83

13.43

15.72

Integral Bell Joint: ASTM D3139

![](_page_36_Picture_1.jpeg)

APPROX.

WEIGHT

(LBS/JNT)

69

117

169

239

300

STOP LINE

DISTANCE

MIN, E

(IN)

5 3/4

6 1/2

7 1/4

7 3/4

APPROX. WEIGHT (LBS/FT)

3.21

5.50

8.36

11.87

14,51

I.D. Inside Dameter

O.D. Outside Diameter

D⁹ Bell Outside Diameter

the end of spigot

E Distance between Assembly Mark to

T Wall Thickness

![](_page_36_Picture_2.jpeg)

SUBMITTAL AND DATA SHEET

PIPE SIZE AVERAGE O.D. NOM. I.D. (IN) (IN) (IN) PRES 4.80 4.39 4 6 6.90 6.31 8.28 8 9.05 11.10 10 10.16 12 13.20 12.08 PRESS 4.23 4 4.80 6.90 6.09 6 8 9.05 7.98 10 11.10 9.79 12 13.20 11.65 PRESS 4 4.80 4.07 6 6.90 5.86 8 9.05 7.68 9.42 10 11.10 12 13.20 11.20

Consult JM Eagle" for CSA and other listing availability prior to shipment. Note: *FM Approvals Pressure Class 150 psi for DR 18 and 200 psi for DR * Contact your JM eagleTM sales representative for location availability

![](_page_36_Figure_5.jpeg)

Gasket: Certifications:

Product Standard: ANSI/AWWA C900 Pipe Compound: ASTM D1784 Cells Class 12454 ASTM F477 Integral Bell Joint: ASTM D3139 ANSI/NSF Standard 61 UL Standard 1285 Pipe Length: 20 feet laying length AWWA C605 JM Eagle" Installation Guide

![](_page_36_Picture_8.jpeg)

20 L

![](_page_36_Picture_10.jpeg)

** Nominal depth, depth will vary by pressure class

Installation: ULTRA BLUE[™] PVCO

SUBMITTAL AND DATA SHEET

JM Eagle Building essentials for a better tomorrow

IPS 200 PSI

ASTM F-1483

PIPE SIZE (IN)	APPROX. BELL O.D. (IN)	AVERAGE O.D. (IN)	MIN. T. (IN)	APPROX. I.D.	STOP LINE DISTANCE MIN. E (IN)	APPROX. WEIGHT (LBS/FT)	APPROX. WEIGHT (LBS/JNT)
		·	Pressu	re Rating 200	·····	_	
6	8 1/8	6,625	0.182	6.24	4 1/2	2.5	51
8	10 1/4	8,625	0.236	8.13	4 1/2	4.2	84
10	12 1/4	10.750	0.295	10,13	5 1/2	6.4	127
12	14 3/4	12,750	0.349	12.02	5 1/2	8.9	179

![](_page_36_Figure_15.jpeg)

Right, On Time, All the Time.

![](_page_36_Picture_20.jpeg)

	MIN. T. (1N)	MIN. E (IN)	APPROX. D ⁹ (IN)	APPROX. WEIGHT (LBS/FT)			
sui	URE CLASS 165 psi (DR 25)						
	0.192	5.25	5.57	1.9			
	0.276	6.40	8.00	3.9			
	0.362	7.05	10.50	6.7			
	0.444	8.20	12.88	10.1			
	0.528	8.80	15.31	14.4			
SUF	URE CLASS 235 psi (DR 18)*						
	0.267	5.25	5.87	2.6			
	0.383	6.40	8.43	5.3			
	0.503	7.05	11.06	9.2			
	0.617	8.20	13.57	13.9			
	0.733	8.80	16.13	19.7			
SUF	RE CLASS 305 p	si (DR 14)*					
	0.343	5.25	6.17	3.2			
	0.493	6.40	8.87	6.7			
	0.646	7.05	11.63	11.6			
	0.793	8.20	14.27	17.6			
	0.943	8.80	16.97	25.1			

1111 141 11	
<b>O.</b> D.	I.D.

I D Inside Dameter O.D. Outside Diameter T Wa Thickness D Bell Outside Diameter E Distance between Assembly Mark to the end of spigot

![](_page_36_Figure_25.jpeg)

![](_page_36_Picture_26.jpeg)

Note: These dimensions are for estimating purposes only * Dimension given for Approx. Bell Diameter (BD) is for highest pressure class

![](_page_36_Picture_28.jpeg)

![](_page_36_Picture_29.jpeg)

	PIPE SIZE (IN)	AVERAGE O.D. (IN)	NOM. I.D. (IN)	MIN. T. (IN)	E, (IN)	E ₂ (1N)	APPROX. Dº (IN)	APPROX. WEIGHT (LBS/FT)
ľ		-		Rated psi 305	(DR 14)			
Ī	16	17.40	14.85	1.242	8 ½	9 ½	21.68	43.77
ſ				Rated 235 psi	(DR 18)			
	14	15.30	13.50	0.850	7 1/8	8 1/8	19.00	26.75
	16	17.40	15.35	0.967	8 ½	9 4/8	21.62	34.86
	18	19.50	17.20	1.083	8 3/8	9 1/8	24.22	48.95
[	20	21.60	19.06	1.200	9	1 0 1/8	26.85	54.22
[	24	25.80	22.76	1.433	10	11 2/8	32.06	77.97
	30	32:00	28.23	1.778	11 7/8	13 1/8	37.81	117.82
				Rated 200 psi	(DR 21)*			
	14	15.30	13.75	0.729	7 1/8	8 1/8	18.22	23.07
_	16	17.40	15.64	0.829	8 4/8	9 4/8	20.72	30.04
菁	18	19.50	17.53	0.929	8 3/8	9 1/8	23.22	37.27
100	20	21.60	19.42	1.029	9	10 1/8	25.72	46.71
	24	25.80	23.19	1.229	10	11 2/8	30.72	67.53
	30	32.00	28.77	1.524	11 7/8	13 1/8	38.10	103.71
	36	38.30	34.43	1.824	12 3/8	14 1/8	45.60	152.16
				Rated 165 ps	(DR 25)			
	14	15.30	14.00	0.612	7 1/8	8 1/8	17.94	19.48
	16	17.40	15.92	0.696	8 4/8	9 4/8	20.41	25.38
	18	19.50	17.85	0.780	8 3/8	9 1/8	22.87	31.99
	20	21.60	19.77	0.864	9	10 1/8	25.34	39.46
	24	25.80	23.61	1.032	10	11 2/8	30.27	56.98
	30	32.00	29.29	1.280	11 7/8	13 1/8	37.12	88.49
	36	38.30	35.05	1.532	12 3/8	14 1/8	44.43	128.41
	42	44.50	40.73	1.780	14 1/8	16 3/8	51.85	176.02
	48*	50.80	46.49	2.032	14 7/8	17 3/8	58.93	231.22
			_	Rated 125 psi	(DR 32.5)*	_		
	14	15.30	14.30	0.471	7 1/8	8 1/8	17.48	15.14
	16	17.40	16.27	0.535	8 4/8	9 4/8	19.88	19.63
	18	19.50	18.23	0.600	8 3/8	9 1/8	23.30	24.75
	20	21.60	20.19	0.665	9	10 1/8	24.38	30.54
	24	25.80	24.12	0.794	10	11 2/8	29.47	44.11
	30	32.00	29.91	0.985	11 7/8	13 1/8	36.55	68.45
	36	38.30	35.80	1.178	12 3/8	14 1/8	43.10	99.22
	42	44.50	41.60	1.369	14 1/8	16 3/8	50.93	135.49
	48	50.80	47.49	1.563	14 7/8	17 3/8	57.61	178.49

![](_page_36_Picture_31.jpeg)

## **Product Description:**

![](_page_36_Picture_33.jpeg)

### AWWA C-905 Municipal Water Pipe

North American Pipe's AWWA C-905 PVC product line is manufactured to meet the needs of modern municipal water distribution systems. With top quality raw materials and modern processing technology North American Pipe's C-905 pipe meets all industry standards in addition to our own rigorous quality control standards. North American Pipe's C-905 pipe utilizes Reiber style gaskets hroughout the entire product offering North American Pipe produces a broad range of CIOD pipe in DR-14, DR-18, DR-21, DR-25, DR-32.5, DR-41 and DR-51 classifications. Whether specifying or installing our pipe you can be assured that North American Pipe will provide the pipe _ "Right, On Time, All the Time" ____

### This product is made in accordance with the following specifications: AWWA C905 ASTM D1784 ASTM F477

PPI TR-3

Short Form Specification for North American Pipe Corporation AWWA C-905 Municipal Water Pipe

Water main transmission pipe shall be made in

accordance with AWWA C905 from a compound conforming to a cell classification of 12454 as defined by ASTM D1784. Integral bells shall

incorporate gaskets meeting the requirements of

assembled joint shall meet the requirements of

20 feet. The pipe and gasket must be tested and

ASTM F477 and be locked into the bell. The

approved for contact with potable water in

accordance with ANSI/NSF 61. The pipe and

gasket shall be listed by Underwriters Laboratory.

ANSI/NSF 14 UL 1285

ASTM D3139 ANSI/NSF 61

![](_page_36_Picture_40.jpeg)

![](_page_36_Picture_41.jpeg)

2801 Post Oak Blvd. | Suite 600 | Houston | TX | 77056 Phone: 713-840-7473 Toll Free 800-999-7473 Fax: 713-552-0087

Eng	gine	ers ering	5		
<b>www.colliersengineering.com</b> Copyright © 2024. Colliers Engineering & Design All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.					
Formerly Know	n as	KF ENGINEERS +			
PROTECT YOURSELF      ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE  FOR STATE SPECIFIC DIRECT PHONE NUMBERS					
	WWWW.CA			T	
EV DATE DRAWN BY DESCRIPTION					
REV					
CLAYTON J. LINNEY CLAYTON J. LINNEY 111543 CLAYTON J. LINNEY 111543 CENSED ONAL COLLINNEY CLAYTON J. LINNEY 111543 COLLINNEY CLAYTON J. LINNEY CLAYTON J. LINNEY CLAYTON J. LINNEY CLAYTON J. LINNEY COLLINE COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 - TBPLS Firm#: 10194550					
CLAYT TEXAS LICENSE LICENSE COLLIERS EN TBPE Firm#: F-1490	D PROFES D PROFES SE NUMBI GINEERIN 09 - 1	LINE SSIONAL E ER: 11154. G & DESIG BPLS Firm	NEY SN, INC. 5, 1019	R 4550	
CLAYT TEXAS LICENSE LICENS COLLIERS ENI TBPE Firm#: F-1490 PRF	CENS SONAL SONAL SONAL D PROFES D PROFE	LINI SSIONAL E ER: 11154: G & DESIG BPLS Firm	NEY NGINEE SN, INC. h#: 1019	R 4550	
CLAYT TEXAS LICENSE LICENS COLLIERS END TBPE Firm#: F-1490 PRF FISCHI U PLAT #	CLIMI FOF CLIMI	ARD ARD ARD ARD ARD ARD ARD	VY 24 NEY MINGINEE 3 3N, INC. 3 3N, INC. 3 3N, INC. 3 3N, INC. 3 3N, INC. 3 3N, INC. 3 3 3N, INC. 3 3 3N, INC. 3 3 3 N, INC. 3 3 3 N, INC. 3 3 3 N, INC. 3 3 3 N, INC. 3 3 3 N, INC. 3 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 3 N, INC. 3 N, INC. INC. 3 N, INC. 3 N, INC. 1 N, INC. N, INC. INC. INC. INC. INC. INC. INC. INC.	R 4550 <b>S</b>	
CLAYT TEXAS LICENSE LICENS COLLIERS END TBPE Firm#: F-1490 PRE FISCHI U PLAT #	SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL	ARD C 2 1180 ARD C 2 1180	VY 24 NEY MINE 3 SN, INC. 1019 0 EN 0 0 14	R 4550	
CLAYT TEXAS LICENSE LICENSE COLLIERS END TBPE Firm#: F-1490 PRF FISCHI U PLAT # SAN BEX	COLLEF	ARD CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC DUNT A CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC C CONIC C CONIC C CONIC C C CONIC C C C CONIC C C C C C C C C C C C C C C C C C C	VEY NGINEE Son, INC. 14: 1019 CO14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD14 OD	R 4550 S 4 N) 31 4 V, INC.	
CLAYT TEXAS LICENSE LICENSE COLLIERS END TBPE Firm#: F-1490 PRE FISCHI U PLAT # SAN BEX Colliers Engineering & Design	CLIMI GINEERIN D PROFES SE NUMB GINEERIN D PROFES SE NUMB GINEERIN D PROFES SE NUMB GINEERIN D PROFES SE NUMB GINEERIN TEXT	ARD CONIC ARD CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC C CONIC C CONIC C CONIC C CONIC C CONIC C CONIC C C CONIC C CONIC C C C CONIC C C C C C C C C C C C C C C C C C C	VEY INGINEE Son, INC. 14: 1019 OEN OIL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OUL4 OU	R 4550 S 4 N) S 4 N) S 1 4 N, INC.	
CLAYT TEXAS LICENSE LICENSE COLLIERS END TBPE Firm#: F-1490 PRF FISCHI U PLAT # SAN BEX SAN BEX SAN BEX SAN SAN BEX SAN SET TITLE NOJECT NUMBER: 314-60-01	SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL SONAL	ARD CONIC DUNT ARD CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC CONIC C	VEY NEY NGINEE 3 SN, INC. 1119 2 0 0 110 0 1194550 0 1194550 0 1194550 CHECKE C ET 3	R 4550 S 4 N) 31 4 N, INC.	

# 

## **ADS POTABLE WATER SERVICE TUBING (CTS)**

ADS Potable water service tubing (CTS) is a leader in today's potable water service market. Its flexibility and durability distinguish it from the competition and make it ideal for a variety of applications.

ADS CTS tubing is strong and resistant to many common causes of damage such as vibrations, surface loads and pressure surges.

## **APPLICATIONS:**

Residential & Commercial Water Service Well/Pump Water Systems Municipal Service Lines Farm & Ranch Water Systems

## FEATURES:

0

- Material conforms to ASTM D3350 requirements Certified to meet NSF 14/61 standard
- Durable plastic material stands the test of time
- Flexibility makes it ideal for a variety of projects Strength withstands weather and the human element
- Incremental footage markers printed every 2 feet
- throughout each coil length

### Light weight Chemically resistant

installation and more.

 Consistent outside diameter regardless of wall thickness or pressure rating

## **BENEFITS:**

- Resistant to rot or corrosion Fast and easy to install
- Easy installation provides cost-efficiency
- Flexible lengths can be installed in uneven terrain Available in many lengths

ADS Service: ADS representatives are committed to providing you with the answers to all your questions, including specifications, and

The Most Advanced Name in Drainage Systems

## **DS Poly**Flex

![](_page_37_Picture_20.jpeg)

![](_page_37_Picture_21.jpeg)

P	SDR	9 (200 psi) 3
3/4**	1"	11/4"
0.875 ±0.004	1.125 ±0.005	1.375 ±0.0
0.097 +0.01 (2.5 +0.25)	0.125 +0.012 (3.2 +0.30)	0.153 +0.0 (3.9 +0.3
200 (1379)	200 (1379)	200 (1379)
46 ±2	78 ±3	125 ±4
(151 +7)	(256 ±10)	(410 ±1

![](_page_37_Picture_32.jpeg)

The Smith-Blair Quantum[®] The coupling's 5/8" bolts are Blair's Flexi-Coat[®] epoxy system Coupling accommodates up to 1.65- quick and easy to install because no maintains superior flexibility as the inches of Pipe O.D. differential with a disassembly is required. single flange and gasket.

sleeve and follower flanges provide deflection (3° per end) and makes a protection over a wide temperature the tensile strength and corrosion leak-resistant joint that allows for range and can be shipped with resistance that is necessary for limited line movement due to minimal damage. couplings to withstand the expansion and contraction.

lives.

punishment they must endure during The Quantum coupling comes and all cast ductile parts, the installation and throughout their long standard with fusion bonded NSF 61 Quantum[®] is the proven answer for

product is installed on the pipe. The Quantum also provides for Additionally, this durable epoxy The Quantum's tough ductile iron misalignment and settlement coating provides superior corrosion

> With a 250 PSI working pressure approved epoxy coating. Smith- WIDE rangeability couplings.

WARNING THESE PRODUCTS DO NOT RESTRAIN AXIAL PIPE OR PRODUCT MOVEMENT

Material Specifications High Strength Ductile Iron ASTM A536 High Strength Ductile Iron ASTM A536 Flange Nitrile (Buna-N) NSF 61 approved Gasket Fusion Bonded Flexi-Coat[®] Epoxy per AWWA Coating C213 HSLA steel per ANSI A21 11 (AWWA C111) with

Flexi-Coat epoxy finish. Stainless Steel optional Heavy Hex HSLA steel per ANSI A21.11 with Fluoropolymer Coating (to prevent galling). Material specifications subject to change,

![](_page_37_Picture_44.jpeg)

Nom. Size (in.)	Q.D. Range (in.)	With Epoxy Coated Alloy Bolts & Nuts	With St Bol	
		Catalog Number	Cata	
1 1/2	1.81 - 2.28	461-01810228-000	461-01	
2	2.34 - 2.85	461-02340285 000	461-02	
2 1/2	2.84 - 3.35	461-02840335-000	461-02	
3	3.46 - 4.21	461-03460421-090	461-0.	
4	4.46 - 5.60	461-04460560-000	461-04	
6	6.54 - 7.65	401-06540765-000	461-06	
8	8.54 - 9.85	461-08540985-000	461-08	
10	10.05 - 12.20	461-10651220-000	461-10	
12	12 75 14 40	461 10751140 000	1	

Nom. Size (in.)	O.D. Bange (in )	With Epoxy Coated Alloy Bolts & Nuts	With St Bot
()	in things (in.)	Catalog Number	Catal
4	4.46 - 5.60	462-04460560-000	462-04
6	6.54 - 7.65	462-06540765-000	462-06
8	8.54 - 9.85	462-08540985-000	462-08
10	10.65 - 12.20	462-10651220-000	462-10
12	12.75 - 14.40	462-12751440-000	462-12

Physical Address	Mailing
Smith-Blair, Inc.	Smith-E
30 Globe Ave.	PO B
Texarkana, AR 71854	Texarkana

 $\bigcirc$ 

BEXAR COUNTY TEXAS									
<b>Colliers</b> Engineerin & Design	g _{col}	SAN ANTONIO (KFW) 3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 COLLIERS ENGINEERING & DESIGN, INC. TBPE Firm#: F-14909 TBPLS Firm#: 10194550							
SCALE: DATE	:	DRAWN BY: MS	CHECKED BY: CG						
PROJECT NUMBER: 314-60-01	DRAWIN OWDT	DRAWING NAME: OWDT3146001							
SHEET TITLE: WATER DETAILS (SHEET 4 OF 5)									
SHEET NUMBER:									

8.7

![](_page_38_Picture_0.jpeg)

estrainer (UFR1390-C-xx-U style)       Image: Construction of the standard of the sta	
SERIES 1390-C RESTRAINT DEVICE FOR CS05 PVC PIPE BELL AND SPIGOT JOINTS CAST SIZES 14" - 36"         1300 SPLIT RESTRAINER         I 300 ASSEMBLY         I 300 ASSEMBLY         I 300 ASSEMBLY         I 300 SPLIT RESTRAINER         I 300 ASSEMBLY         I SOURT Colspan="2">I SOURT Colspan="2">I SOURT Colspan="2">I SOURT Colspan="2"         I SOURT Colspan="2"         I SOURT Colspan="2"         I SOURT Colspan="2"         I SOURT Colspan="2" <td colspan<="" th=""></td>	
CAST SIZES 14" - 36"         1300 SPLIT RESTRAINER         I 300 ASSEMBLY         I 300 LINIT (SPLIT RNS)         I 300 LINIT (SPLIT RNS)         CAMPRIC BOLTS         I 300 LINIT (SPLIT RNS)         CAMPRIC BOLTS         I 300 LINIT (SPLIT RNS)         CAMPRIC BOLTS         I SUBLE 14" - 36"	
PVC Pre-write       CAMPRIC BOLTS         PVC Pre-write       CAMPRIC BOLTS         PVC Pre-write       CAMPRIC BOLTS         PVC Pre-write       CAMPRIC BOLTS         PVC Pre-write       Stream Strea	
NX       Output	
$\frac{1}{1260} \underbrace{(1)}_{PT1300-C164} \underbrace{(2)}_{P13(5)} \underbrace{(2)}_{P13($	
BC MN       CLAMPING BOLTS         CLAMPING BOLTS       CLAMPING BOLTS         PYC Pres MT       CLAMPING BOLTS         PYC Pres MT       B         Marcine Control       A presex         Marcine Control	
PVC Pipe         PVC Pipe BELL         GRIP Pipe           SPIC Difference         SPIC Pipe With Pipe         SPIC Difference         GRIP Pipe           B         OP Pipe OD         A         A PROX MAX QITY         Size         BC Max         BC Max         BC Min         APPROX.         /// Susar           OP         Cataboo No.         A         Proc No.         Max         QITY.         Size         BC Max         BC Min         APPROX.         // Susar           OP         Cataboo No.         A         Proc No.         Max         QITY.         Size         BC Max         BC Min         APPROX.         // Susar           OP         Cataboo No.         A         Proc No.         Max         QITY.         Size         BC Max         BC Min         APPROX.         // Susar           12.00         UFR1390C-164.U         4         24-172         24'         6         34' x 30'         1.1'8' x 7'         24.75'         22.50'         2050'         147'           12.00         UFR1390C-264.U         5'         28-11/16'         28' 12'         1'x 48''         12'         1'18'' x 5'' 22'         20'''         20''''         20'''''         20''''''         20'''''''         20''''''         20''''''	
Charmon Di Pie CD         PVC Pipe with         Di Pie CD         OD CANTAGO NO.         OD CANTAGO NO. <th colsp<="" td=""></th>	
PVC Pier wm         A         B         C         Restraining Roos         CLAMPRIS Bolts         BC Max         BC Max         BC Max         Approx         JSUBAT           DD         Caraco No.         4         Approx         Max         D         Size         Qrv         Qrv         Size         Size	
Struc 1380-C         A         Approx         Cx         Other         Struc         Struc         BC Max         BC Max         P         Struc         To Struc         BC Max	
17.40       UFR1390-C-16-U       4*       244/16*       28*       6       3/4* x 30*       8       7/8* x*       22.50*       20.50*       147         19.50       UFR1390-C-16-U       5*       28-11/16*       28*       8       3/4* x 30*       8       1*x 7*       22.50*       20.60       147         21.60       UFR1390-C-16-U       5*       28-3/16*       8       3/4* x 30*       8       1*x 7*       22.50*       20.60       147         21.60       UFR1390-C-20-U       5*       33-7/8*       28*       12       1/4* x 36*       8       1+18* x 5-1/2*       31.50*       29.50*       406         25.00       UFR1390-C-24-U       5*       33-7/8*       28*       12       1*x 48*       12       1-1/8* x 5*       12       15.0*       29.50*       406       33.0*       29.50*       406       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*       36.18*	
Example       Dirk 1390-C-24-U       5'       33//8'       28'       12       14'' x 36''       12       1-1/8'' x 5''       38.18''       36.18''       600         38.30       UFR1390-C-36-U       7'       48-1/4''       38''       12       1'' x 48''       12       1-1/8'' x 5''       38.18''       600       600         38.30       UFR1390-C-36-U       7''       48-1/4''       38''       12       1'' x 48''       12       1-1/8'' x 5''       45.50''       44.00''       675         FEATURES         Ide '' A 36'' Sizes: Cast Ductile Iron per ASTM A536 Grade 65-45-12         Side Clamping Bolts and Nuts         Rods (included) - High strength, Iow alloy steel per ANSI / AWWA C111/A21.11         Rated at full rated pressure of any class of C905 PVC Pipe, minimum 2:1 safety factor         Casting manufactured in the U.S.A.         Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availabil specifications, are subject to change without notice. Please verify that your product information is current.         The Ford Meter Box Company, Inc.       P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443       Submitted By:         Phone: 260-563-3171 / Fax: 800-826-3487         Overseas Fax	
FEATURES         14" - 36" Sizes: Cast Ductile Iron per ASTM A536 Grade 65-45-12         Side Clamping Bolts and Nuts         Rods (included) - High strength, low alloy steel per ANSI / AWWA C111/A21.11         Rated at full rated pressure of any class of C905 PVC Pipe, minimum 2:1 safety factor         Casting manufactured in the U.S.A.         Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availabil specifications, are subject to change without notice. Please verify that your product information is current.         Image: Proof Meter Box Company, Inc.         P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443         Phone: 260-563-3171 / Fax: 800-826-3487         Overseas Fax: 260-563-0167         http://www.fordmeterbox.com         01/31/14	
FEATURES         14" - 36" Sizes: Cast Ductile Iron per ASTM A536 Grade 65-45-12         Side Clamping Bolts and Nuts         Rods (included) - High strength, low alloy steel per ANSI / AWWA C111/A21.11         Rated at full rated pressure of any class of C905 PVC Pipe, minimum 2:1 safety factor         Casting manufactured in the U.S.A.         Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availabil specifications, are subject to change without notice. Please verify that your product information is current.         Image: Proverseas Fax: 280-563-3171 / Fax: 800-826-3487         Overseas Fax: 280-563-0167         http://www.fordmeterbox.com         01/31/14	
Casting manufactured in the U.S.A. Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availabil specifications, are subject to change without notice. Please verify that your product information is current. The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 http://www.fordmeterbox.com 01/31/14	
Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availabil specifications, are subject to change without notice. Please verify that your product information is current. The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 http://www.fordmeterbox.com 01/31/14	
The Ford Meter Box Company, Inc. P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443 Phone: 260-563-3171 / Fax: 800-826-3487 Overseas Fax: 260-563-0167 http://www.fordmeterbox.com 01/31/14	
ries A   Price List Key	
b create List Price, use the Base Price on Black Body & Solid Black Lid in each ategory and add the desired style and or color to the Base Price.	
Color Key Color Body Only Only Option Key Description Cost	
1 Black \$0.00 \$0.00 A AMR Pad Locator Add \$5.95	
1         Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5.95           2         Green         \$ 0.90         \$0.85         C         Cast Iron Reader         Add \$5.70           3         Blue         \$ 0.90         \$0.85         D         Bolt Down (Add to Body Only)         Add \$1.95	
I         Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5.95           2         Green         \$0.90         \$0.85         C         Cast Iron Reader         Add \$5.70           3         Blue         \$0.90         \$0.85         D         Bolt Down (Add to Body Only)         Add \$1.95           4         Gray         \$1.70         \$1.65         E         Rebar Installed         Add \$2.25           5         Purple         \$1.45         \$1.40         K         Plastic Key Lock         Add \$5.00	
I         Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5.95           2         Green         \$0.90         \$0.85         C         Cast Iron Reader         Add \$5.70           3         Blue         \$0.90         \$0.85         D         Bolt Down (Add to Body Only)         Add \$1.95           4         Gray         \$1.70         \$1.65         E         Rebar Installed         Add \$2.25           5         Purple         \$1.45         \$1.40         K         Plastic Key Lock         Add \$5.00           6         Sand         \$1.70         \$1.65         M         Magnet Detector         Add \$2.10           7         Red         N/A         \$6.85         N         Houston Key Lock         Add \$5.00	
1Black\$0.00\$0.00AAMR Pad LocatorAdd \$5.952Green\$0.90\$0.85CCast Iron ReaderAdd \$5.703Blue\$0.90\$0.85DBolt Down (Add to Body Only)Add \$1.954Gray\$1.70\$1.65ERebar InstalledAdd \$2.255Purple\$1.45\$1.40KPlastic Key LockAdd \$2.106Sand\$1.70\$1.65MMagnet DetectorAdd \$2.107RedN/A\$6.85NHouston Key LockAdd \$1.407RedN/A\$6.85NHouston Key LockAdd \$1.408Flastic ReaderAdd \$1.40TMolded Touch Read HoleAdd \$1.30	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$1.95         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         7       Molded Touch Read Hole       Add \$1.40       T       Molded Touch Read Hole       Add \$1.30         0       Small AMR Pad Locator       Add \$1.30       U       Small AMR Pad Locator       Add \$2.10	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$1.95         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$2.10         7       Red       N/A       \$ 6.85       N       Houston Key Lock       Add \$1.40         7       Red       N/A       \$ 6.85       N       Houston Key Lock       Add \$1.40         7       Red       N/A       \$ 6.85       N       Houston Key Lock       Add \$1.40         7       Def N/A       \$ 6.85       N       Houston Key Lock       Add \$1.40         7       Def N/A       Def Seator       Add \$1.40       T       Molded Touch Read Hole       Add \$1.30         0       Def W1200.1. LID       Drilled Touch Read Hole       Add \$2.10       Ma	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iran Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$1.95         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$5.00         8       Plastic Reader       Add \$1.40       T       Molded Touch Read Hole       Add \$1.40         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         9       Small AMR Pad Locator       Add \$1.40       T       Molded Touch Read Hole       Add \$1.40         10       Small AMR Pad Locator       Add \$2.10       T       Molded Touch Read Hole       Add \$2.10         Id Options	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$1.95         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$5.00         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         1       Molded Touch Read Hole       Add \$1.40       T       Molded Touch Read Hole       Add \$1.40         1       Options       DFW1200.1. LD       Small AMR Pad Locator       Add \$2.10       Matking       Black         1       Top View       Top View       Free n       Black       Gree n       Gree n	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$5.70         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$5.00         6       Sand       \$1.70       \$1.65       F       Rebar Installed       Add \$5.00         6       Sand       \$1.70       \$1.65       F       Rebar Installed       Add \$5.00         7       Red       N/A       \$6.85       M       Magnet Detector       Add \$5.00         8       Plastic Reader       Add \$1.40       Add \$1.40       Add \$1.40         9       Small AMR Pad Locator       Add \$1.40       Add \$1.30         0       Small AMR Pad Locator       Add \$1.40       Add \$1.40         10       Small AMR Pad Locator       Add \$2.10         Id Options         Marking Lid Color         Marking Lid Color         Water or Biack, Blue, Green, Gr	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$5.70         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$5.00         8       Plastic Reader       Add \$1.40       T       Moled Touch Read Hole       Add \$1.40         0       Small AMR Pad Locator       Add \$3.15       Z       Drilled Touch Read Hole       Add \$2.10         10       Options	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Bhee       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$5.70         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$2.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$2.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         U       Small AMR Pad Locator       Add \$1.40       K       Plastic Reader       Add \$1.40         U       Small AMR Pad Locator       Add \$1.40       K       U       Small AMR Pad Locator       Add \$1.40         U       Small AMR Pad Locator       Add \$1.40       K       Matking       Lid Color         Vater       To View       Fe/Vi200.1, LiD       E       Small AMR Pad Locator       Add \$2.10         DifWi200.1, LiD       FW1200.1, LiD       Base Price       Bla	
1       Black       \$0.00       \$0.00       A       AMR Pad Locator       Add \$5.95         2       Green       \$0.90       \$0.85       C       Cast Iron Reader       Add \$5.70         3       Blue       \$0.90       \$0.85       D       Bolt Down (Add to Body Only)       Add \$5.70         4       Gray       \$1.70       \$1.65       E       Rebar Installed       Add \$2.25         5       Purple       \$1.45       \$1.40       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       K       Plastic Key Lock       Add \$5.00         6       Sand       \$1.70       \$1.65       M       Magnet Detector       Add \$5.00         7       Red       N/A       \$6.85       N       Houston Key Lock       Add \$1.40         7       Molded Touch Read Hole       Add \$1.40       T       Molded Touch Read Hole       Add \$1.40         0       Small AMR Pad Locator       Add \$1.40       T       Molded Touch Read Hole       Add \$1.40         0       DfW1200.1. LID       DfW1200.1. LID       Back Black       Black       Black         0       BfW200.1. LID       DfW1200.1. LID       Base Price       Mater	
I         Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5.95           3         Blue         \$0.90         \$0.85         C         Cast Iron Reader         Add \$5.70           4         Green         \$0.90         \$0.85         D         Bolt Down (Add to Body Only)         Add \$5.70           5         Purple         \$1.45         \$1.40         K         Plastic Key Lock         Add \$5.00           6         Sand         \$1.70         \$1.65         K         Plastic Key Lock         Add \$5.00           7         Red         N/A         \$6.85         N         Houston Key Lock         Add \$1.40           1         Molded Touch Read Hole         Add \$1.00         T         Molded Touch Read Hole         Add \$1.00           0         Smail AMR Pad Locator         Add \$1.00         T         Molded Touch Read Hole         Add \$1.00           0         Smail AMR Pad Locator         Add \$1.00         T         Molded Touch Read Hole         Add \$1.00           0         Corrent         FW1200.1 LID         Smail AMR Pad Locator         Add \$2.10         Mater of Green Read Hole         Add \$2.10           0         FW109.1 LID         Gree Nee Corren Hole         Base Price	
1     Black     \$0.00     \$0.00     A     AMR Pad Locator     Add \$5.95       2     Green     \$0.90     \$0.85     C     Cast Iron Reader     Add \$5.70       3     Blue     \$0.90     \$0.85     D     Bolt Down (Add to Body Only)     Add \$5.70       4     Greyn     \$1.70     \$1.65     K     Plastic Key Lock     Add \$5.20       6     Sand     \$1.70     \$1.65     M     Magnet Detector     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$1.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$1.00       7     Medde Touch Read Hole     Add \$1.00     T     Medd \$1.00     T     Medd \$1.00       7     Medde Touch Read Hole     Add \$1.00     T     Medd \$1.00     T     Medd \$1.00       8     Plastic Reader     Add \$1.00     T     Medd \$1.00     T     Medd \$1.00       10     Options     Item Description     Back Blue     Medd \$1.00     Medd \$1.00       10     Figure Colored Touch Read Hole     Add \$1.00     Black     Green       10     Figure Colored Touch Read Hole     Add \$1.00     Black     Black       10     Figure Color	
1     Black     \$0.00     \$0.00     A     AMR Pad Locator     Add \$5.95       2     Green     \$0.90     \$0.85     C     Cast tron Reader     Add \$5.95       3     Blue     \$0.90     \$0.85     D     Bolt Down (Add to Body Only)     Add \$5.25       4     Grey     \$1.70     \$1.65     K     Plastic Key Lock     Add \$5.00       6     Sand     \$1.70     \$1.65     N     Magnet Detector     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$1.40       8     Plastic Reader     Add \$1.40     Nd \$6.31.60     Nd \$6.31.60       9     DFWIDO.LLD     Small AMR Pad Locator     Add \$3.30       10     Options     Imack     Madd \$1.40       11     Current     Nd \$6.85     Reclam       12     Drilled Touch Read Hole     Add \$2.10       13     Detector     Reclam     Reclam       14     Goren	
I         Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5.95           3         Blue         \$0.90         \$0.85         C         Cast Iron Reader         Add \$5.70           4         Green         \$0.90         \$0.85         D         Bolt Down (Add to Body Only)         Add \$5.25           5         Purple         \$1.45         \$1.40         E         Return Installed         Add \$5.00           6         Sand         \$1.70         \$1.65         K         Plastic Key Lock         Add \$5.00           7         Red         NA         \$6.85         N         Houston Key Lock         Add \$5.10           8         Plastic Red Hole         Add \$1.40         Stato         Add \$1.40         Stato           10         Small AMR Pad Locator         Add \$1.40         Stato         R         Plastic Red Hole         Add \$1.40           10         Small AMR Pad Locator         Add \$1.30         Red \$1.00         Red \$1.00 <t< td=""></t<>	
Black     \$0.00     \$0.00     A     AMR Pad Locator     Add \$5.95       2     Green     \$0.90     \$0.85     C     Cast iron Reader     Add \$5.70       3     Blace     \$0.30     \$0.85     C     Cast iron Reader     Add \$5.70       4     Grey     \$1.70     \$1.65     Bit Down (Add to Body Only)     Add \$5.00       5     Purple     \$1.45     \$1.40     K     Plastic Key Lock     Add \$5.00       6     Sand     \$1.70     \$1.65     N     Magnet Detector     Add \$5.00       7     Red     N/A     \$6.85     N     Houston Key Lock     Add \$5.00       7     Moldel Touch Read Hole     Add \$3.10     N     Add \$3.10     N       7     Moldel Touch Read Hole     Add \$3.10     N     N     N       8     Snall AMR Pad Locator     Add \$3.10     N     N     N       9     DefW1200.1 LID     U     Snall AMR Pad Locator     Add \$3.10       10     Snall AMR Pad Locator     Add \$3.10     N     N     N       10     Snall AMR Pad Locator     Add \$3.10     N     N     N       10     Snall AMR Pad Locator     Add \$3.10     N     N     N       10     Snall CA	
Black         \$0.00         \$0.00         A         AMR Pad Locator         Add \$5:95           3         Blue         \$0.30         \$0.85         C         Cast low Reader         Add \$5:70           4         Grey         \$1:70         \$1:65         Bolt Down (Add to Body Only)         Add \$5:06           5         Purple         \$1:45         \$1:40         K         Plastic Key Lock         Add \$5:00           6         Sand         \$1:70         \$1:65         N         Houston Key Lock         Add \$5:00           7         Red         N/A         \$6:65         N         Houston Key Lock         Add \$5:00           8         Plastic Reader         Add \$5:00         R         Plastic Reader         Add \$5:10           9         Differ Touch Read Hole         Add \$5:10         N         Houston Key Lock         Add \$5:10           10         Differ Touch Read Hole         Add \$5:10         N         Molded Touch Read Hole         Add \$5:10           10         Differ Touch Read Hole         Add \$5:00         N         Reader         Add \$5:00           10         Differ Touch Read Hole         Add \$5:00         N         Reader         N         Add \$5:00           10	

					11:	Pť		1		
	Engineering									
Copyri	& Design www.colliersengineering.com									awing
and al whom be cop	and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Colliers Engineering & Design.									
For	PROTECT YOURSELF ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S CUPERCE ANAMULEDE IN ANY CATE								OF ISON	
FC	FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM								≡ S	
DESCRIPTION										
DRAWN BY										
REV DATE		$\left  \right $								
	STATE OF TELE									
CLAYTON J. LINNEY 111543										
	Clayfor hun									
	5/15/224 CLAYTON J. LINNEY TEXAS LICENSED PROFESSIONAL ENGINEER									
ТВР	COI E Firi	LLIERS m#: F-1	ENC 1490	GINE )9	ERIN - T	G & I BPLS	DESIC Firm	5N, IN 1#: 1(	NC. 01945	550
		P	RE	LI	MI FOR	NA	RY	7		
	FIS	SCH	H J س	ER JN	G II]	AF 2	RD	E	NS	
	PLAT #24-11800144									+
	SAN ANTONIO BEXAR COUNTY TEXAS									
	ColliersSAN ANTONIO (KFW)Bengineering & Design3421 Paesanos Parkway San Antonio, TX 78231 Phone: 210.979.8444 Colliers ENGINEERING & DESIGN, INC. TBPLS Firm#: F14909 TBPLS Firm#: 10194550								) NC.	
SCALE	SCALE: DATE: DRAWN BY: CHECKED BY: MS CG PROJECT NUMBER: DRAWING NAME: 314-60-01 OWDT3146001								BY:	
SHEET	SHEET TITLE: WATER DETAILS (SHEET 5 OF 5)							)F		
SHEET	SHEET NUMBER: 8.8									

- OF THE SITE BOUNDARY.
- DIFFERENT BEST MANAGEMENT PRACTICE AND WILL SHOW IT ON THIS PLAN WITH NOTATION IN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE

- TO BE DISTURBED ON THIS PLAN. IF ADDITIONAL VEGETATED AREAS ARE DISTURBED, THEY SHOULD BE PROTECTED WITH APPROPRIATE BEST MANAGEMENT PRACTICES UNTIL THE AREAS HAVE BEEN STABILIZED AS PER THE SPECIFICATIONS OF THE SWPPP. THE AREAS OF THIS ADDITIONAL SOIL DISTURBANCE AND THE MEASURES USED SHOULD BE SHOWN ON THE SITE PLAN AND NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.
- THE SPECIFICATIONS OF THE SWPPP. THE CONTRACTOR MAY MODIFY THE CONTROLS AS AND THE SITE PLAN AND NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.
- EQUIPMENT AND STORAGE ARE TO BE FIELD DETERMINED. LOCATIONS SHALL BE UPDATED ON THIS PLAN.

- PER THE SWPPP AND PROJECT SPECIFICATIONS PRIOR TO REMOVAL OF ANY BMP'S AND/OR PRIOR TO FILING A NOTICE OF TERMINATION (NOT).
- HAVE BEEN STABILIZED PER SWPPP AND PROJECT SPECIFICATIONS. THIS PHASING SHOULD BE NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.

- FROM THE APPROPRIATE CONSTRUCTION DOCUMENTS.
- DEMONSTRATE COMPLIANCE WITH THE TPDES STORMWATER POLLUTION PREVENTION PLAN REGULATIONS ONLY
- STORMWATER POLLUTION PREVENTION PLAN AND COMPLYING WITH THE REGULATIONS CONTAINED WITHIN IT.

![](_page_39_Figure_17.jpeg)

![](_page_39_Picture_20.jpeg)

![](_page_39_Figure_21.jpeg)

![](_page_39_Figure_29.jpeg)

- OF THE SITE BOUNDARY.
- DIFFERENT BEST MANAGEMENT PRACTICE AND WILL SHOW IT ON THIS PLAN WITH NOTATION IN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE

- TO BE DISTURBED ON THIS PLAN. IF ADDITIONAL VEGETATED AREAS ARE DISTURBED, THEY SHOULD BE PROTECTED WITH APPROPRIATE BEST MANAGEMENT PRACTICES UNTIL THE AREAS HAVE BEEN STABILIZED AS PER THE SPECIFICATIONS OF THE SWPPP. THE AREAS OF THIS ADDITIONAL SOIL DISTURBANCE AND THE MEASURES USED SHOULD BE SHOWN ON THE SITE PLAN AND NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.
- THE SPECIFICATIONS OF THE SWPPP. THE CONTRACTOR MAY MODIFY THE CONTROLS AS AND THE SITE PLAN AND NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.

- AND/OR PRIOR TO FILING A NOTICE OF TERMINATION (NOT).
- HAVE BEEN STABILIZED PER SWPPP AND PROJECT SPECIFICATIONS. THIS PHASING SHOULD BE NOTED WITHIN THE MODIFICATIONS SECTION WITH THE SIGNATURE AND DATE OF THE RESPONSIBLE PARTY.

- FROM THE APPROPRIATE CONSTRUCTION DOCUMENTS.
- DEMONSTRATE COMPLIANCE WITH THE TPDES STORMWATER POLLUTION PREVENTION PLAN REGULATIONS ONLY
- STORMWATER POLLUTION PREVENTION PLAN AND COMPLYING WITH THE REGULATIONS CONTAINED WITHIN IT.

![](_page_40_Figure_17.jpeg)

![](_page_40_Figure_28.jpeg)

![](_page_40_Figure_29.jpeg)

![](_page_41_Figure_0.jpeg)

RESIDENTIAL LOTS = 148

![](_page_41_Figure_17.jpeg)

![](_page_41_Figure_20.jpeg)

NOTE: DO NOT SCALE DRAWINGS FOR CONSTRUCTION.