

CRYSTAL CLEAR SPECIAL UTILITY




KINGSBURY ROAD PIPELINE PHASE II

Sheet List Table	
Sheet Number	Sheet Title
G0.0	COVER SHEET
G1.0	GENERAL NOTES AND LEGEND
G1.1	KEY MAP AND ALIGNMENT DATA TABLE
G1.2	CONTROL POINTS
WM1.0	STA. 100+00 TO STA. 107+00
WM1.1	STA. 107+00 TO STA. 116+00
WM1.2	STA. 116+00 TO STA. 124+00
WM1.3	STA. 124+00 TO END
WM1.4	RAILROAD AND GRAVEL PIT PROFILES
WM1.5	WEST AND KINGSBURY RD PROFILES
D1.0	MISCELLANEOUS DETAILS
D1.1	MISCELLANEOUS DETAILS 2
D1.2	TXDOT TRAFFIC CONTROL DETAILS
D1.3	TREE PROTECTION DETAILS
D1.4	EROSION CONTROL DETAILS



VICINITY MAP
NOT TO SCALE



M&S ENGINEERING
POWER & UTILITY ENGINEERS

TxEng Firm #F-1394 -
TBPELS Firm #10169800

MAIN OFFICE
P.O. BOX 970
SPRING BRANCH,
TEXAS 78070
PHONE # (830) 228-5446
FAX # (830) 885-2170

BRANCH OFFICE
376 LANDA STREET
NEW BRAUNFELS,
TEXAS 78130

SHEET
G0.0

GENERAL NOTES:

- WHERE SURVEY WORK HAS BEEN INCLUDED, THE HORIZONTAL DATUM USED IS NAD 83 TEXAS STATE PLANE COORDINATES. THE BENCHMARK DATUM USED IS SOUTH CENTRAL ZONE NAVD 88 DATUM.
- ALL PROPERTY CORNERS, MONUMENTS, AND BENCHMARKS WITHIN THE LIMITS OF CONSTRUCTION SHALL BE PROTECTED BY THE CONTRACTOR. ANY SURVEY MARKERS DESTROYED DURING CONSTRUCTION SHALL BE REPLACED BY THE CONTRACTOR, THROUGH USE OF A PROFESSIONAL SURVEYOR REGISTERED IN THE STATE OF TEXAS, AT NO ADDITIONAL COST TO THE OWNER.
- CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE RULES AND REGULATIONS OF OSHA, EPA, AND ANY OTHER FEDERAL, STATE, OR LOCAL REGULATORY AGENCIES THAT MAY APPLY.
- CALL 811 SHALL BE NOTIFIED A MINIMUM OF TWO BUSINESS DAYS PRIOR TO ANY EXCAVATION.
- IF ACCESS TO PRIVATE PROPERTY IS AFFECTED, SUCH ACCESS SHALL BE RESTORED AT THE END OF EACH WORK DAY.
- THE CONTRACTOR SHALL ENSURE THAT ALL REQUIRED PERMITS ARE IN PLACE PRIOR TO CONSTRUCTION AND THAT COPIES OF ALL PERMITS ARE RETAINED ON SITE AT ALL TIMES.
- THE LOCATIONS OF EXISTING UTILITIES, PAVEMENT, TREES/SHRUBS, AND OTHER FEATURES ARE APPROXIMATE ONLY. EXISTING CONDITIONS SHALL BE FIELD VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. OWNER OF EXISTING MATERIALS AND THE CONTRACTOR SHALL NOTIFY THE ENGINEER AND OWNER OF ANY DISCREPANCIES PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS. NO ADDITIONAL PAYMENT WILL BE MADE UNLESS SPECIFICALLY IDENTIFIED FOR PAYMENT IN THE CONTRACT DOCUMENTS AND PRIOR APPROVAL IS GIVEN BY OWNER AND ENGINEER. THE CONTRACTOR, SHALL AT THEIR EXPENSE AND COST, CONSTRUCT ALL IMPROVEMENTS IN SUCH A MANNER THAT WILL PROTECT ALL EXISTING UNDERGROUND UTILITIES.
- EXISTING FEATURES IMPACTED DURING CONSTRUCTION, INCLUDING BUT NOT LIMITED TO DRIVEWAYS, CURBING, LANDSCAPING, GROUND COVERS, MAILBOXES, FENCING, SIGNAGE, AND EXISTING UTILITIES AND SERVICES SHALL BE REPLACED IN KIND. DRIVEWAYS IMPACTED SHALL BE RECONSTRUCTED TO MATCH PRECONSTRUCTION GRADING.
- CONTRACTOR SHALL COORDINATE ALL IMPACTS WITH PROPERTY OWNERS. THE CONTRACTOR SHALL ASSUME FULL RESPONSIBILITY FOR ANY AND ALL DAMAGES TO EXISTING FACILITIES.
- IT IS THE CONTRACTOR'S RESPONSIBILITY TO DOCUMENT EXISTING CONDITIONS PRIOR TO CONSTRUCTION BY MEANS OF PHOTOGRAPHS AND/OR VIDEO.
- ALL DRAINAGE FEATURES IMPACTED DURING CONSTRUCTION, INCLUDING BUT NOT LIMITED TO SWALES, CULVERTS, AND STRUCTURES, SHALL BE REPLACED IN-KIND AND TO THEIR ORIGINAL GRADE AND LOCATION BY THE CONTRACTOR.
- IN LOCATIONS WHERE CONSTRUCTION IS IN CLOSE PROXIMITY TO EXISTING UTILITY POLES, CONTRACTOR SHALL COORDINATE THE BRACING OF POLES WITH THE APPROPRIATE UTILITY OWNERS IN ADVANCE OF WORK IN A GIVEN AREA TO AVOID PROJECT DELAYS. BRACING POLES DURING CONSTRUCTION AND RELATION OF ANY EXISTING UTILITIES SHALL BE CONSIDERED INCIDENTAL TO THE OVERALL WORK, AND NO ADDITIONAL COMPENSATION SHALL BE AUTHORIZED.
- THE OWNER SHALL BEAR ALL COSTS FOR MATERIAL TESTING (CONCRETE/ASPHALT REPLACEMENT) AND COMPACTION TESTING OF SUBGRADES AND BASE AS PART OF THE OVERALL PROJECT COSTS. TESTING RESULTS SHALL BE SUBMITTED TO THE ENGINEER AND CONTRACTOR.
- THE CONTRACTOR SHALL SUBMIT AS-BUILT DRAWINGS OF ALL NEWLY INSTALLED MAINS. AS-BUILT INFORMATION SHALL BE SUBMITTED FOR ALL VALVES, FITTINGS, AND OTHER MAJOR APPURTENANCES AS WELL AS AT LOCATIONS FOR INSTALLED PIPELINE A MINIMUM OF EVERY 150 FEET. INFORMATION SHOULD INCLUDE DEPTH OF BURY.
- IF NECESSARY, TRANSFER OF WATER SERVICE LINES SHALL BE PERFORMED AT NIGHT TO ACCOMMODATE BUSINESSES AND RESIDENCES IN THE AREA. THE COST SHALL BE CONSIDERED SUBSIDARY TO OTHER BID ITEMS.
- WHERE REMOVAL OF BASE AND PAVEMENT IS NECESSARY FOR THIS PROJECT, ALL BASE AND PAVEMENT SHALL BE REPLACED IN ACCORDANCE WITH THE CONSTRUCTION DOCUMENTS. ALL PAVEMENT UTILITY CUTS SHALL BE SAW CUT OR REMOVED TO THE NEAREST JOINT.
- NO UTILITY TRENCHES OR PITS ARE TO BE LEFT OPEN OVERNIGHT. BACKFILLING WILL OCCUR DAILY AND AS SOON AS PRACTICAL FOLLOWING CONSTRUCTION OPERATIONS.
- CONSTRUCTION OPERATIONS SHALL BE CONDUCTED IN SUCH A MANNER AS TO PROTECT ROADWAY FACILITIES AT ALL TIMES.
- IN THE EVENT THAT THE PLANS AND SPECIFICATIONS DISAGREE, THE INFORMATION ON THE PLANS SHALL GOVERN. THE ENGINEER OF RECORD SHALL BE THE INTERPRETER OF THE DOCUMENTS.
- CONSTRUCTION OF ALL CCSUD WATER UTILITY INFRASTRUCTURE MUST ADHERE TO CCSUD TECHNICAL SPECIFICATIONS, DETAILS AND APPROVED EQUIPMENT LIST.
- THE OWNER SHALL SUPPLY ALL WATER NEEDED FOR CONSTRUCTION TESTING AND DISINFECTION. THE CONTRACTOR SHALL NOT BE REQUIRED TO PAY FOR THIS WATER.
- THE CONTRACTOR IS RESPONSIBLE FOR KEEPING STREETS AND SIDEWALKS ADJACENT TO PROJECT FREE OF MUD AND DEBRIS FROM THE CONSTRUCTION.
- COSTS FOR ROCK EXCAVATION SHALL BE INCLUDED WITHIN THE APPROPRIATE BID LINE ITEMS IN THE CONTRACT. NO ADDITIONAL COMPENSATION SHALL BE PROVIDED FOR THE EXCAVATION OF, OR HANDLING/DISPOSAL OF, ROCK DURING CONSTRUCTION.

UNION PACIFIC RAILROAD NOTES

- THE UTILITY OWNER (CCSUD) HAS AN EXECUTED UPRR UTILITY CROSSING AGREEMENT TO INSTALL THE WATERLINE. ALL TERMS AND CONDITIONS OF THE AGREEMENT MUST BE MET BY THE CONTRACTOR.
- FOR REFERENCE, THE UPRR FOLDER NUMBER IS 3148-31.
- THE CONTRACTOR IS RESPONSIBLE FOR COMPLETING THE UPRR CONSTRUCTION OBSERVATION REQUIREMENTS PRIOR TO CONSTRUCTION TAKING PLACE ON, UNDER OR ABOVE THE UPRR PROPERTY.
- PRIOR TO FINAL ACCEPTANCE BY CCSUD, HAUL ROADS AND WATERWAY CROSSINGS CONSTRUCTED FOR TEMPORARY CONTRACTOR ACCESS MUST BE REMOVED, ACCUMULATED SEDIMENT REMOVED FROM THE DITCH OR WATERWAY AND THE AREA RESTORED TO THE ORIGINAL GRADE AND REVEGETATED. ALL LAND CLEARING DEBRIS SHALL BE DISPOSED OF PROPERLY.
- SOIL DISTURBANCES SHALL BE MINIMIZED BY EXPOSING ONLY THE SMALLEST PRACTICAL AREA OF LAND REQUIRED FOR THE CLEARING AND GRADING ACTIVITY AND FOR THE CONSTRUCTION ACTIVITY, FOR THE SHORTEST PRACTICAL PERIOD OF TIME.
- MUD/DIRT INADVERTENTLY TRACKED OFF-SITE AND ONTO PUBLIC STREETS SHALL BE REMOVED IMMEDIATELY BY THE CONTRACTOR.
- ALL DISTURBED AREAS SHALL BE RESTORED PER SPECIFICATION SECTION 01700 "SITE RESTORATION".

CRYSTAL CLEAR SPECIAL UTILITY DISTRICT (CCSUD) WATER MAIN NOTES

- CONSTRUCTION OF ALL CCSUD WATER UTILITY INFRASTRUCTURE MUST ADHERE TO CCSUD'S TECHNICAL SPECIFICATIONS, DETAILS AND APPROVED EQUIPMENT LIST.
- REMOVE ONLY VEGETATION, TREES, STUMPS, RUBBISH, AND OTHER MATERIAL NECESSARY FOR CONSTRUCTION AND DISPOSE OF OFF SITE.
- THE CONNECTION LOCATIONS LISTED IN THE PLANS ARE BASED ON BEST AVAILABLE INFORMATION. THE CONTRACTOR SHALL FIELD LOCATE EXISTING WATER MAIN LOCATIONS AT ALL TIE-IN LOCATIONS TO VERIFY SIZE, ELEVATION, AND MATERIAL PRIOR TO ORDERING MATERIALS FOR CONNECTION.
- THE CONTRACTOR SHALL MAINTAIN MINIMUM SEPARATION BETWEEN UTILITIES PER TCEQ STANDARDS.
- UNLESS OTHERWISE SPECIFIED, ALL PVC WATER MAINS SHALL BE C900 DR 18, COLORED BLUE IN ACCORDANCE WITH SPECIFICATION SECTION 02650 - PVC PIPE FOR WATER MAINS.
- ALL DUCTILE IRON WATER MAINS SHALL BE PRESSURE CLASS CONFORMING TO AWWA C151 AND CEMENT LINED.
- WATER MAINS SHALL BE RESTRAINED WITH RESTRAINT LENGTHS OF FITTINGS SHOWN IN PLANS. THRUST BLOCKING IS REQUIRED AT ALL FITTINGS AND BENDS IN ACCORDANCE WITH THE THRUST BLOCKING DETAIL PROVIDED AND SPECIFICATION SECTION 02680 - JOINT RESTRAINTS AND THRUST BLOCKING.
- LOCATIONS OF COMBINATION AIR VALVES SHOWN ARE APPROXIMATE. INSTALL AIR RELEASE VALVES AT THE HIGH POINT IN THE WATER MAIN FOR THE LOCATIONS GIVEN.
- THE CONTRACTOR SHALL COORDINATE PRESSURE TESTING OF NEW WATER MAINS WITH OWNER AND ENGINEER AT LEAST TWO BUSINESS DAYS PRIOR. PRESSURE TESTING REQUIREMENTS ARE INCLUDED IN THE SPECIFICATIONS.
- ALL WATER MAINS SHALL BE DISINFECTED PER AWWA AND TCEQ STANDARDS.
- THE OWNER SHALL SUPPLY ALL WATER NEEDED FOR CONSTRUCTION TESTING AND DISINFECTION. THE CONTRACTOR SHALL NOT BE REQUIRED TO PAY FOR THIS WATER.
- UNLESS NOTED OTHERWISE, ALL WATER MAIN P.I.'S SHALL BE ACHIEVED USING THE WATER MAIN MANUFACTURER'S ALLOWABLE JOINT DEFLECTION.
- WATER MAINS, FIRE HYDRANTS, APPURTENANCES, AND VALVES THAT ARE ABANDONED SHALL BE CUT AND PLUGGED PER SPECIFICATION SECTION 02500 - ABANDONMENT OF WATER INFRASTRUCTURE.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MEETING 98% COMPACTION ON ALL TRENCH BACKFILL AND PAYING FOR THE TESTS TO BE PERFORMED BY A THIRD PARTY. COMPACTION TESTS WILL BE DONE AT ONE LOCATION POINT RANDOMLY SELECTED OR AS INDICATED BY CCSUD INSPECTOR/TEST ADMINISTRATOR. PER EACH 12-INCH LOOSE LIFT 400 LINEAR FEET AT A MINIMUM. PERMITS WILL NOT BE ACCEPTED AND FINALIZED BY CCSUD WITHOUT THIS REQUIREMENT BEING MET AND VERIFIED BY PROVIDING ALL NECESSARY DOCUMENTED TEST RESULTS.

STORMWATER POLLUTION PREVENTION PLAN NOTES:

- CONTRACTOR IS RESPONSIBLE FOR DEVELOPING A STORM WATER POLLUTION PREVENTION PLAN (SWPPP) PER TCEQ.
- PRIOR TO CONSTRUCTION, MAKE CERTAIN THE NOTICE OF INTENT (NOI) OR CONSTRUCTION SITE NOTICE (CSN) HAS BEEN FILED AND POSTED ON SITE FOR PUBLIC VIEWING AND THE SWPPP IS AVAILABLE AT THE JOBSITE AT ALL TIMES.
- CONTRACTOR IS RESPONSIBLE FOR ALL POLLUTION PREVENTION SHOWN IN THE SWPPP.
- INSTALL STORM WATER POLLUTION PREVENTION CONTROLS PRIOR TO ANY SITE PREPARATION WORK (CLEARING, GRUBBING, EXCAVATION).
- THE PLACEMENT OF STORM WATER POLLUTION PREVENTION CONTROLS SHALL BE IN ACCORDANCE WITH THE APPROVED STORM WATER POLLUTION PREVENTION CONTROL PLAN.
- INSTALL AND MAINTAIN POLLUTION CONTROL MEASURES IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND WITH PROJECT SPECIFICATIONS.
- POLLUTION CONTROL MEASURES SHALL BE REPAIRED, REESTABLISHED, ADJUSTED OR REINSTALLED WITH EACH SUBSEQUENT PHASE OF CONSTRUCTION IN ACCORDANCE WITH THE SWPPP.
- ANY MAJOR VARIATION IN MATERIALS OR LOCATIONS OF CONTROLS OR FENCES FROM THOSE SHOWN IN THE APPROVED PLAN SHALL REQUIRE A REVISION AND MUST BE APPROVED BY THE ENGINEER(S) APPROPRIATE. MINOR CHANGES TO BE MADE AS FIELD REVISIONS TO THE STORM WATER POLLUTION PREVENTION CONTROL PLAN MAY BE REQUIRED BY THE ENGINEER DURING THE COURSE OF CONSTRUCTION TO CORRECT CONTROL INADEQUACIES.
- CONTRACTOR IS RESPONSIBLE FOR ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE, AND SHALL REMOVE THE ACCUMULATION OF OFF-SITE SEDIMENT PROMPTLY.
- THE CONTRACTOR IS REQUIRED TO INSPECT THE CONTROLS AND FENCES AT INTERVALS OF AT LEAST ONE EVERY TWO (2) WEEKS AND IMMEDIATELY AFTER SIGNIFICANT RAINFALL EVENTS TO INSURE THAT THEY ARE FUNCTIONING PROPERLY. THE PERSON(S) RESPONSIBLE FOR MAINTENANCE OF CONTROLS AND FENCES SHALL IMMEDIATELY MAKE ANY NECESSARY REPAIRS TO DAMAGED AREAS. SILT ACCUMULATION AT CONTROLS MUST BE REMOVED WHEN THE DEPTH REACHES SIX (6) INCHES. CONTRACTOR SHALL MAINTAIN SEDIMENT TRAPS AND BASINS.
- DEFICIENCIES NOTED DURING THE INSPECTION WILL BE CORRECTED AND DOCUMENTED WITHIN SEVEN CALENDAR DAYS OR BEFORE THE NEXT ANTICIPATED STORM EVENT.
- OFF-SITE MATERIAL STORAGE AREAS USED SOLELY BY THE PROJECT ARE CONSIDERED PART OF THE PROJECT.
- MAINTAIN RECORDS OF PROJECT MILESTONE DATES AND FIELD CHANGES AS REQUIRED BY THE SWPPP.
- PRIOR TO FINAL ACCEPTANCE BY CCSUD, HAUL ROADS AND WATERWAY CROSSINGS CONSTRUCTED FOR TEMPORARY CONTRACTOR ACCESS MUST BE REMOVED, ACCUMULATED SEDIMENT REMOVED FROM THE DITCH OR WATERWAY AND THE AREA RESTORED TO THE ORIGINAL GRADE AND REVEGETATED. ALL LAND CLEARING DEBRIS SHALL BE DISPOSED OF PROPERLY.
- SOIL DISTURBANCES SHALL BE MINIMIZED BY EXPOSING ONLY THE SMALLEST PRACTICAL AREA OF LAND REQUIRED FOR THE CLEARING AND GRADING ACTIVITY AND FOR THE CONSTRUCTION ACTIVITY, FOR THE SHORTEST PRACTICAL PERIOD OF TIME.
- MUD/DIRT INADVERTENTLY TRACKED OFF-SITE AND ONTO PUBLIC STREETS SHALL BE REMOVED IMMEDIATELY BY THE CONTRACTOR.
- ALL DISTURBED AREAS SHALL BE RESTORED PER SPECIFICATION SECTION 01700 "SITE RESTORATION".

**TCEQ WATER DISTRIBUTION SYSTEM
GENERAL CONSTRUCTION NOTES**

- THIS WATER DISTRIBUTION SYSTEM MUST BE CONSTRUCTED IN ACCORDANCE WITH THE CURRENT TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) RULES AND REGULATIONS FOR PUBLIC WATER SYSTEMS 30 TEXAS ADMINISTRATIVE CODE (TAC) CHAPTER 290 SUBCHAPTER D. WHEN CONFLICTS ARE NOTED WITH LOCAL STANDARDS, THE MORE STRINGENT REQUIREMENT SHALL BE APPLIED. AT A MINIMUM, CONSTRUCTION FOR PUBLIC WATER SYSTEMS MUST ALWAYS MEET TCEQ'S RULES AND REGULATIONS FOR PUBLIC WATER SYSTEMS.
- ALL NEWLY INSTALLED PIPES AND RELATED PRODUCTS MUST CONFORM TO AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)/NSF INTERNATIONAL STANDARD 61 AND MUST BE CERTIFIED BY AN ORGANIZATION ACCREDITED BY ANSI [§290.44(A)(1)].
- PLASTIC PIPE FOR USE IN PUBLIC WATER SYSTEMS MUST BEAR THE NSF INTERNATIONAL STANDARD 61 (NSF 61) AND HAVE AN ASTM DESIGN PRESSURE RATING OF AT LEAST 150 PSI OR A STANDARD DIMENSION RATIO OF 26 OR LESS [§290.44(A)(2)].
- NO PIPE WHICH HAS BEEN USED FOR ANY PURPOSE OTHER THAN THE CONVEYANCE OF DRINKING WATER SHALL BE ACCEPTED OR RELOCATED FOR USE IN ANY PUBLIC DRINKING WATER SUPPLY [§290.44(A)(3)].
- ALL WATER-LINE CROSSINGS OF WASTEWATER MAINS SHALL BE PERPENDICULAR [§290.44(E)(4)].
- WATER TRANSMISSION AND DISTRIBUTION LINES SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS; HOWEVER, THE TOP OF THE WATER LINE MUST BE LOCATED BELOW THE FROST LINE AND IN NO CASE SHALL THE TOP OF THE WATER LINE BE LESS THAN 24 INCHES BELOW GROUND SURFACE [§290.44(A)(4)].
- THE MAXIMUM ALLOWABLE LEAD CONTENT OF PIPES, PIPE FITTINGS, PLUMBING FITTINGS, AND FIXTURES IS 0.25 PERCENT [§290.44(B)].
- THE CONTRACTOR SHALL INSTALL APPROPRIATE AIR RELEASE DEVICES WITH VENT OPENINGS TO THE ATMOSPHERE COVERED WITH 16-MESH OR FINER, CORROSION RESISTANT SCREENING MATERIAL OR AN ACCEPTABLE EQUIVALENT [§290.44(D)(1)].
- THE CONTRACTOR SHALL NOT PLACE THE PIPE IN WATER OR WHERE IT CAN BE FLOODED WITH WATER OR SEWAGE DURING ITS STORAGE OR INSTALLATION [§290.44(F)(1)].
- WHEN WATERLINES ARE LAID UNDER ANY FLOWING OR INTERMITTENT STREAM OR SEMI-PERMANENT BODY OF WATER THE WATERLINE SHALL BE ISOLATED FROM THE WATERLINES BY WATERTIGHT PIPE ENCASEMENT. VALVES MUST BE PROVIDED ON EACH SIDE OF THE CROSSING WITH FACILITIES TO ALLOW THE UNDERWATER PORTION OF THE SYSTEM TO BE ISOLATED AND TESTED [§290.44(F)(2)].
- PURSUANT TO 30 TAC §290.44(A)(5), THE HYDROSTATIC LEAKAGE RATE SHALL NOT EXCEED THE AMOUNT ALLOWED OR RECOMMENDED BY THE MOST CURRENT AWWA FORMULAS FOR PVC PIPE, CAST IRON AND DUCTILE IRON PIPE. INCLUDE THE FORMULAS IN THE NOTES ON THE PLANS.
- THE HYDROSTATIC LEAKAGE RATE FOR POLYVINYL CHLORIDE (PVC) PIPE AND APPURTENANCES SHALL NOT EXCEED THE AMOUNT ALLOWED OR RECOMMENDED BY FORMULAS IN AMERICA WATER WORKS ASSOCIATION (AWWA) C-605 AS REQUIRED IN 30 TAC §290.44(A)(5). PLEASE ENSURE THAT THE FORMULA FOR THIS CALCULATION IS CORRECT AND MOST CURRENT FORMULA IS IN USE;

STORMWATER POLLUTION PREVENTION PLAN NOTES:

- CONTRACTOR IS RESPONSIBLE FOR DEVELOPING A STORM WATER POLLUTION PREVENTION PLAN (SWPPP) PER TCEQ.

O

THE HYDROSTATIC LEAKAGE RATE FOR DUCTILE IRON (DI) PIPE AND APPURTENANCES SHALL NOT EXCEED THE AMOUNT ALLOWED OR RECOMMENDED BY FORMULAS IN AMERICA WATER WORKS ASSOCIATION (AWWA) C-600 AS REQUIRED IN 30 TAC §290.44(A)(5). PLEASE ENSURE THAT THE FORMULA FOR THIS CALCULATION IS CORRECT AND MOST CURRENT FORMULA IS IN USE;

Q

WHERE: $Q = \frac{LD/P}{148,000}$

• Q = THE QUANTITY OF MAKEUP WATER IN GALLONS PER HOUR,

• L = THE LENGTH OF THE PIPE SECTION BEING TESTED, IN FEET,

• D = THE NOMINAL DIAMETER OF THE PIPE IN INCHES, AND

• P = THE AVERAGE TEST PRESSURE DURING THE HYDROSTATIC TEST IN POUNDS PER SQUARE INCH (PSI).

L

WHERE: $L = \frac{LD/P}{148,000}$

• L = THE QUANTITY OF MAKEUP WATER IN GALLONS PER HOUR,

• S = THE LENGTH OF THE PIPE SECTION BEING TESTED, IN FEET,

• D = THE NOMINAL DIAMETER OF THE PIPE IN INCHES, AND

• P = THE AVERAGE TEST PRESSURE DURING THE HYDROSTATIC TEST IN POUNDS PER SQUARE INCH (PSI).

D

THE CONTRACTOR SHALL MAINTAIN A MINIMUM SEPARATION DISTANCE IN ALL DIRECTIONS OF NINE FEET BETWEEN THE PROPOSED WATERLINE AND WASTEWATER COLLECTION FACILITIES INCLUDING MANHOLES. IF THIS DISTANCE CANNOT BE MAINTAINED, THE CONTRACTOR MUST IMMEDIATELY NOTIFY THE PROJECT ENGINEER FOR FURTHER DIRECTION. SEPARATION DISTANCES, INSTALLATION METHODS, AND MATERIALS UTILIZED MUST MEET §290.44(E)(1)-(4).

1110

THE SEPARATION DISTANCE FROM A POTABLE WATERLINE TO A WASTEWATER MAIN OR LATERAL, MANHOLE OR CLEANOUT SHALL BE A MINIMUM OF NINE FEET. IF THE NINE-FOOT SEPARATION DISTANCE CANNOT BE MAINTAINED, THE CONTRACTOR SHALL USE A SPACER BASED IN A JOINT OF AT LEAST 150 PSI PRESSURE CLASS PIPE AT LEAST 10 FEET LONG AND TWO NOMINAL SIZES LARGER THAN THE NEW CONVEYANCE. THE SPACE AROUND THE CARRIER PIPE SHALL BE SUPPORTED AT FIVE-FOOT INTERVALS WITH SPACERS OR BE FILLED TO THE SPRINGLINE WITH WASHED SAND. THE ENCASEMENT PIPE SHALL BE CENTERED ON THE CROSSING AND BOTH ENDS SEALED WITH CEMENT GROUT OR MANUFACTURED SEALANT [§290.44(E)(5)].

1111

FIRE HYDRANTS SHALL NOT BE INSTALLED WITHIN NINE FEET VERTICALLY OR HORIZONTALLY OF ANY WASTEWATER LINE, WASTEWATER LATERAL, OR WASTEWATER SERVICE LINE REGARDLESS OF CONSTRUCTION [§290.44(E)(6)].

1112

SUCTION COVERS TO PUMPING EQUIPMENT SHALL NOT CROSS WASTEWATER MAINS, WASTEWATER LATERALS, OR WASTEWATER SERVICE LINES. RAW WATER SUPPLY LINES SHALL NOT BE INSTALLED WITHIN FIVE FEET OF ANY TILE OR CONCRETE WASTEWATER MAIN, WASTEWATER LATERAL, OR WASTEWATER SERVICE LINE [§290.44(E)(7)].

1113

WATERLINES SHALL NOT BE INSTALLED CLOSER THAN TEN FEET TO SEPTIC TANK DRAINFIELDS [§290.44(E)(8)].

1114

THE CONTRACTOR SHALL DISINFECT THE NEW WATERLINES IN ACCORDANCE WITH AWWA STANDARD C-651-14 OR MOST RECENT, THEN FLUSH AND SAMPLE THE LINES BEFORE BEING PLACED INTO SERVICE. SAMPLES SHALL BE COLLECTED FOR MICROBIOLOGICAL ANALYSIS TO CHECK THE EFFECTIVENESS OF THE DISINFECTION PROCEDURE WHICH SHALL BE REPEATED IF CONTAMINATION PERSISTS. A MINIMUM OF ONE SAMPLE FOR EACH 1,000 FEET OF COMPLETED WATERLINE WILL BE REQUIRED OR AT THE NEXT AVAILABLE SAMPLING POINT BEYOND 1,000 FEET AS DESIGNATED BY THE DESIGN ENGINEER [§290.44(F)(3)].

1115

DECHLORINATION OF DISINfecting WATER SHALL BE IN STRICT ACCORDANCE WITH CURRENT AWWA STANDARD C655-09 OR MOST RECENT.

LEGEND:


W 4"	PROP 4" C900 PVC WATER LINE
W 8"	PROP 8" C900 PVC WATER LINE
W 12"	PROP 12" C900 PVC WATER LINE
	PROP SERVICE LINE
W	PROP WATER METER
△	PROP GATE VALVE
□	PROP 90° BEND
□	PROP 45° BEND
H	PROP TEE
□	PROP REDUCER
○	PROP CUT AND PLUG
○	PROP COMBINATION AIR VALVE
○	PROP FIRE HYDRANT
○	PROP ENCASED PIPE
○	PROP OPEN CUT / REPAIR
○	PROP TRENCHLESS INSTALLATION
○	PROP BORE & RECEIVING PITS
○	LENGTH OF PIPE TO BE RESTRAINED
○	ENTIRE LENGTH OF PIPE TO BE RESTRAINED
○	NO SEPARATE PAY ITEM

OE

KINGSBURY PH II WATER MAIN					
Number	Station	Length	Line/Chord Direction	Northing	Easting
L1	100+00.00	345.741	N $9^{\circ} 48' 09.13''$ W	13784817.59	2339444.86
L2	103+45.74	46.137	N $26^{\circ} 16' 36.55''$ E	13785158.29	2339386.00
L3	103+91.88	75.775	S $63^{\circ} 44' 03.70''$ E	13785199.66	2339406.42
L4	104+67.65	7.532	S $74^{\circ} 59' 03.70''$ E	13785166.12	2339474.37
L5	104+75.19	244.704	N $82^{\circ} 45' 43.09''$ E	13785164.17	2339481.65
L6	107+19.89	102.070	N $80^{\circ} 10' 26.35''$ E	13785105.00	2339724.40
L7	108+21.96	3.000	N $35^{\circ} 08' 18.36''$ E	13785212.42	2339824.98
L8	108+24.96	142.879	N $9^{\circ} 49' 36.04''$ W	13785214.87	2339826.70
L9	109+67.84	29.959	N $9^{\circ} 49' 42.00''$ W	13785355.66	2339802.32
L10	109+97.80	481.787	N $10^{\circ} 37' 14.24''$ W	13785385.18	2339797.20
L11	114+79.58	6.928	N $34^{\circ} 51' 26.45''$ E	13785858.71	2339708.41
L12	114+86.51	59.174	N $80^{\circ} 08' 50.00''$ E	13785864.39	2339712.37
L13	115+45.69	12.038	N $35^{\circ} 09' 45.51''$ E	13785874.52	2339770.67
L14	115+57.73	758.989	N $80^{\circ} 09' 40.84''$ E	13785884.36	2339777.60
L15	123+16.71	5.122	N $35^{\circ} 16' 35.14''$ E	13786014.05	2340525.43
L16	123+21.84	338.609	N $9^{\circ} 43' 24.86''$ W	13786018.23	2340528.39
L17	126+60.44	14.160	N $35^{\circ} 12' 08.67''$ E	13786351.98	2340471.20
L9	126+74.61	145.735	N $9^{\circ} 43' 16.84''$ W	13786363.55	2340479.36
L18	128+20.34	16.983	N $35^{\circ} 12' 08.67''$ E	13786507.19	2340454.75
L19	128+37.32	37.927	N $9^{\circ} 43' 18.30''$ W	13786652.07	2340464.54
L20	128+75.25	66.282	N $37^{\circ} 31' 04.65''$ W	13786558.45	2340458.14
L21	129+41.53	16.893	N $82^{\circ} 46' 47.92''$ W	13786611.02	2340417.77
L22	129+58.43	160.267	N $37^{\circ} 31' 03.78''$ W	13786613.15	2340401.01
L23	131+18.69	332.006	N $38^{\circ} 12' 08.65''$ W	13786740.27	2340303.41
L24	134+50.70	4.364	N $5^{\circ} 34' 58.82''$ E	13787001.17	2340098.08
L25	134+55.06	73.188	N $50^{\circ} 33' 07.24''$ E	13787005.51	2340098.51


CALLED 86.59 ACRES
SAV. EXCEPT 5.2 ACRES
LESLIE BAKER & PARTNERS
VOL. 1141, PG. 954
O.P.R.G.C.T.

CALLED 8.00 ACRES
WILLIAM FORTIN
VOL. 2674, PG. 745
O.P.R.G.C.T.



0 75 150 300

M & S ENGINEERING
POWER & UTILITY ENGINEERS
TXENG FIRM # F-1394 | TBPEL FIRM #10169800



CRYSTAL CLEAR SUD
KINGSBURY ROAD PIPELINE PHASE II

KEY MAP AND ALIGNMENT DATA TABLE

STATE OF TEXAS
BRADY, KCS, B
105051
LICENSED PROFESSIONAL ENGINEER
December 18, 2025

JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

SHEET:


G1.1



POINT NUMBER	NORTHING	EASTING	ELEVATION	DESCRIPTION
CP #1	13785279.55	2340798.13	605.55	SET IRON ROD
CP #2	13787151.53	2339993.47	619.96	IRON ROD
CP #3	13785113.32	2339491.84	607.70	SET IRON ROD
CP #5	13785202.18	2339841.98	607.45	SET IRON ROD
CP #6	13785996.10	2340604.73	607.45	SET IRON ROD
CP #7	13785842.05	2339749.70	611.73	SET IRON ROD
BM	13787160.93	2340054.08	622.05	60D NAIL IN PP
BM	13785300.69	2340743.00	609.49	TOP OF FH

0 75 150 300
SCALE (FEET)

M & S ENGINEERING
POWER & UTILITY ENGINEERS
TXENG FIRM # F-1394 | TBPEL FIRM #10169800
WWW.MSENENG.COM | (830) 228-5446



Brady, KCS, B
December 18, 2025

CRYSTAL CLEAR SUD KINGSBURY ROAD PIPELINE PHASE II



CONTROL POINTS

JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

SHEET:

G1.2





Brady, KCS, B
105051
December 18, 2025

KINGSBURY ROAD PIPELINE PHASE II

WM1.0

CRYSTAL CLEAR SUD

STA. 100+00 TO STA. 107+00

JOB: 14CCSUD001
DATE:

DRAWN: KV

PM: CP

DESIGN: CP

DM: BK

PEER:

OTHER:

REVISIONS:

DELTA

DESCRIPTION

DATE

SHEET:



MATCHLINE STA. 107+00
SEE SHEET WM1.1


0 10 20 40
SCALE (FEET)

UPRR CONSTRUCTION REQUIREMENTS
THE CONTRACTOR SHALL REFER TO AND
ADHERE TO THE UPRR CONSTRUCTION
REQUIREMENTS AND PIPELINE
CROSSING AGREEMENT PROVIDED
WITHIN THE CONTRACT DOCUMENTS.


NOTES:

- CONSTRUCTION WITHIN THIS PROPERTY BOUNDARY MUST BE SUBSTANTIALLY COMPLETE WITHIN 90 DAYS FROM THE START OF CONSTRUCTION ON THAT PROPERTY.
- CONTRACTOR TO COORDINATE WITH GUADALUPE COUNTY FOR PERMITTING OF CONSTRUCTION ACTIVITIES WITHIN THE COUNTY RIGHT-OF-WAY.
- BORE PITS LOCATED CLOSER THAN 10-FT FROM THE EDGE OF PAVEMENT IN TXDOT RIGHT-OF-WAY MUST BE REINFORCED WITH WOOD OR STAKES TO INSURE THAT THE EXISTING ROADWAY OR PITS DO NOT COLLAPSE. REINFORCED WALL SHORING AND/OR TRENCH BOX PROTECTION IS REQUIRED FOR ALL HOLES, PITS, AND TRENCHES DEEPER THAN 5-FT.
- THE JOINT LENGTHS PROVIDED IN THE CONSTRUCTION DRAWINGS ARE BASED ON CALCULATIONS. IF CALCULATED RESTRAINT LENGTH DOES NOT FALL ON A JOINT, RESTRAINTS SHALL BE INSTALLED TO THE NEXT FURTHEST JOINT.

TRENCH EXCAVATION SAFETY PROTECTION
CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONTRACTOR MAY REVIEW THESE DRAWINGS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS, AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS, AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.



MATCHLINE STA. 107+00 SEE SHEET WM1.0



NOTES:


1. CONTRACTOR TO COORDINATE WITH GUADALUPE COUNTY FOR PERMITTING OF CONSTRUCTION ACTIVITIES WITHIN THE COUNTY RIGHT-OF-WAY.
2. RESTRAINT LENGTHS PROVIDED IN THE CONSTRUCTION DRAWINGS, ARE BASED ON CALCULATIONS. IF CALCULATED RESTRAINT LENGTH DOES NOT FALL ON A JOINT, RESTRAINTS SHALL BE INSTALLED TO THE NEXT FURTHEST JOINT.



December 18, 2025

TRENCH EXCAVATION SAFETY PROTECTION
CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROGRAMS, SITES, PROGRAMS, AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

MATCHLINE STA. 112+00 THIS SHEET



CRYSTAL CLEAR SUD KINGSBURY ROAD PIPELINE PHASE II

JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE


SHEET:

WM1.1



MATCHLINE STA. 121+00
SEE SHEET WM1.1



MATCHLINE STA. 121+00
SEE SHEET WM1.1



0 10 20 40
SCALE (FEET)

M&S ENGINEERING
POWER & UTILITY ENGINEERS

TXENG FIRM # F-1394 | TBPELS FIRM #10169800
WWW.MSENGL.COM | (830) 228-5446



December 18, 2025

MATCHLINE STA. 124+00
SEE SHEET WM1.3

MATCHLINE STA. 121+00
SEE SHEET WM1.1

TRENCH EXCAVATION SAFETY PROTECTION
CONTRACTOR AND/OR CONTRACTOR'S
INDEPENDENTLY RETAINED EMPLOYEE OR
STRUCTURAL
DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT
CONSULTANT, IF ANY, SHALL REVIEW THESE
PLANS AND AVAILABLE GEOTECHNICAL
INFORMATION AND THE ANTICIPATED
INSTALLATION TIMES WITHIN THE PROJECT
WORK AREA IN ORDER TO IMPLEMENT
CONTRACTOR'S TRENCH EXCAVATION
SAFETY PROTECTION SYSTEMS, PROGRAMS,
AND/OR PROCEDURES. THE CONTRACTOR'S
IMPLEMENTATION OF THESE SYSTEMS,
PROGRAMS AND/OR PROCEDURES SHALL
PROVIDE FOR ADEQUATE TRENCH
EXCAVATION SAFETY PROTECTION THAT
COMPLIES WITH THE OSHA
STANDARDS FOR TRENCH EXCAVATIONS.
SPECIFICALLY, CONTRACTOR AND/OR
CONTRACTOR'S INDEPENDENTLY RETAINED
EMPLOYEE OR SAFETY CONSULTANT SHALL
IMPLEMENT A TRENCH SAFETY PROGRAM IN
ACCORDANCE WITH OSHA STANDARDS
GOVERNING THE PRESENCE AND ACTIVITIES
OF INDIVIDUALS WORKING IN AND AROUND
TRENCH EXCAVATION.



KINGSBURY RD PIPELINE PHASE II
KINGSBURY RD


STA. 116+00 TO STA. 124+00

JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

WM1.2








PROFILE STA 100+00 TO STA 103+00

FOR PLAN VIEW SEE SHT. WM1.0

SCALE:
H: 1" = 20', V: 1" = 2'



PROFILE STA 103+00 TO STA 104+60

FOR PLAN VIEW SEE SHT. WM1.0

SCALE:
H: 1" = 20', V: 1" = 2'

UPRR CONSTRUCTION REQUIREMENTS
THE CONTRACTOR SHALL REFER TO AND
ADHERE TO THE UPRR CONSTRUCTION
REQUIREMENTS AND PIPELINE
CROSSING AGREEMENT PROVIDED
WITHIN THE CONTRACT DOCUMENTS.

NOTES:

1. L= LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
2. L_u= UPPER BEND LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
3. L_l= LOWER BEND LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
4. WHERE RESTRAINED LENGTHS OVERLAP, ALL PIPE BETWEEN FITTINGS SHOULD BE RESTRAINED.
5. TOP OF CASING (T.O.C.).
6. THE RESTRAINT LENGTHS PROVIDED IN THE CONSTRUCTION DRAWINGS, ARE BASED ON CALCULATIONS. IF CALCULATED RESTRAINT LENGTH DOES NOT FALL ON A JOINT, RESTRAINTS SHALL BE INSTALLED TO THE NEXT FURTHEST JOINT.

TRENCH EXCAVATION SAFETY PROTECTION
CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S INDEPENDENTLY RETAINED SAFETY PROTECTION SYSTEMS, PROGRAMS, AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLIES WITH AS A MINIMUM, OSHA STANDARDS AND EXCETIONS, SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

**CRYSTAL CLEAR SUD
KINGSBURY ROAD PIPELINE PHASE II
RAILROAD AND GRAVEL PIT
PROFILES**


JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

SHEET:


WM1.4



**M&S ENGINEERING
POWER & UTILITY ENGINEERS**
TXENG FIRM # F-1394 | TBPELS FIRM #10169800
www.mseng.com | (830) 228-5446



December 18, 2025




PROFILE STA 114+60 TO STA 115+80
FOR PLAN VIEW SEE SHT. WM1.1

NOTES:

1. L_1 = LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
2. L_2 = UPPER BEND LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
3. L_3 = LOWER BEND LENGTH OF PIPE TO BE RESTRAINED IN BOTH DIRECTIONS.
4. WHEN RESTRAINED LENGTHS OVERLAP, ALL PIPE BETWEEN FITTINGS SHOULD BE RESTRAINED.
5. T.O.C. = TOP OF CASING.
6. THE RESTRAINT LENGTHS PROVIDED IN THE CONSTRUCTION DRAWINGS ARE BASED ON CALCULATIONS. IF CALCULATED RESTRAINT LENGTH DOES NOT FALL ON A JOINT, RESTRAINTS SHALL BE INSTALLED TO THE NEXT FURTHEST JOINT.

**CRYSTAL CLEAR SUD
KINGSBURY ROAD PIPELINE PHASE II**
**WEST AND KINGSBURY RD
PROFILES**



TRENCH EXCAVATION SAFETY PROTECTION
CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH SAFETY PROTECTION SYSTEMS, PROGRAMS, AND/OR PROCEDURES. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLETES WITH AS A MINIMUM, OSHA STANDARDS AND EXCULSIONS, SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.



PROFILE 134+00 TO STA 135+40
FOR PLAN VIEW SEE SHT. WM1.3

M&S ENGINEERING
POWER & UTILITY ENGINEERS

TXENG FIRM # F-1394 | TBPEL FIRM #10169800




December 18, 2025

JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

WM1.5










December 18, 2025

KINGSBURY ROAD PIPELINE PHASE II
MISCELLANEOUS DETAILS 2


JOB: 14CCSUD001
DATE:
DRAWN: KV PM: CP
DESIGN: CP DM: BK
PEER: OTHER:
REVISIONS:
DELTA DESCRIPTION DATE

SHEET:
D1.1






LINEAR CONSTRUCTION THROUGH STAND OF TREES





PAVING UNDER TREES



TYPICAL TREE GROUPING PROTECTION

TREE ROOT ZONES ARE OFTEN IRREGULAR IN SHAPE. THEY GENERALLY FOLLOW THE CONTOURS OF THE CROWN. PLACE PROTECTIVE FENCE AT THE EDGE OF THE CRITICAL ROOT ZONE FOLLOWING THE CONTOURS OF THE DRIPLINE.




TYPICAL TREE PROTECTION

NOTES:

- CRITICAL ROOT ZONE IS 1 FT. AWAY FROM TREE TRUNK FOR EVERY 1 IN. OF TREE DIAMETER MEASURED AT 4 FT. HEIGHT.
- WATER TREES EVERY 2 WEEKS WITH A MINIMUM OF 100 GALLONS PER TREE.
- SPRAY TREE WITH WATER TO REMOVE CONSTRUCTION DUST WHEN DIRECTED.
- CONSTRUCTION FENCE SHALL BE 4 FT. TALL.
- DO NOT PERFORM WORK OR STORE EQUIPMENT WITHIN PROTECTED AREA.
- COVER THE CRITICAL ROOT ZONE BETWEEN THE PROTECTED AREA AND THE CONSTRUCTION ZONE WITH 4 IN. OF MULCH.
- PERFORM TREE TRIMMING AND WOUND REPAIR PER STANDARD SPECIFICATIONS.
- DAMAGED AND EXPOSED ROOTS SHALL BE TRIMMED AND TREATED PER STANDARD SPECIFICATIONS. BACKFILL EXPOSED ROOTS WITH TOPSOIL WITHIN 24 HOURS OF EXPOSURE.
- PLACE PLASTIC UNDER CONCRETE PLACED IN THE CRITICAL ROOT ZONE.
- PLACE A ROOT BARRIER IN THE CRITICAL ROOT ZONE AT THE EDGE OF TREATED SUBGRADE TO THE DEPTH OF THE SUBGRADE.
- ALL WORK IS SUBSIDIARY TO BID ITEM.

Texas Department of Transportation		Austin District Standard
TREE PROTECTION DETAILS		
TPD-19(AUS)		
©TxDot 2020	CONT	SECT
REVISIONS	JOB	HIGHWAY
06/16: SHEET CREATED		
04/19: APPROVED	DIST	COUNTY
		SHEET NO.



KINGSBURY ROAD PIPELINE PHASE II
TREE PROTECTION DETAILS



D1.3



DISCLAIMER: This standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA. SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.

SEDIMENT CONTROL FENCE USAGE GUIDELINES


A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.

DATE
FILE

GENERAL NOTES

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.



VERTICAL TRACKING



Texas Department of Transportation		Design Division Standard			
		FILE: ec116	DN: TxDOT	CK: KM	DW: VP
© TxDOT: JULY 2016		CONT	SECT	JOB	HIGHWAY
REVISIONS					
		DIST	COUNTY	SHEET NO.	

CRYSTAL CLEAR SUD
KINGSBURY ROAD PIPELINE PHASE II
EROSION CONTROL DETAILS

JOB: 14CCSUD001	
DATE:	
DRAWN: KV	PM: CP
DESIGN: CP	DM: BK
PEER: OTHER:	
REVISIONS:	
DELTA	DESCRIPTION DATE

SHEET:

D1.4



December 18, 2025