THE OAKS AT THE DOMINION SAN ANTONIO, TEXAS **CIVIL CONSTRUCTION PLANS**

RODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE© UNLESS OTHERWISE NOTED. Imagery © 2015, CAPCOG, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Age



PREPARED FOR:

AGORA ASSETS, LLC 8 DOMINION DR, UNIT 102 SAN ANTONIO, TEXAS 78257

DECEMBER 2024





2000 NW LOOP 410 I SAN ANTONIO, TX 78213 I 210.375.9000 TEXAS ENGINEERING FIRM #470 I TEXAS SURVEYING FIRM #1002880

SHEET INDEX

Sheet Description	Sheet No.
COVER SHEET	C0.00
GENERAL NOTES	C0.10
DEMOLITION PLAN	C0.20
OVERALL DRAINAGE PLAN	C1.00
SD LINE A PLAN & PROFILE ~ STA. 1+00.00 TO 5+40.00	C1.01
SD LINE A PLAN & PROFILE ~ STA. 5+40.00 TO 9+80.00	C1.02
SD LINE A PLAN & PROFILE ~ STA. 9+80.00 TO END	C1.03
SD LINE A1 PLAN & PROFILE ~ STA. 1+00.00 TO END	
DRAINAGE DETAILS	C1.10
DRAINAGE DETAILS	C1.11
LIVE OAK VALLEY PLAN & PROFILE ~ STA. 1+00.00 TO 6+50	0.00 C2.00
LIVE OAK VALLEY PLAN & PROFILE ~ STA. 6+50.00 TO 12+	50.00 C2.01
LIVE OAK VALLEY PLAN & PROFILE ~ STA. 12+50.00 TO EN	D C2.02
RED OAK WAY PLAN & PROFILE ~ STA. 1+00.00 TO 6+00.00) C2.03
RED OAK WAY PLAN & PROFILE ~ STA. 6+00.00 TO END	C2.04
STREET DETAILS	C2.10
OVERALL SIGNAGE PLAN	C2.20
SIGNAGE DETAILS	C2.21
OVERALL UTILITY PLAN	C3.00
OVERALL WATER PLAN	C4.00
WATER DETAILS	C4.10
SS LINE A PLAN & PROFILE ~ 1+00.00 TO END	C5.01
SS LINE A1 PLAN & PROFILE ~ 1+00.00 TO END	C5.02
SS LINE B PLAN & PROFILE ~ 1+00.00 TO END	C5.03
SS LINE B1 PLAN & PROFILE ~ 1+00.00 TO END	C5.04
TEMPORARY POLLUTION ABATEMENT PLAN	C8.00
TEMPORARY POLLUTION ABATEMENT DETAILS	C8.01
PERMANENT POLLUTION ABATEMENT PLAN	C8.02
BASIN PLAN	C8.03
BASIN DETAILS	C8.04

DEMOLITION NOTES

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ACQUIRING ALL NECESSARY PERMITS/APPROVALS BEFORE BEGINNING DEMOLITION.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING FROM THE SITE ALL ITEMS SHOWN TO BE DEMOLISHED UNLESS OTHERWISE INDICATED. ALL MATERIALS SHALL BE DEMOLISHED AND REMOVED FROM SITE I REGULATIONS
- ALL EXISTING ITEMS NOT SPECIFICALLY NOTED TO BE DEMOLISHED SHALL REMAIN. CONTRACTOR IS RESPONSIBLE FOR REPLACING EXISTING ITEMS 3. ALL SELECT FILL MATERIAL PROVIDED SHALL BE APPROVED BY THE REMOVED DURING DEMOLITION THAT WERE TO REMAIN.
- CONTRACTOR IS RESPONSIBLE FOR COORDINATION WITH ALL UTILITY 4. ALL ELEVATIONS AND PROPOSED CONTOURS SHOWN ON THIS GRADING PLAN 3. ALL FILL MATERIAL IS TO BE IN PLACE AND COMPACTED BEFORE COMPANIES REGARDING REMOVAL OF EXISTING SERVICES, POWER POLES TO BE REMOVED, VERIFYING UTILITIES ARE SHUT OFF OR DISCONNECTED, AND HAT ALL POSSIBLE SAFETY PRECAUTIONS HAVE BEEN ENACTED TO ENSURE THE SAFEST ENVIRONMENT FOR ALL PERSONNEL.
- LOCATION AND DEPTH OF EXISTING UTILITIES SHOWN HEREON ARE APPROXIMATE ONLY. ACTUAL LOCATIONS AND DEPTHS MUST BE VERIFIED BY THE CONTRACTOR PRIOR TO THE CONSTRUCTION AND THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL UTILITIES, WHETHER SHOWN ON THE PLANS OR NOT, THROUGHOUT ALL PHASES OF 6. THE CONTRACTOR SHALL VERIFY THE SUITABILITY OF ALL EXISTING AND 6. CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES FOR CONSTRUCTION
- ALL NECESSARY EROSION CONTROL MEASURES ARE TO BE IN PLACE PRIOR TO CONSTRUCTION. EROSION CONTROL MEASURES ARE TO BE MAINTAINED AND IN WORKING CONDITION AT ALL TIMES.
- CONTRACTOR SHALL CONFIRM WITH THE OWNER OR HIS DESIGNATE WHETHER TO SALVAGE AND MAKE ARRANGEMENTS TO STORE TRANSPLANTABLE TREES PRIOR TO REMOVAL.
- FOR TREES SHOWN TO REMAIN, THE CONTRACTOR SHALL INSTALL TREE PROTECTION IN ACCORDANCE WITH THE PROJECT PLANS AND SPECIFICATIONS. THE CONTRACTOR SHALL NOT REMOVE OR DAMAGE ANY TREES WITHOUT A PERMIT TO DO SO.
- NO PARKING AND/OR STORAGE SHALL BE ALLOWED WITHIN THE DRIP LINE OF THE TREES TO REMAIN.
- THE CONTRACTOR SHALL SAW CUT EXISTING PAVEMENT, CURBS AND SIDEWALKS AT NEW PAVEMENT, CURB AND SIDEWALK JUNCTURES, NO JAGGED OR IRREGULAR CUTS WILL BE ACCEPTED.
- THE CONTRACTOR SHALL PROTECT ALL PROPERTY PINS, BENCH MARKS, CONSTRUCTION STAKES, HUBS, OR OTHER KEY CONTROL POINTS. THE CONTRACTOR SHALL BE RESPONSIBLE TO RE-ESTABLISH ANY SUCH POINTS AT THEIR OWN EXPENSE.
- 2. DEMOLITION CONTRACTOR IS RESPONSIBLE FOR CLEARING THE SITE OF ALL OBSTRUCTIONS THAT EXIST ON THIS SITE PRIOR TO THE START OF CONSTRUCTION OR DURING THE CONSTRUCTION SO AS TO NOT IMPEDE THE BUILDING CONSTRUCTION CONTRACTOR.
- MATERIAL OR EQUIPMENT SCHEDULED FOR REMOVAL TO BE SALVAGED AND REUSED. CONTRACTOR SHALL REPLACE AT HIS EXPENSE ANY DESTROYED MATERIAL OR EQUIPMENT THAT WAS MARKED FOR SALVAGE
- 4. CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVAL AND DISPOSAL OF ALL HAZARDOUS MATERIAL OFFSITE FOLLOWING ALL APPLICABLE DISPOSABLE REGULATIONS. ON SITE CONCRETE PROPOSED FOR DEMOLITION MAY BE REUSED ON SITE AS FILL AS LONG AS IT IS CRUSHED, FREE OF REBAR, WIRE MESH AND DEBRIS AND CAN MEET GEOTECHNICAL SPECIFICATIONS.
- . CONTRACTOR SHALL REMOVE ALL EXISTING IRRIGATION PIPING ON SITE UNLESS SHOWN OTHERWISE. CUT AND CAP LATERALS AT PROJECT LIMITS TO ALLOW PROPER FUNCTION OF ZONES INTENDED TO REMAIN OR EXTEND OFF-SITE.
- . CONTRACTOR SHALL NOT DEMOLISH ANY PUBLIC WATER OR SANITARY SEWER LINES WITHOUT APPROVAL. EXISTING WATER AND SANITARY SEWER SERVICES SHALL REMAIN OPERATIONAL UNTIL NEW SERVICE IS COMPLETE CUT AND CAP ANY ABANDONED SANITARY SEWER AND WATER SERVICES AT THE EXISTING MAIN. NO ABANDONED SERVICES SHALL REMAIN CONNECTED TO THE PUBLIC MAIN.
- 7. THE USE OF EXPLOSIVES WILL NOT BE PERMITTED.
- 8. ALL WASTE MATERIAL REMAINING AFTER OWNER SALVAGE IS COMPLETE AND RESULTING FROM DEMOLITION OPERATIONS BECOMES THE PROPERTY OF THE CONTRACTOR. APPROPRIATE DISPOSAL OF WASTE MATERIAL SHALL BE THE PROVIDE LIST OF ITEMS TO BE SALVAGED.
-). THE CONTRACTOR SHALL MAINTAIN THE SITE IN A CLEAN AND ORDERLY MANNER.
- . THE CONTRACTOR SHALL MEET ALL LOCAL, STATE, AND FEDERAL REGULATIONS FOR DUST CONTROL. THE CONTRACTOR SHALL BE RESPONSIBLE AT THEIR OWN EXPENSE FOR ANY FUGITIVE DUST ON ADJOINING PROPERTIES.

GRADING NOTES

- 1. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THIS SCOPE OF 1. THE CONTRACTOR WILL BE RESPONSIBLE FOR DETERMINING EXACT LOCATION WORK WHERE NOT SPECIFICALLY COVERED IN THE SPECIFICATIONS OR GEOTECHNICAL REPORT SHALL CONFORM TO ALL APPLICABLE CITY, COUNTY AND TXDOT STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (LATEST EDITION).
- ACCORDANCE WITH ALL APPLICABLE, FEDERAL, STATE AND LOCAL 2. SITE PREPARATION, GRADING, EXCAVATION AND FILL SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT GEOTECHNICAL REPORT AND SPECIFICATIONS.
 - GEOTECHNICAL ENGINEER PRIOR TO PLACING AND COMPACTING.
 - REFLECT FINISHED GRADES. THE THICKNESS OF PAVING, BASE, GRASS, TOPSOIL, AND MULCH MUST BE SUBTRACTED TO OBTAIN SUBGRADE FI EVATIONS.
 - 5. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER OF ANY QUESTIONS THAT MAY ARISE CONCERNING THE INTENT, PLACEMENT, OR 5. CONTRACTOR IS RESPONSIBLE FOR COMPLYING TO THE SPECIFICATIONS OF LIMITS OF DIMENSIONS OR GRADES NECESSARY FOR CONSTRUCTION OF THIS PROJECT
 - PROPOSED SITE CONDITIONS INCLUDING GRADES AND DIMENSIONS BEFORE COMMENCEMENT OF CONSTRUCTION. THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY OF ANY DISCREPANCIES.
 - 7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ACQUIRING ALL PERMITS, TESTS, APPROVALS AND ACCEPTANCES REQUIRED TO COMPLETE CONSTRUCTION OF THIS PROJECT.
 - THE CONTRACTOR SHALL REMOVE TOP SOIL GRASS ROOTS DEBRIS FTC. AND DISPOSE OFF SITE THOSE MATERIALS NOT SUITABLE FOR EMBANKMENT AND TOPSOIL. CLEAN STRIPPINGS AND TOPSOIL MAY BE STOCKPILED ON SITE FOR REUSE IN A LOCATION SPECIFIED BY THE OWNER.
 - THE SITE CONTRACTOR SHALL BE RESPONSIBLE FOR SITE STABILIZATION. ALL DISTURBED AREAS SHALL BE REVEGETATED IN ACCORDANCE WITH PROJECT SPECIFICATIONS AND TPDES/SWPPP REQUIREMENTS. REFERENCE THE LANDSCAPE ARCHITECT'S PLAN, IF APPLICABLE.
 - 10. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS (EROSION 9. ALL CONCRETE FOR ENCASEMENTS SHALL HAVE A MINIMUM 28 DAY CONTROL MEASURES) TO KEEP DRAINAGE AND SILT FROM WASHING ONTO ADJACENT PROPERTÝ, STREETS, OR DRAINAGE WAYS. CONTRACTOR SHALL IMMEDIATELY REMOVE SILT/DEBRIS WHICH WASHES OFFSITE OR INTO EXISTING STORM DRAIN SYSTEMS. (SEE SWPPP PLANS & TPDES BOOK).
 - 11. THE CONTRACTOR SHALL OBTAIN GRADES SHOWN HEREON WITHIN +/-ONE-TENTH (0.10) FOOT.
 - 12. IN PROPOSED PAVING AREAS, IT IS INTENDED THAT THE MINIMUM GRADE IS 1% ALL EARTHEN SLOPES SHALL BE A MAXIMUM OF 3:1 AND A MINIMUM 12. ALL GARBAGE OR SPOIL MATERIAL FROM THIS WORK SHALL BE REMOVED OF 2.0% UNLESS OTHERWISE SHOWN.
- CONTRACTOR SHALL COORDINATE WITH THE OWNER TO IDENTIFY ANY 13. ACCESSIBILITY: SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2%. SIDEWALK 13. GAS AND ELECTRIC ALIGNMENTS SHOWN ON THIS DRAWING ARE CONCEPTUAL. LONGITUDINAL SLOPE ALONG ACCESSIBLE ROUTES SHALL NOT EXCEED 5%, UNLESS OTHERWISE NOTED. SIDEWALK CURB RAMPS SHALL NOT EXCEED 8.33%. (SEE CURB RAMP DETAILS). CURB RAMP LANDINGS SHALL NOT EXCEED 2%. ACCESSIBLE PARKING STALLS SHALL NOT EXCEED 2% IN ANY DIRECTION
 - 14. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING TO ITS ORIGINAL, OR BETTER, CONDITION ANY DAMAGE DONE TO EXISTING TREES, BUILDINGS, UTILITIES, FENCES, PAVEMENT, CURBS, OR DRIVEWAYS (NO SEPARATE PAY 15. REFER TO INTERIOR PLUMBING DRAWINGS FOR TIE-IN OF ALL UTILITIES. ITEMS)
 - 15. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION IN WORKING NEAR UTILITIES, GAS LINES, SEWER, OR EXISTING APPURTENANCES. PRIOR TO PERFORMING ANY EXCAVATION, CONTRACTOR SHALL CONTACT ALL UTILITY COMPANIES AND ENSURE UTILITIES HAVE BEEN ADEQUATELY LOCATED AND IDENTIFIED. THE ENGINEER SHALL BE NOTIFIED IF ANY UTILITY CONFLICTS ARE DISCOVERED.
 - PROJECT. DRAINAGE SHALL BE DIRECTED AWAY FROM ALL BUILDING FOUNDATIONS. CONTRACTOR SHOULD TAKE PRECAUTIONS NOT TO ALLOW ANY PONDING OF WATER.
 - 17. FOR FILL PLACEMENT ON HILL SIDES OR STEEP SLOPE AREAS, THE CONTRACTOR SHALL REFERENCE THE PROJECT SPECIFICATIONS AND GEOTECHNICAL REPORT FOR SPECIAL INSTRUCTIONS REGARDING BENCHING.
- RESPONSIBILITY OF THE CONTRACTOR AT HIS OWN EXPENSE. OWNER WILL 18. NO WORK SHALL BE PERFORMED IN A PUBLIC RIGHT-OF-WAY WITHOUT A PERMIT

OCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCOG, Digital Globe, Texas

SITE UTILITY NOTES

OF ALL UTILITIES AND DRAINAGE STRUCTURES WHETHER SHOWN ON THE PLANS OR NOT. THE CONTRACTOR SHALL UNCOVER EXISTING UTILITIES PRIOR TO CONSTRUCTION TO VERIFY SIZE, GRADE, AND LOCATION. THI CONTRACTOR SHALL NOTIFY THE ENGINEER IMMEDIATELY OF ANY DEVIATIONS FROM PLANS PRIOR TO BEGINNING CONSTRUCTION. ANY DAMAGE T EXISTING UTILITIES, WHETHER SHOWN ON THE PLANS OR NOT, SHALL BE THE

CONTRACTOR'S RESPONSIBILITY TO REPAIR, AT HIS EXPENSE. 2. DRAWINGS DO NOT SHOW ALL EXISTING UTILITIES. ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD WHETHER SHOWN ON THIS PLAN OR NOT (PRIOR TO INSTALLATION OF ANY NEW LINES).

INSTALLATION OF PROPOSED UTILITIES

4. CONTRACTOR SHALL CALL FOR THE LOCAL JURISDICTIONAL INSPECTIONS AT LEAST 48 HOURS PRIOR TO STARTING CONSTRUCTION.

THE LOCAL JURISDICTION WITH REGARDS TO MATERIALS AND INSTALLATION OF THE UTILITIES AND STORM DRAINS.

INSTALLATION REQUIREMENTS, SPECIFICATIONS AND ALL TESTING. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF

THIS PROJECT SHALL COMPLY WITH THE FOLLOWING AS APPLICABLE: A. CURRENT "SAN ANTONIO WATER SYSTEM STANDARD SPECIFICATIONS FOR CONSTRUCTION"

- B. CURRENT "SAN ANTONIO WATER SYSTEM UTILITY SERVICE REGULATIONS"
- C. CURRENT CITY OF SAN ANTONIO "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION"
- D. CURRENT TXDOT "STANDARD SPECIFICATIONS FOR CONSTRUCTION OF HIGHWAYS, STREETS, AND DRAINAGE" E. CURRENT CITY OF SAN ANTONIO "RIGHT-OF-WAY ORDINANCE AND CRITERIA MANUAL"

MINIMUM TRENCH WIDTH SHALL BE 2 FEET.

COMPRESSION STRENGTH AT 3000 P.S.I.

10. CONTRACTOR SHALL PROTECT ALL EXISTING TREES, FENCES, PAVING, UTILITIES, AND OTHER STRUCTURES SCHEDULED TO REMAIN. ANY STRUCTURE DAMAGED BY THE CONTRACTOR SHALL BE REPAIRED BY THE CONTRACTOR AT THEIR EXPENSE. THE CONTRACTOR SHALL FURNISH THE ENGINEER WITH ALL FINAL UTILITY

AS-BUILT MEASUREMENTS, TOPS AND LENGTH OF SERVICE CONNECTIONS OF THE PROJECT

- FROM THE SITE BY THE CONTRACTOR AT HIS SOLE EXPENSE. THE ACTUAL DESIGN AND LOCATIONS SHALL BE DETERMINED BY THE LOCAL SERVICE PROVIDER OR MEP ENGINEER.
- 14. CONTRACTOR SHALL COORDINATE TELE. COMMUNICATIONS, CABLE, ELECTRIC AND GAS LINE INSTALLATION WITH LOCAL SERVICE PROVIDER. THE SERVICE PROVIDER WILL BE RESPONSIBLE FOR INSTALLATION OF GAS LINE TO WITHIN 5' OF BUILDING.
- 16. SEE IRRIGATION, LIGHTING AND ARCHITECTURAL PLANS FOR ADDITIONAL CONDUIT LOCATIONS AS APPLICABLE. VERIFY ALL CONDUIT AND SLEEVE LOCATIONS PRIOR TO PLACING ANY PAVEMENT.
- 17. CONTRACTOR SHALL INSTALL ALL CONDUITS WITH A MINIMUM 4-FOOT SWEEP RADIUS. ALL CONDUITS SHALL HAVE A PULL STRING TO BE INSTALLED BY THE CONTRACTOR.
- 16. POSITIVE DRAINAGE SHALL BE MAINTAINED THROUGHOUT THE SCOPE OF THE 18. NO WORK SHALL BE ALLOWED WITHIN THE PUBLIC RIGHT-OF-WAY WITHOUT AN APPROVED PERMIT.
 - 19. THE CONSTRUCTION OF UNDERGROUND PRIMARY ELECTRIC AND GAS DISTRIBUTION SYSTEMS SHALL BE GOVERNED BY THE ENGINEERING CONSTRUCTION PLANS PREPARED BY THE LOCAL SERVICE PROVIDER. THIS DRAWING SHALL SERVE ONLY AS REFERENCE DOCUMENT TO COORDINATE LOCATION OF THE PROPOSED PRIMARY ELECTRIC AND GAS DISTRIBUTION SYSTEM. THE LOCAL SERVICE PROVIDER'S CONSTRUCTION DRAWINGS AND 12. CONTRACTOR SHALL PROVIDE ALL NECESSARY FITTINGS FOR THE PROJECT CONSTRUCTION DETAILS SHALL GOVERN.
 - 20. CONTRACTOR SHALL INCLUDE IN HIS BID A 4" PVC CONDUIT FOR TELEPHONE 13. CONTRACTOR SHALL PROVIDE TEMPORARY BLOWOFFS AS REQUIRED TO AND A 2" PVC CONDUIT FOR CABLE TV TO BE IN THE SAME TRENCH AS UNDERGROUND ELECTRIC LINES. CONTRACTOR SHALL VERIFY WITH APPROPRIATE UTILITY COMPANY PRIOR TO CONSTRUCTION ON NUMBER AND SIZE OF CONDUITS NEEDED FOR UTILITY SERVICE TO ALL BUILDINGS.
 - 21. BEDDING FOR ALL UTILITIES SHALL BE PER THE PROJECT SPECIFICATIONS. NO WATER JETTING OF BACKFILL MATERIAL WILL BE ALLOWED.

SANITARY SEWER NOTES

- 1. SEWER PIPE WHERE WATER LINE CROSSES SHALL BE 160 P.S.I. AND MEET 1. THE REQUIREMENTS OF ASTM D2241 WITH ONE 20' JOINT CENTERED AT WATER MAIN.
- 2. NO VERTICAL STACKS SHALL BE ALLOWED
- 3. WHEN HORIZONTAL DISTANCE BETWEEN SEWER PIPES AND WATER MAIN IS LESS THAN 9 FT. OF SEPARATION, SEWER MAIN SHALL BE INSTALLED WITH 160 PSI (MIN) PRESSURE PIPE AND FITTINGS IN ACCORDANCE WITH ISU CONSTRUCTION CRITERIA FOR CONSTRUCTION OF SEWER MAINS IN THE VICINITY OF WATER MAINS.
- 4. ALL SEWER PIPES SHALL BE PVC (SDR 26), UNLESS OTHERWISE NOTED.
- 5. PRIOR TO CONSTRUCTION CONTRACTOR IS TO VERIFY EXISTING INVERT OF 4. CONTRACTOR IS RESPONSIBLE FOR REMOVAL OF ALL WASTE MATERIALS EXISTING SANITARY SEWER MAINS AND ALERT ENGINEER IMMEDIATELY OF ANY DIFFERENCE FROM INVERT SHOWN ON PLANS.
- 6. CONTOURS SHOWN ARE FOR GRAPHICAL USE ONLY.
- 7. MANHOLE OPENINGS ARE 30" AS PER TCEQ CHAPTER 217.55
- 8. CONTRACTOR TO INSTALL PERMANENT MARKERS AT THE END OF ALL SEWER LATERALS, PER HOUSE LATERAL DETAIL DD-854-01.
- 9. ALL 6" SEWER LATERALS WILL BE SET AT A MINIMUM 2% SLOPE.
- 10. BACKFILL MUST COMPLY WITH LSUC SPECIFICATIONS 804.4
- 11. TOPS OF EXISTING MANHOLES SHALL BE ADJUSTED AS NECESSARY TO BE FLUSH WITH PROPOSED PAVEMENT ELEVATIONS, AND TO BE 0.50 FEET ABOVE FINISHED GROUND ELEVATIONS IN UNPAVED AREAS WITH WATER TIGHT LIDS

WATER NOTES

- 1. ALL MATERIALS AND CONSTRUCTION PROCEDURES FOR THE WATER SYSTEM WITHIN THE SCOPE OF THIS CONTRACT SHALL CONFORM TO ALL APPLICABLE SAWS CONSTRUCTION SPECIFICATIONS.
- 2. MACHINE CHLORINATION SHALL BE BY THE CONTRACTOR ACCORDING TO THE SERVICE PROVIDER'S CONSTRUCTION SPECIFICATIONS. . ALL WATER LINES SHALL BE FOUR-FOOT (4') BURY UNLESS OTHERWISE
- NOTED.
- ALL WATER LINES SHALL BE PVC PIPE UNLESS OTHERWISE INDICATED. ALL 6 & 8-INCH PVC WATER LINES SHALL BE CLASS 150 DR(18), MEETING AWWA C900 STANDARDS. ALL SERVICES 4 INCH AND SMALLER SHALL BE SCHEDULE 80 PVC. DUCTILE IRON WATER LINES SHALL BE CLASS 50.
- 5. ALL WATER LINES MUST BE INSTALLED A MINIMUM DISTANCE OF 9-FEET HORIZONTALLY FROM SANITARY SEWER MAINS AND LATERALS. ALL VERTICAL CROSSINGS MUST CONFORM TO TCEQ, 30 TAC, CHAPTER 290, SEPARATION REQUIREMENTS AND METHODS. WHENEVER POSSIBLE ALL WATER LINES SHALL CROSS ABOVE SANITARY SEWER LINES.
- 6. THE CONTRACTOR SHALL PERFORM A HYDROSTATIC TEST ON THE FIRE LINE PER THE FIRE DEPARTMENT'S REQUIREMENTS. THE HYDROSTATIC TEST SHALL FOLLOW THE PROCEDURE LISTED IN THE LOCAL FIRE CODE.
- 7. ALL OTHER LINES SHALL BE HYDROSTATICALLY TESTED BY THE CONTRACTOR, PER LOCAL JURISDICTIONAL REQUIREMENTS.
- 8. AT THE COMPLETION OF CONSTRUCTION, THE CONTRACTOR SHALL FURNISH THE OWNER WITH ALL FITTING-TO-FITTING DIMENSIONS. TYPES, AND MANUFACTURER OF MATERIALS USED AND LOCATIONS FOR ALL VALVES, BENDS. ETC.
- 9. THE SITE SHALL BE EXCAVATED OR FILLED TO SUBGRADE PRIOR TO THE CONSTRUCTION OF WATER AND FIRE LINES BY THE CONTRACTOR.
- 10. ALL SERVICES SHALL BE BROUGHT TO WITHIN 5 FEET OF THE BUILDING. BUILDING CONTRACTOR SHALL INCLUDE IN THEIR BID THE COST TO CONNECT ALL SERVICES TO THE BUILDING.
- 11. REFER TO PLUMBING PLAN FOR LOCATION OF ALL WATER SERVICES TO BUILDING.
- INDICATED ON THE PLANS OR AS NEEDED AT NO ADDITIONAL PAYMENT.
- FACILITATE FLUSHING THE LINES AFTER THE TESTING AND DISINFECTION PROCESS.
- 14. UNIT PRICE BID FOR "STANDARD FIRE HYDRANT ASSEMBLY" SHALL INCLUDE FIRE HYDRANT, 6" GATE VALVE, 6" VALVE BOX, ANCHOR BEND, AND ALL 6" DUCTILE IRON PIPE REQUIRED TO COMPLETE INSTALLATION. (DUCTILE IRON PIPE SHALL INCLUDE ALL PIPE FROM THE TEE ON THE MAIN LINE TO THE FIRE HYDRANT.)
- 15. ALL FITTINGS SHALL BE MECHANICAL JOINT.
- 16. CONTRACTOR MUST BE AN APPROVED SAWS AND APPROVED FIRELINE CONTRACTOR.
- 17. ALL PIPE DIMENSIONS ARE APPROXIMATE ONLY.
- 18. CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND COMPLETING AND COORDINATING ALL NECESSARY TESTS.
- 19. THRUST BLOCKS SHALL BE PROVIDED AT ALL BENDS, TEES, AND VALVES AS INDICATED ON THE ATTACHED WATER DISTRIBUTION SYSTEM DETAIL SHEET. 20. ALL FDC STANDPIPES SHALL HAVE A 4" LINE CONNECTING TO FIRE
- SPRINKLER SYSTEM OF EACH BUILDING. CONTRACTOR SHALL VERIFY SIZE OF LINE WITH MEP PLANS. IF DISCREPANCIES EXIST MEP PLAN SHALL GOVERN AND CIVIL ENGINEER SHALL BE NOTIFIED IMMEDIATELY. CONTRACTOR SHALL REFER TO MEP PLANS FOR DETAILS OF CONNECTION AND ALIGNMENT OF

- SPECIFICATIONS, AND THE CURRENT CITY, COUNTY OR TXDOT.
- 2. THE CONTRACTOR SHALL PROTECT ALL EXISTING UTILITIES. THE DAMAGED FACILITIES AT CONTRACTOR'S EXPENSE.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING TO ORIGINAL OR DRIVEWAYS, LANDSCAPING AND STRUCTURES.
- UPON PROJECT COMPLETION.
- 5. WATER JETTING THE BACKFILL OF STORM DRAIN TRENCHES WILL NOT BE PERMITTED.
- TO INSIDE FACE OF STRUCTURES.
- 8. ALL STORM DRAIN TO JUNCTION BOX CONNECTIONS SHALL HAVE CONCRETE
- COLLARS.
- 10. TOPS OF MANHOLES, JUNCTION BOXES AND GRATES SHALL BE SET FLUSH
- TO FINISHED SURFACE BASED UPON GRADING PLAN.
- BOXES, AND DROP STRUCTURES TO DRAIN.

VEGETATION NOTES

ACCEPTANCE OF THE SUBDIVISION

CAUTION UNDERGROUND UTILITIES

ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THIS SCOPE OF WORK SHALL COMPLY WITH THE PROJECT GEOTECH REPORT, THE PROJECT

CONTRACTOR SHOULD EXERCISE EXTREME CAUTION WHEN WORKING NEAR OPERATIONS, THE CONTRACTOR WILL BE REQUIRED TO REPAIR OR REPLACE

BETTER CONDITION DAMAGE DONE TO EXISTING FENCES, CURBS, STREETS,

6. NORTHINGS AND EASTINGS LISTED ON THESE PLANS ARE TO CENTER OF BOX FOR JUNCTION BOXES AND GRATE INLETS AND TO OUTSIDE CORNER FACE OF CURB FOR ALL CURB AND COMBINATION INLETS. ALL LENGTHS OF PIPE ARE

WHERE INDICATED ON PLAN. CONTRACTOR SHALL CONNECT STORM DRAIN PIPE TO JUNCTION BOXES PER MANUFACTURES SPECIFICATIONS.

9. ALL GRATE INLETS MUST BE HS20 EQUIVALENT RATED GRATES.

11. CONTRACTOR SHALL GROUT INVERTS OF ALL STORM DRAIN INLETS, JUNCTION

ALL DISTURBED AREAS ON THE SITE TO BE REVEGETATED PRIOR TO

THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF EXISTING UTILITIES AS SHOWN ON THESE PLANS IS BASED ON RECORDS OF THE VARIOUS UTILITY COMPANIES. AND WHERE POSSIBLE MEASUREMENTS TAKEN IN THE FIELD. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE. THE CONTRACTOR SHALL BE REQUIRED TO LOCATE ALL PUBLIC OR PRIVATE UTILITIES INCLUDING BUT NOT LIMITED TO EXISTING UTILITIES AND SHOULD THEY BE DAMAGED DURING CONSTRUCTION WATER. SEWER, TELEPHONE, AND FIBER OPTIC LINES, SITE LIGHTING ELECTRIC SECONDARY ELECTRIC, PRIMARY ELECTRICAL DUCT BANKS, LANDSCAPE IRRIGATION FACILITIES, AND GAS LINES. THE CONTRACTOR MUST CONTACT 1-800-DIG-TESS AND CALL THE APPROPRIATE UTILITY COMPANIES AT LEAST 72 HOURS BEFORE ANY EXCAVATION AND/OR START OF CONSTRUCTION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO RELOCATE ALL EXISTING UTILITIES (WHETHER SHOWN ON PLANS OR NOT) WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS. ANY UTILITY CONFLICTS THAT ARISE SHOULD BE COMMUNICATED TO THE ENGINEER IMMEDIATELY AND PRIOR TO CONSTRUCTION. ANY DAMAGE TO EXISTING UTILITIES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND THE REPAIR SHALL BE AT CONTRACTORS SOLE EXPENSE WHETHER THE UTILITY IS SHOWN ON THESE PLANS OR NOT.

CAUTION OVERHEAD UTILITIES

7. CONTRACTOR SHALL ENSURE PROPER SIZE OF JUNCTION BOXES NEEDED CONTRACTOR TO EXERCISE EXTREME CAUTION WHEN WORKING UNDER "HIGH VOLTAGE TRANSMISSION LINES". A WORKING HEIGHT OF 30' FROM GROUND ELEVATION WILL BE OBSERVED WHEN WORKING UNDER THE HIGH VOLTAGE LINE. COORDINATE ALL WORK WITH THE LOCAL UTILITY PROVIDER.

TRENCH EXCAVATION SAFETY PROTECTION

CONTRACTOR AND/ OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/ GEOTECHNICAL/ SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS. PROGRAMS AND /OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM. OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

PLA JOE DA				NO. REVISION	DATE
AT NO. 3 NO TE SIGNER	THE UAKS AT THE DUMINION	PAPE-DAWSON	ANDR		
23-1 126 DECEME	SAN ANTONIO, LEXAS	THE ENGINEERS			
180(510–00 ER 20 AA		2000 NW LOOP 410 I SAN ANTONIO, TX 78213 I 210.375.9000	BELLTO		
0417 6 024	GENERAL NOTES	TEXAS ENGINEERING FIRM #470 I TEXAS SURVEYING FIRM #10028800	/2024		

C0.10

HFFT



THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL AERIAL IMAGERY PROVIDED BY GOOGL® UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCOC, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Agency.

ate: September 8, 2023, 11:49 AM - User ID: aarring ile: P:\126\10\06\Design\Civil\DM-1261006.dwg







PLAN

DEMOLITION

PLAT NO.	23	-11800)417
JOB NO.		12610-06	5
DATE	DECE	MBER 20	24
DESIGNER		AA	
CHECKED	ΕK	DRAWN	AA
SHEET	С	0.20	



te: September 8, 2023, 11:49 AM — User ID: aarringt e: P:\126\10\06\Desian\Civil\0D-1261006.dwa



:e: September 8, 2023, 11:50 AM — User ID: aarrington :: P:\126\10\06\Design\Civil\SDA1—1261006.dwg



ate: September 8, 2023, 11:50 AM - User ID: aarrington le: P:\126\10\06\Design\Civil\SDA1-1261006.dwg











HIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.









Jate: September 8, 2023, 11:51 AM - User ID: aarringto ile: P: \126\10\06\Design\Civil\STA1-1261006.dwg







Jate: September 8, 2023, 11:51 AM — User ID: aarringtor ile: P:\126\10\06\Design\Civil\STA1—1261006.dwg



Jate: September 8, 2023, 11:52 AM - User ID: aarrington ile: P:\126\10\06\Design\Civil\STA1-1261006.dwg

8.	FILL	MATER	RIAL	SHOU	LD E	ЗE	NATI	√E	ON-	SITE	MATE	RIAL,	FREE	0
	DELE	TERIOUS	S MA	TERIAL	. WITH	ΗA	MINI	MUM	CBF	R VALI	UE OI	- 2.5	AND	ΑF
	MAXIN	NUM OI	- 20	THE	GRA	VEL	SIZE	SHO	OULD	NOT	EXCE	ED 3	INCH	ES II
	DIAME	ETER. L	IME	APPLIC	OITAC	N RA	ATE S	SHOL	JLD E	BE RE-	–EVAl	UATE	D FOR	TH
	FILL	MATERI.	AL.	THE N	IATER	IAL	SHOU	JLD	BE F	PLACED) AS	PER	APPLIC	CABL
	CITY	OR COU	JNTY	GUIDE	LINES	•								

C2.02

SHEET

ate: September 8, 2023, 11:52 AM - User ID: aarrington e: P:\126\10\06\Design\Civil\STA1-1261006.dwg

с _р

THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL AERIAL IMAGERY PROVIDED BY GOOGLE© UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCOG, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Agency.

THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

te: September 8, 2023, 11:53 AM - User ID: aarring :: P:\126\10\06\Design\Civil\SG0A-1261006.dwg

LEGAL DESCRIPTION: LOTS 1-21, BLOCK 59, N.C.B. 1638 LOTS 1-22, & 901-902, BLOCK 60, N.C.B LOTS 1-12, BLOCK 61, N.C.B. 1638 (PLAT NO. 23-11800417)	ATION MAP 0T-TO-SCALE 5 16385 LE: 1"= 60' 120'	SS: VALLEY , TX 78257	NOISINA ON ON IIIIIIIIIIIIIIIIIIIIIIIIIIIIII	
		ITEM	Z	0006
SYM	BOL PROPERTY BOUNDARY	NUMBER	NOS (A	210.375.
Street Name	STREET SIGN	531.57	ER.	78213 1
STOP	R1–1 30"X30"	531.3	PE-D	AN ANTONIO, T
Street PEAD	D3 W 9"	531.55	EN	P 410 I 5
NO OUTLET	W14-2 36"			2000 NW LOO
	TRAFFIC FLOW ARROW			
REFERENCE SHEET CO.10 FOR	NOTES.		E OAKS AT THE DOMINION SAN ANTONIO, TEXAS	

PLAT NO. <u>23-11800417</u> JOB NO. <u>12610-06</u> DATE <u>DECEMBER 2024</u>

CHECKED EK DRAWN AA

SHEET _____ C2.20

DESIGNER AA

14

ite: September 8, 2023, 11:53 AM - User ID: aarrington e: P:\126\10\06\Design\Civil\SGDT-1261006.dwg

HIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSWITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL AERIAL IMAGERY PROVIDED BY GOOGLE UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

BLK 48 NCB 16385

HIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

OCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

SAWS CONSTRUCTION NOTES (LAST REVISED JANUARY 2022)

- CONTRACT SHALL BE APPROVED BY THE SAN ANTONIO WATER SYSTEM (SAWS) AND COMPLY WITH THE PLANS, SPECIFICATIONS, GENERAL CONDITIONS AND WITH THE FOLLOWING AS APPLICABLE:
- CRITERIA FOR DOMESTIC WASTEWATER SYSTEM", TEXAS ADMINISTRATIVE
- WATER", TAC TITLE 30 PART 1 CHAPTER 290. B.CURRENT TXDOT "STANDARD SPECIFICATIONS FOR CONSTRUCTION OF HIGHWAYS, STREETS AND DRAINAGE".
- C.CURRENT "SAN ANTONIO WATER SYSTEM STANDARD SPECIFICATIONS FOR WATER AND SANITARY SEWER CONSTRUCTION".
- D.CURRENT CITY OF SAN ANTONIO "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION".
- E. CURRENT CITY OF SAN ANTONIO "UTILITY EXCAVATION CRITERIA MANUAL" (UECM).
- 2. THE CONTRACTOR SHALL NOT PROCEED WITH ANY PIPE INSTALLATION WORK UNTIL THEY OBTAIN A COPY OF THE APPROVED COUNTER PERMIT OR GENERAL CONSTRUCTION PERMIT (GCP) FROM THE CONSULTANT AND HAS BEEN NOTIFIED BY SAWS CONSTRUCTION INSPECTION DIVISION TO PROCEED WITH THE WORK AND HAS ARRANGED A MEETING WITH THE INSPECTOR AND CONSULTANT FOR THE WORK REQUIREMENTS. WORK COMPLETED BY THE CONTRACTOR WITHOUT AN APPROVED COUNTER PERMIT AND/OR A GCP WILL BE SUBJECT TO REMOVAL AND REPLACEMENT AT THE EXPENSE OF THE CONTRACTORS AND/OR THE DEVELOPER.
- 3. THE CONTRACTOR SHALL OBTAIN THE SAWS STANDARD DETAILS FROM THE SAWS WEBSITE, HTTP://WWW.SAWS.ORG/BUSINESS_CENTER/SPECS. UNLESS OTHERWISE NOTED WITHIN THE DESIGN PLANS.
- INSPECTION DIVISION AT (210) 233-2973, ON NOTIFICATION PROCEDURES THAT WILL BE USED TO NOTIFY AFFECTED HOME RESIDENTS AND/OR PROPERTY OWNERS 48 HOURS PRIOR TO BEGINNING ANY WORK.
- LOCATION AND DEPTH OF EXISTING UTILITIES AND SERVICE LATERALS SHOWN ON THE PLANS ARE UNDERSTOOD TO BE APPROXIMATE. ACTUAL LOCATIONS AND DEPTHS MUST BE FIELD VERIFIED BY THE CONTRACTOR AT LEAST 1 WEEK PRIOR TO CONSTRUCTION. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO LOCATE UTILITY SERVICE LINES AS REQUIRED FOR CONSTRUCTION AND TO PROTECT THEM DURING CONSTRUCTION AT NO COST TO SAWS.
- 6. THE CONTRACTOR SHALL VERIFY THE EXACT LOCATION OF UNDERGROUND UTILITIES AND DRAINAGE STRUCTURES AT LEAST 1-2 WEEKS PRIOR TO CONSTRUCTION WHETHER SHOWN ON PLANS OR NOT. PLEASE ALLOW UP TO 7 BUSINESS DAYS FOR LOCATES REQUESTING PIPE LOCATION MARKERS ON SAWS FACILITIES. THE
- SAWS UTILITY LOCATES: HTTP://WWW.SAWS.ORG/SERVICE/LOCATES COSA DRAINAGE (210) 207-0724 OR (210) 207-6026 COSA TRAFFIC SIGNAL OPERATIONS (210) 206-8480 COSA TRAFFIC SIGNAL DAMAGES (210) 207-3951 • TEXAS STATE WIDE ONE CALL LOCATOR 1-800-545-6005 OR 811
- 7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING EXISTING FENCES, CURBS, STREETS, DRIVEWAYS, SIDEWALKS, LANDSCAPING AND STRUCTURES TO ITS ORIGINAL OR BETTER CONDITION IF DAMAGES ARE MADE AS A RESULT OF THE PROJECT'S CONSTRUCTION.
- 8. ALL WORK IN TEXAS DEPARTMENT OF TRANSPORTATION (TXDOT) AND/OR BEXAR COUNTY RIGHT-OF-WAY SHALL BE DONE IN ACCORDANCE WITH RESPECTIVE CONSTRUCTION SPECIFICATIONS AND PERMIT REQUIREMENTS.
- 9. THE CONTRACTOR SHALL COMPLY WITH CITY OF SAN ANTONIO OR OTHER GOVERNING MUNICIPALITY'S TREE ORDINANCES WHEN EXCAVATING NEAR TREES.
- 10. THE CONTRACTOR SHALL NOT PLACE ANY WASTE MATERIALS IN THE 100-YEAR FLOOD PLAIN WITHOUT FIRST OBTAINING AN APPROVED FLOOD PLAIN PERMIT.
- 11. HOLIDAY WORK: CONTRACTORS WILL NOT BE ALLOWED TO PERFORM SAWS WORK ON SAWS RECOGNIZED HOLIDAYS. REQUEST SHOULD BE SENT TO CONSTWORKREQ@SAWS.ORG.

WEEKEND WORK CONTRACTORS ARE REQUIRED TO NOTICY THE SAWS INSPECTION CONSTRUCTION DEPARTMENT 48 HOURS IN ADVANCE TO REQUEST WEEKEND WORK. REQUEST SHOULD BE SENT TO CONSTWORKREQ@SAWS.ORG.

- ANY AND ALL SAWS UTILITY WORK INSTALLED WITHOUT HOLIDAY/WEEKEND APPROVAL WILL BE SUBJECT TO BE UNCOVERED FOR PROPER INSPECTION.
- MEETING THE COMPACTION RÉQUIREMENTS ON ALL TRENCH BACKFILL AND FOR PAYING FOR THE TESTS PERFORMED BY A THIRD PARTY. COMPACTION TESTS WILL BE DONE AT ONE LOCATION POINT RANDOMLY SELECTED, OR AS INDICATED BY THE SAWS INSPECTOR AND/OR THE TEST ADMINISTRATOR. PER EACH 12-INCH LOOSE LIFT PER 400 LINEAR FEET AT A MINIMUM. THIS PROJECT WILL NOT BE ACCEPTED AND FINALIZED BY SAWS WITHOUT THIS REQUIREMENT BEING MET AND VERIFIED BY PROVIDING ALL NECESSARY DOCUMENTED TEST RESULTS.
- 13. A COPY OF ALL TESTING REPORTS SHALL BE FORWARDED TO SAWS CONSTRUCTION INSPECTION DIVISION.

1. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF THIS

A.CURRENT TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) "DESIGN CODE (TAC) TITLE 30 PART 1 CHAPTER 217 AND "PUBLIC DRINKING

4. THE CONTRACTOR IS TO MAKE ARRANGEMENTS WITH THE SAWS CONSTRUCTION

FOLLOWING CONTACT INFORMATION ARE SUPPLIED FOR VERIFICATION PURPOSES:

12. COMPACTION NOTE (ITEM 804): THE CONTRACTOR SHALL BE RESPONSIBLE FOR

SAWS WATER NOTES

1. PRIOR TO TIE-INS, ANY SHUTDOWNS OF EXISTING MAINS OF ANY SIZE MUST BE COORDINATED WITH THE SAWS CONSTRUCTION INSPECTION DIVISION AT LEAST ONE WEEK IN ADVANCE OF THE SHUTDOWN. THE CONTRACTOR MUST ALSO PROVIDE A SEQUENCE OF WORK AS RELATED TO THE TIE-INS; THIS IS AT NO ADDITIONAL COST TO SAWS OR THE PROJECT AND IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO SEQUENCE THE WORK ACCORDINGLY. • FOR WATER MAINS 12" OR HIGHER: SAWS EMERGENCY OPERATIONS CENTER (210)233-2014

2. ASBESTOS CEMENT (AC) PIPE, ALSO KNOWN AS TRANSITE PIPE WHICH IS KNOWN TO CONTAIN ASBESTOS-CONTAINING MATERIAL (ACM), MAY BE LOCATED WITHIN THE PROJECT LIMITS. SPECIAL WASTE MANAGEMENT PROCEDURES AND HEALTH AND SAFETY REQUIREMENTS WILL BE APPLICABLE WHEN REMOVAL AND/OR DISTURBANCE OF THIS PIPE OCCURS. SUCH WORK IS TO BE MADE UNDER SPECIAL SPECIFICATION ITEM NO. 3000, "SPECIAL SPECIFICATION FOR HANDLING ASBESTOS CEMENT PIPE".

3. VALVE REMOVAL: WHERE THE CONTRACTOR IS TO ABANDON A WATER MAIN, THE CONTROL VALVE LOCATED ON THE ABANDONING BRANCH WILL BE REMOVED AND REPLACED WITH A CAP/PLUG. (NSPI)

4. SUITABLE ANCHORAGE/THRUST BLOCKING OR JOINT RESTRAINT SHALL BE PROVIDED AT ALL OF THE FOLLOWING MAIN LOCATIONS: DEAD ENDS, PLUGS, CAPS, TEES, CROSSES, VALVES, AND BENDS, IN ACCORDANCE WITH THE STANDARD DRAWINGS DD-839 SERIES AND ITEM NO. 839, IN THE SAWS STANDARD SPECIFICATIONS FOR CONSTRUCTION.

5. ALL VALVES SHALL READ "OPEN RIGHT".

- 6. PRVS REQUIRED: CONTRACTOR TO VERIFY THAT NO PORTION OF THE TRACT IS BELOW GROUND ELEVATION OF 1215 FEET WHERE THE STATIC PRESSURE WILL NORMALLY EXCEED 80 PSI. AT ALL SUCH LOCATIONS WHERE THE GROUND LEVEL IS BELOW 1215 FEET, THE DEVELOPER OR BUILDER SHALL INSTALL AT EACH LOT, ON THE CUSTOMERIS SIDE OF THE METER, AN APPROVED TYPE PRESSURE REGULATOR IN CONFORMANCE WITH THE PLUMBING CODE OF THE CITY OF SAN ANTONIO. NO DUAL SERVICES ALLOWED FOR ANY LOT(S) IF *PRV IS/ARE REQUIRED FOR SUCH LOT(S), ONLY SINGLE SERVICE CONNECTIONS SHALL BE ALLOWED. *NOTE: A PRESSURE REGULATOR IS ALSO KNOWN AS A PRESSURE REDUCING VALVE (PRV).
- 7. PIPE DISINFECTION WITH DRY HTH FOR PROJECTS LESS THAN 800 LINEAR FEET. (ITEM NO. 847.3): MAINS SHALL BE DISINFECTED WITH DRY HTH WHERE SHOWN IN THE CONTRACT DOCUMENTS OR AS DIRECTED BY THE INSPECTOR, AND SHALL NOT EXCEED A TOTAL LENGTH OF 800 FEET. THIS METHOD OF DISINFECTION WILL ALSO BE FOLLOWED FOR MAIN REPAIRS. THE CONTRACTOR SHALL UTILIZE ALL APPROPRIATE SAFETY MEASURE TO PROTECT HIS PERSONNEL DURING DISINFECTION OPERATIONS.

8. BACKFLOW PREVENTION DEVICES:

- ALL IRRIGATION SERVICES WITHIN RESIDENTIAL AREAS ARE REQUIRED TO HAVE BACKFLOW PREVENTION DEVICES. • ALL COMMERCIAL BACKFLOW PREVENTION DEVICES MUST BE APPROVED BY SAWS PRIOR TO INSTALLATION.
- 9. FINAL CONNECTION TO THE EXISTING WATER MAIN SHALL NOT BE MADE UNTIL THE WATER MAIN HAS BEEN PRESSURE TESTED, CHLORINATED, AND SAWS HAS RELEASED THE MAIN FOR TIE-IN AND USE
- 10. DIVISION VALVES: DIVISION VALVES SHOWN ON PLANS OR NOT SHOWN ON PLANS BUT FOUND IN THE FIELD SHALL ONLY BE OPERATED BY SAWS DISTRIBUTION AND COLLECTION STAFF AND ONLY WITH PRIOR WRITTEN APPROVAL OF THE SAWS DIRECTOR OF PRODUCTION AND OPERATIONS AND PROPER COORDINATION WITH ALI SAWS DEPARTMENTS. CONTRACTOR SHALL PROVIDE WRITTEN NOTIFICATION TO THE INSPECTOR A MINIMUM OF TWO WEEKS IN ADVANCE TO START THE COORDINATION PROCESS AND WILL BE INFORMED BY THE INSPECTOR WHEN THE DIVISION VALVE WILL BE OPERATED BY THE SAWS DISTRIBUTION AND COLLECTION STAFF. THE DIVISION VALVE CAN ONLY BE OPERATED BY SAWS DISTRIBUTION AND COLLECTION STAFF MEMBER NOT THE INSPECTOR OR THE CONTRACTOR. OPERATION OF A DIVISION VALVE WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE SAWS DISTRIBUTION AND COLLECTION STAFF WILL CONSTITUTE A MATERIAL BREACH OF ANY WRITTEN SAWS CONTRACT OR PERMIT IN ADDITION TO SUBJECTING THE CONTRACTOR TO LIABILITY FOR ANY AND ALL FINES, FEES, OR OTHER DAMAGES, DIRECT OR CONSEQUENTIAL, THAT MAY ARISE FROM OR BE CAUSED BY THE OPERATION OF THE VALVE WITHOUT PRIOR WRITTEN PERMISSION. PLEASE BE INFORMED THAT THE APPROVAL OF THE OPERATION OR OPENING OR CLOSING OF A DIVISION VALVE CAN TAKE SEVERAL WEEKS FOR APPROVAL. DIVISION VALVES WILL ALSO HAVE A VALVE LID LABELED DIVISION VALVE AND A LOCKING MECHANISM INSTALLED WITH A KEY. THE LOCK AND KEY MECHANISM WILL BE PAID FOR BY THE CONTRACTOR BUT WILL BE INSTALLED BY SAWS DISTRIBUTION AND COLLECTION STAFF.

l	DEVELOPER'S NAME: AGORA ASSETS, LLC
l	ADDRESS: 8 DOMINION DR. SUITE 107
l	CITY: SAN ANTONIO STATE: TEXAS ZIP: 78257
	PHONE#_(210) 698-3000 FAX#N/A
l	SAWS BLOCK MAP# 122658 TOTAL EDU'S 56 TOTAL ACREAGE 17.
l	TOTAL LINEAR FOOTAGE OF PIPE: 3140 12" PVC PLAT NO. 23-11800
l	NUMBER OF LOTS 55 SAWS JOB NO. XX
•	

C4.10

THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCOG, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Agency.

:e: September 8, 2023, 11:55 AM — User ID: aarrington :: P:\126\10\06\Design\Civil\SSA1—1261006.dwg

IS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

ate: September 8, 2023, 11:55 AM — User ID: aarrington 1e: P:\126\10\06\Design\Civil\SSA1—1261006.dwg

IS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

PROJECT EXISTING EXISTING PROPOSED EXISTING FLOODPLA PLAT BOU FLOW ARR

FLOW ARF STORM DR SILT FENC INLET PRO

ROCK BEI

GRAVEL F

LIMITS	
GRADE	1120
GRADE	
D GRADE FEMA 100 YEAR JIN JINDARY	1120
ROW (PROPOSED)	
ROW (EXISTING)	
RAINAGE	
CE	
OTECTION	•••
RM	***
FILTER BAGS	•••

GENERAL NOTES

1. DO NOT DISTURB VEGETATED AREAS (TREES, GRASS, WEEDS, BRUSH, ETC.) ANY MORE THAN NECESSARY FOR CONSTRUCTION.

2. LOCATIONS OF CONSTRUCTION ENTRANCE/EXITS, CONCRETE WASHOUT PITS, AND CONSTRUCTION EQUIPMENT AND MATERIAL STORAGE YARDS TO BE DETERMINED IN THE FIELD.

3. STORM WATER POLLUTION PREVENTION CONTROLS MAY NEED TO BE MODIFIED IN THE FIELD TO ACCOMPLISH THE DESIRED EFFECT. ALL MODIFICATIONS ARE TO BE NOTED ON THIS EXHIBIT AND SIGNED AND DATED BY THE RESPONSIBLE PARTY.

4. RESTRICT ENTRY/EXIT TO THE PROJECT SITE TO DESIGNATED LOCATIONS BY USE OF ADEQUATE FENCING, IF NECESSARY.

5. ALL STORM WATER POLLUTION PREVENTION CONTROLS ARE TO BE MAINTAINED AND IN WORKING CONDITIONS AT ALL TIMES.

CONTRACTOR, TO THE EXTENT PRACTICAL, SHALL MINIMIZE THE AMOUNT OF AREA DISTURBED. AS SOON AS PRACTICAL, ALL DISTURBED SOIL THAT WILL NOT BE COVERED BY IMPERVIOUS COVER SUCH AS PARKWAY AREAS, EASEMENT AREAS, EMBANKMENT SLOPES, ETC. WILL BE STABILIZED PER APPLICABLE PROJECT SPECIFICATIONS.

7. BEST MANAGEMENT PRACTICES MAY BE INSTALLED IN STAGES TO COINCIDE WITH THE DISTURBANCE OF UPGRADIENT AREAS.

8. BEST MANAGEMENT PRACTICES MAY BE REMOVED IN STAGES ONCE THE WATERSHED FOR THAT PORTION CONTROLLED BY THE BEST MANAGEMENT PRACTICES HAS BEEN STABILIZED.

9. ALL TEMPORARY BMPs WILL BE REMOVED ONCE WATERSHED IS STABILIZED.

10. MUD OR DIRT INADVERTENTLY TRACKED OFF-SITE AND ONTO EXISTING STREETS SHALL BE REMOVED IMMEDIATELY BY HAND OR MECHANICAL BROOM SWEEPING.

11. TEMPORARY BMPs SHOWN ON THIS SHEET ARE FOR GRAPHICAL PURPOSES AND MAY NOT BE TO SCALE. BMPs SHALL BE LOCATED WITHIN THE PROJECT LIMITS.

12. UPON COMPLETION OF THE PROJECT AND BEFORE FINAL PAYMENT IS ISSUED, CONTRACTOR SHALL REMOVE ALL SEDIMENT AND EROSION CONTROL MEASURES.

13. CONTRACTOR SHALL BE RESPONSIBLE FOR CONSTRUCTION SEQUENCING AND REMOVAL OF TEMPORARY POLLUTION ABATEMENT MEASURES THAT CONFLICT WITH SITE IMPROVEMENTS SUCH AS LANDSCAPING AND FENCES SO AS TO PREVENT SEDIMENT FROM ESCAPING THE PROJECT SITE.

14. CPS ENERGY WILL FUNCTION AS A SECONDARY OPERATOR ON THIS PROJECT AND BE INSTALLING ELECTRIC UTILITIES FOR ON-SITE CONSTRUCTION AND OFF-SITE FEED TO THE PROJECT.

TEMPORARY POLLUTION ABATEMENT NOTES

1. CONSTRUCTION OF CIVIL INFRASTRUCTURE AND DRAINAGE STRUCTURES MAY PRECEDE HOME CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR PLACING SILT FENCE ALONG THE DOWN GRADIENT SIDE OF THE DISTURBED AREA PERPENDICULAR TO THE DRAINAGE FLOW.

2. ROCK BERMS SHALL BE PLACED IN AREAS WHERE DRAINAGE FLOW IS CONCENTRATED DUE TO NATURAL CONDITIONS OR CONSTRUCTION ACTIVITIES SUCH AS AT DRAINAGE STRUCTURES. THESE BERMS WILL BE MAINTAINED UNTIL THEY ARE NO LONGER NEEDED OR UNTIL THEY ARE REPLACED WITH PERMANENT POLLUTION ABATEMENT MEASURES.

3. THIS PROJECT DOES NOT INCLUDE THE INSTALLATION OF ABOVE GROUND STORAGE TANKS (AST) WITH VOLUME(S) GREATER THAN OR EQUAL TO 500 GALLONS.

4. DRAINAGE PATTERNS ARE ILLUSTRATED BY FLOW ARROWS. SLOPES VARY THROUGHOUT THE SITE; TYPICAL SLOPES IN THIS PROJECT WILL RANGE FROM 1% TO 20%.

5. THE NATURE OF CONSTRUCTION IS SUCH THAT IT IS DIFFICULT TO PREDICT AREAS THAT WILL BE DISTURBED AND RE-VEGETATED. THE CONSTRUCTION PLANS INCLUDE A NOTE ON EXHIBIT 3 WHICH WILL REQUIRE THE CONTRACTOR TO RE-VEGETATE DISTURBED AREAS WITH SEEDING, HYDROMULCH, OR SOD AND SPRINKLING. ALL IMPERVIOUS COVER AREAS WILL BE DISTURBED.

THE ENGINEERING SEAL HAS BEEN AFFIXED TO THIS SHEET ONLY FOR THE PURPOSE OF DEMONSTRATING COMPLIANCE WITH THE POLLUTION ABATEMENT SIZING AND TREATMENT REQUIREMENTS OF THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY'S EDWARDS AQUIFER TECHNICAL GUIDANCE MANUA THIS SHEET HAS BEEN PREPARED FOR PURPOSES

EXHIBIT

OF POLLUTION ABATEMENT ONLY. ALL OTHER CIVIL ENGINEERING RELATED INFORMATION SHOULD E ACQUIRED FROM THE APPROPRIATE SHEET IN THE CIVIL IMPROVEMENT PLANS.

NO. REVISION	**************************************	TE E Solution			
				2000 NW LOOP 410 L SAN ANTONIO TX 78213 L 210 375 9000	IEXAS ENGINEERING FIRM #470 I IEXAS SURVEYING FIRM #10028800
		SAN ANIONIO, IEXAS			

N	
LAT NO.	23-11800417
OB NO	12610-06
ATE [DECEMBER 2024
	AA
HECKED_	EK DRAWN AA
HEET	C8.00

S DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery B 2016, CAPCOG, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Agency.

HIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016,CAPCOG,Digital Globe,Texas Orthoimagery Program, USDA Farm Service Agency.

-EXISTING 15' ENGINEERED VEGETATIVE FILTER

HIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCOG, Digital Globe, Texas Orthoimagery Program, USDA Farm Service Agency.

	JELLYFISH DESIGN NOTES							
	JELLYFISH TREATMENT CAPACITY IS A FUNCTION OF THE TOP SLAB IS SHOWN. THE 8' x 12' [2438 x 3658] JELLYFISH CONTECH ENGINEERED SOLUTIONS. IF THE SITE CONDITI REQUIRED.	CARTE I PEAK IONS E	RIDGE SIZE, TYPE AND Q TREATMENT CAPACITY I EXCEED THE TOTAL BYPA	UANTITY. THE STANDAR IS 5.88 CFS [166.50 L/s]. M/ ASS CAPACITY OF THE SY	D PEAK DI AXIMUM B 'STEM, AN	VERSION VAI YPASS CAPA UPSTREAM	JLT STY CITY IS DIVERS	YLE WITH DETERM SION STRU
	CARTRIDGE SIZE		54	40		27		
	FLOW RATE HIGH-FLO / DRAINDOWN (cfs [L/s])		0.178/0.089 [5.10/2.55]	0.133/0.065 [3.68/1.84]	0.089/0	0.045 [2.55/1.2	81 (0.049/0.02
	MAXIMUM CARTRIDGE QUANTITY, HI-FLO / DRAINDOWN			<u> </u>	30/6	•	-	
	MAXIMUM TREATMENT		5.88 [166.50]	4.41 [124.88]	4.41 [124.88] 2.94 [83.25]			1.62
	OUTLET INVERT TO STRUCTURE INVERT (A) (ft. [mm])		6.50 [1981]	5.33 [1625]	5.33 [1625] 4.25 [1295]			3.25
	FINISHED GRADE TO OUTLET INVERT (SHALLOW) (B)			DETERMINE	D BY CON	TECH		
	FINISHED GRADE TO OUTLET INVERT (STANDARD) (B) (ft. [r	mm])	5.67 [1727]		4	.58 [1396]		
I IS E)	FRAME AND COVER TRE STANDARD TOP SLAB CONFIGURATION SLAB CONFIGURATION SLAB (DIAMETER VARIES) (LE NOT TO SCALE N		24" H COVER LOW TOP NFIGURATION TH VARIES) TO SCALE	D STRUCTURE ID WATER QUALITY PEAK FLOW RATE RETURN PERIOD NUMBER OF CAR CARTRIDGE SIZE RIM ELEVATION PIPE DATA: INLET PIPE 1 INLET PIPE 1 INLET PIPE 2 OUTLET PIPE SEE GENERAL NO SIZING REQUIREN NOTES / SPECIAL	SIT ATA F FLOW RAT (cfs [L/s]) OF PEAK I TRIDGES F (54, 40, 27 INVERT INVERT	ESPEC REQUIR (cfs [L/s]) =LOW (yrs) REQUIRED (H , 15) MAT'L OR INLET AN MENTS:	F / DD)	SLOPE
	 <u>GENERAL NOTES:</u> 1. CONTECH TO PROVIDE ALL MATERIALS U 2. FOR SITE SPECIFIC DRAWINGS WITH DET. SOLUTIONS REPRESENTATIVE. www.Cond 3. ALTERNATE UNITS ARE IN MILLIMETERS [4. JELLYFISH WATER QUALITY STRUCTURE CONTRACTOR TO CONFIRM STRUCTURE 5. STRUCTURE SHALL MEET AASHTO HS-20 COVER OF 0' - 10' [3048], AND GROUNDWA CONFIRM ACTUAL GROUNDWATER ELEVA 6. STRUCTURE SHALL BE PRECAST CONCRI 7. OUTLET PIPE INVERT IS EQUAL TO THE C. 8. THE OUTLET PIPE DIAMETER FOR NEW IN GREATER SLOPE. 9. NO PRODUCT SUBSTITUTIONS SHALL BE A ENGINEER OF RECORD. INSTALLATION NOTES A. ANY SUB-BASE, BACKFILL DEPTH, AND/C BY ENGINEER OF RECORD. B. CONTRACTOR TO PROVIDE EQUIPMENT C. CONTRACTOR WILL INSTALL AND LEVEL APPROVED WATERSTOP OR FLEXIBLE B D. CARTRIDGE INSTALLATION, BY CONTECI OF DEBRIS. CONTACT CONTECH TO COM 	JNLESS FAILED techES. [mm] UN SHALL MEETS OR PE ATER EI ATION. ETE CC CARTRIE NSTALL ACCEP OR ANT WITH S ACCEP	S NOTED OTHERWISE. STRUCTURE DIMENSION .com NLESS NOTED OTHERWIS BE IN ACCORDANCE WI S REQUIREMENTS OF PR RAPPROVING JURISDIC LEVATION AT, OR BELOV CASTINGS SHALL MEET ONFORMING TO ASTM C- DGE DECK ELEVATION. ATIONS IS RECOMMEND PTED UNLESS SUBMITTE TI-FLOTATION PROVISION SUFFICIENT LIFTING ANE TRUCTURE, SEALING TH LLL OCCUR ONLY AFTER ATE CARTRIDGE INSTAL	IS AND WEIGHT, PLEASE SE. TH ALL DESIGN DATA AND OJECT. TION REQUIREMENTS, WI V, THE OUTLET PIPE INVE AASHTO M306 LOAD RAT 857, ASTM C-918, AND AA DED TO BE ONE PIPE SIZE D 10 DAYS PRIOR TO PRO IS ARE SITE-SPECIFIC DE O REACH CAPACITY TO LII IE JOINTS, LINE ENTRY AN SITE HAS BEEN STABILIZI LATION WITH SITE STABIL	CONTACT D INFORM/ HICHEVER RT ELEVA ING AND I SHTO LOA LARGER 1 DJECT BID SIGN CON FT AND SE ND EXIT PO ED AND TH JZATION.	YOUR CONT ATION CONTA IS MORE ST TION. ENGIN BE CAST WIT D FACTOR D THAN THE INL DATE, OR AS SIDERATION THE STRUC DINTS (NON-S IE JELLYFISH	ECH EN NINED II RINGEN EER OF H THE (ESIGN I ET PIPI DIREC S AND S CTURE. SHRINK	IGINEERE N THIS DF T, ASSUM RECORI CONTECH METHOD. E AT EQU TED BY T SHALL BE GROUT V S CLEAN

OF THE ,123,935;	CONTECH® ENGINEERED SOLUTIONS LLC www.ContechES.com 9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069	JELLYFISH JFPD0812 PEAK DIVERSION CONFIGURATION STANDARD DETAIL
	800-338-1122 513-645-7000 513-645-7993 FAX	

