

FED RD DIV. NO.	PROJECT NO.		SHEET NO.
6	-		1
STATE	STATE DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD

ROSE VALLEY UNIT #2

ABBOTT RD & FM 1346
BEXAR COUNTY, TX

INDEX OF SHEETS
SEE SHEET 2 FOR INDEX OF SHEETS

LIMITS
FROM: ABBOTT RD & FM1346 INTERSECTION
TO: 0.86 MILES NORTH OF ABBOTT RD & FM 1346 INTERSECTION


NET LENGTH OF PROJECT = 4435.75 FT 0.84 MI

ROAD CLASSIFICATION
SECONDARY ARTERIAL

POSTED SPEED
ABBOTT RD= 40 MPH

AREA OF DISTRIBUTED SOIL
1.61 ACRES

FOR WORK CONSISTING OF ROADWAY WIDENING, AND PAVEMENT MARKINGS
TO ACCOMMODATE TURN LANES .



LOCATION MAP
N.T.S.

EXCEPTIONS: N/A
EQUATIONS: N/A
R.R. CROSSINGS: N/A

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA NAME	114275 P.E. #	1/5/2026 DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230
210.660.1960 / TBPE Firm Registration No. 20623

GENERAL
 1 TITLE SHEET
 2 INDEX OF SHEETS
 3 EXISTING TYPICAL SECTIONS
 4-5 PROPOSED TYPICAL SECTIONS
 6-7 GENERAL NOTES
 8-9 SUMMARY OF QUANTITIES

TRAFFIC CONTROL PLAN
 10 TRAFFIC CONTROL PLAN SEQUENCE OF WORK
 11 TRAFFIC CONTROL PLAN SCHEDULE OF BARRICADES
 12 TRAFFIC CONTROL PLAN PHASE 1 STEP 1 TYPICAL SECTIONS
 13 TRAFFIC CONTROL PLAN PHASE 1 STEP 1/2 TYPICAL SECTIONS
 14 TRAFFIC CONTROL PLAN PHASE 1 STEP 2 TYPICAL SECTIONS
 15 TRAFFIC CONTROL PLAN PHASE 1 STEP 1 DETOUR LAYOUT
 16 TRAFFIC CONTROL PLAN PHASE 1 STEP 2 DETOUR LAYOUT
 17 TRAFFIC CONTROL PLAN PHASE 2 STEP 1 & 2 TYPICAL SECTIONS
 18 TRAFFIC CONTROL PLAN PHASE 2 STEP 1 DETOUR LAYOUT
 19 TRAFFIC CONTROL PLAN PHASE 2 STEP 3 & 4 TYPICAL SECTIONS
 20 TRAFFIC CONTROL PLAN PHASE 2 STEP 3 DETOUR LAYOUT

TRAFFIC CONTROL PLAN STANDARDS
 21-32 *BC (1)-21 THRU BC (12)-21
 33 *TCP (1-1)-18
 34 *TCP (1-2)-18
 35 *TCP (2-3)-23
 36 *TCP (2-8)-23
 37 *TCP (3-1)-13
 38 *TCP (7-1)-13
 39 *WZ (SPTM)-23
 40 *WZ(RCD)-13
 41 *TREATMENT FOR VARIOUS EDGE CONDITIONS

ROADWAY DETAILS
 42-43 HORIZONTAL ALIGNMENT DATA
 44-51 ROADWAY PLAN & PROFILE
 52 INTERSECTION LAYOUT
 53-55 DRIVEWAY PLAN AND PROFILE
 56 ROSE BRANCH PLAN AND PROFILE
 57 ROSE BRANCH DEVELOPMENT PLAN AND PROFILE

DRAINAGE DETAILS
 58 CROSSING PLAN AND PROFILE
 59 DRAINAGE DETAILS

DRAINAGE STANDARDS
 60 *SETP-PD

SIGNING AND PAVEMENT MARKINGS
 61-64 SIGNING, PAVEMENT MARKINGS AND SW3P LAYOUT
 65 SMALL SIGN DETAILS
 66 SOSS

SIGNING AND PAVEMENT MARKINGS STANDARDS
 67 *SMD(GEN)-08
 68-70 *SMD(SLIP-1)-08 THRU SMD(SLIP-3)-08
 71 *D&OM(2)-25
 72 *D&OM(3)-25
 73 *D&OM(4)-25
 74-76 *PM (1)-22 THRU PM (3)-22

ENVIRONMENTAL ISSUES
 77-78 STORMWATER POLLUTION PREVENTION PLAN (SW3P)

ENVIRONMENTAL ISSUES STANDARDS
 79 *EC (1)-16
 80 *EC (2)-16
 81 *EC (3)-16

CROSS SECTIONS
 82-91 CROSS SECTIONS

*TXDOT STANDARDS

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA 114275 1/5/2026		
NAME	P.E. #	DATE





Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

INDEX OF SHEETS

SHEET 1 OF 1

FED.RD. DIV./NO.	PROJECT NO.		SHEET
6	-		2
STATE	DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD



95% SUBMITTAL



PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



ROSE VALLEY SOUTH UNIT #2


EXISTING TYPICAL SECTIONS

N.T.S.		SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	SHEET	
6	-	3	
STATE	DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD



- ① 2" HMA TY D PG70-22
- ② BONDING COURSE (0.12 GAL/SY)
- ③ 2.75" HMA TY B PG64-22
- ④ BONDING COURSE (0.12 GAL/SY)
- ⑤ 2.75" HMA TY B PG64-22
- ⑥ PRIME COAT (MC-30 OR AE-P) (0.20 GAL/SY)
- ⑦ 18" FL BS (CMP IN PLC) (TYD GR1-2) (FNAL POS CY)
- ⑧ 8" LIME TREATMENT SUBGRADE

NOTES:
1. LIME TREATMENT
LIME TREATMENT @22.8 LB/SY FOR 8 INCHES DEPTH
OF TREATMENT. REFER TO GEOTECH REPORT PSI
PROJECT NO. 0312-3441 FOR ADDITIONAL INFORMATION.





PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA 114275 1/5/2026		
NAME	P.E. #	DATE

LEGACY
ENGINEERING GROUP
Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

PROPOSED TYPICAL SECTIONS

N.T.S.		SHEET 1 OF 2	
FED.RD. DIV./NO.	PROJECT NO.		SHEET
6	-	-	4
STATE	DIST.		COUNTY
TEXAS	SAT		BEXAR
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD



NOTES:
1. LIME TREATMENT
LIME TREATMENT @22.8 LB/SY FOR 8 INCHES DEPTH
OF TREATMENT. REFER TO GEOTECH REPORT PSI
PROJECT NO. 0312-3441 FOR ADDITIONAL INFORMATION.
2. O.C.S.T.
ITEM 0316-7071 ASPH (AC-15P, AC-20-5TR OR AC-20XP)
@0.32 GAL/SY
ITEM 0316-7211 AGGR (TY-PB, GR-4) (SAC-B) @ 1CY/130 SY
(CONTRACTOR TO REFER TO TXDOT MATERIAL SPECIFICATIONS
AND STANDARDS FOR GUIDANCE CONCERNING CONSTRUCTION
OF ALL PAVEMENT AND O.C.S.T.)

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275
NAME	P.E. #
1/5/2026	



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

PROPOSED TYPICAL SECTIONS

N.T.S.		SHEET 2 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	SHEET		
6		5		
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	

GENERAL NOTES

- ALL CONSTRUCTION AND MATERIALS TO BE IN ACCORDANCE WITH THE TEXAS DEPARTMENT OF TRANSPORTATION (TXDOT) "STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MAINTAINANCE OF HIGHWAY, STREETS AND BRIDGES SEPTEMBER 2024" AND CITY OF SAN ANTONIO "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION" DATED JUNE 2008 WITH ALL APPLICABLE AMENDMENTS AND ANY SPECIAL SPECIFICATIONS ISSUED FOR THE PROJECT UNLESS OTHERWISE SPECIFIED.
- NO EXTRA PAYMENT SHALL BE ALLOWED FOR WORK CALLED FOR ON THE PLANS, BUT NOT INCLUDED ON THE BID SCHEDULE. THIS INCIDENTAL WORK WILL BE REQUIRED AND SHALL BE INCLUDED IN THE PAY ITEM TO WHICH IT RELATES.
- CONFLICTS IN THE PLANS AND/OR SPECIFICATIONS FOUND BY THE CONTRACTOR SHALL BE PROMPTLY REPORTED TO THE INSPECTOR BEFORE PROCEEDING WITH CONSTRUCTION.
- BIDDERS ARE HEREBY NOTIFIED TO MAKE SUBSURFACE INVESTIGATIONS AS THEY DEEM NECESSARY. NO ADDITIONAL PAYMENT SHALL BE MADE FOR ROCK, SAND, GRAVEL OR OTHER UNSTABLE CONDITIONS ENCOUNTERED IN STREET EXCAVATION, BOX CULVERT EXCAVATION, STRUCTURAL EXCAVATION, OR CHANNEL EXCAVATION.
- THE CONTRACTOR SHALL LIMIT WORK ACTIVITIES TO THE STREET RIGHTS-OF-WAY AND EASEMENTS. NO PROVISIONS HAVE BEEN MADE FOR WORK ACTIVITIES OR STORAGE OF MATERIALS AND/OR EQUIPMENT ON PRIVATE PROPERTY.
- THE CONTRACTOR SHALL PRESERVE ALL CONSTRUCTION STAKES, MARKERS, ETC. ANY CONSTRUCTION STAKES, MARKERS, ETC., REMOVED BY THE CONTRACTOR OR THE CONTRACTOR'S EMPLOYEES SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.
- DUE TO FEDERAL REGULATIONS TITLE 49, PART 192.181, GAS UTILITY OWNERS MUST MAINTAIN ACCESS TO GAS VALVES AT ALL TIMES. THE CONTRACTOR MUST PROTECT AND WORK AROUND ANY GAS VALVES THAT ARE IN THE PROJECT AREA.
- DURING THE CONSTRUCTION, THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE OF FENCING. DAMAGED FENCING SHALL BE REPLACED WITH EQUAL OR BETTER MATERIALS AND WORKMANSHIP. THE CONTRACTOR SHALL COORDINATE WITH THE LANDOWNER FOR WORK WITHIN PRIVATE PROPERTY. EASEMENT FENCES MAY BE REMOVED AND REPLACED AS REQUIRED. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAINTAIN AND SET UP TEMPORARY FENCING FOR LIVESTOCK AS NECESSARY FOR ALL PHASES OF WORK. NO SEPARATE PAYMENT SHALL BE MADE FOR MAINTAINING FENCING.
- CONTRACTOR SHALL PROTECT FROM DAMAGE ALL TREES WITHIN THE PROJECT'S RIGHT-OF-WAY AND VARIOUS CONSTRUCTION AND FILL EASEMENTS EXCEPT FOR THOSE TREES SPECIFICALLY DESIGNATED BY THE "CONSTRUCTION INSPECTOR" TO BE REMOVED FOR CONSTRUCTION PURPOSES AND WILL BE SUBSIDIARY TO THE VARIOUS BID ITEMS FOR THE PROJECT. ALL TREES WHICH ARE NOT DESIGNED FOR REMOVAL AND ARE DAMAGED BY CONTRACTOR SHALL BE COMPENSATED FOR OR REPLACED BY THE CONTRACTOR TO THE SATISFACTION OF BEXAR COUNTY OR THE PROPERTY OWNER.
- CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/GEOTECHNICAL/SAFETY EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITE(S) WITHIN THE PROJECT WORK AREA IN ORDER TO DEVELOP THE CONTRACTOR'S PLAN TO IMPLEMENT THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS.
- THE CONTRACTOR'S PLANS SHALL PROVIDE ADEQUATE TRENCH SAFETY SYSTEMS THAT COMPLY WITH AS MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS, SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL DEVELOP STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.
- THE CONTRACTOR SHALL MAINTAIN ALL ADJOINING STREETS AND TRAVELED ROUTES FREE FROM SPILLED AND/OR TRACKED CONSTRUCTION MATERIALS.
- ANY CAVERN OR SOLUTION CHANNELS ENCOUNTERED DURING CONSTRUCTION SHALL BE REPORTED TO THE ENGINEER AND THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) REGION 13 OFFICE WITH A REQUEST FOR APPROVAL OF CONSTRUCTION.
- ALL WASTE MATERIAL SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND IT WILL BE HIS SOLE RESPONSIBILITY TO DISPOSE OF THIS MATERIAL OFF THE LIMITS OF THE RIGHT-OF-WAY AND TO PRIVATE OWNERS. NO WASTE MATERIALS SHALL BE PLACED IN EXISTING LOWS THAT WILL BLOCK OR ALTER FLOW LIMITS OF EXISTING NATURAL DRAINAGE. THE CONTRACTOR SHALL NOT PLACE ANY WASTE MATERIALS IN THE 100-YEAR FLOODPLAIN WITHOUT FIRST OBTAINING A FLOOD PLAIN DEVELOPMENT PERMIT FROM THE APPROPRIATE ENTITY.
- CONTRACTOR IS TO MAINTAIN UNRESTRICTED DRAINAGE OF THE PROJECT SITE AND ADJACENT AREAS DURING CONSTRUCTION.
- AFTER COMPLETION OF ALL WORK, THE CONTRACTOR SHALL REMOVE ALL DEBRIS FROM THE RIGHT-OF-WAY AND LEAVE THE WORK AREA NEAT AND CLEAN. ANY TEMPORARY FILL TO FACILITATE CONSTRUCTION SHALL BE REMOVED AND DISPOSED OF IN A MANNER APPROVED BY THE COUNTY ENGINEER.
- ALL DISTURBED AREAS SHALL BE FINISHED WITH TOPSOIL AND HYDROMULCH OR SOD AS NOTED ON THE PLANS.
- CONTRACTOR TO VERIFY EXISTING ELEVATIONS AT ALL TIE-IN LOCATIONS PRIOR TO CONSTRUCTION. NOTIFY ENGINEER IF SIGNIFICANT DISCREPANCIES EXIST.
- THE EXISTING CONDITIONS AND UTILITIES SHOWN ON THE PLANS WERE DETERMINED AT THE TIME OF PLAN PREPARATION (NOVEMBER 2025). THE UTILITY LOCATIONS SHOWN ARE APPROXIMATE ONLY. THE ACTUAL LOCATIONS AND DEPTHS OF UTILITIES SHOWN ON THE PLANS INCLUDING THOSE WHICH HAVE BEEN ADDED, ELIMINATED, ADJUSTED AND/OR RELOCATED AFTER THE AFOREMENTIONED DATE OF PLAN PREPARATION MUST BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DAMAGES TO THE EXISTING UTILITIES DUE TO NEGLIGENCE OF THE CONTRACTOR OR DUE TO EXCAVATION OUTSIDE OF THE DEFINED CONSTRUCTION LIMITS OF THIS PROJECT. CONTRACTOR SHALL HAVE THE SOLE RESPONSIBILITY OF FIELD VERIFYING EACH UTILITY LOCATION AND COORDINATING AND NOTIFYING OWNERS AT LEAST SEVENTY-TWO (72) HOURS PRIOR TO EXCAVATION.
- OVERHEAD UTILITIES MAY EXIST ON THE PROPERTY. WE HAVE NOT ATTEMPTED TO MARK THOSE SINCE THEY ARE CLEARLY VISIBLE. BUT YOU SHOULD LOCATE THEM BEFORE BEGINNING ANY CONSTRUCTION. TEXAS LAW, SECTION 752, HEALTH AND SAFETY CODE FORBIDS ALL ACTIVITIES IN WHICH PERSONS OR THINGS MAY COME WITHIN SIX (6) FEET OF LIVE OVERHEAD HIGH VOLTAGE LINES. CONTRACTORS AND OWNERS ARE LEGALLY RESPONSIBLE FOR SAFETY OF CONSTRUCTION WORKERS UNDER THIS LAW. THIS LAW CARRIES BOTH CRIMINAL AND CIVIL LIABILITY, TO ARRANGE FOR LINES TO BE TURNED OFF OR MOVED, CONTACT CPS AT 210-978-3500.
- CONTRACTOR SHALL BE RESPONSIBLE OR ACQUIRING ALL PERMITS, TESTS, APPROVALS AND ACCEPTANCES REQUIRED COMPLETING CONSTRUCTION OF THIS PROJECT.
- CONTRACTOR SHALL NOTIFY THE COUNTY AT (210) 335-6700 TWENTY FOUR (24) HOURS PRIOR TO THE BACKFILL OF ANY TRENCHES TO SCHEDULE FOR DENSITY TESTING AS REQUIRED.
- IF SUSPECTED CONTAMINATION IS ENCOUNTERED DURING CONSTRUCTION OPERATIONS, BEXAR COUNTY SHALL BE NOTIFIED IMMEDIATELY. THE NOTIFICATION SHOULD INCLUDE THE STATION NUMBER, TYPE OF CONTAMINATED MEDIA, EVIDENCE OF CONTAMINATION AND MEASURES TAKEN TO CONTAIN THE CONTAMINATED MEDIA AND PREVENT PUBLIC ACCESS. THE CONTAMINATED SOIL AND/OR GROUNDWATER SHALL NOT BE REMOVED FROM THE LOCATION WITHOUT PRIOR BEXAR COUNTY APPROVAL. THE CONTRACTOR MUST STOP THE EXCAVATION IMMEDIATELY AND CONTACT THE BEXAR COUNTY INSPECTOR. THE CONTRACTOR WILL NOT RE-COMMENCE EXCAVATION ACTIVITIES WITHOUT WRITTEN PERMISSION FROM BEXAR COUNTY.
- LOCATION OF ALL CONCRETE FOUNDATIONS SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
- ALL SPOILS FROM EXCAVATION SHALL BE PLACED IN A TRUCK OR TRAILER TO BE REMOVED DAILY AND SHALL NOT BE PLACED ON THE GROUND OR ROADWAY.
- ALL STREETS AND/OR DRIVEWAYS MUST BE BORED, IF NECESSARY. NO OPEN CUT OF STREETS OR DRIVEWAYS WILL BE ALLOWED.
- REMOVE EXISTING RAISED PAVEMENT MARKERS AND EXISTING PAVEMENT MARKINGS AS THE WORK PROGRESSES OR AS APPROVED. THIS WORK IS SUBSIDIARY TO THE VARIOUS BID ITEMS.
- ANY MATERIALS REMOVED AND NOT REUSED AND DETERMINED TO BE SALVAGEABLE SHALL BE STORED WITHIN THE PROJECT LIMITS AT AN APPROVED LOCATION OR DELIVERED UNDAMAGED TO THE STORAGE YARD AS DIRECTED. PROPERLY DISPOSE UNSALVAGEABLE MATERIALS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.
- ANY SIGN PANELS THAT ARE ADJUSTED OR REMOVED AND REPLACED, SHALL BE DONE THE SAME WORKDAY UNLESS OTHERWISE APPROVED. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF THIS PROJECT SHALL CONFORM TO APPLICABLE CITY OF SAN ANTONIO STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (LATEST ADDITION), TXDOT STANDARD SPECIFICATIONS AS WELL AS PROVISIONS APPLICABLE TO THE PROJECT AND AS OTHER SAFETY CODE AND INSPECTION REQUIREMENTS OF THE FIRE DEPARTMENT.
- MATERIAL FURNISHED BY THE CONTRACTOR SHALL BE NEW, UN-DEPRECIATED STOCK. ALL EQUIPMENT SHALL BE NEW, UNLESS NOTED OTHERWISE ON THE PLANS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING TO ORIGINAL CONDITION, OR BETTER, ANY DAMAGE DONE TO EXISTING BUILDINGS, RETAINING WALLS, UTILITIES, FENCES, PAVEMENT, CURBS OR DRIVEWAYS (NO SEPARATE PAY ITEM). CONTRACTOR SHALL RESTORE THE CONSTRUCTION AREA TO ORIGINAL CONDITION, OR BETTER, PRIOR TO FINAL INSPECTION.

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

GENERAL NOTES

SHEET 1 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	SHEET
STATE	DIST.	COUNTY
6	-	6
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
		ABBOTT RD

32. CONTRACTOR IS RESPONSIBLE FOR KEEPING STREETS AND SIDEWALKS ADJACENT TO THE PROJECT FREE OF MUD AND DEBRIS FROM THE CONSTRUCTION AT ALL TIMES.

33. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN ALL EROSION CONTROL FACILITIES BEFORE, DURING AND AFTER ALL CONSTRUCTION ACTIVITIES IN ACCORDANCE WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS.

34. ALL JOINTS, SEALS, CONNECTIONS, AND MODIFICATIONS NECESSARY FOR PROPER INSTALLATION OF RCP SHALL BE SUBSIDIARY TO THE RCP PAY ITEM.

35. FOR PEDESTRIAN SAFETY, THE CONTRACTOR SHALL INSTALL ORANGE PLASTIC CONSTRUCTION FENCING (4 FEET TALL MINIMUM) AROUND ALL OPEN EXCAVATIONS OR AS DIRECTED BY THE ENGINEER. SUCH FENCING SHALL NOT OBSTRUCT SIGHT LINES OF THE TRAVELING PUBLIC.

36. CONTRACTOR SHALL BE RESPONSIBLE FOR CLEARING ANY CONSTRUCTION MATERIALS FROM ADJACENT WATERWAYS AFTER A FLOOD EVENT. REPAIR OF ANY DAMAGES TO DRAINAGE STRUCTURES IN THE PROJECT AREA, OR DOWNSTREAM CAUSED BY CONSTRUCTION DEBRIS SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

37. PREPARATION OF RIGHT OF WAY SHALL INCLUDE ALL DRIVEWAY PENETRATION AREAS.

TRAFFIC NOTES

GENERAL AND SPECIAL CONDITIONS

1. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO SEE THAT ALL TRAFFIC CONTROL DEVICES ARE PROPERLY INSTALLED AND MAINTAINED AT THE JOB SITE IN ACCORDANCE WITH THE PLANS, SPECIFICATIONS AND RELATED INDUSTRY STANDARDS AND REGULATIONS. THE CONTRACTOR SHALL SUBMIT FOR REVIEW A SIGN AND BARRICADE PLAN CONFORMING TO THE REQUIREMENTS OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES. THE COUNTY'S CONSTRUCTION INSPECTOR AND THE TRAFFIC ENGINEERING REPRESENTATIVE WILL ONLY BE RESPONSIBLE TO INSPECT THE TRAFFIC CONTROL DEVICES BEING DEPLOYED. IF, IN THE OPINION OF THE TRAFFIC ENGINEERING REPRESENTATIVE AND THE CONSTRUCTION INSPECTOR, THE TRAFFIC CONTROL DEVICES DO NOT CONFORM TO ESTABLISHED STANDARDS OR ARE INCORRECTLY PLACED OR ARE INSUFFICIENT IN QUANTITY TO PROTECT THE GENERAL PUBLIC, THE CONSTRUCTION INSPECTOR SHALL HAVE THE OPTION TO STOP CONSTRUCTION OPERATIONS AT NO EXPENSE TO THE COUNTY UNTIL SUCH TIME AS THE CONDITIONS ARE CORRECTED BY THE CONTRACTOR.

2. PRIOR TO MOVING ANY TRAFFIC SIGNS OR TRAFFIC SIGNALS, THE CONTRACTOR SHALL CONTACT THE COUNTY'S TRAFFIC OPERATIONS SECTION. PRIOR TO COMPLETION OF THE CONTRACT AND REMOVAL OF THE BARRICADES, THE CONTRACTOR SHALL AGAIN CONTACT THE TRAFFIC OPERATIONS SECTION. THE BARRICADES SHALL NOT BE REMOVED UNTIL ALL APPLICABLE PERMANENT TRAFFIC SIGNS AND SIGNALS ARE IN PLACE.

3. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN AND MAINTAIN TEMPORARY STOP SIGNS AND ALL OTHER TRAFFIC CONTROL DEVICES REQUIRED TO PROTECT THE GENERAL PUBLIC. IF THE COUNTY HAS REMOVED PERMANENT STOP SIGNS, THE CONTRACTOR SHALL REQUEST THAT TEMPORARY SIGNS BE FURNISHED TO THE CONSTRUCTION SITE SO THAT THEY CAN BE REINSTALLED BY HIM. ALL PERMANENT SIGNS OR TRAFFIC CONTROL DEVICES MISSING OR DAMAGED UPON COMPLETION OF CONSTRUCTION SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.

4. THE CONTRACTOR MUST CONTACT THE COUNTY ENGINEER OR HIS DESIGNATED REPRESENTATIVE 72 HOURS IN ADVANCE (NOT INCLUDING WEEKENDS OR HOLIDAYS) OF ANY MINOR STREET CLOSURE. THIS MUCH TIME IS NECESSARY TO INSTALL ADVISORY SIGNS AND GIVE THE MOTORIST A MINIMUM OF 3 DAYS NOTICE OF THE STREET CLOSURE. THE TRAFFIC ENGINEERING OFFICE WILL MAKE THE NECESSARY ARRANGEMENTS AND NOTIFY ALL EMERGENCY SERVICES AND AGENCIES.

5. AS WORK PROGRESSES, LOCATION OF TEMPORARY TRAFFIC CONTROL DEVICES WILL BE ADJUSTED AND MODIFIED AS NECESSARY BY THE CONTRACTOR, WITH THE APPROVAL OF THE TRAFFIC ENGINEER OR HIS DESIGNATED REPRESENTATIVE.

6. IF THE NEED ARISES, ADDITIONAL TEMPORARY TRAFFIC CONTROL DEVICES, SPECIAL DIRECTIONAL DEVICES AND/OR BUSINESS NAME SIGNS MAY BE ORDERED BY THE TRAFFIC ENGINEERING REPRESENTATIVE AT THE CONTRACTOR'S EXPENSE.

7. TEMPORARY TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE TXDOT "BC-07" SHEETS AND TO THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

8. THE CONTRACTOR MUST MAINTAIN ALL STREETS OPEN TO THROUGH TRAFFIC BY REPAIRING TRENCHES, POTHOLEs, LEVELING UP WITH ASPHALT, ETC., AT NO DIRECT PAYMENT. COST TO BE INCLUDED WITH OTHER ITEMS.

9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING SUITABLE ACCESS ACCOMMODATIONS FOR SCHOOL CHILDREN AND PEDESTRIANS.

10. THE CONTRACTOR SHALL PROVIDE ACCESS FOR DELIVERY OF MAIL BY THE U.S. POSTAL SERVICE.

11. THE CONTRACTOR SHALL PROVIDE FOR ACCESS TO RESIDENCES AND ALL BUSINESSES AT ALL TIMES WITHIN ALL PHASES OF THE WORK.

12. WHEN CONSTRUCTION WORK NECESSITATES THE UTILIZATION OF VEHICLE PATHS OTHER THAN THE LANES NORMALLY USED, TRAFFIC CONTROL MARKINGS NO LONGER APPLICABLE SHALL BE REMOVED AND APPROVED TEMPORARY PAVEMENT MARKINGS AND SIGNS SHALL BE INSTALLED IN ACCORDANCE WITH PART VI OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

13. ALL TEMPORARY TRAFFIC CONTROL DEVICES, ETC., SHALL BE PROVIDED BY THE CONTRACTOR WITHOUT DIRECT PAYMENT, UNLESS OTHERWISE NOTED OR STATED.

14. THE CONSTRUCTION INSPECTOR SHALL MONITOR THE CONTRACTOR'S TRAFFIC CONTROL DEVICES AND WILL BE RESPONSIBLE TO FURNISH ALL RESIDENTS AND BUSINESSES WITH PROGRESS ADVISORIES ON ALL PHASES DURING THE COURSE OF CONSTRUCTION.

15. ANY DAMAGE TO PERMANENT TRAFFIC SIGNALS, THE CONTROLLER BOX, LOOPS OR CONDUITS DURING OR UPON COMPLETION OF THE PROJECT SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. THE DECISION TO REPAIR AS OPPOSED TO REPLACE THE DAMAGED EQUIPMENT SHALL BE MADE BY THE COUNTY TRAFFIC ENGINEERING SECTION.

16. CONTRACTOR SHALL PROVIDE APPROPRIATE SAFE ACCESS AND BARRICADE WORK AT ALL TIMES TO PROTECT THE PUBLIC. THE SITE MUST BE LEFT IN A SECURE SAFE CONDITION AT NIGHT. THIS INCLUDES SUBSTANTIAL BARRICADES AROUND ALL TRENCHES, OPEN EXCAVATIONS, EQUIPMENT, ETC. IT IS THE CONTRACTOR'S RESPONSIBILITY TO TAKE NECESSARY PRECAUTIONS TO PROTECT THE PUBLIC THROUGHOUT THE DURATION OF THE PROJECT.

17. ANY QUESTIONS REGARDING PHASING OR STAGING WILL BE STRICTLY HANDLED BY BEXAR COUNTY WHICH HAS COMPLETE AUTHORITY TO MAKE FINAL DECISIONS ON ANY CHANGES OR MODIFICATIONS.

18. EXISTING CROSS DRAINS SHALL BE TEMPORARILY EXTENDED AS REQUIRED BY THE PLANS FOR TEMPORARY WIDENING OF ROADWAYS. NO DIRECT PAYMENT.

19. ANY ADDITIONAL CONSTRUCTION THAT IS NOT SHOWN AND IS REQUIRED TO COMPLETE THE TEMPORARY PAVEMENT SECTION FOR TEMPORARY WIDENING OF ROADWAYS WILL BE AT NO DIRECT PAYMENT TO THE CONTRACTOR, COST TO BE INCLUDED IN OTHER ITEMS.

20. WHEN DROP-OFF ADJACENT TO THE ROADWAY (TEMPORARY OR OTHERWISE) EXCEEDS TWO (2) INCHES AND IS LESS THAN TWO (2) FEET, THE CONTRACTOR SHALL PROVIDE DELINEATED DRUMS OR VERTICAL PANELS IN ACCORDANCE WITH THE MOST CURRENT STANDARDS BY BEXAR COUNTY PUBLIC WORKS & THE TEXAS DEPARTMENT OF TRANSPORTATION. HOWEVER, THIS WILL ONLY BE POSSIBLE IF A MINIMUM BUFFER ZONE OF FOUR (4) FEET IS AVAILABLE BETWEEN THE EDGE OF TRAVELWAY AND THE WARNING OR CONTROL DEVICE. THE DRUMS OR PANELS SHALL BE PLACED AT TWENTY-FIVE (25) FOOT INTERVALS ALONG THE EDGE OF THE TEMPORARY ROADWAY. THERE WILL BE NO SEPARATE PAY FOR THIS WORK.

21. WHEN A DROP-OFF ON THE ROADWAY (TEMPORARY OR OTHERWISE) EXCEEDS TWO (2) FEET, THE CONTRACTOR SHALL PLACE A TEMPORARY PROTECTIVE BARRIER ON THE EDGE OF THE TEMPORARY ROADWAY CONFORMING TO THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, UNLESS OTHERWISE STATED ON PLANS. THE COST OF CONCRETE TRAFFIC BARRIERS (PORTABLE) FOR TEMPORARY WIDENING OF ROADWAYS SHALL NOT BE PAID DIRECTLY.

22. WHEN TWO-WAY TRAFFIC IS ROUTED ON ONE-SIDE OF THE EXISTING OR PROPOSED CENTER OF ROADWAY, AS PART OF STAGED CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY BEXAR COUNTY 48 HOURS PRIOR TO THE INSTALLATION OF TEMPORARY MARKINGS. CENTERLINE DIVIDING TWO-WAY TRAFFIC SHALL CONSIST OF SOLID DOUBLE YELLOW LINES, UNLESS BARRICADES OR BARRELS ARE APPROVED FOR SHORT TERM USE.

23. ADDITIONAL TEMPORARY WIDENING MAY BE REQUIRED FOR SLOPES TO MAINTAIN THE MINIMUM TRAVEL SURFACE. EMBANKMENT SHALL BE AT NO DIRECT PAYMENT, COST TO BE INCLUDED IN OTHER ITEMS.

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

GENERAL NOTES

SHEET 2 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	HEET
6	-	7
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
		ABBOTT RD

TRAFFIC CONTROL PLAN QUANTITIES											
PLAN SHEET NO.	STATION TO STATION	502 7001	503 7001	505 7001	505 7003	510 7001	662 7112	662 7114			
		BARRICADES, SIGNS AND TRAFFIC HANDLING	PORTABLE CHANGEABLE MESSAGE SIGN	TMA (STATIONARY)	TMA (MOBILE OPERATION)	ONE-WAY TRAF CONT (FLAGGER CONT)	WK ZN PAV MRK SHT TERM (TAB)TY W	WK ZN PAV MRK SHT TERM (TAB)TY Y-2			
		MO	DAY	DAY	DAY	HR	EA	EA			
- BEGIN TO END											
PROJECT TOTALS		2	56	39	2	32	36	212			


ROADWAY QUANTITIES											
PLAN SHEET NO.	STATION TO STATION	0104 7006	* 0104 XXXX	0105 7026	0110 7001	0132 7005	0247 7188	0260 7004	0260 7020	0310 7013	0316 7071
		REMOV CONC (RIPRAP)	REMOV DRIVEWAY	RMV (6") TRT/UNTRT BASE & ASPH PAV	EXCAV (ROADWAY)	EMBANK (FNL)(OC)(TY C)	FL BS (CMP IN PLC)(TYD GR1-2)(FINAL POS)	LIME (COMMERCIAL LIME SLURRY)	LIME TRT (SUBGRADE) (8")	PRIME COAT(MC-30 OR AE-P)	ASPH (AC-15P, AC-20-5TR OR AC-20XP)
		SY	SY	SY	CY	CY	CY	TON	SY	GAL	CY
44	BEGIN TO 104+00		46	158	373	122	871	21	1808	349	
45	104+00 TO 110+00		83	122	187	17	492	12	1033	197	
46	110+00 TO 116+00										
47	116+00 TO 122+00										
48	122+00 TO 128+00										
49	128+00 TO 134+00										
50	134+00 TO 140+00	2	56		323	129	368	10	796	148	442
51	140+00 TO END	3	52		177	64	518	12	1035	194	529
PROJECT TOTALS		5	237	280	1060	332	2249	55	4672	888	971
* SEE NOTE 1											

ROADWAY QUANTITIES										
PLAN SHEET NO.	STATION TO STATION	0341 7001	0341 7048	0354 7051	0464 7003	0467 7307	0496 7007	0530 7016	0560 7012	3007 7001
		D-GR HMA TY-B PG64-22	D-GR HMA TY-D PG70-22	PLANE ASPH CONC PAV(2")	RC PIPE (CL III)(18 IN)	SET (TY II) (18 IN) (RCP) (6:1) (C)	REMOV STR (PIPE)	DRIVEWAYS (SURF TREAT)	RELOCATE EXISTING MAILBOX	BONDING COURSE
		TON	TON	SY	LF	EA	LF	SY	EA	GAL
44	BEGIN TO 104+00	516	183					51		392
45	104+00 TO 110+00	285	100					74	2	216
46	110+00 TO 116+00									
47	116+00 TO 122+00									
48	122+00 TO 128+00									
49	128+00 TO 134+00									
50	134+00 TO 140+00	202	78	79				41	1	153
51	140+00 TO END	271	105	94	31	2	22	55	2	205
PROJECT TOTALS		1274	466	173	31	2	22	221	5	966

NOTES:
1. THIS ITEM IS SUBSIDIARY TO INSTALLATION
DRIVEWAYS (SURF TREAT)-530 7016

SIGNING QUANTITIES									
PLAN SHEET NO.	STATION TO STATION	644 7001	644 7073	REMOVE SM RD SN SUP&AM TY10BWG(1)SA(P)	IN SM RD SN SUP&AM	EA	EA	EA	EA
		EA	EA						
61	BEGIN TO 110+00	4	4						
62	110+00 TO 122+00								
63	122+00 TO 134+00	1							
64	134+00 TO END	2	1						
PROJECT TOTALS		7	5						

DRAINAGE QUANTITIES										
PLAN SHEET NO.	STATION	105.1	307.1	401.1	401.4	403.1	407.4	410.2	XXX.01	XXX.02
		CHANNEL EXCAVATION	CONCRETE RIPRAP	DRAIN PIPE (30" DIAM RCP CLASS IV)	SAFETY END TREATMENT	JUNCTION BOX (COMPLETE) 4X4X4"	CONCRETE COLLAR	GRAVEL SUBGRADE FILLER	8-12" DIAM ROCK RUBBLE	GRATE INLET
		CY	CY	LF	EA	EA	EA	CY	SY	EA
50	144+82.53									
51	110+00 TO 122+00	57	6	92	1	1	1	6	5	1
PROJECT TOTALS		57	6	92	1	1	1	6	5	1



PAVEMENT MARKINGS QUANTITIES		0666 7018	0666 7024	0666 7036	0666 7042	0666 7045	0666 7066	0666 7123	0666 7132	0666 7411	0666 7423	0672 7002	0672 7004	0677 7001
PLAN SHEET NO.	STATION TO STATION	REFL PAV MRK TY I (W)8"(DOT)(100 MIL)	REFL PAV MRK TY I (W)8"(SLD)(100M IL)	REFL PAV MRK TY I (W)24"(SLD)(100 MIL)	REFL PAV MRK TY I (W)(ARROW)(100 MIL)	REFL PAV MRK TY I(W)(DBL ARROW)(100MIL)	REFL PAV MRK TY I (W)(WORD)(100M IL)	REFL PAV MRK TY I (Y)24"(SLD)(100 MIL)	REFL PAV MRK TY I(Y)(MED NOSE)(100MIL)	REFL PAV MRK TY I (W)6"(SLD)(100M IL)	REFL PAV MRK TY I-C	REFL PAV MRKR TY II-A-A	ELIM EXT PM & MRKS (4")	
61	BEGIN TO 110+00	14	220	33	2	2	2					1420	1350	11
62	110+00 TO 122+00													18
63	122+00 TO 134+00													88
64	134+00 TO END	12	211		2			145	1	1384	2354	11	134	
PROJECT TOTALS		26	431	33	4	2	2	145	1	2804	3704	22	152	88

SW3P QUANTITIES		0161 7002	0164 7009	0168 7001	0506 7004	0506 7011	0506 7039	0506 7041
PLAN SHEET NO.	STATION TO STATION	COMPOST MANUF TOPSOIL (4")	DRILL SEED (PERM_RURAL_S AND)	VEGETATIVE WATERING	ROCK FILTER DAMS (INSTALL) (TY 4)	ROCK FILTER DAMS (REMOVE)	TEMP SEDMT CONT FENCE (INSTALL)	TEMP SEDMT CONT FENCE (REMOVE)
61	BEGIN TO 110+00	2750	2750	43	57	57	869	869
62	110+00 TO 122+00							
63	122+00 TO 134+00							
64	134+00 TO END	3134	3134	49	133	133	1098	1098
PROJECT TOTALS		5884	5884	92	190	190	1967	1967



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

SUMMARY OF QUANTITIES

SHEET 2 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	SHEET
6	-	9
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
-	-	ABBOTT RD

1. GENERAL

- A. HANDLE TRAFFIC APPROPRIATELY THROUGHOUT THE PROJECT DURING CONSTRUCTION. PROVIDE FOR THE SAFETY OF THE TRAVELING PUBLIC AT ALL TIMES. ROADWAY CLOSURES ARE NOT ALLOWED UNLESS OTHERWISE SPECIFIED IN THE PLANS AND/OR AS APPROVED BY THE ENGINEER. PROVIDE ACCESS TO PROPERTIES AND BUSINESSES ADJACENT TO THE RIGHT-OF-WAY AT ALL TIMES DURING THE DURATION OF THE PROJECT. THE ADEQUACY OF THE PROPERTY ACCESS WILL BE DETERMINED BY THE COUNTY AND ENGINEER DO NOT LEAVE EQUIPMENT IN A POSITION THAT WILL ENDANGER THE TRAVELING PUBLIC. MAINTAIN ADEQUATE SAFETY PROVISIONS THROUGHOUT THE PROJECT BY INCLUSION OF SIGNING, MARKINGS, SIGNALS, BARRIERS AND BARRICADES. CONFORM TO THE LATEST EDITION OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMC) WHEN USING THESE PROVISIONS.
- B. THE USE OF THE RIGHT-OF-WAY IS NOT EXCLUSIVE. COOPERATE WITH THE COUNTY, THE VARIOUS UTILITY COMPANIES AND CONTRACTORS, AS REQUIRED TO ALLOW ADJUSTMENTS TO BE MADE BY OTHERS. IF BY VIRTUE OF THE ADJUSTMENTS OF THESE UTILITIES THE CONTRACTOR IS DELAYED, AN EXTENSION OF THE WORKING TIME MAY BE GRANTED. IF IN THE OPINION OF THE ENGINEER IT IS WARRANTED.
- C. ALL DETOURS, TRAFFIC MOVEMENTS, ETC., ARE DIRECTLY RELATED TO THE SEQUENCE OF WORK; THEREFORE, PROCEED WITH CONSTRUCTION OPERATIONS IN CONFORMITY WITH THE DETAILS SHOWN ON THE PLANS AND AS REQUIRED BY THIS NARRATIVE.
- D. PROPOSE AND/OR RECOMMEND ANY MODIFICATIONS TO THE SEQUENCE OF WORK FOR CONSIDERATION TO THE ENGINEER IN WRITING, INCLUDE ANY CHANGES TO THE VARIOUS PAY ITEMS, IMPACT TO TRAFFIC, AND THE EFFECT OF THE OVERALL PROJECT IN TIME AND COST, ETC., WITH ANY MAJOR RECOMMENDED MODIFICATIONS, WRITTEN APPROVAL FROM THE ENGINEER IS REQUIRED PRIOR TO PROCEEDING WITH ANY CONSTRUCTION OPERATION BASED ON A REVISED PHASE/SEQUENCE OF WORK.
- E. OFF-DUTY POLICE OFFICERS MAY BE HIRED TO SUPPLEMENT THE WORK FORCE TO CONTROL TRAFFIC AT INTERSECTIONS DURING THE DETOURING OF TRAFFIC, CLOSURE OF ROADWAY AND/OR INTERSECTIONS, AND ANY OTHER CRITICAL PHASES OF TRAFFIC HANDLING AS DETERMINED BY THE ENGINEER.
- F. THE ENGINEER MAY DIRECT THE CONTRACTOR TO VARY THE NUMBER AND LOCATIONS OF SIGNS AND BARRICADES FROM THAT INDICATED ON THE PLANS.
- G. COOPERATE FULLY WITH THE VARIOUS UTILITY COMPANIES.
- H. WEEKEND HOURS ARE DEFINED AS THE HOURS BETWEEN FRIDAY 9:00 PM TO MONDAY 5:00 AM.
- I. OFF PEAK HOURS ARE DEFINED AS A TIME FRAME BETWEEN 8:00 PM TO 5:00 AM MONDAY THRU FRIDAY.
- J. MAINTAIN POSITIVE DRAINAGE DURING CONSTRUCTION, INCLUDING OFFSITE DRAINAGE FROM ADJACENT PROPERTIES AND AVOID IMPEDING FLOW FROM PRIVATE PROPERTY.
- K. PLACE CONSTRUCTION EXITS AS NEEDED OR AS DIRECTED BY THE ENGINEER.
- L. DAILY LANE CLOSURES WILL BE USED IN ACCORDANCE WITH STATE TCP STANDARDS.
- M. DROP OFF CONDITIONS OF GREATER THAN 2 IN. MUST HAVE A 3:1 SLOPE AT THE END OF EACH DAY, AS WELL AS THROUGHOUT THE PROJECT WHERE ACCESS TO ADJACENT PROPERTIES IS ALLOWED TO DRIVEWAYS AND SIDE STREETS.
- N. PLANNING, SURFACE TREATMENTS AND OVERLAYS SHALL BE PERFORMED IN THE DIRECTION OF TRAFFIC.
- O. MAINTAIN ACCESS TO ADJACENT PROPERTIES AND INTERSECTING SIDE STREETS AT ALL TIMES DURING CONSTRUCTION. FOR PROPERTIES WITH MULTIPLE ACCESS DRIVEWAYS, COORDINATE WITH PROPERTY OWNERS FOR A SINGLE DRIVEWAY FULL CLOSURE IN ORDER TO MAINTAIN ACCESS. FOR PROPERTIES WITH SINGLE ACCESS DRIVEWAYS OR ONE-WAY DRIVEWAYS, CONSTRUCT DRIVEWAYS IN HALF-SECTIONS, UNLESS APPROVED BY PROPERTY OWNER AND ENGINEER.
- P. CONTRACTOR TO GIVE 7 DAYS ADVANCED NOTICE TO THE PUBLIC USING PORTABLE CHANGEABLE MESSAGE SIGNS BEFORE EACH LONG TERM TCP PHASE/STEP.

2. SEQUENCE OF WORK

THE SEQUENCE OF WORK WILL BE AS FOLLOWS UNLESS OTHERWISE DIRECTED/APPROVED BY THE COUNTY INSPECTOR. THIS PROJECT WILL BE CONSTRUCTED IN (3) PHASES. BEFORE THE COMMENCEMENT OF EACH PHASE, INSTALL TRAFFIC CONTROL DEVICES AND SW3P MEASURES AS SHOWN AND/OR DIRECTED BY THE COUNTY INSPECTOR. APPROVAL BY THE ENGINEER MUST BE OBTAINED PRIOR TO THE BEGINNING OF CONSTRUCTION. REFER TO "BARRICADES AND CONSTRUCTION STANDARDS". PREPARING ROW / REMOVAL OF EXISTING ITEMS TO BE DONE ONLY IN AREAS WHERE WORK IS OCCURRING, AS PER THE PHASES NOTED BELOW. A BRIEF DESCRIPTION OF THESE PHASES ARE AS FOLLOWS:

PHASE 1 - ABBOTT ROAD RECONSTRUCTION AT FM 1346 INTERSECTION

THE INTENT OF THIS PHASE IS TO RECONSTRUCT ABBOTT RD WITH A RIGHT TURN LANE AT FM 1346 INTERSECTION (BEGIN PROJECT TO STA 107+00.11).

STEP 1 - NORTHBOUND ABBOTT ROAD RECONSTRUCTION (BEGIN PROJECT TO STA 107+00.11)

THE INTENT OF THIS STEP IS TO RECONSTRUCT THE NORTHBOUND SIDE OF ABBOTT ROAD USING A DAILY SHOULDER CLOSURE ALONG FM 1346 AND A LONG TERM ONE-LANE ONE-WAY TCP SETUP ALONG ABBOTT ROAD WITH A DETOUR. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY.

1. INSTALL TCP SIGNS AND BARRICADES PER TXDOT TCP STANDARD (1-1b)-18, (2-8)-23, AND TCP PHASE 1 STEP 1 TYPICAL SECTIONS. REFER TO TCP PHASE 1 STEP 1 DETOUR.
2. SAWCUT EXISTING ROADWAY
3. EXCAVATE AND REMOVE ITEMS PER PLANS
4. COMPACT, EMBANK, AND LIME TREAT SUBGRADE
5. RECONSTRUCT DRIVEWAYS
6. PLACE 18" FLEX BASE
7. PAVE 5.5" HMA TYPE B
8. PAVE 2" HMA TYPE D

STEP 2 - SOUTHBOUND ABBOTT ROAD RECONSTRUCTION (BEGIN PROJECT TO STA 107+00.11)

THE INTENT OF THIS STEP IS TO RECONSTRUCT THE SOUTHBOUND SIDE OF ABBOTT ROAD USING A DAILY SHOULDER CLOSURE ALONG FM 1346 AND A LONG TERM ONE-LANE ONE-WAY TCP SETUP ALONG ABBOTT ROAD WITH A DETOUR. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY.

1. INSTALL TCP SIGNS AND BARRICADES PER TXDOT TCP STANDARD (1-1b)-18, (2-8)-23, AND TCP PHASE 1 STEP 2 TYPICAL SECTIONS. REFER TO TCP PHASE 1 STEP 2 DETOUR.
2. SAWCUT EXISTING ROADWAY
3. EXCAVATE AND REMOVE ITEMS PER PLANS
4. COMPACT, EMBANK, AND LIME TREAT SUBGRADE
5. RECONSTRUCT DRIVEWAYS
6. PLACE 18" FLEX BASE
7. PAVE 5.5" HMA TYPE B
8. PAVE 2" HMA TYPE D

PHASE 2 - ROADWAY WIDENING ALONG ABBOTT ROAD

THE INTENT OF THIS PHASE IS TO WIDEN BOTH SIDES OF ABBOTT ROAD, RECONSTRUCT EXISTING DRIVEWAYS, AND CONSTRUCT A PROPOSED DRIVEWAY (STA 136+42.15 TO END PROJECT).

STEP 1 - NORTHBOUND ABBOTT ROAD WIDENING (STA 136+42.82 TO END PROJECT)

THE INTENT OF THIS STEP IS TO WIDEN THE NORTHBOUND SIDE OF ABBOTT ROAD USING A LONG TERM ONE-LANE ONE-WAY TCP SETUP ALONG ABBOTT ROAD WITH A DETOUR. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY. REFER TO TXDOT STANDARD WZ(RCD)-13 FOR APPLICABLE TCP SIGNING.

1. INSTALL TCP SIGNS AND BARRICADES PER TXDOT TCP STANDARD (2-8)-23 AND TCP PHASE 2 STEP 1 TYPICAL SECTION. REFER TO TCP PHASE 2 STEP 1 DETOUR.
2. SAWCUT EXISTING ROADWAY
3. MILL, EXCAVATE, AND REMOVE ITEMS PER PLANS
4. COMPACT, EMBANK, AND LIME TREAT SUBGRADE
5. PLACE 18" FLEX BASE
6. PAVE 5.5" HMA TYPE B

7. PAVE 2" HMA TYPE D

STEP 2 - NORTHBOUND ABBOTT ROAD DRIVEWAY RECONSTRUCTION

THE INTENT OF THIS STEP IS TO RECONSTRUCT THE DRIVEWAYS ALONG THE NORTHBOUND SIDE OF ABBOTT ROAD USING A DAILY SHOULDER CLOSURE ALONG ABBOTT ROAD. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY.

1. INSTALL TCP SIGNS AND BARRICADES PER TXDOT TCP STANDARD (1-1)-18 AND TCP PHASE 2 STEP 2 TYPICAL SECTION
2. RECONSTRUCT EXISTING DRIVEWAYS

STEP 3 - SOUTHBOUND ABBOTT ROAD WIDENING (STA 136+42.15 TO END PROJECT)

THE INTENT OF THIS STEP IS TO WIDEN THE SOUTHBOUND SIDE OF ABBOTT ROAD USING A LONG TERM ONE-LANE ONE-WAY TCP SETUP ALONG ABBOTT ROAD WITH A DETOUR. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY.

1. INSTALL TOP SIGNS AND BARRICADES PER TXDOT TOP STANDARD (2-8)-23 AND TCP PHASE 2 STEP 3 TYPICAL SECTION. REFER TO TCP PHASE 2 STEP 3 DETOUR.
2. SAWCUT EXISTING ROADWAY
3. MILL, EXCAVATE, AND REMOVE ITEMS PER PLANS
4. COMPACT, EMBANK, AND LIME TREAT SUBGRADE
5. PLACE 18" FLEX BASE
6. PAVE 5.5" HMA TYPE B
7. PAVE 2" HMA TYPE D

STEP 4 - SOUTHBOUND ABBOTT ROAD DRIVEWAY CONSTRUCTION

THE INTENT OF THIS STEP IS TO CONSTRUCT A DRIVEWAY ALONG THE SOUTHBOUND SIDE OF ABBOTT ROAD USING LONG-TERM LANE SHIFTS ALONG ABBOTT ROAD. CONTRACTOR TO BACKFILL ALL DROP OFF CONDITIONS WITH A 3:1 SLOPE AT THE END OF EACH WORKDAY.

1. INSTALL TCP SIGNS AND BARRICADES PER TXDOT TOP STANDARD (2-3a)-23 AND TCP PHASE 2 STEP 4 TYPICAL SECTION
2. CONSTRUCT PROPOSED DRIVEWAY

PHASE 3 - ONE COURSE SURFACE TREATMENT, PERMANENT PAVEMENT MARKINGS AND SIGNAGE ALONG ABBOTT ROAD

THE INTENT OF THIS PHASE IS TO PLACE A ONE COURSE SURFACE TREATMENT FROM STA 136+42.15 TO STA 144+24.84, PLACE PERMANENT PAVEMENT MARKINGS AND SIGNAGE.

PLACE THE ONE COURSE SURFACE TREATMENT USING A ONE-LANE TWO-WAY TCP SETUP PER TXDOT TCP STANDARD (1-2)-18 AND TCP (7-1)-13. INSTALL SHORT TERM PAVEMENT MARKING TABS PER TXDOT STANDARD WZ(STPM)-23 UNTIL FINAL PAVEMENT MARKINGS ARE INSTALLED. INSTALL THE PERMANENT PAVEMENT MARKINGS FOLLOWING TXDOT TCP STANDARD (3-1)-13 AND NO LATER THAN 14 CALENDAR DAYS AFTER PLACEMENT OF THE OCST. INSTALL THE PERMANENT SIGNING USING A DAILY SHOULDER CLOSURE FOLLOWING TXDOT TCP STANDARD (1-1)-18.

95% SUBMITTAL

PRELIMINARY
FOR REVIEW ONLY
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT
TO CHANGE. THEY ARE NOT INTENDED FOR
CONSTRUCTION OR PERMIT PURPOSES. THEY WERE
PREPARED BY, OR UNDER THE SUPERVISION OF:
EDWARD GALICIA 114275 1/5/2026
NAME P.E. # DATE




Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2 TRAFFIC CONTROL PLAN SEQUENCE OF WORK

SHEET 1 OF 1

FED.RD. DIV./NO.	PROJECT NO.	SHOOT
6	-	10
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
-	-	ABBOTT RD



NOTES:

- CERTAIN SIGNS MUST BE USED IN CONJUNCTION WITH OTHER SIGNS. EXAMPLE: "FLAGGERS AHEAD" MUST HAVE A "BE PREPARED TO STOP" SIGN.
- BARRICADES AND WARNING SIGNS ON THIS SHEET ARE MINIMAL CONSTRUCTION ZONE SIGNING. ADDITIONAL BARRICADES, WARNING SIGNS, ARROW PANELS, CONES, ETC. IN ACCORDANCE WITH CURRENT BC STANDARDS AND THE TEXAS MUTCD, MAY BE REQUIRED IN AREAS OF ACTUAL CONSTRUCTION.
- A DISTANCE PLAQUE IN FEET OR MILES MAY BE REQUIRED FOR USE IN CONJUNCTION WITH WARNING SIGNS.
- UTILIZE EXPERIENCED FLAGGERS AT ALL TIMES.
- TRUCK MOUNTED ATTENUATORS (TMA) WILL BE REQUIRED FOR THIS PROJECT.

0' 200' 400'
SCALE: 1"=400'

95% SUBMITTAL


PRELIMINARY FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275 1/5/2026
NAME	P.E. # DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623


ROSE VALLEY SOUTH UNIT #2
TRAFFIC CONTROL PLAN
SCHEDULE OF BARRICADES

SCALE: 1" = 400'		SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	11	SHEET
6	-	-	
STATE	DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD




PHASE 1 STEP 1 - TCP TYPICAL SECTION (ABBOTT RD)

PROP & ABBOTT RD STA 100+22.82 TO STA 106+00.00



NOTES:

1. USE PROP & FOR TCP LAYOUT CONTROL, UNLESS OTHERWISE SPECIFIED.



PHASE 1 STEP 1 - TCP TYPICAL SECTION (ABBOTT RD)

PROP & ABBOTT RD STA 106+00.00 TO STA 107+00.11

**PRELIMINARY
FOR REVIEW ONLY**

THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:


EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

**ROSE VALLEY SOUTH UNIT #2
TRAFFIC CONTROL PLAN
PHASE 1 STEP 1
TYPICAL SECTIONS**

N.T.S.			SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	SHEET		
6	-	12		
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	



PHASE 1 STEP 1 - TCP TYPICAL SECTION (FM 1346)

FM 1346 STA 213+68.55 TO STA 219+58.55


* SEE ROADWAY LAYOUTS FOR WIDENING LIMITS

LEGEND

- ↑ EXISTING TRAFFIC FLOW
- ↓ TCP TRAFFIC FLOW
- ▨ CONSTRUCTION THIS PHASE/STEP
- CONSTRUCTED PREVIOUS PHASE/STEP

NOTES:

1. USE PROP C FOR TCP LAYOUT CONTROL, UNLESS OTHERWISE SPECIFIED.



PHASE 1 STEP 2 - TCP TYPICAL SECTION (FM 1346)

FM 1346 STA 210+92.70 TO STA 213+04.95 AND STA 214+04.00 TO STA 217+49.91

* SEE ROADWAY LAYOUTS FOR WIDENING LIMITS

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275
NAME P.E. # DATE	




Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

**TRAFFIC CONTROL PLAN
PHASE 1 STEP 1/2
TYPICAL SECTIONS**

N.T.S.			SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	SHEET		
6	-	13		
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	



PHASE 1 STEP 2 - TCP TYPICAL SECTION (ABBOTT RD)


PROP Q ABBOTT RD STA 100+22.82 TO STA 106+00.00

LEGEND

- Existing Traffic Flow (Upward Arrow)
- TCP Traffic Flow (Downward Arrow)
- Construction This Phase/Step (Hatching)
- Constructed Previous Phase/Step (Solid Gray)

NOTES:

1. USE PROP Q FOR TCP LAYOUT CONTROL, UNLESS OTHERWISE SPECIFIED.



PHASE 1 STEP 2 - TCP TYPICAL SECTION (ABBOTT RD)

PROP Q ABBOTT RD STA 106+00.00 TO STA 107+00.11

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA 114275 1/5/2026		
NAME	P.E. #	DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2


TRAFFIC CONTROL PLAN


PHASE 1 STEP 2


TYPICAL SECTIONS

N.T.S. SHEET 1 OF 1

FED.RD. DIV./NO.	PROJECT NO.	SHEET
6	-	14
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
		ABBOTT RD









PHASE 2 STEP 1 - TCP TYPICAL SECTION (ABBOTT RD)

PROP 6 ABBOTT RD STA 136+42.82 TO END PROJECT



NOTES:

1. USE PROP 6 FOR TCP LAYOUT CONTROL, UNLESS OTHERWISE SPECIFIED.



PHASE 2 STEP 2 - TCP TYPICAL SECTION (ABBOTT RD)

PROP 6 ABBOTT RD STA 136+42.82 TO END PROJECT
* SEE DRIVEWAY PLAN AND PROFILE SHEETS FOR DRIVEWAY LOCATIONS AND CONSTRUCTION LIMITS

95% SUBMITTAL


PRELIMINARY FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275
NAME	P.E. #
1/5/2026	
DATE	




Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2
TRAFFIC CONTROL PLAN
PHASE 2 STEP 1 & 2
TYPICAL SECTIONS

N.T.S.			SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	SHEET		
6		17		
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	





PHASE 2 STEP 3 - TCP TYPICAL SECTION (ABBOTT RD)


PROP 6 ABBOTT RD STA 136+42.15 TO END PROJECT

LEGEND

- EXISTING TRAFFIC FLOW
- TCP TRAFFIC FLOW
- CONSTRUCTION THIS PHASE/STEP
- CONSTRUCTED PREVIOUS PHASE/STEP

NOTES:

1. USE PROP 6 FOR TCP LAYOUT CONTROL, UNLESS OTHERWISE SPECIFIED.



PHASE 2 STEP 4 - TCP TYPICAL SECTION (ABBOTT RD)

PROP 6 ABBOTT RD STA 136+42.15 TO END PROJECT

* SEE DRIVEWAY PLAN AND PROFILE SHEETS FOR DRIVEWAY LOCATION AND CONSTRUCTION LIMITS

95% SUBMITTAL


PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2
TRAFFIC CONTROL PLAN
PHASE 2 STEP 3 & 4
TYPICAL SECTIONS

N.T.S.			SHEET 1 OF 1	
FED.RD. DIV./NO.	PROJECT NO.	SHEET		
6	-	19		
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	



BARRICADE AND CONSTRUCTION (BC) STANDARD SHEETS GENERAL NOTES:

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

- The Barricade and Construction Standard Sheets (BC sheets) are intended to show typical examples for placement of temporary traffic control devices, construction pavement markings, and typical work zone signs. The information contained in these sheets meet or exceed the requirements shown in the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
- The development and design of the Traffic Control Plan (TCP) is the responsibility of the Engineer.
- The Contractor may propose changes to the TCP that are signed and sealed by a licensed professional engineer for approval. The Engineer may develop, sign and seal Contractor proposed changes.
- The Contractor is responsible for installing and maintaining the traffic control devices as shown in the plans. The Contractor may not move or change the approximate location of any device without the approval of the Engineer.
- Geometric design of lane shifts and detours should, when possible, meet the applicable design criteria contained in manuals such as the American Association of State Highway and Transportation Officials (AASHTO), "A Policy on Geometric Design of Highways and Streets," the TxDOT "Roadway Design Manual" or engineering judgment.
- When projects abut, the Engineer(s) may omit the END ROAD WORK, TRAFFIC FINES DOUBLE, and other advance warning signs if the signing would be redundant and the work areas appear continuous to the motorists. If the adjacent project is completed first, the Contractor shall erect the necessary warning signs as shown on these sheets, the TCP sheets or as directed by the Engineer. The BEGIN ROAD WORK NEXT X MILES sign shall be revised to show appropriate work zone distance.
- The Engineer may require duplicate warning signs on the median side of divided highways where median width will permit and traffic volumes justify the signing.
- All signs shall be constructed in accordance with the details found in the "Standard Highway Sign Designs for Texas," latest edition. Sign details not shown in this manual shall be shown in the plans or the Engineer shall provide a detail to the Contractor before the sign is manufactured.
- The temporary traffic control devices shown in the illustrations of the BC sheets are examples. As necessary, the Engineer will determine the most appropriate traffic control devices to be used.
- Where highway construction or maintenance work is being undertaken, other than mobile operations as defined by the Texas Manual on Uniform Traffic Control Devices, CSJ limit signs are required. CSJ limit signs are shown on BC(2). The OBEY WARNING SIGNS STATE LAW sign, STAY ALERT TALK OR TEXT LATER and the WORK ZONE TRAFFIC FINES DOUBLE sign with plaque shall be erected in advance of the CSJ limits. The BEGIN ROAD WORK NEXT X MILES, CONTRACTOR and END ROAD WORK signs shall be erected at or near the CSJ limits. For mobile operations, CSJ limit signs are not required.
- Traffic control devices should be in place only while work is actually in progress or a definite need exists.
- The Engineer has the final decision on the location of all traffic control devices.
- Inactive equipment and work vehicles, including workers' private vehicles must be parked away from travel lanes. They should be as close to the right-of-way line as possible, or located behind a barrier or guardrail, or as approved by the Engineer.

WORKER SAFETY NOTES:

- Workers on foot who are exposed to traffic or to construction equipment within the right-of-way shall wear high-visibility safety apparel meeting the requirements of ISEA "American National Standard for High-Visibility Apparel," or equivalent revisions, and labeled as ANSI 107-2004 standard performance for Class 2 or 3 risk exposure. Class 3 garments should be considered for high traffic volume work areas or night time work.
- Except in emergency situations, flagger stations shall be illuminated when flagging is used at night.

COMPLIANT WORKZONE TRAFFIC CONTROL DEVICES


- Only pre-qualified products shall be used. The "Compliant Work Zone Traffic Control Devices List" (CWZTCD) describes pre-qualified products and their sources.
- Work zone traffic control devices shall be compliant with the Manual for Assessing Safety Hardware (MASH).

THE DOCUMENTS BELOW CAN BE FOUND ON-LINE AT
<http://www.txdot.gov>

- COMPLIANT WORK ZONE TRAFFIC CONTROL DEVICES LIST (CWZTCD)
- DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS)
- MATERIAL PRODUCER LIST (MPL)
- ROADWAY DESIGN MANUAL - SEE "MANUALS (ONLINE MANUALS)"
- STANDARD HIGHWAY SIGN DESIGNS FOR TEXAS (SHSD)
- TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD)
- TRAFFIC ENGINEERING STANDARD SHEETS

SHEET 1 OF 12


 Texas Department of Transportation	Traffic Safety Division Standard			
BARRICADE AND CONSTRUCTION GENERAL NOTES AND REQUIREMENTS				
BC (1) - 21				
FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
4-03 7-13	-	-	-	ABBOT RD
9-07 8-14	DIST	COUNTY	SHEET NO.	
5-10 5-21	-	BEXAR	21	



May be mounted on back of "ROAD WORK AHEAD" (CW20-1D) sign with approval of Engineer. (See note 2 below)

1. The typical minimum signing on a crossroad approach should be a "ROAD WORK AHEAD" (CW20-1D) sign and a (G20-2) "END ROAD WORK" sign, unless noted otherwise in plans.
2. The Engineer may use the reduced size 36" x 36" "ROAD WORK AHEAD" (CW20-1D) sign mounted back to back with the reduced size 36" x 18" "END ROAD WORK" (G20-2) sign on low volume crossroads (see Note 4 under "Typical Construction Warning Sign Size and Spacing"). See the "Standard Highway Sign Designs for Texas" manual for sign details. The Engineer may omit the advance warning signs on low volume crossroads. The Engineer will determine whether a road is low volume as per TMUTCD Part 5. This information shall be shown in the plans.
3. Based on existing field conditions, the Engineer/Inspector may require additional signs such as FLAGGER AHEAD, LOOSE GRAVEL, or other appropriate signs. When additional signs are required, these signs will be considered part of the minimum requirements. The Engineer/Inspector will determine the proper location and spacing of any sign not shown on the BC sheets, Traffic Control Plan sheets or the Work Zone Standard Sheets.
4. The "ROAD WORK NEXT X MILES" (G20-1aT) sign shall be required at high volume crossroads to advise motorists of the length of construction in either direction from the intersection. The Engineer will determine whether a roadway is considered high volume.
5. Additional traffic control devices may be shown elsewhere in the plans for higher volume crossroads.
6. When work occurs in the intersection area, appropriate traffic control devices, as shown elsewhere in the plans or as determined by the Engineer/Inspector, shall be in place.


WORK AREAS IN MULTIPLE LOCATIONS WITHIN CSJ LIMITS



When extended distances occur between minimal work spaces, the Engineer/Inspector should ensure additional "ROAD WORK AHEAD" (CW20-1D) signs are placed in advance of these work areas to remind drivers they are still within the project limits. See the applicable TCP sheets for exact location and spacing of signs and channelizing devices.

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING AT THE CSJ LIMITS

SAMPLE LAYOUT OF SIGNING FOR WORK BEGINNING DOWNSTREAM OF THE CSJ LIMITS




The Contractor shall determine the appropriate distance to be placed on the G20-1 series signs and "BEGIN ROAD WORK NEXT X MILES" (G20-5T) sign for each specific project. This distance shall replace the "X" and shall be rounded to the nearest whole mile with the approval of the Engineer. No decimals shall be used.

The "BEGIN WORK ZONE" (G20-9TP) and "END WORK ZONE" (G20-2bT) shall be used as shown on the sample layout when advance signs are required outside the CSJ Limits. They inform the motorist of entering or leaving a part of the work zone lying outside the CSJ Limits where traffic fines may double if workers are present.

CSJ limit signing is required for highway construction and maintenance work, with the exception of mobile operations.

Area for placement of "ROAD WORK AHEAD" (CW20-1D) sign and other signs or devices as called for on the Traffic Control Plan.

Contractor will install a regulatory speed limit sign at the end of the work zone.



CSJ LIMITS AT T-INTERSECTION

1. The Engineer will determine the types and location of any additional traffic control devices, such as a flagger and accompanying signs, or other signs, that should be used when work is being performed at or near an intersection.
2. If construction closes the road at a T-intersection, the Contractor shall place the "CONTRACTOR NAME" (G20-6T) sign behind the Type 3 Barricades for the road closure (see BC10 also). The "ROAD WORK NEXT X MILES" left arrow (G20-1bTL) and "ROAD WORK NEXT X MILES" right arrow (G20-1bTR) signs shall be replaced by the detour signing called for in the plans.

TYPICAL CONSTRUCTION WARNING SIGN SIZE AND SPACING ^{1-5,6}		
SIZE		SPACING
Sign Number or Series	Conventional Road	Expressway/ Freeway
CW20 ⁴	48" x 48"	48" x 48"
CW21		
CW22		
CW23		
CW25		
CW1, CW2, CW7, CW8, CW9, CW11, CW14	36" x 36"	48" x 48"
CW3, CW4, CW5, CW6, CW8-3, CW10, CW12	48" x 48"	48" x 48"
*	*	*

* For typical sign spacings on divided highways, expressways and freeways, see Part 6 of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) typical application diagrams or TCP Standard Sheets.

△ Minimum distance from work area to first Advance Warning sign nearest the work area and/or distance between each additional sign.

GENERAL NOTES

1. Special or larger size signs may be used as necessary.
2. Distance between signs should be increased as required to have 1500 feet advance warning.
3. Distance between signs should be increased as required to have 1/2 mile or more advance warning.
4. 36" x 36" "ROAD WORK AHEAD" (CW20-1D) signs may be used on low volume crossroads at the discretion of the Engineer as per TMUTCD Part 5. See Note 2 under "Typical Location of Crossroad Signs".
5. Only diamond shaped warning sign sizes are indicated.
6. See sign size listing in "TMUTCD", Sign Appendix or the "Standard Highway Sign Designs for Texas" manual for complete list of available sign design sizes.

LEGEND	
—	Type 3 Barricade
○ ○ ○	Channelizing Devices
—	Sign
X	See Typical Construction Warning Sign Size and Spacing chart or the TMUTCD for sign spacing requirements.


SHEET 2 OF 12

Texas Department of Transportation Traffic Safety Division Standard

BARRICADE AND CONSTRUCTION PROJECT LIMIT

BC (2) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT	JOB	HIGHWAY
REVISIONS	-	-	-	ABBOT RD
9-07 8-14 7-13 5-21	DIST	COUNTY	SHEET NO.	
	-	BEXAR	22	




DATE: 1/5/2026 8:28:33 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates-FM-1346\4 - Design\Plan Set\02 TCP Standard

TYPICAL APPLICATION OF WORK ZONE SPEED LIMIT SIGNS

Work zone speed limits shall be regulatory, established in accordance with the "Procedures for Establishing Speed Zones," and approved by the Texas Transportation Commission, or by City Ordinance when within Incorporated City Limits.

Reduced speeds should only be posted in the vicinity of work activity and not throughout the entire project.

Regulatory work zone speed signs (R2-1) shall be removed or covered during periods when they are not needed.



GUIDANCE FOR USE:

LONG/INTERMEDIATE TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit should be included on the design of the traffic control plans when restricted geometrics with a lower design speed are present in the work zone and modification of the geometrics to a higher design speed is not feasible.

Long/Intermediate Term Work Zone Speed Limit signs, when approved as described above, should be posted and visible to the motorist when work activity is present. Work activity may also be defined as a change in the roadway that requires a reduced speed for motorists to safely negotiate the work area, including:

- a) rough road or damaged pavement surface
- b) substantial alteration of roadway geometrics (diversions)
- c) construction detours
- d) grade
- e) width

f) other conditions readily apparent to the driver

As long as any of these conditions exist, the work zone speed limit signs should remain in place.

SHORT TERM WORK ZONE SPEED LIMITS

This type of work zone speed limit may be included on the design of the traffic control plans when workers or equipment are not behind concrete barrier, when work activity is within 10 feet of the traveled way or actually in the traveled way.

Short Term Work Zone Speed Limit signs should be posted and visible to the motorists only when work activity is present. When work activity is not present, signs shall be removed or covered. (See Removing or Covering on BC(4)).


GENERAL NOTES

1. Regulatory work zone speed limits should be used only for sections of construction projects where speed control is of major importance.
2. Regulatory work zone speed limit signs shall be placed on supports at a 7 foot minimum mounting height.
3. Speed zone signs are illustrated for one direction of travel and are normally posted for each direction of travel.
4. Frequency of work zone speed limit signs should be:

40 mph and greater	0.2 to 2 miles
35 mph and less	0.2 to 1 mile
5. Regulatory speed limit signs shall have black legend and border on a white reflective background (See "Reflective Sheeting" on BC(4)).
6. Fabrication, erection and maintenance of the "ADVANCE SPEED LIMIT" (CW3-5) sign, "WORK ZONE" (G20-5aP) plaque and the "SPEED LIMIT" (R2-1) signs shall not be paid for directly, but shall be considered subsidiary to Item 502.
7. Turning signs from view, laying signs over or down will not be allowed, unless as otherwise noted under "REMOVING OR COVERING" on BC(4).
8. Techniques that may help reduce traffic speeds include but are not limited to:
 - A. Law enforcement.
 - B. Flagger stationed next to sign.
 - C. Portable changeable message sign (PCMS).
 - D. Low-power (drone) radar transmitter.
 - E. Speed monitor trailers or signs.
9. Speeds shown on details above are for illustration only. Work Zone Speed Limits should only be posted as approved for each project.
10. For more specific guidance concerning the type of work, work zone conditions and factors impacting allowable regulatory construction speed zone reduction see TxDOT form #1204 in the TxDOT e-form system.


SHEET 3 OF 12

 Texas Department of Transportation			
BARRICADE AND CONSTRUCTION WORK ZONE SPEED LIMIT			
BC (3) - 21			
FILE: bc-21.dgn <input checked="" type="checkbox"/> TxDOT November 2002		DN: TxDOT CK: TxDOT DW: TxDOT CK: TxDOT CONT SECT JOB HIGHWAY REVISIONS 9-07 8-14 7-13 5-21	
DIST 9-07 7-13		COUNTY ABBOT RD BEXAR	
SHEET NO. 23			



* When placing skid supports on unlevel ground, the leg post lengths must be adjusted so the sign appears straight and plumb. Objects shall NOT be placed under skids as a means of leveling.


** When plaques are placed on dual-leg supports, they should be attached to the upright nearest the travel lane. Supplemental plaques (advisory or distance) should not cover the surface of the parent sign.



Splicing embedded perforated square metal tubing in order to extend post height will only be allowed when the splice is made using four bolts, two above and two below the splice point. Splice must be located entirely behind the sign substrate, not near the base of the support. Splice insert lengths should be at least 5 times nominal post size, centered on the splice and of at least the same gauge material.

STOP/SLOW PADDLES

- STOP/SLOW paddles are the primary method to control traffic by flaggers. The STOP/SLOW paddle size should be 24" x 24".
- STOP/SLOW paddles shall be retroreflectorized when used at night.
- STOP/SLOW paddles may be attached to a staff with a minimum length of 6' to the bottom of the sign.
- Any lights incorporated into the STOP or SLOW paddle faces shall only be as specifically described in Section 6E.03 Hand Signaling Devices in the TMUTCD.



SHEETING REQUIREMENTS (WHEN USED AT NIGHT)		
USAGE	COLOR	SIGN FACE MATERIAL
BACKGROUND	RED	TYPE B OR C SHEETING
BACKGROUND	ORANGE	TYPE B _{FL} OR C _{FL} SHEETING
LEGEND & BORDER	WHITE	TYPE B OR C SHEETING
LEGEND & BORDER	BLACK	ACRYLIC NON-REFLECTIVE FILM

CONTRACTOR REQUIREMENTS FOR MAINTAINING PERMANENT SIGNS WITHIN THE PROJECT LIMITS

- Permanent signs are used to give notice of traffic laws or regulations, call attention to conditions that are potentially hazardous to traffic operations, show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, specific service (LOGO), or cultural information. Drivers proceeding through a work zone need the same, if not better route guidance as normally installed on a roadway without construction.
- When permanent regulatory or warning signs conflict with work zone conditions, remove or cover the permanent signs until the permanent sign message matches the roadway condition. For details for covering large guide signs see the TS-CD standard.
- When existing permanent signs are moved and relocated due to construction purposes, they shall be visible to motorists at all times.
- If existing signs are to be relocated on their original supports, they shall be installed on crashworthy bases as shown on the SMD Standard sheets. The signs shall meet the required mounting heights shown on the BC Sheets or the SMD Standards. This work should be paid for under the appropriate pay item for relocating existing signs.
- If permanent signs are to be removed and relocated using temporary supports, the Contractor shall use crashworthy supports as shown on the BC standard sheets, TLRS standard sheets or the CWZTCD list. The signs shall meet the required mounting heights shown on the BC, or the SMD standard sheets during construction. This work should be paid for under the appropriate pay item for relocating existing signs.
- Any sign or traffic control device that is struck or damaged by the Contractor or his/her construction equipment shall be replaced as soon as possible by the Contractor to ensure proper guidance for the motorists. This will be subsidiary to Item 502.

GENERAL NOTES FOR WORK ZONE SIGNS

- Contractor shall install and maintain signs in a straight and plumb condition and/or as directed by the Engineer.
- Wooden sign posts shall be painted white.
- Barricades shall NOT be used as sign supports.
- All signs shall be installed in accordance with the plans or as directed by the Engineer. Signs shall be used to regulate, warn, and guide the traveling public safely through the work zone.
- The Contractor may furnish either the sign design shown in the plans or in the "Standard Highway Sign Designs for Texas" (SHSD). The Engineer/Inspector may require the Contractor to furnish other work zone signs that are shown in the TMUTCD but may have been omitted from the plans. Any variation in the plans shall be documented by written agreement between the Engineer and the Contractor's Responsible Person. All changes must be documented in writing before being implemented. This can include documenting the changes in the Inspector's TxDOT diary and having both the Inspector and Contractor initial and date the agreed upon changes.
- The Contractor shall furnish sign supports listed in the "Compliant Work Zone Traffic Control Device List" (CWZTCD) for small roadside signs. Supports for temporary large roadside signs shall meet the requirements detailed on the Temporary Large Roadside Signs (TLRS) standard sheets. The Contractor shall install the sign support in accordance with the manufacturer's recommendations. If there is a question regarding installation procedures, the Contractor shall furnish the Engineer a copy of the manufacturer's installation recommendations so the Engineer can verify the correct procedures are being followed.
- The Contractor is responsible for installing signs on approved supports and replacing signs with damaged or cracked substrates and/or damaged or marred reflective sheeting as directed by the Engineer/Inspector.
- Identification markings may be shown only on the back of the sign substrate. The maximum height of letters and/or company logos used for identification shall be 1 inch.
- The Contractor shall replace damaged wood posts. New or damaged wood sign posts shall not be spliced.

DURATION OF WORK (as defined by the "Texas Manual on Uniform Traffic Control Devices" Part 6)

- The types of sign supports, sign mounting height, the size of signs, and the type of sign substrates can vary based on the type of work being performed. The Engineer is responsible for selecting the appropriate size sign for the type of work being performed. The Contractor is responsible for ensuring the sign support, sign mounting height and substrate meets manufacturer's recommendations in regard to crashworthiness and duration of work requirements.
 - Long-term stationary - work that occupies a location more than 3 days.
 - Intermediate-term stationary - work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than one hour.
 - Short-term stationary - daytime work that occupies a location for more than 1 hour in a single daylight period.
 - Short, duration - work that occupies a location up to 1 hour.
 - Mobile - work that moves continuously or intermittently (stopping for up to approximately 15 minutes.)

SIGN MOUNTING HEIGHT

- The bottom of Long-term/Intermediate-term signs shall be at least 7 feet, but not more than 9 feet, above the paved surface, except as shown for supplemental plaques mounted below other signs.
- The bottom of Short-term/Short Duration signs shall be a minimum of 1 foot above the pavement surface but no more than 2 feet above the ground.
- Long-term/Intermediate-term Signs may be used in lieu of Short-term/Short Duration signing.
- Short-term/Short Duration signs shall be used only during daylight and shall be removed at the end of the workday or raised to appropriate Long-term/Intermediate sign height.
- Regulatory signs shall be mounted at least 7 feet, but not more than 9 feet, above the paved surface regardless of work duration.

SIZE OF SIGNS

- The Contractor shall furnish the sign sizes shown on BC (2) unless otherwise shown in the plans or as directed by the Engineer.

SIGN SUBSTRATES

- The Contractor shall ensure the sign substrate is installed in accordance with the manufacturer's recommendations for the type of sign support that is being used. The CWZTCD lists each substrate that can be used on the different types and models of sign supports.
- "Mesh" type materials are NOT an approved sign substrate, regardless of the tightness of the weave.
- All wooden individual sign panels fabricated from 2 or more pieces shall have one or more plywood cleat, 1/2" thick by 6" wide, fastened to the back of the sign and extending fully across the sign. The cleat shall be attached to the back of the sign using wood screws that do not penetrate the face of the sign panel. The screws shall be placed on both sides of the splice and spaced at 6" centers. The Engineer may approve other methods of splicing the sign face.

REFLECTIVE SHEETING

- All signs shall be retroreflective and constructed of sheeting meeting the color and retro-reflectivity requirements of DMS-8300 for rigid signs or DMS-8310 for roll-up signs. The web address for DMS specifications is shown on BC(1).
- White sheeting, meeting the requirements of DMS-8300 Type A, shall be used for signs with a white background.
- Orange sheeting, meeting the requirements of DMS-8300 Type B_{FL} or Type C_{FL}, shall be used for rigid signs with orange backgrounds.

SIGN LETTERS

- All sign letters and numbers shall be clear, and open rounded type uppercase alphabet letters as approved by the Federal Highway Administration (FHWA) and as published in the "Standard Highway Sign Design for Texas" manual. Signs, letters and numbers shall be of first class workmanship in accordance with Department Standards and Specifications.

REMOVING OR COVERING

- When sign messages may be confusing or do not apply, the signs shall be removed or completely covered.
- Long-term stationary or intermediate stationary signs installed on square metal tubing may be turned away from traffic 90 degrees when the sign message is not applicable. This technique may not be used for signs installed in the median of divided highways or near any intersections where the sign may be seen from approaching traffic.
- Signs installed on wooden skids shall not be turned at 90 degree angles to the roadway. These signs should be removed or completely covered when not required.
- When signs are covered, the material used shall be opaque, such as heavy mil black plastic, or other materials which will cover the entire sign face and maintain their opaque properties under automobile headlights at night, without damaging the sign sheeting.
- Burlap shall NOT be used to cover signs.
- Duct tape or other adhesive material shall NOT be used to affix to a sign face.
- Signs and anchor stubs shall be removed and holes backfilled upon completion of work.

SIGN SUPPORT WEIGHTS

- Where sign supports require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand should be used.
- The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight.
- Rock, concrete, iron, steel or other solid objects shall not be permitted for use as sign support weights.
- Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs.
- Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall NOT be used.
- Rubber ballasts designed for channelizing devices should not be used for ballast on portable sign supports. Sign supports designed and manufactured with rubber bases may be used when shown on the CWZTCD list.
- Sandbags shall only be placed along or laid over the base supports of the traffic control device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners. Sandbags shall be placed along the length of the skids to weigh down the sign support.
- Sandbags shall NOT be placed under the skid and shall not be used to level sign supports placed on slopes.

FLAGS ON SIGNS

- Flags may be used to draw attention to warning signs. When used, the flag shall be 16 inches square or larger and shall be orange or fluorescent red-orange in color. Flags shall not be allowed to cover any portion of the sign face.

SHEET 4 OF 12

 Texas Department of Transportation		Traffic Safety Division Standard	
		FILE: bc-21.dgn	DN: TxDOT
<input checked="" type="checkbox"/> TxDOT November 2002		CONT	SECT
		JOB	HIGHWAY
<small>REVISIONS</small>		-	-
<small>9-07 8-14</small>		ABBOT RD	
<small>7-13 5-21</small>		COUNTY	SHEET NO.
		-	BEXAR

BARRICADE AND CONSTRUCTION TEMPORARY SIGN NOTES

BC (4) - 21

WHEN NOT IN USE, REMOVE THE PCMS FROM THE RIGHT-OF-WAY OR PLACE THE PCMS BEHIND BARRIER OR GUARDRAIL WITH SIGN PANEL TURNED PARALLEL TO TRAFFIC

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: 1/5/2026 8:28:34 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates-FM_1346\4 - Design\Plan Set\02 TCP Standards\bc-21.dgn

PORTABLE CHANGEABLE MESSAGE SIGNS

- The Engineer/Inspector shall approve all messages used on portable changeable message signs (PCMS).
- Messages on PCMS should contain no more than 8 words (about four to eight characters per word), not including simple words such as "TO," "FOR," "AT," etc.
- Messages should consist of a single phase, or two phases that alternate. Three-phase messages are not allowed. Each phase of the message should convey a single thought, and must be understood by itself.
- Use the word "EXIT" to refer to an exit ramp on a freeway; i.e., "EXIT CLOSED." Do not use the term "RAMP."
- Always use the route or interstate designation (IH, US, SH, FM) along with the number when referring to a roadway.
- When in use, the bottom of a stationary PCMS message panel should be a minimum 7 feet above the roadway, where possible.
- The message term "WEEKEND" should be used only if the work is to start on Saturday morning and end by Sunday evening at midnight. Actual days and hours of work should be displayed on the PCMS if work is to begin on Friday evening and/or continue into Monday morning.
- The Engineer/Inspector may select one of two options which are available for displaying a two-phase message on a PCMS. Each phase may be displayed for either four seconds each or for three seconds each.
- Do not "flash" messages or words included in a message. The message should be steady burn or continuous while displayed.
- Do not present redundant information on a two-phase message; i.e., keeping two lines of the message the same and changing the third line.
- Do not use the word "Danger" in message.
- Do not display the message "LANES SHIFT LEFT" or "LANES SHIFT RIGHT" on a PCMS. Drivers do not understand the message.
- Do not display messages that scroll horizontally or vertically across the face of the sign.
- The following table lists abbreviated words and two-word phrases that are acceptable for use on a PCMS. Both words in a phrase must be displayed together. Words or phrases not on this list should not be abbreviated, unless shown in the TMUTCD.
- PCMS character height should be at least 18 inches for trailer mounted units. They should be visible from at least 1/2 (.5) mile and the text should be legible from at least 600 feet at night and 800 feet in daylight. Truck mounted units must have a character height of 10 inches and must be legible from at least 400 feet.
- Each line of text should be centered on the message board rather than left or right justified.
- If disabled, the PCMS should default to an illegible display that will not alarm motorists and will only be used to alert workers that the PCMS has malfunctioned. A pattern such as a series of horizontal solid bars is appropriate.

WORD OR PHRASE	ABBREVIATION	WORD OR PHRASE	ABBREVIATION
Access Road	ACCS RD	Major	MAJ
Alternate	ALT	Miles	MI
Avenue	AVE	Miles Per Hour	MPH
Best Route	BEST RTE	Minor	MNR
Boulevard	BLVD	Monday	MON
Bridge	BRDG	Normal	NORM
Cannot	CANT	North	N
Center	CTR	Northbound	(route) N
Construction	CONST AHD	Parking	PKING
Ahead		Road	RD
CROSSING	XING	Right Lane	RT LN
Detour Route	DETOUR RTE	Saturday	SAT
Do Not	DONT	Service Road	SERV RD
East	E	Shoulder	SHLDR
Eastbound	(route) E	Slippery	SLIP
Emergency	EMER	South	S
Emergency Vehicle	EMER VEH	Southbound	(route) S
Entrance, Enter	ENT	Speed	SPD
Express Lane	EXP LN	Street	ST
Expressway	EXPWY	Sunday	SUN
XXXX Feet	XXXX FT	Telephone	PHONE
Fog Ahead	FOG AHD	Temporary	TEMP
Freeway	FRWY, FWY	Thursday	THURS
Freeway Blocked	FWY BLKD	To Downtown	TO DWNTN
Friday	FRI	Traffic	TRAF
Hazardous Driving	HAZ DRIVING	Travelers	TRVLRS
Hazardous Material	HAZMAT	Tuesday	TUES
High-Occupancy	HOV	Time Minutes	TIME MIN
Vehicle	HWY	Upper Level	UPR LEVEL
Highway		Vehicles (s)	VEH, VEHs
Hour(s)	HR, HRS	Warning	WARN
Information	INFO	Wednesday	WED
It Is	ITS	Weight Limit	WT LIMIT
Junction	JCT	Left	LFT
Left	LFT	Left Lane	LFT LN
Lane Closed	LN CLOSED	Lane Closed	LN CLOSED
Lower Level	LWR LEVEL	West	W
Maintenance	MAINT	Westbound	(route) W
Roadway		Wet Pavement	WET PVMT
designation # IH-number, US-number, SH-number, FM-number		Will Not	WONT

RECOMMENDED PHASES AND FORMATS FOR PCMS MESSAGES DURING ROADWORK ACTIVITIES

(The Engineer may approve other messages not specifically covered here.)

Phase 1: Condition Lists

Road/Lane/Ramp Closure List

FREEWAY CLOSED X MILE	FRONTAGE ROAD CLOSED	ROADWORK XXX FT	ROAD REPAIRS XXXX FT
ROAD CLOSED AT SH XXX	SHOULDER CLOSED XXX FT	FLAGGER XXXX FT	LANE NARROWS XXXX FT
ROAD CLSD AT FM XXXX	RIGHT LN CLOSED XXX FT	RIGHT LN NARROWS XXXX FT	TWO-WAY TRAFFIC XX MILE
RIGHT X LANES CLOSED	RIGHT X LANES OPEN	MERGING TRAFFIC XXXX FT	CONST TRAFFIC XXX FT
CENTER LANE CLOSED	DAYTIME LANE CLOSURES	LOOSE GRAVEL XXXX FT	UNEVEN LANES XXXX FT
NIGHT LANE CLOSURES	I-XX SOUTH EXIT CLOSED	DETOUR X MILE	ROUGH ROAD XXXX FT
VARIOUS LANES CLOSED	EXIT XXX CLOSED	ROADWORK PAST SH XXXX	ROADWORK NEXT FRI-SUN
EXIT CLOSED	RIGHT LN TO BE CLOSED	BUMP XXXX FT	US XXX EXIT X MILES
MALL DRIVEWAY CLOSED	X LANES CLOSED TUE - FRI	TRAFFIC SIGNAL XXXX FT	LANES SHIFT *
XXXXXXXXX BLVD CLOSED			

Other Condition List

MERGE RIGHT	FORM X LINES RIGHT	AT FM XXXX	SPEED LIMIT XX MPH
DETOUR NEXT X EXITS	USE XXXXX RD EXIT	BEFORE RAILROAD CROSSING	MAXIMUM SPEED XX MPH
USE EXIT XXX	USE EXIT I-XX NORTH	NEXT X MILES	MINIMUM SPEED XX MPH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N	PAST US XXX EXIT	ADVISORY SPEED XX MPH
TRUCKS USE US XXX N	WATCH FOR TRUCKS	XXXXXX TO XXXXXX	RIGHT LANE EXIT
WATCH FOR TRUCKS	EXPECT DELAYS	US XXX TO FM XXXX	USE CAUTION
EXPECT DELAYS	PREPARE TO STOP	REDUCE SPEED XXX FT	DRIVE SAFELY
REDUCE SPEED XXX FT	END SHOULDER USE	USE OTHER ROUTES	DRIVE WITH CARE
USE OTHER ROUTES	WATCH FOR WORKERS	STAY IN LANE *	

Phase 2: Possible Component Lists

Action to Take/Effect on Travel List	Location List	Warning List	** Advance Notice List
MERGE RIGHT	FORM X LINES RIGHT	AT FM XXXX	SPEED LIMIT XX MPH
DETOUR NEXT X EXITS	USE XXXXX RD EXIT	BEFORE RAILROAD CROSSING	MAXIMUM SPEED XX MPH
USE EXIT XXX	USE EXIT I-XX NORTH	NEXT X MILES	MINIMUM SPEED XX MPH
STAY ON US XXX SOUTH	USE I-XX E TO I-XX N	PAST US XXX EXIT	ADVISORY SPEED XX MPH
TRUCKS USE US XXX N	WATCH FOR TRUCKS	XXXXXX TO XXXXXX	RIGHT LANE EXIT
WATCH FOR TRUCKS	EXPECT DELAYS	US XXX TO FM XXXX	USE CAUTION
EXPECT DELAYS	PREPARE TO STOP	REDUCE SPEED XXX FT	DRIVE SAFELY
REDUCE SPEED XXX FT	END SHOULDER USE	USE OTHER ROUTES	DRIVE WITH CARE
USE OTHER ROUTES	WATCH FOR WORKERS	STAY IN LANE *	
STAY IN LANE *			

* LANES SHIFT in Phase 1 must be used with STAY IN LANE in Phase 2.

** See Application Guidelines Note 6.

APPLICATION GUIDELINES

- Only 1 or 2 phases are to be used on a PCMS.
- The 1st phase (or both) should be selected from the "Road/Lane/Ramp Closure List" and the "Other Condition List".
- A 2nd phase can be selected from the "Action to Take/Effect on Travel, Location, General Warning, or Advance Notice Phase Lists".
- A Location Phase is necessary only if a distance or location is not included in the first phase selected.
- If two PCMS are used in sequence, they must be separated by a minimum of 1000 ft. Each PCMS shall be limited to two phases, and should be understandable by themselves.
- For advance notice, when the current date is within seven days of the actual work date, calendar days should be replaced with days of the week. Advance notification should typically be for no more than one week prior to the work.

WORDING ALTERNATIVES

- The words RIGHT, LEFT and ALL can be interchanged as appropriate.
- Roadway designations IH, US, SH, FM and LP can be interchanged as appropriate.
- EAST, WEST, NORTH and SOUTH (or abbreviations E, W, N and S) can be interchanged as appropriate.
- Highway names and numbers replaced as appropriate.
- ROAD, HIGHWAY and FREEWAY can be interchanged as needed.
- AHEAD may be used instead of distances if necessary.
- FT and MI, MILE and MILES interchanged as appropriate.
- AT, BEFORE and PAST interchanged as needed.
- Distances or AHEAD can be eliminated from the message if a location phase is used.

PCMS SIGNS WITHIN THE R.O.W. SHALL BE BEHIND GUARDRAIL OR CONCRETE BARRIER OR SHALL HAVE A MINIMUM OF FOUR (4) PLASTIC DRUMS PLACED PERPENDICULAR TO TRAFFIC ON THE UPSTREAM SIDE OF THE PCMS, WHEN EXPOSED TO ONE DIRECTION OF TRAFFIC. WHEN EXPOSED TO TWO WAY TRAFFIC, THE FOUR DRUMS SHOULD BE PLACED WITH ONE DRUM AT EACH OF THE FOUR CORNERS OF THE UNIT.

FULL MATRIX PCMS SIGNS

- When Full Matrix PCMS signs are used, the character height and legibility/visibility requirements shall be maintained as listed in Note 15 under "PORTABLE CHANGEABLE MESSAGE SIGNS" above.
- When symbol signs, such as the "Flagger Symbol" (CW20-7) are represented graphically on the Full Matrix PCMS sign and, with the approval of the Engineer, it shall maintain the legibility/visibility requirement listed above.
- When symbol signs are represented graphically on the Full Matrix PCMS, they shall only supplement the use of the static sign represented, and shall not substitute for, or replace that sign.
- A full matrix PCMS may be used to simulate a flashing arrow board provided it meets the visibility, flash rate and dimming requirements on BC(7), for the same size arrow.

BARRICADE AND CONSTRUCTION PORTABLE CHANGEABLE MESSAGE SIGN (PCMS)

BC (6) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT November 2002	REVISIONS	-	-	-
				ABBOT RD
9-07 8-14				
7-13 5-21				
		COUNTY	SHEET NO.	
				BEXAR

GENERAL NOTES

- For long term stationary work zones on freeways, drums shall be used as the primary channelizing device.
- For intermediate term stationary work zones on freeways, drums should be used as the primary channelizing device but may be replaced in tangent sections by vertical panels, or 42" two-piece cones. In tangent sections, one-piece cones may be used with the approval of the Engineer but only if personnel are present on the project at all times to maintain the cones in proper position and location.
- For short term stationary work zones on freeways, drums are the preferred channelizing device but may be replaced in tapers, transitions and tangent sections by vertical panels, two-piece cones or one-piece cones as approved by the Engineer.
- Drums and all related items shall comply with the requirements of the current version of the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
- Drums, bases, and related materials shall exhibit good workmanship and shall be free from objectionable marks or defects that would adversely affect their appearance or serviceability.
- The Contractor shall have a maximum of 24 hours to replace any plastic drums identified for replacement by the Engineer/Inspector. The replacement device must be an approved device.

GENERAL DESIGN REQUIREMENTS

Pre-qualified plastic drums shall meet the following requirements:




- Plastic drums shall be a two-piece design; the "body" of the drum shall be the top portion and the "base" shall be the bottom.
- The body and base shall lock together in such a manner that the body separates from the base when impacted by a vehicle traveling at a speed of 20 MPH or greater but prevents accidental separation due to normal handling and/or air turbulence created by passing vehicles.
- Plastic drums shall be constructed of lightweight flexible, and deformable materials. The Contractor shall NOT use metal drums or single piece plastic drums as channelization devices or sign supports.
- Drums shall present a profile that is a minimum of 18 inches in width at the 36 inch height when viewed from any direction. The height of drum unit (body installed on base) shall be a minimum of 36 inches and a maximum of 42 inches.
- The top of the drum shall have a built-in handle for easy pickup and shall be designed to drain water and not collect debris. The handle shall have a minimum of two widely spaced 9/16 inch diameter holes to allow attachment of a warning light, warning reflector unit or approved compliant sign.
- The exterior of the drum body shall have a minimum of four alternating orange and white retroreflective circumferential stripes not less than 4 inches nor greater than 8 inches in width. Any non-reflective space between any two adjacent stripes shall not exceed 2 inches in width.
- Bases shall have a maximum width of 36 inches, a maximum height of 4 inches, and a minimum of two footholds of sufficient size to allow base to be held down while separating the drum body from the base.
- Plastic drums shall be constructed of ultra-violet stabilized, orange, high-density polyethylene (HDPE) or other approved material.
- Drum body shall have a maximum unballasted weight of 11 lbs.
- Drum and base shall be marked with manufacturer's name and model number.

RETROREFLECTIVE SHEETING

- The stripes used on drums shall be constructed of sheeting meeting the color and retroreflectivity requirements of Departmental Materials Specification DMS-8300, "Sign Face Materials." Type A or Type B reflective sheeting shall be supplied unless otherwise specified in the plans.
- The sheeting shall be suitable for use on and shall adhere to the drum surface such that, upon vehicular impact, the sheeting shall remain adhered in-place and exhibit no delaminating, cracking, or loss of retroreflectivity other than that loss due to abrasion of the sheeting surface.


BALLAST

- Unballasted bases shall be large enough to hold up to 50 lbs. of sand. This base, when filled with the ballast material, should weigh between 35 lbs (minimum) and 50 lbs (maximum). The ballast may be sand in one to three sandbags separate from the base, sand in a sand-filled plastic base, or other ballasting devices as approved by the Engineer. Stacking of sandbags will be allowed, however height of sandbags above pavement surface may not exceed 12 inches.
- Bases with built-in ballast shall weigh between 40 lbs. and 50 lbs. Built-in ballast can be constructed of an integral crumb rubber base or a solid rubber base.
- Recycled truck tire sidewalls may be used for ballast on drums approved for this type of ballast on the CWZTCD list.
- The ballast shall not be heavy objects, water, or any material that would become hazardous to motorists, pedestrians, or workers when the drum is struck by a vehicle.
- When used in regions susceptible to freezing, drums shall have drainage holes in the bottoms so that water will not collect and freeze becoming a hazard when struck by a vehicle.
- Ballast shall not be placed on top of drums.
- Adhesives may be used to secure base of drums to pavement.




DETECTABLE PEDESTRIAN BARRICADES

- When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Refer to WZ(BTS-2) for Pedestrian Control requirements for Sidewalk Diversions, Sidewalk Detours and Crosswalk Closures.
- Where pedestrians with visual disabilities normally use the closed sidewalk, a Detectable Pedestrian Barricade shall be placed across the full width of the closed sidewalk instead of a Type 3 Barricade.
- Detectable pedestrian barricades similar to the one pictured above, longitudinal channelizing devices, some concrete barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path.
- Tape, rope, or plastic chain strung between devices are not detectable, do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" and should not be used as a control for pedestrian movements.
- Warning lights shall not be attached to detectable pedestrian barricades.
- Detectable pedestrian barricades should use 8" nominal barricade rails as shown on BC(10) provided that the top rail provides a smooth continuous rail suitable for hand trailing with no splinters, burrs, or sharp edges.



18" x 24" Sign
(Maximum Sign Dimension)
Chevron CW1-8, Opposing Traffic Lane
Divider, Driveway sign D70a, Keep Right
R4 series or other signs as approved
by Engineer



12" x 24" Vertical Panel
mount with diagonals
sloping down towards
travel way

Plywood, Aluminum or Metal sign
substrates shall NOT be used on
plastic drums

SIGNS, CHEVRONS, AND VERTICAL PANELS MOUNTED ON PLASTIC DRUMS

- Signs used on plastic drums shall be manufactured using substrates listed on the CWZTCD.
- Chevrons and other work zone signs with an orange background shall be manufactured with Type B_{FL} or Type C_{FL} Orange sheeting meeting the color and retroreflectivity requirements of DMS-8300, "Sign Face Material," unless otherwise specified in the plans.
- Vertical Panels shall be manufactured with orange and white sheeting meeting the requirements of DMS-8300 Type A or Type B. Diagonal stripes on Vertical Panels shall slope down toward the intended traveled lane.
- Other sign messages (text or symbolic) may be used as approved by the Engineer. Sign dimensions shall not exceed 18 inches in width or 24 inches in height, except for the R9 series signs discussed in note 8 below.
- Signs shall be installed using a 1/2 inch bolt (nominal) and nut, two washers, and one locking washer for each connection.
- Mounting bolts and nuts shall be fully engaged and adequately torqued. Bolts should not extend more than 1/2 inch beyond nuts.
- Chevrons may be placed on drums on the outside of curves, on merging tapers or on shifting tapers. When used in these locations, they may be placed on every drum or spaced not more than on every third drum. A minimum of three (3) should be used at each location called for in the plans.
- R9-9, R9-10, R9-11 and R9-11a Sidewalk Closed signs which are 24 inches wide may be mounted on plastic drums, with approval of the Engineer.

SHEET 8 OF 12

 Texas Department of Transportation		Traffic Safety Division Standard			
		FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT
© TxDOT November 2002 REVISIONS 4-03 8-14 9-07 5-21 7-13		CONT	SECT	JOB	HIGHWAY
		-	-	-	ABBOT RD
		DIST	COUNTY	SHEET NO.	
		-	BEXAR	28	

BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES

BC (8) - 21

FILE: bc-21.dgn

DN: TxDOT

CK: TxDOT

DW: TxDOT

CK: TxDOT

© TxDOT November 2002

REVISIONS

4-03 8-14

9-07 5-21

7-13

CONT

SECT

JOB

HIGHWAY

DIST

COUNTY

SHEET NO.

BEXAR


28

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

FILE: bc-21.dgn

DATE: 1/5/2026 8:28:35 AM


FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates\Design\Plan Set\02 TCP Standards\bc-21.dgn



FIXED
(Rigid or self-righting)

1. Vertical Panels (VP's) are normally used to channelize traffic or divide opposing lanes of traffic.
2. VP's may be used in daytime or nighttime situations. They may be used at the edge of shoulder drop-offs and other areas such as lane transitions where positive daytime and nighttime delineation is required. The Engineer/Inspector shall refer to the Roadway Design Manual for additional requirements on the use VP's for drop-offs.
3. VP's should be mounted back to back if used at the edge of cuts adjacent to two-way two lane roadways. Stripes are to be reflective orange and reflective white and should always slope downward toward the travel lane.
4. VP's used on expressways and freeways or other high speed roadways, may have more than 270 square inches of retroreflective area facing traffic.
5. Self-righting supports are available with portable base. See "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
6. Sheeting for the VP's shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300, unless noted otherwise.
7. Where the height of reflective material on the vertical panel is 36 inches or greater, a panel stripe of 6 inches shall be used.



VERTICAL PANELS (VPs)



PORTABLE

1. Opposing Traffic Lane Dividers (OTLD) are delineation devices designed to convert a normal one-way roadway section to two-way operation. OTLD's are used on temporary centerlines. The upward and downward arrows on the sign's face indicate the direction of traffic on either side of the divider. The base is secured to the pavement with an adhesive or rubber weight to minimize movement caused by a vehicle impact or wind gust.
2. The OTLD may be used in combination with 42" cones or VPs.
3. Spacing between the OTLD shall not exceed 500 feet. 42" cones or VPs placed between the OTLD's should not exceed 100 foot spacing.
4. The OTLD shall be orange with a black non-reflective legend. Sheeting for the OTLD shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.

OPPOSING TRAFFIC LANE DIVIDERS (OTLD)




DRIVEABLE

1. The chevron shall be a vertical rectangle with a minimum size of 12 by 18 inches.
2. Chevrons are intended to give notice of a sharp change of alignment with the direction of travel and provide additional emphasis and guidance for vehicle operators with regard to changes in horizontal alignment of the roadway.
3. Chevrons, when used, shall be erected on the outside of a sharp curve or turn, or on the far side of an intersection. They shall be in line with and at right angles to approaching traffic. Spacing should be such that the motorist always has three in view, until the change in alignment eliminates its need.
4. To be effective, the chevron should be visible for at least 500 feet.
5. Chevrons shall be orange with a black non-reflective legend. Sheeting for the chevron shall be retroreflective Type B_{FL} or Type C_{FL} conforming to Departmental Material Specification DMS-8300, unless noted otherwise. The legend shall meet the requirements of DMS-8300.
6. For Long Term Stationary use on tapers or transitions on freeways and divided highways, self-righting chevrons may be used to supplement plastic drums but not to replace plastic drums.

CHEVRONS

GENERAL NOTES

1. Work Zone channelizing devices illustrated on this sheet may be installed in close proximity to traffic and are suitable for use on high or low speed roadways. The Engineer/Inspector shall ensure that spacing and placement is uniform and in accordance with the "Texas Manual of Uniform Traffic Control Devices" (TMUTCD).
2. Channelizing devices shown on this sheet may have a driveable, fixed or portable base. The requirement for self-righting channelizing devices must be specified in the General Notes or other plan sheets.
3. Channelizing devices on self-righting supports should be used in work zone areas where channelizing devices are frequently impacted by errant vehicles or vehicle related wind gusts making alignment of the channelizing devices difficult to maintain. Locations of these devices shall be detailed elsewhere in the plans. These devices shall conform to the TMUTCD and the "Compliant Work Zone Traffic Control Devices List" (CWZTCD).
4. The Contractor shall maintain devices in a clean condition and replace damaged, nonreflective, faded, or broken devices and bases as required by the Engineer/Inspector. The Contractor shall be required to maintain proper device spacing and alignment.
5. Portable bases shall be fabricated from virgin and/or recycled rubber. The portable bases shall weigh a minimum of 30 lbs.
6. Pavement surfaces shall be prepared in a manner that ensures proper bonding between the adhesives, the fixed mount bases and the pavement surface. Adhesives shall be prepared and applied according to the manufacturer's recommendations.
7. The installation and removal of channelizing devices shall not cause detrimental effects to the final pavement surfaces, including pavement surface discoloration or surface integrity. Driveable bases shall not be permitted on final pavement surfaces. The Engineer/Inspector shall approve all application and removal procedures of fixed bases.



LONGITUDINAL CHANNELIZING DEVICES (LCD)

1. LCDs are crashworthy, lightweight, deformable devices that are highly visible, have good target value and can be connected together. They are not designed to contain or redirect a vehicle on impact.
2. LCDs may be used instead of a line of cones or drums.
3. LCDs shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
4. LCDs should not be used to provide positive protection for obstacles, pedestrians or workers.
5. LCDs shall be supplemented with retroreflective delineation as required for temporary barriers on BC(7) when placed roughly parallel to the travel lanes.
6. LCDs used as barricades placed perpendicular to traffic should have at least one row of reflective sheeting meeting the requirements for barricade rails as shown on BC(10). Place reflective sheeting near the top of the LCD along the full length of the device.

WATER BALLASTED SYSTEMS USED AS BARRIERS

1. Water ballasted systems used as barriers shall not be used solely to channelize road users, but also to protect the work space per the appropriate Manual for Assessing Safety Hardware (MASH) crashworthiness requirements based on roadway speed and barrier application.
2. Water ballasted systems used to channelize vehicular traffic shall be supplemented with retroreflective delineation or channelizing devices to improve daytime/nighttime visibility. They may also be supplemented with pavement markings.
3. Water ballasted systems used as barriers shall be placed in accordance to application and installation requirements specific to the device, and used only when shown on the CWZTCD list.
4. Water ballasted systems used as barriers should not be used for a merging taper except in low speed (less than 45 MPH) urban areas. When used on a taper in a low speed urban area, the taper shall be delineated and the taper length should be designed to optimize road user operations considering the available geometric conditions.
5. When water ballasted systems used as barriers have blunt ends exposed to traffic, they should be attenuated as per manufacturer recommendations or flared to a point outside the clear zone.

If used to channelize pedestrians, longitudinal channelizing devices or water ballasted systems must have a continuous detectable bottom for users of long canes and the top of the unit shall not be less than 32 inches in height.

HOLLOW OR WATER BALLASTED SYSTEMS USED AS LONGITUDINAL CHANNELIZING DEVICES OR BARRIERS

Posted Speed	Formula	Minimum Desirable Taper Lengths			Suggested Maximum Spacing of Channelizing Devices	
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent
30	WS^2	150'	165'	180'	30'	60'
35	$L = \frac{WS^2}{60}$	205'	225'	245'	35'	70'
40		265'	295'	320'	40'	80'
45		450'	495'	540'	45'	90'
50		500'	550'	600'	50'	100'
55		550'	605'	660'	55'	110'
60		600'	660'	720'	60'	120'
65		650'	715'	780'	65'	130'
70		700'	770'	840'	70'	140'
75		750'	825'	900'	75'	150'
80		800'	880'	960'	80'	160'

** Taper lengths have been rounded off.
L=Length of Taper (FT.) W=Width of Offset (FT.)
S=Posted Speed (MPH)

SUGGESTED MAXIMUM SPACING OF CHANNELIZING DEVICES AND MINIMUM DESIRABLE TAPER LENGTHS

SHEET 9 OF 12



BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES


BC (9) - 21

FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
©	TxDOT	November 2002	CONT	SECT	JOB	HIGHWAY			
			-	-	-				
9-07	8-14								
7-13	5-21								
			DIST	COUNTY	SHEET NO.				
			-	BEXAR	29				


TYPE 3 BARRICADES

- Refer to the Compliant Work Zone Traffic Control Devices List (CWZTCD) for details of the Type 3 Barricades and a list of all materials used in the construction of Type 3 Barricades.
- Type 3 Barricades shall be used at each end of construction projects closed to all traffic.
- Barricades extending across a roadway should have stripes that slope downward in the direction toward which traffic must turn in detouring. When both right and left turns are provided, the chevron striping may slope downward in both directions from the center of the barricade. Where no turns are provided at a closed road, striping should slope downward in both directions toward the center of roadway.
- Striping of rails, for the right side of the roadway, should slope downward to the left. For the left side of the roadway, striping should slope downward to the right.
- Identification markings may be shown only on the back of the barricade rails. The maximum height of letters and/or company logos used for identification shall be 1".
- Barricades shall not be placed parallel to traffic unless an adequate clear zone is provided.
- Warning lights shall NOT be installed on barricades.
- Where barricades require the use of weights to keep from turning over, the use of sandbags with dry, cohesionless sand is recommended. The sandbags will be tied shut to keep the sand from spilling and to maintain a constant weight. Sand bags shall not be stacked in a manner that covers any portion of a barricade rails reflective sheeting. Rock, concrete, iron, steel or other solid objects will NOT be permitted. Sandbags should weigh a minimum of 35 lbs and a maximum of 50 lbs. Sandbags shall be made of a durable material that tears upon vehicular impact. Rubber (such as tire inner tubes) shall not be used for sandbags. Sandbags shall only be placed along or upon the base supports of the device and shall not be suspended above ground level or hung with rope, wire, chains or other fasteners.
- Sheeting for barricades shall be retroreflective Type A or Type B conforming to Departmental Material Specification DMS-8300 unless otherwise noted.

Barricades shall NOT be used as a sign support.




TYPICAL STRIPING DETAIL FOR BARRICADE RAIL



TYPICAL PANEL DETAIL FOR SKID OR POST TYPE BARRICADES

Each roadway of a divided highway shall be barricaded in the same manner.


R11-2
ROAD CLOSED
NAME
ADDRESS
CITY
STATE
CONTRACTOR
G20-67
M4-10L
DETOUR




PERSPECTIVE VIEW

The three rails on Type 3 barricades shall be reflectorized orange and reflective white stripes on one side facing one-way traffic and both sides for two-way traffic.

Barricade striping should slant downward in the direction of detour.




PLAN VIEW



PERSPECTIVE VIEW

These drums are not required on one-way roadway



PLAN VIEW


CULVERT WIDENING OR OTHER ISOLATED WORK WITHIN THE PROJECT LIMITS

- Where positive redirection capability is provided, drums may be omitted.
- Plastic construction fencing may be used with drums for safety as required in the plans.
- Vertical Panels on flexible support may be substituted for drums when the shoulder width is less than 4 feet.
- When the shoulder width is greater than 12 feet, steady-burn lights may be omitted if drums are used.
- Drums must extend the length of the culvert widening.


LEGEND

	Plastic drum
	Plastic drum with steady burn light or yellow warning reflector
	Steady burn warning light or yellow warning reflector


CONES



Two-Piece cones



One-Piece cones



Tubular Marker

28" Cones shall have a minimum weight of 9 1/2 lbs.

42" 2-piece cones shall have a minimum weight of 30 lbs. including base.

- Traffic cones and tubular markers shall be predominantly orange, and meet the height and weight requirements shown above.
- One-piece cones have the body and base of the cone molded in one consolidated unit. Two-piece cones have a cone shaped body and a separate rubber base, or ballast, that is added to keep the device upright and in place.
- Two-piece cones may have a handle or loop extending up to 8" above the minimum height shown, in order to aid in retrieving the device.
- Cones or tubular markers shall have white or orange reflective bands as shown above. The reflective bands shall have a smooth, sealed outer surface and meet the requirements of Departmental Material Specification DMS-8300 Type A or Type B.
- 28" cones and tubular markers are generally suitable for short duration and short-term stationary work as defined on BC(4). These should not be used for intermediate-term or long-term stationary work unless personnel is on-site to maintain them in their proper upright position.
- 42" two-piece cones, vertical panels or drums are suitable for all work zone durations.
- Cones or tubular markers used on each project should be of the same size and shape.

SHEET 10 OF 12

	Texas Department of Transportation	Traffic Safety Division Standard
BARRICADE AND CONSTRUCTION CHANNELIZING DEVICES		
BC (10) - 21		
FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT
© TxDOT November 2002	CONT	SECT
REVISIONS	JOB	HIGHWAY
9-07 8-14	-	-
7-13 5-21	DIST	COUNTY
		SHEET NO.
		30
BEXAR		

Alternate
Min. 2 drums or 1 Type 3 barricade
On one-way roads downstream drums or barricade may be omitted here

Drums, vertical panels or 42" cones at 50' maximum spacing
Approx. 50'
STOCKPILE
Desirable stockpile location is outside clear zone.

Channelizing devices parallel to traffic should be used when stockpile is within 30' from travel lane.

TRAFFIC CONTROL FOR MATERIAL STOCKPILES

WORK ZONE PAVEMENT MARKINGS

GENERAL

1. The Contractor shall be responsible for maintaining work zone and existing pavement markings, in accordance with the standard specifications and special provisions, on all roadways open to traffic within the CSJ limits unless otherwise stated in the plans.
2. Color, patterns and dimensions shall be in conformance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD).
3. Additional supplemental pavement marking details may be found in the plans or specifications.
4. Pavement markings shall be installed in accordance with the TMUTCD and as shown on the plans.
5. When short term markings are required on the plans, short term markings shall conform with the TMUTCD, the plans and details as shown on the Standard Plan Sheet WZ(STPM).
6. When standard pavement markings are not in place and the roadway is opened to traffic, DO NOT PASS signs shall be erected to mark the beginning of the sections where passing is prohibited and PASS WITH CARE signs at the beginning of sections where passing is permitted.
7. All work zone pavement markings shall be installed in accordance with Item 662, "Work Zone Pavement Markings."

RAISED PAVEMENT MARKERS

1. Raised pavement markers are to be placed according to the patterns on BC(12).
2. All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and Departmental Material Specification DMS-4200 or DMS-4300.

PREFABRICATED PAVEMENT MARKINGS

1. Removable prefabricated pavement markings shall meet the requirements of DMS-8241.
2. Non-removable prefabricated pavement markings (foil back) shall meet the requirements of DMS-8240.


MAINTAINING WORK ZONE PAVEMENT MARKINGS

1. The Contractor will be responsible for maintaining work zone pavement markings within the work limits.
2. Work zone pavement markings shall be inspected in accordance with the frequency and reporting requirements of work zone traffic control device inspections as required by Form 599.
3. The markings should provide a visible reference for a minimum distance of 300 feet during normal daylight hours and 160 feet when illuminated by automobile low-beam headlights at night, unless sight distance is restricted by roadway geometrics.
4. Markings failing to meet this criteria within the first 30 days after placement shall be replaced at the expense of the Contractor as per Specification Item 662.

REMOVAL OF PAVEMENT MARKINGS

1. Pavement markings that are no longer applicable, could create confusion or direct a motorist toward or into the closed portion of the roadway shall be removed or obliterated before the roadway is opened to traffic.
2. The above shall not apply to detours in place for less than three days, where flaggers and/or sufficient channelizing devices are used in lieu of markings to outline the detour route.
3. Pavement markings shall be removed to the fullest extent possible, so as not to leave a discernable marking. This shall be by any method approved by TxDOT Specification Item 677 for "Eliminating Existing Pavement Markings and Markers".
4. The removal of pavement markings may require resurfacing or seal coating portions of the roadway as described in Item 677.
5. Subject to the approval of the Engineer, any method that proves to be successful on a particular type pavement may be used.
6. Blast cleaning may be used but will not be required unless specifically shown in the plans.
7. Over-painting of the markings SHALL NOT BE permitted.
8. Removal of raised pavement markers shall be as directed by the Engineer.
9. Removal of existing pavement markings and markers will be paid for directly in accordance with Item 677, "ELIMINATING EXISTING PAVEMENT MARKINGS AND MARKERS," unless otherwise stated in the plans.
10. Black-out marking tape may be used to cover conflicting existing markings for periods less than two weeks when approved by the Engineer.

Temporary Flexible-Reflective Roadway Marker Tabs



Height of sheeting
is usually more than
1/4" and less than 1".

STAPLES OR NAILS SHALL NOT BE USED TO SECURE TEMPORARY FLEXIBLE-REFLECTIVE ROADWAY MARKER TABS TO THE PAVEMENT SURFACE

1. Temporary flexible-reflective roadway marker tabs used as guidemarks shall meet the requirements of DMS-8242.
2. Tabs detailed on this sheet are to be inspected and accepted by the Engineer or designated representative. Sampling and testing is not normally required, however at the option of the Engineer, either "A" or "B" below may be imposed to assure quality before placement on the roadway.
 - A. Select five (5) or more tabs at random from each lot or shipment and submit to the Construction Division, Materials and Pavement Section to determine specification compliance.
 - B. Select five (5) tabs and perform the following test. Affix five (5) tabs at 24 inch intervals on an asphaltic pavement in a straight line. Using a medium size passenger vehicle or pickup, run over the markers with the front and rear tires at a speed of 35 to 40 miles per hour, four (4) times in each direction. No more than one (1) out of the five (5) reflective surfaces shall be lost or displaced as a result of this test.
3. Small design variances may be noted between tab manufacturers.
4. See Standard Sheet WZ(STPM) for tab placement on new pavements. See Standard Sheet TCP(7-1) for tab placement on seal coat work.

RAISED PAVEMENT MARKERS USED AS GUIDEMARKS

1. Raised pavement markers used as guidemarks shall be from the approved product list, and meet the requirements of DMS-4200.
2. All temporary construction raised pavement markers provided on a project shall be of the same manufacturer.
3. Adhesive for guidemarks shall be bituminous material hot applied or butyl rubber pad for all surfaces, or thermoplastic for concrete surfaces.

Guidemarks shall be designated as:

YELLOW - (two amber reflective surfaces with yellow body).
WHITE - (one silver reflective surface with white body).

DEPARTMENTAL MATERIAL SPECIFICATIONS

PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
TRAFFIC BUTTONS	DMS-4300
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240
TEMPORARY REMOVABLE, PREFABRICATED PAVEMENT MARKINGS	DMS-8241
TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS	DMS-8242

A list of prequalified reflective raised pavement markers, non-reflective traffic buttons, roadway marker tabs and other pavement markings can be found at the Material Producer List web address shown on BC(1).

SHEET 11 OF 12




BARRICADE AND CONSTRUCTION PAVEMENT MARKINGS

BC (11) - 21


FILE:	bc-21.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	February 1998	CONT	SECT	JOB		HIGHWAY			
REVISIONS		-	-	-					
2-98	9-07 5-21								
1-02	7-13	DIST	COUNTY						
11-02	8-14	-	BEXAR						

105


PAVEMENT MARKING PATTERNS



REFLECTORIZED PAVEMENT MARKINGS - PATTERN A




RAISED PAVEMENT MARKERS - PATTERN A



REFLECTORIZED PAVEMENT MARKINGS - PATTERN B


Pattern A is the TxDOT Standard, however Pattern B may be used if approved by the Engineer. Prefabricated markings may be substituted for reflectorized pavement markings.

CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO-LANE, TWO-WAY HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectorized pavement markings.



RAISED PAVEMENT MARKERS




REFLECTORIZED PAVEMENT MARKINGS

Prefabricated markings may be substituted for reflectorized pavement markings.


Prefabricated markings may be substituted for reflectorized pavement markings.

LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



REFLECTORIZED PAVEMENT MARKINGS











Prefabricated markings may be substituted for reflectorized pavement markings.




RAISED PAVEMENT MARKERS

TWO-WAY LEFT TURN LANE

STANDARD WORK ZONE PAVEMENT MARKINGS DETAILS



Raised pavement markers used as standard pavement markings shall be from the approved products list and meet the requirements of Item 672 "RAISED PAVEMENT MARKERS."






BARRICADE AND CONSTRUCTION PAVEMENT MARKING PATTERNS

BC (12) - 21

FILE: bc-21.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT February 1998	CONT	SECT	JOB	HIGHWAY
1-97 9-07 5-21	-	-	-	ABBOT RD
2-98 7-13	DIST	COUNTY	SHEET NO.	
11-02 8-14	-	BEXAR	32	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any portion of this standard to any other language. TxDOT is not responsible for incorrect results or damages resulting from its use.

DATE: 1/5/2026 8:28:37 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates_FM_1346\4 - Design Plan Set\02-TECHNICAL\4-CONVENTIONAL ROAD WORK\TCP (1-1).dgn



LEGEND	
Type 3 Barricade	Channelizing Devices
Heavy Work Vehicle	Truck Mounted Attenuator (TMA)
Trailer Mounted Flashing Arrow Board	Portable Changeable Message Sign (PCMS)
Sign	Traffic Flow
Flag	Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30		150'	165'	180'	30'	60'	120'	90'
35	$L = \frac{WS^2}{60}$	205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45		450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only

** Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

GENERAL NOTES

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- Inactive work vehicles or other equipment should be parked near the right-of-way line and not parked on the paved shoulder.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.
- See TCP(5-1) for shoulder work on divided highways, expressways and freeways.
- CW21-5 "SHOULDER WORK" signs may be used in place of CW20-1D "ROAD WORK AHEAD" signs for shoulder work on conventional roadways.

Texas Department of Transportation  Traffic Operations Division Standard




TRAFFIC CONTROL PLAN CONVENTIONAL ROAD SHOULDER WORK

TCP (1-1) - 18

FILE: tcp1-1-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
2-94 4-98	-	-	-	ABBOT RD
8-95 2-12	DIST	COUNTY	SHEET NO.	
1-97 2-18	-	BEXAR	33	

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any standard or practice to another standard or practice. TxDOT is not responsible for incorrect results or damages resulting from its use.

DATE: 1/5/2026 8:28:38 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates_FM_1346\4 - Design Plan
P:\DESIGN_PROJECTS\Martinez Creek Estates_FM_1346\4 - Design Plan



LEGEND	
Type 3 Barricade	Channelizing Devices
Heavy Work Vehicle	Truck Mounted Attenuator (TMA)
Trailer Mounted Flashing Arrow Board	Portable Changeable Message Sign (PCMS)
Sign	Traffic Flow
Flag	Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths *			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "X" Distance	Suggested Longitudinal Buffer Space "B" Distance	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30		150'	165'	180'	30'	60'	120'	90'	200'
35	$L = \frac{WS^2}{60}$	205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45		450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70		700'	770'	840'	70'	140'	800'	475'	730'
75		750'	825'	900'	75'	150'	900'	540'	820'

* Conventional Roads Only

** Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
	✓	✓		

GENERAL NOTES

- Flags attached to signs where shown are REQUIRED.
- All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
- The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4D "ONE LANE ROAD AHEAD" sign, but proper sign spacing shall be maintained.
- Sign spacing may be increased or an additional CW20-1D "ROAD WORK AHEAD" sign may be used if advance warning ahead of the flagger or R1-2 "YIELD" sign is less than 1500 feet.
- A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
- Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect wider work spaces.

TCP (1-2a)

- R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work spaces should be no longer than one half city block. In rural areas on roadways with less than 2000 ADT, work spaces should be no longer than 400 feet.
- R1-2 "YIELD" sign with R1-2aP "TO ONCOMING TRAFFIC" plaque shall be placed on a support at a 7 foot minimum mounting height.

TCP (1-2b)

- Flaggers should use two-way radios or other methods of communication to control traffic.
- Length of work space should be based on the ability of flaggers to communicate.
- If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain adequate stopping sight distance to the flagger and a queue of stopped vehicles (see table above).
- Channelizing devices on the center-line may be omitted when a pilot car is leading traffic and approved by the Engineer.
- Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.



Traffic Operations Division Standard

TRAFFIC CONTROL PLAN ONE-LANE TWO-WAY TRAFFIC CONTROL

TCP (1-2)-18



FILE: tcp1-2-18.dgn	DN:	CK:	DW:	CK:
© TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
4-90 4-98	-	-	-	ABBOT RD
2-94 2-12	DIST	COUNTY	SHEET NO.	
1-97 2-18	-	BEXAR	34	

DISCLAIMER. The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of standards established by other organizations. TxDOT does not assume responsibility for damage to persons or property resulting from the use of this standard.

DISCLAIMER:

The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TXDOT for any purpose whatsoever. TXDOT assumes no responsibility for incorrect results or damages resulting from its use.

The use
kind is made



LEGEND								
 Type 3 Barricade						Channelizing Devices		
 Heavy Work Vehicle					Truck Mounted Attenuator (TMA)			
 Trailer Mounted Flashing Arrow Board					Raised Pavement Markers Ty II-AA			
 Sign					Traffic Flow			
 Flag					Flagger			
Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent		
30	$L = \frac{WS^2}{60}$	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	$L = WS$	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60		600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

* Conventional Roads Only

* Taper lengths have been rounded off.

L=Length of Taper (FT) W=Width of Offset (FT) S=Posted Speed (MPH)

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

GENERAL NOTES

1. Flags attached to signs where shown, are REQUIRED.
2. All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
3. When work space will be in place less than three days existing pavement markings may remain in place. Channelizing devices shall be used to separate traffic.
4. Flagger control should NOT be used unless roadway conditions or heavy traffic volume require additional emphasis to safely control traffic. Flagger should be positioned at end of traffic queue.
5. The R4-1 "DO NOT PASS," R4-2 "PASS WITH CARE" and construction regulatory speed zone signs may be installed within CW20-1D "ROAD WORK AHEAD" signs. Proper spacing of signs shall be maintained.
6. Conflicting pavement marking shall be removed for long term projects.
7. A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted.
8. Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.

TCP (2-3a)



9. Conflicting pavement markings shall be removed for long-term projects. For shorter durations where traffic is directed over a yellow centerline, channelizing devices which separate two-way traffic should be spaced on tapers at 20' or 15' if posted speeds are 35 mph or slower, and for tangent sections, at 1/2(S) where S is the speed in mph. This tighter device spacing is intended for the area of the conflicting markings, not the entire work zone.



TRAFFIC CONTROL PLAN TRAFFIC SHIFTS ON TWO-LANE ROADS

TCP (2-3) -23

FILE:	tcp (2-3)-23, dgn	DN:	CK:	DW:	CK:
(C) TxDOT	April 2023	CONT	SECT	JOB	HIGHWAY
REVISIONS		-	-	-	ABBOT R
2-85	4-98	2-18			
8-95	3-03	4-23			
1-97	2-12				
		DIST	COUNTY		HEET
		-	BEXAR		35






LEGEND				
*	Trail Vehicle		ARROW BOARD DISPLAY	
**	Shadow Vehicle			
***	Work Vehicle			RIGHT Directional
	Heavy Work Vehicle			LEFT Directional
	Truck Mounted Attenuator (TMA)			Double Arrow
	Traffic Flow			CAUTION (Alternating Diamond or 4 Corner Flash)
TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
				

GENERAL NOTES

1. TRAIL, SHADOW, and LEAD vehicles shall be equipped with arrow boards as illustrated. When a LEAD vehicle is not used the WORK vehicle must be equipped with an arrow board. The Engineer will determine if the LEAD VEHICLE and/or TRAIL VEHICLE are required based on prevailing roadway conditions, traffic volume, and sight distance restrictions.
2. The use of amber high intensity rotating, flashing, oscillating, or strobe lights on vehicles are required. Blue high intensity rotating, flashing, oscillating or strobe lights when mounted on the driver's side of the vehicle may be operated simultaneously with the amber beacons or strobe lights.
3. The use of truck mounted attenuators (TMA) on the SHADOW VEHICLE and TRAIL VEHICLE are required.
4. Reflective sheeting on the rear of the TMA shall meet or exceed the reflectivity and color requirements of DEPARTMENTAL MATERIAL SPECIFICATION DMS 8300, Type A.
5. Flashing arrow boards shall be Type B or Type C as per the Barricade and Construction (BC) standards. The board shall be controlled from inside the vehicle.
6. Each vehicle shall have two-way radio communication capability.
7. When work convoys must change lanes, the TRAIL VEHICLE should change lanes first to shadow the other convoy vehicles.
8. Vehicle spacing between the TRAIL VEHICLE and the SHADOW VEHICLE will vary depending on sight distance restrictions. Motorists approaching the work convoy should be able to see the TRAIL VEHICLE in time to slow down and/or change lanes as they approach the TRAIL VEHICLE. Vehicle spacing between the WORK VEHICLE and SHADOW VEHICLE and vehicle spacing between WORK VEHICLE and LEAD VEHICLE may vary according to terrain, work activity and other factors.
9. "X VEHICLE CONVOY" (CW21-10cT) or "WORK CONVOY" (CW21-10aT) signs shall be used on TRAIL VEHICLES and SHADOW VEHICLES as shown. As an option 48" X 48" diamond shaped "WORK CONVOY" (CW21-10T) or "X VEHICLE CONVOY" (CW21-10bT) signs may be used where adequate mounting space exists. When used, the X VEHICLE CONVOY sign shall have the number of the convoy vehicles displayed on the sign in the number designation "X" location. The "X VEHICLE CONVOY" sign shall not be used on the SHADOW VEHICLE if a TRAIL VEHICLE is used.



10. On two-lane two-way roadways, the work and protection vehicles should pull over periodically to allow motor vehicle traffic to pass. If motorists are not allowed to pass the work convoy, a "DO NOT PASS" (R4-1) sign should be placed on the back of the rearmost protection vehicle.



TRAFFIC CONTROL PLAN MOBILE OPERATIONS UNDIVIDED HIGHWAYS

TCP (3-1) - 13

tcp3-1.dgn		DN: TxDOT	ck: TxDOT	dw: TxDOT	ck: TxDOT
OT	December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS		-	-	-	ABBOT RD
4-98 7-13	DIST	COUNTY		SHEET NO.	
	-	BEXAR		37	



Posted Speed *	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600'
65	700'
70	800'
75	900'

* Conventional Roads Only

TYPICAL USAGE				
MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY
			✓	✓

GENERAL NOTES

1. The traffic control devices detailed on this sheet will be furnished and erected as directed by the Engineer on sections of roadway where tabs must be placed prior to the surfacing operation which will cover or obliterate the existing pavement markings.
2. The devices shown on this sheet are to be used to supplement those required by the BC Standards or others required elsewhere in the plans.
3. Signs shall be erected as detailed on the BC Standards or the Compliant Work Zone Traffic Control Devices List (CWZTCD) on supports approved for Long-Term / Intermediate-Term Work Zone Sign Supports.
4. When surfacing operations take place on divided highways, freeways or expressways, the size of diamond shaped construction warning signs shall be 48" x 48".
5. Signs on divided highways, freeways and expressways will be placed on both right and left sides of the roadway based on roadway conditions as directed by the Engineer.

"DO NOT PASS" SIGN (R4-1) and NO-PASSING ZONES

- Prior to the beginning of construction, all currently striped no-passing zones shall be signed with the DO NOT PASS (R4-1) signs and PASS WITH CARE (R4-2) signs placed at the beginning and end of each zone for each direction of travel except as otherwise provided herein. Signs marking these individual no-passing zones need not be covered prior to construction if the signs supplement the existing pavement markings.
- At the discretion of the Engineer, in areas of numerous no-passing zones, several zones may be combined as a single zone. If passing is to be prohibited over one or more lengthy sections, a DO NOT PASS sign and a NEXT XX MILES (R20-1TP) plaque may be used at the beginning of such zones. The DO NOT PASS sign and the NEXT XX MILES plaque should be repeated every mile to the end of the no-passing zone. In areas where there is considerable distance between no-passing zones, the end of the no-passing zone may be signed with a PASS WITH CARE sign and a NEXT XX MILES plaque.
- Depending on traffic volumes and length of sections, it may be desirable to prohibit passing throughout the project to prevent damage to windshield and lights. The DO NOT PASS sign and NEXT XX MILES plaque should be used and repeated as often as necessary for this purpose. Where several existing zones are to be combined into one individual no-passing zone, the sign at the beginning of the zone should be covered until the surfacing operation has passed this location so as not to have the DO NOT PASS sign conflict with the existing pavement markings. Also, unless one day's operation completes the entire length of such combined zones, appropriate DO NOT PASS and PASS WITH CARE signs should be placed at the beginning and end of the no-passing zones where the surfacing operation has stopped for the day.
- R4-1 and R4-2 are to remain in place until standard pavement markings are installed.

"NO CENTER LINE" SIGN (CW8-12)

- Center line markings are yellow pavement markings that delineate the separation of travel lanes that have opposite directions of travel on a roadway. Divided highways do not typically have center line markings.
- At the time construction activity obliterates the existing center line markings (low volume roads may not have an existing centerline), a NO CENTER LINE (CW8-12) sign should be erected at the beginning of the work area, at approximately 2 mile intervals within the work area, beyond major intersections and other locations deemed necessary by the Engineer.
- The NO CENTER LINE signs are to remain in place until standard pavement markings are installed.

"LOOSE GRAVEL" SIGN (CW8-7)

- When construction begins, a LOOSE GRAVEL (CW8-7) sign should be erected at each end of the work area and repeated at intervals of approximately 2 miles in rural areas and closer in urban areas.
- The LOOSE GRAVEL signs are to remain in place until the condition no longer exists.

PAVEMENT MARKINGS

- Temporary markings for surfacing projects shall be temporary flexible-reflective roadway marker tabs unless otherwise approved by the Engineer. Tabs are to be installed to provide true alignment for striping crews or as directed by the Engineer. Tabs will be placed at the spacing indicated. Tabs should be applied to the pavement no more than two (2) days before the surfacing is applied. After the surfacing is rolled and swept, the cover over the reflective strip shall be removed.
- Tabs shall not be used to simulate edge lines.
- Tab placement for overlay/inlay operations shall be as shown on the WZ(STPM) standard sheet.

COORDINATION OF SIGN LOCATIONS

- The location of warning signs at the beginning and end of a work area are to be coordinated with other signing typically shown on the Barricade and Construction Standards for project limits to ensure adequate sign spacing.
- Where possible the ROAD WORK AHEAD (CW20-1D), LOOSE GRAVEL (CW8-7), and NO CENTER LINE (CW8-12) signs should be placed in the sequence shown following the OBEY WARNING SIGNS STATE LAW (R20-3T) and the TRAFFIC FINES DOUBLE (R20-5T) sign, and one "X" sign spacing prior to the CONTRACTOR (G20-6T) sign, typically located at or near the limits of surfacing. LOOSE GRAVEL and NO CENTER LINE signs will then be repeated as described above.




TRAFFIC CONTROL DETAILS FOR SURFACING OPERATIONS

TCP (7-1) - 13

FILE:	tcp7-1.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	March 1991	CONT	SECT	JOB		HIGHWAY			
		-	-	-					
4-92	4-98								
1-97	7-13	DIST	COUNTY						
		-	BEXAR						

WORK ZONE SHORT TERM PAVEMENT MARKINGS DETAILS




NOTES:

- Short term pavement markings may be prefabricated markings (stick down tape) or temporary flexible reflective roadway marker tabs unless otherwise specified elsewhere in plans.
- Short term pavement markings shall NOT be used to simulate edge lines.
- Dimensions indicated on this sheet are typical and approximate. Variations in size and height may occur between markers or devices made by manufacturers, by as much as 1/4 inch, unless otherwise noted.
- Temporary flexible-reflective roadway marker tabs will require normal maintenance replacement when used on roadways with an ADT per lane of up to 7500 vehicles with no more than 10% truck mix. When roadways exceed these values, additional maintenance replacement of devices should be planned.
- No segment of roadway open to traffic shall remain without permanent pavement markings for a period greater than 14 calendar days. The Contractor will be responsible for maintaining short term pavement markings until permanent pavement markings are in place. When the Contractor is responsible for placement of permanent pavement markings, no segment of roadway shall remain without permanent pavement markings for a period greater than 14 calendar days unless weather conditions prohibit placement. Permanent pavement markings shall be placed as soon as weather permits.
- For two lane, two-way roadways, DO NOT PASS signs shall be erected to mark the beginning of sections where passing is prohibited and PASS WITH CARE signs shall be erected to mark the beginning of sections where passing is permitted. Signs shall be in accordance with the "Texas Manual on Uniform Traffic Control Devices" (TMUTCD) and may be used to indicate the limits of no-passing zones for up to 14 calendar days. Permanent pavement markings should then be placed.
- For low volume two lane, two-way roadways of 4000 ADT or less, no-passing lines may be omitted when approved by the Engineer. DO NOT PASS and PASS WITH CARE signs shall be erected (see note 6).
- For exit gores where a lane is being dropped place wide gore markings or retroreflective channelizing devices to guide motorist through the exit. If channelizing devices are to be used it should be noted elsewhere in the plans. One piece cones are not allowed for this purpose.


TEMPORARY FLEXIBLE, REFLECTIVE ROADWAY MARKER TABS (TABS)

- Temporary flexible-reflective roadway marker tabs detailed on this sheet will be designated Type Y-2 (two amber reflective surfaces with yellow body); Type Y (one amber reflective surface with yellow body); and Type W (one white or silver reflective surface with white body). Additional details may be found on BC(11).
- Tabs shall meet requirements of Departmental Material Specification DMS-8242.
- When dry, tabs shall be visible for a minimum distance of 200 feet during normal daylight hours and when illuminated by automobile low-beam head light at night, unless sight distance is restricted by roadway geometrics.
- No two consecutive tabs nor four tabs per 1000 feet of line shall be missing or fail to meet the visual performance requirements of Note 3.


WORK ZONE SHORT TERM PAVEMENT MARKINGS PATTERNS




CENTER LINE & NO-PASSING ZONE BARRIER LINES FOR TWO LANE TWO-WAY HIGHWAYS




LANE LINES FOR DIVIDED HIGHWAY



LANE & CENTER LINES FOR MULTILANE UNDIVIDED HIGHWAYS



TWO-WAY LEFT TURN LANE



PREFABRICATED PAVEMENT MARKINGS

- Temporary Removable Prefabricated Pavement Markings shall meet the requirements of DMS-8241.
- Non-removable Prefabricated Pavement Markings shall meet the requirements of either DMS-8240 "Permanent Prefabricated Pavement Markings" or DMS-8243 "Temporary Construction-Grade Prefabricated Pavement Markings."


RAISED PAVEMENT MARKERS

- All raised pavement markers used for work zone markings shall meet the requirements of Item 672, "RAISED PAVEMENT MARKERS" and DMS-4200.

DEPARTMENTAL MATERIAL SPECIFICATIONS (DMS) & MATERIAL PRODUCER LISTS (MPL)

- DMSs referenced above can be found along with embedded links to their respective MPLs at the following website:

http://www.txdot.gov/business/contractors_consultants/material_specifications/default.htm




WORK ZONE SHORT TERM PAVEMENT MARKINGS

WZ(STPM)-23


FILE:	wzstpm-23.dgn	DN:	CK:	DW:	CK:
④ TxDOT	February 2023	CONT	SECT	JOB	HIGHWAY
		-	-	-	ABBOT RD
4-92	7-13				
1-97	2-23				
3-03					
		DIST	COUNTY		SHEET NO.
		-	BEXAR		39

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for incorrect results or damages resulting from its use.

DATE: 1/5/2026 8:28:42 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates_FM_1346\4 - Design\Plan Set\02\Int'l Standards\Temporary Road Closure Details.dwg



ROAD CLOSURE BEYOND THE INTERSECTION
Signing for a Numbered Route with an Off-Site Detour



ROAD CLOSURE AT THE INTERSECTION
Signing for an Un-numbered Route with an Off-Site Detour

LEGEND	
	Type 3 Barricade
	Sign

Posted Speed *	Minimum Sign Spacing "X" Distance
30	120'
35	160'
40	240'
45	320'
50	400'
55	500'
60	600'
65	700'
70	800'
75	900'

* Conventional Roads Only

GENERAL NOTES

- This sheet is intended to provide details for temporary work zone road closures. For permanent road closure details see the D&M standards.
- Barricades used shall meet the requirements shown on Barricade and Construction Standard BC10 and listed on the Compliant Work Zone Traffic Control Devices list (CWZTCD).
- Stockpiled materials shall not be placed on the traffic side of barricades.
- Barricades at the road closure should extend from pavement edge to pavement edge.
- Detour signing shown is intended to illustrate the type of signing that is appropriate for numbered routes or un-numbered routes as labeled. It does not indicate the full extent of detour signing required. Detour routes should be signed as shown elsewhere in the plans.
- If the road is open for a significant distance beyond the intersection or there are significant origin/destination points beyond the intersection, the signs and barricades at this location should be located at the edge of the traveled way.
- The Street Name (M4-12T) sign is to be placed above the DETOUR (M4-9S) sign.
- For urban areas where there is a shorter distance between the intersection and the actual closure location, the ROAD CLOSED XX MILES AHEAD (R11-3a) sign may be replaced with a ROAD CLOSED TO THRU TRAFFIC (R11-4) sign. If adequate space does not exist between the intersection and the closure a single ROAD CLOSED AHEAD (CW20-3D) sign spaced as per the table above may replace the ROAD CLOSED 1000 FT (CW20-3B) and ROAD CLOSED 500 FT (CW20-3C) signs.
- Signs and barricades shown shall be subsidiary to Item 502. Locations where these details will be required shall be as shown elsewhere in the plans.




WORK ZONE ROAD CLOSURE DETAILS

WZ(RCD)-13



FILE: wzrcd-13.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT August 1995	CONT	SECT	JOB	HIGHWAY
REVISIONS	-	-	-	ABBOT RD
1-97 4-98 7-13	DIST	COUNTY	SHEET NO.	
2-98 3-03	-	BEXAR	40	

DEFINITION OF TREATMENT ZONES FOR VARIOUS EDGE CONDITIONS



Edge Height (D) in Inches versus Lateral Clearance (Y) in Feet





Edge Condition I
 $S = (3:1)$ (or flatter)



Edge Condition II
 $S = ((2.99:1)$ to $(1:1)$)



Edge Condition III
 S is steeper than $(1:1)$



FACTORS CONSIDERED IN THE GUIDELINES:

- The "Edge Condition" is the slope (S) of the drop-off (H:V). The "Edge Height" is the depth of the drop-off "D".
- Distance "X" is to be the maximum practical under job conditions. Two feet minimum for high speed conditions. Distance "Y" is the lateral clearance from edge of travel lane to edge of dropoff. Distance "Z" does not have a minimum.
- In addition to the factors considered in the guidelines, each construction zone drop-off situation should be analyzed individually, taking into account other variables, such as: traffic mix, posted speed in the construction zone, horizontal curvature, and the practicality of the treatment options.
- The conditions for indicating the use of positive or protective barriers are given by Zone-5 and Figure-1. Traffic barriers are primarily applicable for high speed conditions. Urban areas with speeds of 30 mph or less may have a lesser need for signing, delineation, and barriers. Right-angled edges, however, with "D" greater than 2 inches and located within a lateral offset of 6 feet, may indicate a higher level of treatment.
- If the distance "Y" must be less than 3 feet, the use of a positive barrier may not be feasible. In such a case, consider either: 1) narrowing the lanes to a desired 11 to 12 feet or 10 foot minimum (see CW20-8 sign), or 2) provide an edge slope such as Edge Condition I.


Treatment Types Guidelines:

- No treatment
- CW 8-11 "Uneven Lanes" signs.
- CW 8-9a Shoulder Drop-Off" or CW 8-11 signs plus vertical panels.
- CW8-9a or CW 8-11, signs plus drums. Where restricted space precludes the use of drums, use vertical panels. An edge slope to that of the profered Edge Condition I.
- Check indications (Figure-1) for positive barrier. Where positive barrier is not indicated, the treatment shown above for Zone-4 may be used after consideration of other applicable factors.

Edge Condition Notes:

- Edge Condition I: Most vehicles are able to traverse an edge condition with a slope rate of (3 to 1) or flatter. The slope must be constructed with a compacted material capable of supporting vehicles.
- Edge Condition II: Most vehicles are able to traverse an edge condition with a slope between (2.99 to 1) and (1 to 1) so long as "D" does not exceed 5 inches. Under-carriage drag on most automobiles will occur when "D" exceeds 6 inches. As "D" exceeds 24 inches, the possibility for rollover is greater in most vehicles.
- Edge Condition III: When slopes are greater than (1 to 1) and where "D" is greater than 2 inches, a more difficult control factor may exist for some vehicles, if not properly treated. For example, where "D" is greater than 2 inches and up to 24 inches different types of vehicles may experience different steering control at different edge heights. Automobiles might experience more steering control differential when "D" is greater than 2 inches and up to 5 inches. Trucks, particularly those with high loads, have more steering control differential when "D" is greater than 5 inches and up to 24 inches. When "D" exceeds 24 inches, the possibility of rollover is greater for most vehicles.
- Milling or overlay operations that result in Edge Condition III should not be in place without appropriate warning treatments, and these conditions should not be left in place for extended periods of time.

FIGURE-1: CONDITIONS INDICATING USE OF
POSITIVE BARRIER FOR ZONE 5 ()



- $E = ADT \times T$
Where ADT is that portion of the average daily traffic volume traveling within 20 feet (generally two adjacent lanes) of the edge dropoff condition; and, T is the duration time in years of the dropoff condition.
- Figure-1 provides a practical approach to the use of positive barriers for the protection of vehicles from pavement drop-offs. Other factors, such as the presence of heavy machinery, construction workers, or the mix and volume of traffic may make the use of positive barriers appropriate, even when the edge condition alone may not justify the use of a barrier.
- An approved end treatment should be provided for any positive barrier end located within the clear zone.

These guidelines apply to temporary traffic control areas or work zones where continuous pavement edges or drop-offs exists parallel and adjacent to a lane used by traffic. The edge conditions may be present between shoulders and travel lanes, between adjacent or opposing travel lanes, or at intermediate points across the width of the paved surface. Due to the variability in construction operations, tolerances in the variables may be allowed by the engineer. These guidelines do not apply to short term operations. These guidelines do not constitute a rigid standard or policy; rather, they are guidance to be used in conjunction with engineering judgement. These guidelines may be updated on the Design Division's on-line manuals.

Engineer's Seal

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR OTHER PURPOSES. THEY ARE PREPARED FOR USE UNDER THE SUPERVISION OF EDWARD GALICIA 114275 1/5/2026 NAME P.E. # DATE	
--	--

Date _____



Traffic
Safety
Division
Standard

TREATMENT FOR VARIOUS EDGE CONDITIONS

FILE: edgecon.dgn	DN:	CK:	DW:	CK:
① TxDot August 2000	CONT	SECT	JOB	HIGHWAY
08-01	-	-	-	ABBOT RD
9-21	DIST	COUNTY	SHEET NO.	
	-	BEXAR	41	

Alignment Name: BL FM 1346				Length:	115.828																																																																																																																																											
Alignment Description:																																																																																																																																																
Alignment Style: Alignment\Baseline		Station	Northing	Easting																																																																																																																																												
Element: Linear																																																																																																																																																
POT	(POT)	200+00.000 R1	13703939.838	2205845.652	Tangent: 57.928																																																																																																																																											
PC	(PC)	204+24.214 R1	13704064.887	2206251.017	Chord: 115.814																																																																																																																																											
	Tangential Direction: N72°51'20.822"E				Middle Ordinate: 0.785																																																																																																																																											
	Tangential Length: 424.214				External: 0.785																																																																																																																																											
Element: Circular					Back Tangent Direction: N30°10'02.641"E																																																																																																																																											
PC	(PC)	204+24.214 R1	13704064.887	2206251.017	Back Radial Direction: S59°49'57.359"E																																																																																																																																											
PI	(PI)	209+84.127 R1	13704229.937	2206786.051	Chord Direction: N28°36'51.665"E																																																																																																																																											
CC	(CC)		13701316.289	2207098.919	Ahead Radial Direction: S62°56'19.310"E																																																																																																																																											
PT	(PT)	215+30.210 R1	13704182.244	2207343.929	Ahead Tangent Direction: N27°03'40.690"E																																																																																																																																											
	Radius: 2876.409				PT (PT) 141+42.440 R1 13707791.027 2209171.029																																																																																																																																											
	Delta: 22°01'49.971" Right				PC (PC) 143+62.563 R1 13707987.330 2209270.624																																																																																																																																											
Degree of Curvature (Arc):	01°59'30.913"				Tangential Direction: N26°54'03.408"E																																																																																																																																											
	Length: 1105.995				Tangential Length: 220.123																																																																																																																																											
	Tangent: 559.913				Element: Circular																																																																																																																																											
	Chord: 1099.195				PC (PC) 143+62.563 R1 13707987.330 2209270.624																																																																																																																																											
	Middle Ordinate: 52.994				PI (PI) 144+71.005 R1 13708084.038 2209319.688																																																																																																																																											
	External: 53.989				CC (CC) 13706011.842 2213164.364																																																																																																																																											
	Back Tangent Direction: N72°51'20.822"E				PT (PT) 145+79.403 R1 13708178.190 2209373.493																																																																																																																																											
	Back Radial Direction: S17°08'39.178"E				Radius: 4366.207																																																																																																																																											
	Chord Direction: N83°52'15.807"E				Delta: 02°50'43.764" Right																																																																																																																																											
	Ahead Radial Direction: S04°53'10.793"W				Degree of Curvature (Arc): 01°18'44.118"																																																																																																																																											
	Ahead Tangent Direction: S85°06'49.207"E				Length: 216.840																																																																																																																																											
Element: Linear					Tangent: 108.442																																																																																																																																											
PT	(PT)	215+30.210 R1	13704182.244	2207343.929	Chord: 216.817																																																																																																																																											
POT	(POT)	225+80.549 R1	13704092.777	2208390.451	Middle Ordinate: 1.346																																																																																																																																											
	Tangential Direction: S85°06'49.207"E			External: 1.346																																																																																																																																												
	Tangential Length: 1050.340			Back Tangent Direction: N26°54'03.408"E																																																																																																																																												
Alignment Name: EX_ABBOT_RD_CL				Back Radial Direction: S63°05'56.592"E																																																																																																																																												
Alignment Description:				Chord Direction: N28°19'25.290"E																																																																																																																																												
Alignment Style: Alignment\Baseline	Station	Northing	Easting	Ahead Radial Direction: S60°15'12.828"E																																																																																																																																												
Element: Linear				Ahead Tangent Direction: N29°44'47.172"E																																																																																																																																												
POT	(POT)	100+00.000 R1	13704192.894	2207118.563	PT (PT) 145+79.403 R1 13708178.190 2209373.493																																																																																																																																											
PI	(PI)	103+25.221 R1	13704476.680	2207277.417	POT (POT) 157+14.954 R1 13709164.110 2209936.912																																																																																																																																											
	Tangential Direction: N29°14'19.284"E			Tangential Direction: N29°44'47.172"E																																																																																																																																												
	Tangential Length: 325.221			Tangential Length: 1135.552																																																																																																																																												
Element: Linear				Alignment Name: PR_ABBOT_RD_BL																																																																																																																																												
PI	(PI)	103+25.221 R1	13704476.680	2207277.417	Alignment Description:																																																																																																																																											
PI	(PI)	105+50.873 R1	13704672.809	2207389.005	Alignment Style: Alignment\Baseline																																																																																																																																											
	Tangential Direction: N29°38'15.425"E			Station	Northing	Easting																																																																																																																																										
	Tangential Length: 225.651			Element: Linear				PT (PT) 100+00.000 R1 13704192.520 2207130.990	PI	(PI)	105+50.873 R1	13704672.809	2207389.005	POT (PC) 103+01.117 R1 13704454.595 2207279.274		Tangential Length: 225.651			Tangential Direction: N29°30'05.090"E	Element: Linear				Tangential Length: 301.117	PI	(PI)	105+50.873 R1	13704672.809	2207389.005	Element: Circular	PI	(PI)	119+18.732 R1	13705862.847	2208063.431	PC (PC) 103+01.117 R1 13704454.595 2207279.274		Tangential Direction: N29°32'29.075"E			PI (PI) 103+12.043 R1 13704464.104 2207284.654		Tangential Length: 1367.860			CC (CC) 13704829.838 2206616.072	Element: Linear				PT (PT) 103+22.966 R1 13704473.763 2207289.759	PI	(PI)	119+18.732 R1	13705862.847	2208063.431	Radius: 762.000	PI	(PI)	134+15.207 R1	13707160.761	2208808.317	Delta: 01°38'34.203" Left		Tangential Direction: N29°51'06.912"E			Degree of Curvature (Arc): 07°31'08.872"		Tangential Length: 1496.475			Length: 21.849	Element: Linear				Tangent: 10.925	PI	(PI)	134+15.207 R1	13707160.761	2208808.317	Chord: 21.848	PC	(PC)	140+26.612 R1	13707689.358	2209115.565	Middle Ordinate: 0.078		Tangential Direction: N30°10'02.641"E			External: 0.078		Tangential Length: 611.405			Back Tangent Direction: N29°30'05.090"E	Element: Circular				Back Radial Direction: S60°29'54.910"E	PC	(PC)	140+26.612 R1	13707689.358	2209115.565	Chord Direction: N28°40'47.989"E	PI	(PI)	140+84.540 R1	13707739.441	2209144.675	Ahead Radial Direction: S62°08'29.113"E	CC	(CC)		13708763.052	2207268.358	Ahead Tangent Direction: N27°51'30.887"E	PT	(PT)	141+42.440 R1	13707791.027	2209171.029	Element: Linear		Radius: 2136.584					Delta: 03°06'21.952" Left				Degree of Curvature (Arc):	02°40'53.951"			
Element: Linear				PT (PT) 100+00.000 R1 13704192.520 2207130.990																																																																																																																																												
PI	(PI)	105+50.873 R1	13704672.809	2207389.005	POT (PC) 103+01.117 R1 13704454.595 2207279.274																																																																																																																																											
	Tangential Length: 225.651			Tangential Direction: N29°30'05.090"E																																																																																																																																												
Element: Linear				Tangential Length: 301.117																																																																																																																																												
PI	(PI)	105+50.873 R1	13704672.809	2207389.005	Element: Circular																																																																																																																																											
PI	(PI)	119+18.732 R1	13705862.847	2208063.431	PC (PC) 103+01.117 R1 13704454.595 2207279.274																																																																																																																																											
	Tangential Direction: N29°32'29.075"E			PI (PI) 103+12.043 R1 13704464.104 2207284.654																																																																																																																																												
	Tangential Length: 1367.860			CC (CC) 13704829.838 2206616.072																																																																																																																																												
Element: Linear				PT (PT) 103+22.966 R1 13704473.763 2207289.759																																																																																																																																												
PI	(PI)	119+18.732 R1	13705862.847	2208063.431	Radius: 762.000																																																																																																																																											
PI	(PI)	134+15.207 R1	13707160.761	2208808.317	Delta: 01°38'34.203" Left																																																																																																																																											
	Tangential Direction: N29°51'06.912"E			Degree of Curvature (Arc): 07°31'08.872"																																																																																																																																												
	Tangential Length: 1496.475			Length: 21.849																																																																																																																																												
Element: Linear				Tangent: 10.925																																																																																																																																												
PI	(PI)	134+15.207 R1	13707160.761	2208808.317	Chord: 21.848																																																																																																																																											
PC	(PC)	140+26.612 R1	13707689.358	2209115.565	Middle Ordinate: 0.078																																																																																																																																											
	Tangential Direction: N30°10'02.641"E			External: 0.078																																																																																																																																												
	Tangential Length: 611.405			Back Tangent Direction: N29°30'05.090"E																																																																																																																																												
Element: Circular				Back Radial Direction: S60°29'54.910"E																																																																																																																																												
PC	(PC)	140+26.612 R1	13707689.358	2209115.565	Chord Direction: N28°40'47.989"E																																																																																																																																											
PI	(PI)	140+84.540 R1	13707739.441	2209144.675	Ahead Radial Direction: S62°08'29.113"E																																																																																																																																											
CC	(CC)		13708763.052	2207268.358	Ahead Tangent Direction: N27°51'30.887"E																																																																																																																																											
PT	(PT)	141+42.440 R1	13707791.027	2209171.029	Element: Linear																																																																																																																																											
	Radius: 2136.584																																																																																																																																															
	Delta: 03°06'21.952" Left																																																																																																																																															
Degree of Curvature (Arc):	02°40'53.951"																																																																																																																																															

95% SUBMITTAL		
PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE



ROSE VALLEY SOUTH UNIT #2



HORIZONTAL ALIGNMENT DATA



SHEET 1 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	SHEET
6	-	42
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	HIGHWAY NO.
-	-	ABBOTT RD

PT	(PT)	103+22.966 R1	13704473.763	2207289.759	Degree of Curvature (Arc):	01°18'44.118"
PC	(PC)	106+84.807 R1	13704793.667	2207458.844	Length:	216.840
	Tangential Direction:	N27°51'30.887"E			Tangent:	108.442
	Tangential Length:	361.840			Chord:	216.817
Element: Circular	PC	(PC)	106+84.807 R1	13704793.667	Middle Ordinate:	1.346
	PI	(PI)	106+95.732 R1	13704803.326	External:	1.346
	CC	(CC)		13704437.592	Back Tangent Direction:	N26°54'03.408"E
	PT	(PT)	107+06.655 R1	13704812.835	Back Radial Direction:	S63°05'56.592"E
	Radius:	762.000		2207469.329	Chord Direction:	N28°19'25.290"E
	Delta:	01°38'34.203" Right			Ahead Radial Direction:	S60°15'12.828"E
	Degree of Curvature (Arc):	07°31'08.872"			Ahead Tangent Direction:	N29°44'47.172"E
	Length:	21.849				
	Tangent:	10.925			PT	145+73.759 R1
	Chord:	21.848			POT	157+09.311 R1
	Middle Ordinate:	0.078			Tangential Direction:	N29°44'47.172"E
	External:	0.078			Tangential Length:	1135.552
	Back Tangent Direction:	N27°51'30.887"E				
	Back Radial Direction:	S62°08'29.113"E				
	Chord Direction:	N28°40'47.989"E				
	Ahead Radial Direction:	S60°29'54.910"E				
	Ahead Tangent Direction:	N29°30'05.090"E				
Element: Linear	PT	(PT)	107+06.655 R1	13704812.835	2207469.329	
	PI	(PI)	119+13.089 R1	13705862.847	2208063.431	
		Tangential Direction:	N29°30'05.090"E			
		Tangential Length:	1206.434			
	PI	(PI)	119+13.089 R1	13705862.847	2208063.431	
	PI	(PI)	134+09.564 R1	13707160.761	2208808.317	
		Tangential Direction:	N29°51'06.912"E			
		Tangential Length:	1496.475			
Element: Linear	PI	(PI)	134+09.564 R1	13707160.761	2208808.317	
	PC	(PC)	140+20.969 R1	13707689.358	2209115.565	
		Tangential Direction:	N30°10'02.641"E			
		Tangential Length:	611.405			
	Element: Circular					
	PC	(PC)	140+20.969 R1	13707689.358	2209115.565	
	PI	(PI)	140+78.897 R1	13707739.441	2209144.675	
	CC	(CC)		13708763.052	2207268.358	
	PT	(PT)	141+36.797 R1	13707791.027	2209171.029	
	Radius:	2136.584				
	Delta:	03°06'21.952" Left				
	Degree of Curvature (Arc):	02°40'53.951"				
	Length:	115.828				
	Tangent:	57.928				
	Chord:	115.814				
	Middle Ordinate:	0.785				
	External:	0.785				
	Back Tangent Direction:	N30°10'02.641"E				
	Back Radial Direction:	S59°49'57.359"E				
	Chord Direction:	N28°36'51.665"E				
	Ahead Radial Direction:	S62°56'19.310"E				
	Ahead Tangent Direction:	N27°03'40.690"E				
Element: Linear	PT	(PT)	141+36.797 R1	13707791.027	2209171.029	
	PC	(PC)	143+56.920 R1	13707987.330	2209270.624	
		Tangential Direction:	N26°54'03.408"E			
		Tangential Length:	220.123			
	Element: Circular					
	PC	(PC)	143+56.920 R1	13707987.330	2209270.624	
	PI	(PI)	144+65.362 R1	13708084.038	2209319.688	
	CC	(CC)		13706011.842	2213164.364	
	PT	(PT)	145+73.759 R1	13708178.190	2209373.493	
	Radius:	4366.207				
	Delta:	02°50'43.764" Right				


95% SUBMITTAL		
PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA 114275 1/5/2026		
NAME	P.E. #	DATE

LEGACY ENGINEERING GROUP		
Legacy Engineering Group, PLLC 7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960 TBPE Firm Registration No. 20623		
ROSE VALLEY SOUTH UNIT #2		
HORIZONTAL ALIGNMENT DATA		
SHEET 2 OF 2		
FED.RD. DIV./NO.	PROJECT NO.	SHEET
6	-	43
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
-	-	ABBOTT RD






NO WORK THIS SHEET




NOTES:
1. LOCATION OF UTILITIES ARE APPROXIMATE.
CONTRACTOR TO FIELD VERIFY PRIOR
TO CONSTRUCTION.



0' 25' 50'
SCALE: 1"=50'




NO WORK THIS SHEET



NOTES:
1. LOCATION OF UTILITIES ARE APPROXIMATE.
CONTRACTOR TO FIELD VERIFY PRIOR
TO CONSTRUCTION.



NO WORK THIS SHEET




LEGEND

- TRAFFIC FLOW
- APPARENT ROW
- PROP DITCH FLOW LINE
- SAWCUT
- PROPOSED WIDENING
- PROPOSED DRIVEWAY
- EXISTING MAILBOX TO BE RELOCATED
- PROPOSED MAILBOX
- ASPHALT REMOVAL
- DRIVEWAY NUMBER

NOTES:
1. LOCATION OF UTILITIES ARE APPROXIMATE.
CONTRACTOR TO FIELD VERIFY PRIOR
TO CONSTRUCTION.

0' 25' 50'
SCALE: 1"=50'



95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA	114275	1/5/2026
NAME	P.E. #	DATE


 **LEGACY**
ENGINEERING GROUP
Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2
ROADWAY PLAN & PROFILE
STA 122+00 TO STA 128+00



SCALE: 1" = 50' SHEET 5 OF 8

FED/RD. DIV/NO.	PROJECT NO.	SHEET
6	-	48
STATE	DIST.	COUNTY
TEXAS	SAT	BEXAR
CONT.	SECT.	JOB
-	-	HIGHWAY NO.
		ABBOTT RD

NO WORK THIS SHEET



NOTES:
1. LOCATION OF UTILITIES ARE APPROXIMATE.
CONTRACTOR TO FIELD VERIFY PRIOR
TO CONSTRUCTION.



NO WORK THIS SHEET

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275
NAME	P.E. #
DATE 1/5/2026	







Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623


ROSE VALLEY SOUTH UNIT #2


ROADWAY PLAN & PROFILE
STA 128+00 TO STA 134+00

SCALE: 1" = 50'				SHEET 6 OF 8	
FED.RD. DIV./NO.	PROJECT NO.	SECT.	49		
6	-	-			
STATE	DIST.	COUNTY			
TEXAS	SAT	BEXAR			
CONT.	SECT.	JOB	HIGHWAY NO.		
-	-	-	ABBOTT RD		












DRIVEWAY 1



DRIVEWAY 2

NOTES:
1. LOCATION OF UTILITIES ARE APPROXIMATE.
CONTRACTOR TO FIELD VERIFY PRIOR
TO CONSTRUCTION.



95% SUBMITTAL

**PRELIMINARY
FOR REVIEW ONLY**

THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT
TO CHANGE. THEY ARE NOT INTENDED FOR
CONSTRUCTION OR PERMIT PURPOSES. THEY WERE
PREPARED BY, OR UNDER THE SUPERVISION OF:
WARD GALICIA **114275** **1/5/2026**





Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBDE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

DRIVEWAY PLAN & PROFILE

CALE: 1" = 10'		PROJECT NO.		SHEET 1 OF 4
ED. RD. DIV. NO.	6	-		53
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	





LEGEND

- TRAFFIC FLOW (arrow)
- APPARENT ROW (dashed line)
- PROPOSED WIDENING (shaded area)
- PROPOSED DRIVEWAY (solid line)

NOTES:

- LOCATION OF UTILITIES ARE APPROXIMATE. CONTRACTOR TO FIELD VERIFY PRIOR TO CONSTRUCTION.
- SEE SHEET 52 "DETAIL C" FOR DRIVEWAY PAVEMENT DETAIL.



95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY

THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:

EDWARD GALICIA 114275 1/5/2026

NAME P.E. # DATE


LEGACY
ENGINEERING GROUP

Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623


ROSE VALLEY SOUTH UNIT #2

DRIVEWAY PLAN & PROFILE



SCALE: 1" = 10'				SHEET 2 OF 4		
FED.RD. DIV./NO.	PROJECT NO.	SECTION	LINE	PROJECT NO.	SECTION	LINE
6	-	-	-	-	-	54
STATE	DIST.	COUNTY				
TEXAS	SAT	BEXAR				
CONT.	SECT.	JOB	HIGHWAY NO.			
-	-	-	ABBOTT RD			



DRIVEWAY 5



DRIVEWAY 6



OTES:

- . LOCATION OF UTILITIES ARE APPROXIMATE. CONTRACTOR TO FIELD VERIFY PRIOR TO CONSTRUCTION.
- . SEE SHEET # 52 "DETAIL C" FOR DRIVEWAY PAVEMENT DETAIL.

PAVEMENT DETAIL:

95% SUBMITTAL

**PRELIMINARY
FOR REVIEW ONLY**
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT
TO CHANGE. THEY ARE NOT INTENDED FOR
CONSTRUCTION OR PERMIT PURPOSES. THEY WERE
PREPARED BY, OR UNDER THE SUPERVISION OF:
WARD GALICIA **114275** **1/5/2026**
P.F. # **DATE**







Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TREC Firm Registration No. 20622

ROSE VALLEY SOUTH UNIT #2


DRIVEWAY PLAN & PROFILE

SCALE: 1" = 10'		PROJECT NO.		SHEET 3 OF 4
FED RD. DIV. NO.			SHEET	
6			55	
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	





ROSE VALLEY SOUTH - UNIT 2
ROSE BRANCH
STA. 1+00 - END
BEXAR COUNTY, TEXAS


CURVE TABLE				
CURVE	RADIUS	DELTA	CHORD BEARING	CHORD LENGTH
C3	38.00'	085°5'53"	N71°5'12"E	51.83'
C4	38.00'	085°5'54"	N72°20'55"W	51.64'
C5	83.00'	023°2'05"	N17°10'50"E	33.59'
C6	117.00'	014°56'37"	N12°38'44"E	30.43'



RESIDENTIAL STREET

(NOT TO SCALE)

ROSE BRANCH
(STA. 1+00 - END)
HORIZONTAL SCALE: 1" = 50' H
VERTICAL SCALE: 1" = 5' V

WILLING

0 20 40

SCALE OF FEET
1" = 20'

LEGEND

— PROPERTY BOUNDARY

— SITE LINE

— ROAD CENTERLINE

— 650 — EXISTING 1' CONTOUR

(650) PROPOSED 1' CONTOUR

WASHOUT CROWN

 SIDEWALK TO BE
CONSTRUCTED BY
DEVELOPER

ABBOTT RD BAR DITCH
(EXISTING CONSTRUCTION WITH
PROPOSED FLOW)
STA. 1+00 - STA 1+15.62
STA. 2+50.72 - END
NOT-TO-SCALE

SECTION C1-C1

STA. 100.00--STA 1+44.51 NOT TO SCALE

FREQUENCY	Q(CFS)	SLOPE	D _N (ft)	V (fps)	t _w (ft)
25-YR	21.83	1.44%	0.68	3.30	12.4

BEXAR COUNTY R.O.W. NOTE:
A BEXAR COUNTY PERMIT MUST BE
OBTAINED BEFORE WORKING IN THE
BEXAR COUNTY R.O.W.

NOTE: CONTRACTOR SHALL BEGIN MEASURES TO ESTABLISH VEGETATION IMMEDIATELY AFTER CONSTRUCTION OF EARTHEN DRAIN SECTIONS TO MITIGATE CHANNEL EROSION. CONTRACTOR SHALL USE HYDRO-MULCH SEEDING, SOD LINING, OR OTHER APPROVED METHODS.

STANDARD NOTES:

- IMPROVED EARTHEN CHANNELS AND DETENTION PONDS WILL BE VEGETATED BY SEEDING OR SODING. EIGHTY-FIVE PERCENT (85%) OF THE CHANNEL SURFACE AREA MUST HAVE ESTABLISHED VEGETATION BEFORE THE CITY OF SAN ANTONIO WILL ACCEPT THE CHANNEL FOR MAINTENANCE.
- ALL CONCRETE LINING SHALL DEVELOP A MIN. COMPRESSIVE STRENGTH OF 3,000 PSI IN 28 DAYS.
- FOR CONCRETE LININGS, THE CONCRETE LINING SHALL BE A MINIMUM OF FIVE (5) INCHES THICK AND REINFORCED WITH NO. 4 ROUND BARS @18 INCHES ON CENTER, EACH WAY, WHERE SURCHARGE, NATURE OF GROUND, HEIGHT AND STEEPNESS OF SLOPE, ETC., BECOME CRITICAL, DESIGN SHALL BE IN ACCORDANCE WITH LATEST STRUCTURAL STANDARDS. ALL CONCRETE LINING SHALL DEVELOP A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI LESS THAN THREE (3) HOURS AFTER 15,000 POUNDS PER SQUARE INCH IN TWENTY-EIGHT (28) DAYS. THE DEPTH OF ALL TOE DOWNS SHALL BE 36 INCHES UPSTREAM, 24 INCHES DOWNSTREAM, AND 18 INCHES FOR SIDE SLOPES. THE CITY'S CONSTRUCTION INSPECTOR MAY PERMIT AN 18' TOE DOWN IN ROCK SUBGRADE IN LIEU OF THE ABOVE TOE DOWN REQUIREMENTS. THE HORIZONTAL DIMENSIONS OF TOE DOWNS SHALL NOT BE LESS THAN SIX (6) INCHES.


OPEN EARTHEN CHANNEL NOTE:

- CONTRACTOR SHALL REFERENCE TABLE 9.3.8.1 - "RETARDATION CLASS FOR LINING MATERIALS" PROVIDED ON SHEET C1.4 AND SUPPLIED RETARDANCE CLASS (RC) FOR CHOICE OF COVER WITHIN OPEN EARTHEN CHANNEL CROSS SECTIONS.

MIN. THICKNESS SIDE TOEDOWNS MIN. TH.


CONCRETE RIP-RAP DETAIL (TYP.)

"THIS DOCUMENT IS
RELEASED FOR REVIEW
PURPOSES" UNDER THE
AUTORIZATION OF
RADLEY A. KOETHER, P.E.
105048 NOT TO BE USED
FOR CONSTRUCTION.






SIDE ELEVATION OF TYPICAL PIPE CULVERT MITER


(Showing corrugated metal pipe (CMP) culvert
Details at reinforced concrete pipe (RCP)
culvert are similar.)



ISOMETRIC VIEW OF TYPICAL INSTALLATION





PIPE WITH ANCHOR BARS




SECTION C-C

CROSS PIPE DETAILS




(Cross pipes not shown for clarity.)

Limits of riprap (to be included with SET for payment) 5



SHOWING TYPICAL PIPE CULVERT AND RIPRAP



SHOWING CROSS PIPE WITH BOLTED ANCHOR

SECTION A-A

CROSS PIPE LENGTHS, REQUIRED PIPE SIZES, AND RIPRAP QUANTITIES

Nominal Culvert I.D.	Conc Riprap (CY) 6	Pipe Culvert Spa ~ G	Single Barrel ~ Q1	Multi-Barrel ~ Q1	Q2	Conditions for Use of Cross Pipes	Cross Pipe Sizes
12"	0.6	0' - 9"	N/A	2' - 1"	1' - 9"	3 or more pipe culverts	3" Std (3,500" O.D.)
15"	0.7	0' - 11"	N/A	2' - 5"	2' - 2"		
18"	0.8	1' - 2"	N/A	2' - 10"	2' - 8"		
21"	0.9	1' - 4"	N/A	3' - 2"	3' - 1"	3 or more pipe culverts	3 1/2" Std (4,000" O.D.)
24"	0.9	1' - 7"	N/A	3' - 6"	3' - 7"		
27"	1.0	1' - 8"	N/A	3' - 10"	3' - 11"		
30"	1.1	1' - 10"	N/A	4' - 2"	4' - 4"	2 or more pipe culverts	All pipe culverts
33"	1.2	1' - 11"	4' - 2"	4' - 5"	4' - 8"		
36"	1.3	2' - 1"	4' - 5"	5' - 1"	5' - 10"		
42"	1.5	2' - 4"	4' - 11"	5' - 5"	5' - 10"	All pipe culverts	4" Std (4,500" O.D.)
48"	1.7	2' - 7"	5' - 5"	6' - 0"	6' - 7"		
54"	2.0	3' - 0"	5' - 11"	6' - 9"	7' - 6"		
60"	2.2	3' - 3"	6' - 5"	7' - 4"	8' - 3"	All pipe culverts	5" Std (5,563" O.D.)
66"	2.4	3' - 3"	6' - 11"	7' - 10"	8' - 9"		
72"	2.7	3' - 4"	7' - 5"	8' - 5"	9' - 4"		

① The proper installation of the first cross pipe is critical for vehicle safety. Place the top of the first cross pipe no more than 6" above the flow line.

② Provide cross pipes, except the first bottom pipe, of the size shown in the table. Provide a 3 1/2" standard pipe (4" O.D.) for the first bottom pipe.

③ Install the third cross pipe from the bottom of the culvert using a bolted connection. Ensure that riprap concrete does not flow into the cross pipe so as to permit disassembly of the bolted connection to allow cleanout access. At the Contractor's option, install all other cross pipes using the bolted connection details.

④ Match cross slope as shown elsewhere in the plans. Cross slope of 6:1 or flatter is required for vehicle safety.

⑤ Riprap placed beyond the limits shown will be paid for as concrete riprap in accordance with Item 432, "Riprap."

⑥ Quantities shown are for one end of one reinforced concrete pipe (RCP) culvert. For multiple pipe culverts or for corrugated metal pipe (CMP) culverts, quantities will need to be adjusted. Riprap quantities are for contractor's information only.

MATERIAL NOTES:

Synthetic fibers listed on the "Fibers for Concrete" Material Producer List (MPL) may be used in lieu of steel reinforcing in riprap concrete unless noted otherwise.

Provide cross pipes that meet the requirements of ASTM A53 (Type E or S, Gr B), ASTM A500 (Gr B), or API 5LX52.

Provide ASTM A307 bolts and nuts.

Galvanize all steel components, except concrete reinforcing, after fabrication. Repair galvanizing damaged during transport or construction in accordance with the specifications.


GENERAL NOTES:



Cross pipes are designed for a traversing load of 10,000 pounds at yield as recommended by Research Report 280-2F, "Safety Treatment of Roadside Parallel-Drainage Structures", Texas Transportation Institute, March 1981.

Safety end treatments (SET) shown herein are intended for use in those installations where out of control vehicles are likely to traverse the openings approximately perpendicular to the cross pipes.

Construct concrete riprap and all necessary invert in accordance with the requirements of Item 432, "Riprap."

Payment for riprap and toewall is included in the Price Bid for each Safety End Treatment.





95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY

THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:

EDWARD GALICIA 114275 1/5/2026

NAME P.E. # DATE




Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT#2
SIGNING, PAVEMENT MARKINGS AND SW3P LAYOUT

SCALE: 1" = 50'			
FED.RD. DIV./NO.	PROJECT NO.	SHEET	
6	-	61	
STATE	DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD



NO WORK THIS SHEET




LEGEND	
↑	DIRECTION OF TRAFFIC
—	APPARENT ROW
—	DRILL SEEDING
SCF	TEMP SEDMT CONT FENCE (INSTALL)
RFD	ROCK FILTER DAMS (INSTALL) (TY4)
A	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)
B	REFL PAV MRK TY I (W) 6" (SLD) (100MIL)
C	REFL PAV MRK TY I (Y) 6" (SLD) (100MIL)
D	REFL PAV MRK TY II-A-A
E	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)
F	REFL PAV MRK TY I-C
G	REFL PAV MRK TY I (W) (ARROW) (100MIL)
H	REFL PAV MRK TY I (W) (WORD) (100MIL)
I	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)
J	REFL PAV MRK TY I (W) (DBL ARROW) (100MIL)
K	ELIM EXT PM & MRKS (4")
L	REFL PAV MRK TY I (Y) (MED NOSE) (100 MIL)
M	REFL PAV MRK TY I (Y) 24" (SLD) (100 MIL)
	OBJECT MARKER



SCALE: 1"=50'

NO WORK THIS SHEET



PRELIMINARY	
FOR REVIEW ONLY	
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:	
EDWARD GALICIA	114275
NAME	P.E. #
DATE 1/5/2026	





Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT#2
SIGNING, PAVEMENT MARKINGS
AND SW3P LAYOUT


SCALE: 1" = 50'			SHEET 2 OF 4	
FED.RD.	DIV./NO.	PROJECT NO.	62	SHEET
6				
STATE	DIST.	COUNTY		
TEXAS	SAT	BEXAR		
CONT.	SECT.	JOB	HIGHWAY NO.	
-	-	-	ABBOTT RD	

**LEGEND**

	DIRECTION OF TRAFFIC
	APPARENT ROW
	DRILL SEEDING
	TEMP SEDMT CONT FENCE (INSTALL)
	ROCK FILTER DAMS (INSTALL) (TY4)
	REFL PAV MRK TY I (W) 8" (DOT) (100MIL)
	REFL PAV MRK TY I (W) 6" (SLD) (100MIL)
	REFL PAV MRK TY I (Y) 6" (SLD) (100MIL)
	REFL PAV MRK TY II-A-A
	REFL PAV MRK TY I (W) 8" (SLD) (100MIL)
	REFL PAV MRK TY I-C
	REFL PAV MRK TY I (W) (ARROW) (100MIL)
	REFL PAV MRK TY I (W) (WORD) (100MIL)
	REFL PAV MRK TY I (W) 24" (SLD) (100MIL)
	REFL PAV MRK TY I (W) (DBL ARROW) (100MIL)
	ELIM EXT PM & MRKS (4")
	REFL PAV MRK TY I (Y) (MED NOSE) (100 MIL)
	REFL PAV MRK TY I (Y) 24" (SLD) (100 MIL)
	OBJECT MARKER



SCALE: 1"=50'

NO WORK THIS SHEET

**PRELIMINARY
FOR REVIEW ONLY**

THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT
TO CHANGE. THEY ARE NOT INTENDED FOR
CONSTRUCTION OR PERMIT PURPOSES. THEY WERE
PREPARED BY, OR UNDER THE SUPERVISION OF:


EDWARD GALICIA 114275 1/5/2026
NAME P.E. # DATE




Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT#2
**SIGNING, PAVEMENT MARKINGS
AND SW3P LAYOUT**


SCALE: 1" = 50'			SHEET 3 OF 4	
FED.RD. DIV./NO.	PROJECT NO.			
6	-	-	-	63
STATE	DIST.			COUNTY
TEXAS	SAT			BEXAR
CONT.	SECT.	JOB		HIGHWAY NO.
-	-	-		ABBOTT RD






R3-8 SPL (MR) 36x30;
1.9" Radius, 0.8" Border, 0.5" Indent, Black on White;
M ir=13.25, s=2.5; L ir=4.5, s=2.5;
"ONLY", D 50% spacing;

SHEET 1 OF 4
SIGN NO. 3



D3-1B 36x9;
0.5" Radius, 0.2" Border, White on Blue;
"FM 1346", D;

SHEET 1 OF 4
SIGN NO. 1



D3-1B 36x9;
0.5" Radius, 0.2" Border, White on Blue;
"Abbott", D; "RD", D;

SHEET 1 OF 4
SIGN NO. 1

95% SUBMITTAL

PRELIMINARY FOR REVIEW ONLY		
THESE DOCUMENTS ARE PRELIMINARY AND SUBJECT TO CHANGE. THEY ARE NOT INTENDED FOR CONSTRUCTION OR PERMIT PURPOSES. THEY WERE PREPARED BY, OR UNDER THE SUPERVISION OF:		
EDWARD GALICIA		114275
P.E. #		1/5/2026
DATE		



Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

ROSE VALLEY SOUTH UNIT #2

SMALL SIGN DETAILS

N.T.S.		SHEET 1 OF 1	
FED.RD. DIV./NO.		PROJECT NO.	SHEET
6		-	65
STATE	DIST.	COUNTY	
TEXAS	SAT	BEXAR	
CONT.	SECT.	JOB	HIGHWAY NO.
-	-	-	ABBOTT RD

SUMMARY OF SMALL SIGNS

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of any sign design from TxDOT to SOSS formats or for incorrect results or damages resulting from its use.

PLAN SHEET NO.	SIGN NO.	SIGN NOMENCLATURE	SIGN	DIMENSIONS	FLAT ALUMINUM (TYPE A) EXAL ALUMINUM (TYPE G)	SM RD SGN ASSM TY XXXXX (X) XX (X-XXXX)					BRIDGE MOUNT CLEARANCE SIGNS (See Note 2)		
						POST TYPE	POSTS	ANCHOR TYPE	MOUNTING DESIGNATION				
						FRP = Fiberglass TWT = Thin-Wall 10BWG = 10 BWG S80 = Sch 80	1 or 2	UA=Universal Conc UB=Universal Bolt SA=Slipbase-Conc SB=Slipbase-Bolt WS=Wedge Steel WP=Wedge Plastic	PREFABRICATED	1EXT or 2EXT = # of Ext BM = Extruded Wind Beam WC = 1.12 #/ft Wing Channel EXAL= Extruded Alum Sign Panels			
61	1	R1-1		36X36	10BWG	1	SA	P					
		D3-1B		30X9									
		D3-1B		30X9									
61	2	R2-1		24X30	10BWG	1	SA	P					
61	3	R3-8 SPL (MR)		30x30	10BWG	1	SA	P					
61	4	W3-1		36x30	10BWG	1	SA	P					
63	1	W2-2L		30x30	10BWG	1	SA	P					
64	1	R2-1		24X30	10BWG	1	SA	P					
64	2	W2-2R		30 X 30	10BWG	1	SA	P					

ALUMINUM SIGN BLANKS THICKNESS	
Square Feet	Minimum Thickness
Less than 7.5	0.080"
7.5 to 15	0.100"
Greater than 15	0.125"

The Standard Highway Sign Designs for Texas (SHSD) can be found at the following website.
<http://www.txdot.gov/>

NOTE:

1. Sign supports shall be located as shown on the plans, except that the Engineer may shift the sign supports, within design guidelines, where necessary to secure a more desirable location or to avoid conflict with utilities. Unless otherwise shown on the plans, the Contractor shall stake and the Engineer will verify all sign support locations.
2. For installation of bridge mount clearance signs, see Bridge Mounted Clearance Sign Assembly (BMCS) Standard Sheet.
3. For Sign Support Descriptive Codes, see Sign Mounting Details Small Roadside Signs General Notes & Details SMD(GEN).



SUMMARY OF SMALL SIGNS

SOSS

FILE: sums16.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT
© TxDOT May 1987	CONT	SECT	JOB	HIGHWAY
REVISIONS	-	-	-	ABBOT RD
4-16	DIST	COUNTY	SHEET NO.	
8-16	-	BEXAR	66	

SIGN SUPPORT DESCRIPTIVE CODES

(Descriptive Codes correspond to project estimate and quantities sheets)

SM RD SGN ASSM TY XXXXX(X)XX(X-XXXX)

Post Type

FRP = Fiberglass Reinforced Plastic Pipe (see SMD(FRP))
TWT = Thin-Walled Tubing (see SMD(TWT))
10BWG = 10 BWG Tubing (see SMD(SLIP-1) to (SLIP-3))
S80 = Schedule 80 Pipe (see SMD(SLIP-1) to (SLIP-3))


Number of Posts (1 or 2)

UA = Universal Anchor - Concreted (see SMD(FRP) and (TWT))
UB = Universal Anchor - Bolted down (see SMD(FRP) and (TWT))
WS = Wedge Anchor Steel - (see SMD(TWT))
WP = Wedge Anchor Plastic (see SMD(TWT))
SA = Slipbase - Concreted (see SMD(SLIP-1) to (SLIP-3))
SB = Slipbase - Bolted Down (see SMD(SLIP-1) to (SLIP-3))

Sign Mounting Designation


P = Prefab. "Plain" (see SMD(SLIP-1) to (SLIP-3), (TWT), (FRP))
T = Prefab. "T" (see SMD(SLIP-1) to (SLIP-3), (TWT))
U = Prefab. "U" (see SMD(SLIP-1) to (SLIP-3))
IF REQUIRED
1EXT or 2EXT = Number of Extensions (see SMD(SLIP-1) to (SLIP-3), (TWT))
BM = Extruded Wind Beam (see SMD(SLIP-1) to (SLIP-3))
WC = 1.12 #/ft Wing Channel (see SMD(SLIP-1) to (SLIP-3))
EXAL = Extruded Aluminum Sign Panels (see SMD(SLIP-3))

No more than 2 sign posts should be located within a 7 ft. circle.



TYPICAL SIGN ATTACHMENT DETAIL

Single Signs




Bolts used to mount sign panels to the clamp are 5/16-18 UNC galvanized square head with nut, nylon washer, flat washer and lock washer. The bolt length is 1 inch for aluminum.

When two sign clamps are used to mount signs back-to-back, use a 5/16-18 UNC galvanized hex head per ASTM A307 with nut and helical-spring lock washer. The approximate bolt lengths for various post sizes and sign clamp types are given in the table at right. The bolt length may need to be adjusted depending upon field conditions.

Sign clamps may be either the specific size clamp or the universal clamp.


REQUIRED CLEARANCE FOR BREAKAWAY SUPPORT




To avoid vehicle undercarriage snagging, any substantial remains of a breakaway support, when it is broken away, should not project more than 4 inches above a 60-inch chord (i.e., typical space between wheel paths).

SIGN LOCATION

PAVED SHOULDERS



BEHIND BARRIER




BEHIND GUARDRAIL

**Sign clearance based on distance required for proper guard rail or concrete barrier performance.

RESTRICTED RIGHT-OF-WAY

(When 6 ft. min. is not possible.)




Right-of-way restrictions may be created by rocks, water, vegetation, forest, buildings, a narrow island, or other factors.


In situations where a lateral restriction prevents the minimum horizontal clearance from the edge of the travel lane, signs should be placed as far from the travel lane as practical.

*** Post may be shorter if protected by guardrail or if Engineer determines the post could not be hit due to extreme slope.

T-INTERSECTION



When this sign is needed at the end of a two-lane, two way roadway, the right edge of the sign should be in line with the centerline of the roadway. Place as close to ROW as practical.



* Signs shall be mounted using the following condition that results in the greatest sign elevation:

- (1) a minimum of 7 to a maximum of 7.5 feet above the edge of the travel lane or
- (2) a minimum of 7 to a maximum of 7.5 feet above the grade at the base of the support when sign is installed on the backslope.

The maximum values may be increased when directed by the Engineer.

See the Traffic Operations Division website for detailed drawings of sign clamps, Triangular Slipbase System components and Wedge Anchor System components.

The website address is:
<http://www.txdot.gov/publications/traffic.htm>


Texas Department of Transportation
Traffic Operations Division

SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS GENERAL NOTES & DETAILS

SMD(GEN) -08

© TxDOT July 2002	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
-	-	-	-	-	ABBOT RD
DIST	COUNTY				SHEET NO.
-	BEXAR				67

TRIANGULAR SLIPBASE INSTALLATION GENERAL REQUIREMENTS



NOTE

There are various devices approved for the Triangular Slipbase System. Please reference the Material Producer List for approved slip base systems. http://www.txdot.gov/business/producer_list.htm The devices shall be installed per manufacturers' recommendations. Installation procedures shall be provided to the Engineer by Contractor.

GENERAL NOTES:

1. Slip base shall be permanently marked to indicate manufacturer. Method, design, and location of marking are subject to approval of the TxDOT Traffic Standards Engineer.
2. Material used as post with this system shall conform to the following specifications:
 - 10 BWG Tubing (2.875" outside diameter)
 - 0.134" nominal wall thickness
 - Seamless or electric-resistance welded steel tubing or pipe
 - Steel shall be HSLAS Gr 55 per ASTM A1011 or ASTM A1008
 - Other steels may be used if they meet the following:
 - 55,000 PSI minimum yield strength
 - 70,000 PSI minimum tensile strength
 - 20% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.122" to 0.138"
 - Outside diameter (uncoated) shall be within the range of 2.867" to 2.883"
 - Galvanization per ASTM A123 or ASTM A653 G210. For precoated steel tubing (ASTM A653), recoat tube outside diameter weld seam by metallizing with zinc wire per ASTM B833.
 - Schedule 80 Pipe (2.875" outside diameter)
 - 0.276" nominal wall thickness
 - Steel tubing per ASTM A500 Gr C
 - Other seamless or electric-resistance welded steel tubing or pipe with equivalent outside diameter and wall thickness may be used if they meet the following:
 - 46,000 PSI minimum yield strength
 - 62,000 PSI minimum tensile strength
 - 21% minimum elongation in 2"
 - Wall thickness (uncoated) shall be within the range of 0.248" to 0.304"
 - Outside diameter (uncoated) shall be within the range of 2.855" to 2.895"
 - Galvanization per ASTM A123
3. See the Traffic Operations Division website for detailed drawings of sign clamps and Texas Universal Triangular Slipbase System components. The website address is:
<http://www.txdot.gov/publications/traffic.htm>
4. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.

ASSEMBLY PROCEDURE


Foundat

1. Prepare 12-inch diameter by 42-inch deep hole. If solid rock is encountered, the depth of the foundation may be reduced such that it is embedded a minimum of 18 inches into the solid rock.
2. The Engineer may permit batches of concrete less than 2 cubic yards to be mixed with a portable, motor-driven concrete mixer. For small placements less than 0.5 cubic yards, hand mixing in a suitable container may be allowed by Engineer. Concrete shall be Class A.
3. Push the pipe end of the slip base stub into the center of the concrete. Rotate the stub back and forth while pushing it down into the concrete to assure good contact between the concrete and stub. Continue to work the stub into the concrete until it is between 2 to 4 inches above the ground.
4. Plumb the stub. Allow a minimum of 4 days to set, unless otherwise directed by the Engineer.
5. The triangular slipbase system is multidirectional and is designed to release when struck from any direction.

Support


1. Cut support so that the bottom of the sign will be 7 to 7.5 feet above the edge of the travelway (i.e., edge of the closest lane) when slip plate is below the edge of pavement or 7 to 7.5 feet above slip plate when the slip plate is above the edge of the travelway. The cut shall be plumb and straight.
2. Attach sign to support using connections shown. When multiple signs are installed on the same support, ensure the minimum clearance between each sign is maintained. See SMD(SLIP-2) for clearances based on sign types.

CONCRETE ANCHOR




SM BD SGN ASSM TY XXXXXX(X) SB (X-XXXX)

Concrete anchor consists of 5/8" diameter stud bolt with UNC series bolt threads on the upper end. Heavy hex nut per ASTM A563, and hardened washer per ASTM F436. The stud bolt shall have a minimum yield and ultimate tensile strength of 50 and 75 KSI, respectively. Nuts, bolts and washers shall be galvanized per Item 445, "Galvanizing." Adhesive type anchors shall have stud bolts installed with Type III epoxy per DMS-6100, "Epoxies and Adhesives." Adhesive anchors may be loaded after adequate epoxy cure time per the manufacturer's recommendations. Top of bolt shall extend at least flush with top of the nut when installed. The anchor, when installed in 4000 psi normal-weight concrete with a 5 1/2" minimum embedment, shall have a minimum allowable tension and shear of 3900 and 3100 psi, respectively.




DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by the TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for incorrect results or damages resulting from its use.


DATE:




SM RD SGN ASSM TY XXXXX(1)XX(P)




SM RD SGN ASSM TY XXXXX(1)XX(T)




SM RD SGN ASSM TY XXXXX(1)XX(U)




SM RD SGN ASSM TY XXXXX(1)XX(U)



SM RD SGN ASSM TY S80(1)XX(U-1EXT)





SM RD SGN ASSM TY S80(1)XX(U-2EXT)




SM RD SGN ASSM TY XXXXX(2)XX(P)

All dimensions are in English unless detailed otherwise.


SM RD SGN ASSM TY XXXXX(1)XX(T)
(* - See Note 12)




Detail A



Detail B




Detail C



Detail D

FRICITION CAP DETAIL



Rolled Crimp to engage pipe O.D.

Pipe O.D.
.025" ± .010"

Friction caps may be manufactured from hot rolled or cold rolled steel sheets. The minimum sheet metal thickness shall be 24 gauge for all cap sizes.

The rim edges shall be reasonably straight and smooth. Caps shall be sized and formed in such a manner as to produce a drive-on friction fit and have no tendency to rock when seated on the pipe. The depth shall be sufficient to give positive protection against entrance of rainwater. They shall be free of sharp creases or indentations and show no evidence of metal fracture.

Caps shall have an electrodeposited coating of zinc in accordance with the requirements of ASTM B633 Class FE/ZN 8.

GENERAL NOTES:

1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA

10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF
2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
10. Additional route markers may be added vertically, provided the total sign area does not exceed the maximum allowable amount per Note 1.
11. Additional sign clamp required on the "T-bracket" post for 24 inch height signs. Place the clamp 3 inches above bottom of sign when possible.
12. Post open ends shall be fitted with Friction Caps.
13. Sign blanks shall be the sizes and shapes shown on the plans.


REQUIRED SUPPORT	
	SIGN DESCRIPTION
Regulatory	SUPPORT TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	60-inch YIELD sign (R1-2) TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	48x16-inch ONE-WAY sign (R6-1) TY 10BWG(1)XX(T) TY 10BWG(1)XX(P-BM)
	36x48, 48x36, and 48x48-inch signs TY 10BWG(1)XX(T)
	48x60-inch signs TY S80(1)XX(T)
	48x48-inch signs (diamond or square) TY 10BWG(1)XX(T)
	48x60-inch signs TY S80(1)XX(T)
	48-inch Advance School X-ing sign (S1-1) TY 10BWG(1)XX(T)
	48-inch School X-ing sign (S2-1) TY 10BWG(1)XX(T)
Warning	Large Arrow sign (W1-6 & W1-7) TY 10BWG(1)XX(T)

 Texas Department of Transportation
Traffic Operations Division


SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD(SLIP-2)-08


© TxDOT July 2002	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		-	-	-	ABBOT RD
		DIST	COUNTY	SHEET NO.	
		-	BEXAR	69	




SM RD SGN ASSM TY XXXXX(1)XX(T-2EXT)
(* - See Note 12)





SM RD SGN ASSM TY XXXXX(1)XX(U-XX)



SM RD SGN ASSM TY XXXXX(1)XX(U-XX)



EXTRUDED ALUMINUM SIGN WITH T BRACKET




Splices shall only be allowed behind the sign substrate.

GENERAL NOTES:

1. SIGN SUPPORT # OF POSTS MAX. SIGN AREA



10 BWG	1	16 SF
10 BWG	2	32 SF
Sch 80	1	32 SF
Sch 80	2	64 SF
2. The Engineer may require that a Schedule 80 post be used in place of a 10 BWG where a sign height is abnormally high due to a fill slope.
3. Sign supports shall not be spliced except where shown. Sign support posts shall not be spliced.
4. Aluminum sign blanks shall conform to Departmental Material Specifications DMS-7110 and shall have the following minimum thicknesses: 0.080 for signs less than 7.5 sq. ft., 0.100 for signs 7.5 to 15 sq. ft., and 0.125 for signs greater than 15 sq. ft.
5. Signs that require specific supports due to reasons in addition to windloading are indicated on the "REQUIRED SUPPORT" table on this sheet.
6. For horizontal rectangular signs fabricated from flat aluminum, T-brackets are used for signs 24 inches or less in height. U-brackets are used for signs of greater height.
7. When two triangular slipbase supports are used to support a single sign, they shall not be "rigidly" connected to each other except through the sign panel. This will allow each support to act independently when impacted by an errant vehicle.
8. Wing channel shall meet ASTM A 1011 SS Gr 50 and be galvanized per ASTM A 123.
9. Excess pipe, wing channel, or windbeam shall be cut off so that it does not extend beyond the sign panel (i.e., excess support shall not be visible when the sign is viewed from the front.) Repair galvanized coating at cut support ends per Item 445, "Galvanizing."
10. Sign blanks shall be the sizes and shapes shown on the plans.
11. Additional sign clamp required on the "T-bracket" post for 24 inch high signs. Place the clamp 3 inches above bottom of sign when possible.
12. Post open ends shall be fitted with Friction Caps.




SM RD SGN ASSM TY S80(2)XX(P-EXAL)

* Additional stiffener placed at approximate center of signs when sign width is greater than 10'.

6" panel should be placed at the top of sign for proper mounting.



Extruded Aluminum Sign With T Bracket



3/8" x 4 1/2" square head bolt, nut, flat washer and lock washer per ASTM A307 galvanized per Item 445, "Galvanizing."

Detail E

REQUIRED SUPPORT		
	SIGN DESCRIPTION	SUPPORT
Regulatory	48-inch STOP sign (R1-1)	TY 10BWG(1)XX(T)
	TY 10BWG(1)XX(P-BM)	TY 10BWG(1)XX(T)
	60-inch YIELD sign (R1-2)	TY 10BWG(1)XX(T)
	TY 10BWG(1)XX(P-BM)	TY 10BWG(1)XX(T)
	48x16-inch ONE-WAY sign (R6-1)	TY 10BWG(1)XX(T)
	TY 10BWG(1)XX(P-BM)	TY 10BWG(1)XX(T)
	36x48, 48x36, and 48x48-inch signs	TY 10BWG(1)XX(T)
	48x60-inch signs	TY S80(1)XX(T)
Warning	48x48-inch signs (diamond or square)	TY 10BWG(1)XX(T)
	48x60-inch signs	TY S80(1)XX(T)
	48-inch Advance School X-ing sign (S1-1)	TY 10BWG(1)XX(T)
	48-inch School X-ing sign (S2-1)	TY 10BWG(1)XX(T)
	Large Arrow sign (W1-6 & W1-7)	TY 10BWG(1)XX(T)

Texas Department of Transportation
Traffic Operations Division

SIGN MOUNTING DETAILS SMALL ROADSIDE SIGNS TRIANGULAR SLIPBASE SYSTEM

SMD(SLIP-3)-08

© TxDOT July 2002	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	
9-08	REVISIONS	CONT	SECT	JOB	HIGHWAY
		-	-	-	ABBOT RD
		DIST	COUNTY	SHEET NO.	
		-	BEXAR	70	

OBJECT MARKER - BID ITEM DESCRIPTIONS

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

ed by the "Texas Engineering Practice Act". No warranty of any
use whatsoever. TxDOT assumes no responsibility for the convers
er incorrect results or damages resulting from its use.

PAYMENT	INSTL = Installation
	REPLC = Replacement
TYPE OF OBJECT MARKER	
1, 2, 3, or 4	
NUMBER OF REFLECTORS OR DIRECTION	
X = 3-Size 2 reflector units (Type 2 only)	
Y = 1-Size 3 reflector unit (Type 2 only)	
Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only)	
L = Left Side (Type 3 Object Marker only)	
R = Right Side (Type 3 Object Marker only)	
C = Center (Type 3 Object Marker only)	
TYPE OF POST	
WC = Wing Channel Post	
WFLX = White Flexible Post	
YFLX = Yellow Flexible Post	
TWT = Thin Walled Tubing	
TYPE OF MOUNT	
GND = Ground Embedded (driveable or set in concrete)	
SRF = Surface Mount	
WAS = Wedge Anchor Steel	
WAP = Wedge Anchor Plastic	
IDENTIFICATION	
LL = Low Speed, Low Impact	
HH = High Speed, High Impact	

OBJECT MARKER DEFINITION

Devices used to mark obstructions within or adjacent to the roadway. (See TMUTCD - Chapter 2C, WARNING SIGNS AND OBJECT MARKERS.)










XXXXXX OM ASSM (OM-XX)(XXXXXX)XXXXXX(XX)									
PAYMENT		Type 1 (OM-1) Type 2 (OM-2) Type 3 (OM-3) Type 4 (OM-4)							
INSL = Installation REPLC = Replacement		OM-1	OM-2X	OM-2Y	OM-2Z	OM-3L	OM-3R	OM-3C	OM-4
TYPE OF OBJECT MARKER 1, 2, 3, or 4									
NUMBER OF REFLECTORS OR DIRECTION X = 3-Size 2 reflector units (Type 2 only) Y = 1-Size 3 reflector unit (Type 2 only) Z = 3-Size 1 or 1-Size 4 reflector unit(s) (Type 2 only) L = Left Side (Type 3 Object Marker only) R = Right Side (Type 3 Object Marker only) C = Center (Type 3 Object Marker only)		3-Size 2 reflector units	1-Size 3 reflector unit	1-Size 4 reflector unit or 3-Size 1 reflector units					
TYPE OF POST WC = Wing Channel Post WFLX = White Flexible Post YFLX = Yellow Flexible Post TWT = Thin Walled Tubing									
TYPE OF MOUNT GND = Ground Embedded (drivable or set in concrete) SRF = Surface Mount WAS = Wedge Anchor Steel WAP = Wedge Anchor Plastic									
IDENTIFICATION LL = Low Speed, Low Impact HH = High Speed, High Impact		Yellow - Type B _{FL} or C _{FL} sheeting	White and Yellow - Type B or C sheeting			Alternating Acrylic Black and Retroreflective Yellow - Type B _{FL} or C _{FL} sheeting	Red - Type B _{FL} or C _{FL} sheeting		
DIRECTION [if required] BI = Bi-Directional		TWT	WC	WC	WFLX, YFLX	TWT, WFLX	TWT		
		WAS, WAP	GNDLL	GNDLL	GNDLL, GNDHH, SRFLL, SRFHH	WAS, WAP, GNDLL, GNDHH, SRFLL, SRFHH	WAS, WAP		




REFLECTOR UNIT DIMENSIONS FOR OBJECT MARKERS

DISCLAIMER:

35 AM Martinez Creek Estates FM 13464 - Design Plan Set(08 Traffic Signing)Standards\dom2-25 (1).dxf

DATE: 1/5/2026 8:29:35 AM
FILE: P:\DESIGN PROJECTS\Martine

REFLECTOR UNIT DIMENSIONS FOR OBJECT MARKERS				POST TYPE AND SUPPORT FOUNDATION DETAILS																																				
DEVICE	SIZE 1	SIZE 2	SIZE 3	SIZE 4	WING CHANNEL (WC)		FLEXIBLE POSTS (YFLX, WFLX)		WEDGE ANCHOR SYSTEMS																															
					GND	GND	SRF	WAS	WAP																															
NOTE	1. Size 1 and 4 - Direct applied reflective sheeting for use on flexible post (flx). 2. Size 2 and 3 - For use on wing channel (wc) post only. Use approved metal, plastic, or fiberglass backplate with $\frac{1}{64}$ " mounting holes.					 NOTES <ol style="list-style-type: none"> 1. Embedded Wing Channel (WC) post option may be used for Type 2 object markers and delineators only. 2. 1.12 lbs/ft steel per ASTM A 1011 SS Gr. 50, or ASTM A499. 																																		
TYPES 1, 3, AND 4 OBJECT MARKERS TYPICAL INSTALLATION 		TYPE 2 OBJECT MARKERS TYPICAL INSTALLATION 		 NOTES <ol style="list-style-type: none"> 1. See "Flexible Delineator and Object Marker Posts" Material Producer List for approved devices. 2. Install per manufacturer's recommendations. 3. Post length may vary to meet field conditions. 					NOTE <ol style="list-style-type: none"> 1. Install per manufacturer's recommendations. 																															
				GENERAL NOTES <ol style="list-style-type: none"> 1. Where a restriction prevents consistent placement from the pavement edge, place the affected object markers in line with the innermost edge of the obstruction. 2. When Type 2 object markers are more than 8'-0" from the edge of the pavement, it may not be possible to maintain a height of approximately 4'-0". If this is the case, place the object marker as close to the recommended height as possible. 3. Install all object markers in accordance with the manufacturer's recommendation. 4. Diagonal stripes on Type 3 object markers shall slope down toward the intended travel lane. 5. Object marker substrates shall be 0.080" aluminum sign blank and conform to ASTM B-209 Alloy 6061-T6 or an approved alternative. 					 Texas Department of Transportation																															
 Traffic Safety Division Standard		DEPARTMENTAL MATERIAL SPECIFICATIONS		<table border="1"> <tr> <td>FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES)</td> <td>DMS-4400</td> </tr> <tr> <td>SIGN FACE MATERIALS</td> <td>DMS-8300</td> </tr> <tr> <td>DELINATEATORS, OBJECT MARKERS AND BARRIER REFLECTORS</td> <td>DMS-8600</td> </tr> </table>					FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES)	DMS-4400	SIGN FACE MATERIALS	DMS-8300	DELINATEATORS, OBJECT MARKERS AND BARRIER REFLECTORS	DMS-8600	OBJECT MARKER MATERIAL DESCRIPTION & INSTALLATION																									
FLEXIBLE DELINEATOR & OBJECT MARKER POSTS (EMBEDDED & SURFACE MOUNT TYPES)	DMS-4400																																							
SIGN FACE MATERIALS	DMS-8300																																							
DELINATEATORS, OBJECT MARKERS AND BARRIER REFLECTORS	DMS-8600																																							
		D & OM(2)-25		<table border="1"> <tr> <td>FILE: dom2-25.dgn</td> <td>DN: TxDOT</td> <td>CK: TxDOT</td> <td>DW: TxDOT</td> <td>CK: TxDOT</td> </tr> <tr> <td>© TxDOT</td> <td>May 2025</td> <td>CONT</td> <td>SECT</td> <td>JOB</td> </tr> <tr> <td colspan="5" style="text-align: center;">REVISIONS</td> </tr> <tr> <td>8-04</td> <td>5-25</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3-15</td> <td></td> <td></td> <td></td> <td>ABBOT RD</td> </tr> <tr> <td>7-20</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>					FILE: dom2-25.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT	© TxDOT	May 2025	CONT	SECT	JOB	REVISIONS					8-04	5-25	-	-	-	3-15				ABBOT RD	7-20					71	
FILE: dom2-25.dgn	DN: TxDOT	CK: TxDOT	DW: TxDOT	CK: TxDOT																																				
© TxDOT	May 2025	CONT	SECT	JOB																																				
REVISIONS																																								
8-04	5-25	-	-	-																																				
3-15				ABBOT RD																																				
7-20																																								



OBJECT MARKER MATERIAL DESCRIPTION & INSTALLATION


D & OM(2)-25

DELINERATOR AND OBJECT MARKER APPLICATION AND SPACING		
CONDITION	REQUIRED TREATMENT	MINIMUM SPACING
Fwy./Exp. Tangent	RPMs	See PM and FPM standard sheets
Fwy./Exp. Curve	Single delineators on right side	See delineator spacing table
Fwy/Exp.Ramp	Single delineators on at least one side of ramp (should be on outside of curves) (see Detail 4a on D&OM(4))	100 feet on ramp tangents Use delineator spacing table for ramp curves ("straightway spacing" does not apply to ramp curves)
Acceleration/Deceleration Lane	Double delineators (see Detail 4a on D&OM(4))	100 feet (See Detail 4a on D & OM(4))
Truck Escape Ramp	Single red delineators on both sides	50 feet
Bridge Rail (steel or concrete) and Metal Beam Guard Fence	Bi-Directional Delineators when undivided with one lane each direction Single Delineators when multiple lanes each direction	Equal spacing (100' max) but not less than 3 delineators
Concrete Traffic Barrier (CTB) or Steel Traffic Barrier	Barrier reflectors matching the color of the edge line	Equal spacing 100' max
Cable Barrier	Reflectors matching the color of the edge line Bi-Directional Delineators when within clearzone	Every 5th cable barrier post (up to 100' max)
Cable Barrier Terminus / Impact Head	Object marker on end	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM(6)
Guard Rail Terminus / Impact Head	Divided highway - Object marker on approach end Undivided 2-lane highways - Object marker on approach and departure end	Requires reflective sheeting provided by manufacturer per D & OM (VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM(5) and D & OM(6)
Bridges with no Approach Rail	Type 3 Object Marker (OM-3) at end of rail and 3 single delineators approaching rail	See D & OM(5)
Reduced Width Approaches to Bridge Rail	Type 2 and Type 3 Object Markers (OM-3) and 3 single delineators approaching bridge	Requires reflective sheeting provided by manufacturer per D & OM(VIA) or a Type 3 Object Marker (OM-3) in front of the terminal end See D & OM(5)
Culverts without MBGF	Type 2 Object Markers	See Detail 2 on D & OM(4)
Crossovers	Double yellow delineators and RPMs	See Detail 1 on D & OM(4)
Pavement Narrowing (lane merge) on Freeways/Expressway	Single delineators adjacent to affected lane for full length of transition	100 feet

MINIMUM WARNING DEVICES AT CURVES WITH ADVISORY SPEEDS		
Amount by which Advisory Speed is less than Posted Speed	Turn/Curve Advisory Speed	
	Turn (30 MPH or less)	Curve (35 MPH or more)
5 MPH	• RPMs and Pavement Markings	
10 MPH	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs and Pavement Markings	
15 MPH	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs, Pavement Markings, and Delineators; or • RPMs, Pavement Markings, and One Direction Large Arrow sign(s)	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs, Pavement Markings, and Chevrons; or • RPMs, Pavement Markings, and One Direction Large Arrow sign(s) where geometric conditions or roadside obstacles prevent the installation of chevrons
20 MPH	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs, Pavement Markings, and Chevrons; or • RPMs, Pavement Markings, and One Direction Large Arrow sign(s) where geometric conditions or roadside obstacles prevent the installation of chevrons	
25 MPH or more	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs, Pavement Markings, and Chevrons; or • RPMs, Pavement Markings, and One Direction Large Arrow sign(s) where geometric conditions or roadside obstacles prevent the installation of chevrons	• Advance Horizontal Alignment Warning Sign with Advisory Speed Plaque; and • RPMs, Pavement Markings, and Chevrons

NOTE
A roadway is considered to have pavement markings when either a center line, edge lines, or both are present. A roadway is considered to have RPMs when they are used to supplement centerline pavement markings.

SUGGESTED SPACING FOR DELINEATORS ON HORIZONTAL CURVES




DETAIL 3a

LEGEND

	Delineator
	Bi-directional Delineator
	Sign

NOTE
ONE DIRECTION LARGE ARROW (W1-6) sign should be located at approximately and perpendicular to the extension of the centerline of the tangent section of approach lane.

GENERAL NOTES				
1. Unless otherwise indicated, the delineator or barrier reflector color shall conform to the color of the pavement edge line on the side of the road where the delineators or barrier reflectors are placed.				
2. Barrier reflectors may be used to replace required delineators.				
3. Single red delineators may be mounted on the back side of delineator posts for wrong way driver applications.				
SUGGESTED SPACING FOR CHEVRONS ON HORIZONTAL CURVES				
 <p>NOTE * Supplemental chevrons, at least one pair, may be installed along the tangent at a distance of B. Adverse curve alignment is a factor in determining if supplemental chevrons are needed.</p>				
DELINERATOR AND CHEVRON SPACING		DELINERATOR AND CHEVRON SPACING		
WHEN DEGREE OF CURVE OR RADIUS IS KNOWN		WHEN DEGREE OF CURVE OR RADIUS IS NOT KNOWN		
Degree of Curve	FEET			
	Radius of Curve	Spacing in Curve	Spacing in Straightaway	Chevron Spacing in Curve
		A	2A	B
1	5730	225	450	—
2	2865	160	320	—
3	1910	130	260	200
4	1433	110	220	160
5	1146	100	200	160
6	955	90	180	160
7	819	85	170	160
8	716	75	150	160
9	637	75	150	120
10	573	70	140	120
11	521	65	130	120
12	478	60	120	120
13	441	60	120	120
14	409	55	110	80
15	382	55	110	80
16	358	55	110	80
19	302	50	100	80
23	249	40	80	80
29	198	35	70	40
38	151	30	60	40
57	101	20	40	40

If the degree of curve is not known, delineator spacing may be determined based on the Advisory Speed of the curve. Use the delineator curve spacing for each Advisory Speed (MPH).


DETAIL 3b

LEGEND


	Delineator
	Bi-directional Delineator
	Sign

NOTE
Curve delineator approach and departure spacing should include 3 delineators spaced at 2A. This spacing should be used during design preparation or when the degree of curve is known.


FREWAY DELINEATION FOR RAMPS AND ACCELERATION / DECELERATION LANES




CROSSOVERS



TYPICAL APPLICATION OF DEAD END BARRICADE



TYPICAL DEAD END BARRICADE INSTALLATION



NOTES

1. Barricade striping shall be red and white reflective sheeting for all permanent road closures.
2. Barricade striping is red and white sloping toward the center of the roadway.
3. Type 3 Barricade Supports should be anchored to soil or pavement as described in the Compliant Work Zone Traffic Control Devices list (CWZTCD).

LEGEND	
	Delineator
	Double delineator
	OM-2
	Sign
	Raised Pavement Marker (RPM)
	Traffic Flow




Traffic Safety Division Standard


DELINERATOR & OBJECT MARKER PLACEMENT DETAILS

D & OM(4)-25


FILE:	dom4-25.dgn	DN:	TxDOT	CK:	TxDOT	DW:	TxDOT	CK:	TxDOT
© TxDOT	May 2025	CONT	SECT	JOB		HIGHWAY			
		-	-	-					ABBOT RD
8-04	5-25								
3-15									
7-20									
		COUNTY							
		SHEET NO.							
		-							
		BEXAR							
		73							



**EDGE LINE AND LANE LINES
ONE-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**




**TYPICAL TWO-LANE, TWO-WAY PAVEMENT
MARKINGS THROUGH INTERSECTIONS**




**CENTERLINE AND LANE LINES
FOUR LANE TWO-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**

* 2" minimum for restripe projects when approved by the Engineer. ** 8" minimum for restripe projects when approved by the Engineer.

9"** min. - 10" typ.
(18" max. for traveled way greater than 48' only)




**TYPICAL MULTI-LANE, TWO-WAY PAVEMENT
MARKINGS THROUGH INTERSECTIONS**




**TWO LANE TWO-WAY ROADWAY
WITH OR WITHOUT SHOULDERS**


* 2" minimum for restripe projects when approved by the Engineer.



DETAIL "B"



YIELD LINES



FOUR LANE DIVIDED ROADWAY CROSSOVERS

NOTES

- Where divided highways are separated by median widths at the median opening itself of 30 feet or more, median openings shall be signed as two separate intersections. Each median opening has two width measurements, with one measurement for each approach. The narrow median width will be the controlling width to determine if signs are required. Yield signs are the typical intersection control. Stop signs and stop bars are optional as determined by the Engineer.
- Install median striping (double yellow centerlines and stop lines/yield lines) when a 50' or greater median centerline can be placed. Stop lines shall only be used with stop signs. Yield lines shall only be used with yield signs.
- Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer.

For posted speed on road being marked equal to or less than 40 MPH.


GENERAL NOTES

- Edge line striping shall be as shown in the plans or as directed by the Engineer. The edge line should not be placed less than 6 inches from the edge of pavement. This distance may vary due to pavement raveling or other conditions. Edge lines are not required in curb and gutter sections of roadways.
- The traveled way includes only that portion of the roadway used for vehicular travel. It does not include the parking lanes, sidewalks, berms and shoulders. The traveled ways shall be measured from the center of edge line to the center of edge line of a two lane roadway.

MATERIAL SPECIFICATIONS

PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



NOTE: Traveled way is exclusive of shoulder widths. Refer to General Note 2 for additional details.

GUIDE FOR PLACEMENT OF STOP LINES, EDGE LINE & CENTERLINE


Based on Traveled Way and Pavement Widths for Undivided Roadways

Texas Department of Transportation		Traffic Safety Division Standard
TYPICAL STANDARD PAVEMENT MARKINGS		
FILE: pm1-22.dgn	DN:	CK: DW: CK:
© TxDOT December 2022	CONT:	SECT: JOB HIGHWAY
REVISIONS	-	-
11-78 8-00 6-20	DIST:	COUNTY SHEET NO.
8-95 3-03 12-22	-	BEXAR 74
5-00 2-12		


REFLECTIVE RAISED PAVEMENT MARKERS FOR VEHICLE POSITIONING GUIDANCE

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose. TxDOT assumes no responsibility for damages resulting from its use.


DATE: 1/5/2026 8:29:38 AM
FILE: P:\DESIGN_PROJECTS\Martinez Creek Estates_FM_1346\4 - Design\Plan Set\Right-of-Way\Standard\2022\Signs



CENTERLINE FOR ALL TWO LANE TWO-WAY ROADWAYS




CENTERLINE & LANE LINES FOR FOUR LANE TWO-WAY ROADWAYS




DETAIL "A"

DETAIL "B"

DETAIL "C"




CENTERLINE AND LANE LINES FOR TWO-WAY LEFT TURN LANE



LANE LINES FOR ONE-WAY ROADWAY (NON-FREEWAY FACILITIES)

Raised pavement markers Type II-C-R shall have clear face toward normal traffic and red face toward wrong-way traffic.
See Note 3.



REFLECTORIZED PROFILE PATTERN DETAIL

USING REFLECTIVE PROFILE PAVEMENT MARKINGS

6" EDGE LINE, 6" CENTERLINE
OR 6" LANE LINE

GENERAL NOTES


1. All raised pavement markers placed along broken lines shall be placed in line with and midway between the stripes.
2. On concrete pavements, the raised pavement markers should be placed to one side of the longitudinal joints.
3. Use raised pavement marker Type I-C with undivided roadways, flush medians, and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.

NOTES


1. Edge lines should typically be 6" wide and the materials shall be specified in the plans.
2. Profile markings shall not be placed on roadways with a posted speed limit of 45 MPH or less.

MATERIAL SPECIFICATIONS	
PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240


All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



Type I (Top View)



Type II (Top View)



SECTION A


RAISED PAVEMENT MARKERS



POSITION GUIDANCE USING RAISED MARKERS REFLECTORIZED PROFILE MARKINGS PM(2)-22

FILE:	DN:	CK:	DW:	CK:
pm2-22.dgn				
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
	-	-	-	ABBOT RD
	REVISIONS			
4-77 8-00 6-20				
4-92 2-10 12-22				
5-00 2-12	DIST	COUNTY	SHEET NO.	
	-	BEXAR		75

DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose. TxDOT assumes no responsibility for the conversion of any right-of-way or roadway design to any other standard or practice. TxDOT does not assume responsibility for damages resulting from its use.




NOTES


1. Lane reduction pavement markings are used where the number of through lanes is reduced because of narrowing of the roadway or because of a section of on-street parking in what would otherwise be a through lane. For Texas Super 2 Passing Lanes, see TS2(PL) standard sheets.
2. On divided highways, an additional RIGHT LANE ENDS (W9-1R) sign may be installed in the median aligned with the W9-1R sign on the right side of the highway.
3. Lane reduction arrows are required for speeds of 45 mph or greater. An optional third lane reduction arrow may be added based on engineering judgement. If used, the optional third lane reduction arrow should be centered between the first and last lane reduction arrows.
4. For lane reductions on Freeways and Expressways, signing shall conform to the TxDOT Freeway Signing Handbook.

ADVANCED WARNING SIGN DISTANCE (D)		
Posted Speed	D (ft)	L (ft)
30 MPH	460	$L = \frac{WS^2}{60}$
35 MPH	565	
40 MPH	670	
45 MPH	775	
50 MPH	885	
55 MPH	990	
60 MPH	1,100	
65 MPH	1,200	
70 MPH	1,250	
75 MPH	1,350	


LANE REDUCTION



TYPICAL TWLTL AT ONE-WAY STREET AND RIGHT TURN AUXILIARY LANE




TYPICAL TWLTL AT TWO-WAY CROSS STREET AND RIGHT TURN LANE DROP




A two-way left-turn (TWLTL) lane-use arrow pavement marking should be used at or just downstream from the beginning of a two-way left-turn lane within a corridor. Repeating the marking after each intersection or dedicated turn bay is not required unless stated elsewhere in the plans.

TYPICAL TRANSITION FOR TWLTL AND DIVIDED HIGHWAY



TYPICAL TWO-LANE ROADWAY INTERSECTION WITH LEFT TURN BAYS



* 2" minimum allowed for restripe projects when approved by the Engineer.

GENERAL NOTES

1. Lane use word and arrow markings shall be used where through lanes approaching an intersection become mandatory turn lanes. Lane use word and arrow markings should be used in auxiliary lanes of substantial length. Lane use arrow markings or word and arrow markings may be used in other lanes and turn bays for emphasis. Details for words and arrows are as shown in the Standard Highway Sign Designs for Texas.
2. When lane-use words and arrow markings are used, two sets of arrows should be used if the length of the bay is greater than 180 feet. When a single lane use arrow or word and arrow marking is used for a short turn lane, it should be located at or near the upstream end of the full-width turn lane.
3. Use raised pavement marker Type I-C with undivided highways, flush medians and two way left turn lanes. Use raised pavement marker Type II-C-R with divided highways and raised medians.
4. Length of turn bays, including taper, deceleration, and storage lengths shall be as shown on the plans or as directed by the Engineer. See Chapter 3 of the Roadway Design Manual for additional information on turning lanes or storage lengths.

MATERIAL SPECIFICATIONS

PAVEMENT MARKERS (REFLECTORIZED)	DMS-4200
EPOXY AND ADHESIVES	DMS-6100
BITUMINOUS ADHESIVE FOR PAVEMENT MARKERS	DMS-6130
TRAFFIC PAINT	DMS-8200
HOT APPLIED THERMOPLASTIC	DMS-8220
PERMANENT PREFABRICATED PAVEMENT MARKINGS	DMS-8240

All pavement marking materials shall meet the required Departmental Material Specifications as specified by the plans.



TWO-WAY LEFT TURN LANES, RURAL LEFT TURN BAYS, AND LANE REDUCTION PAVEMENT MARKINGS PM(3)-22

FILE: pm3-22.dgn	DN:	CK:	DW:	CK:
© TxDOT December 2022	CONT	SECT	JOB	HIGHWAY
	-	-	-	ABBOT RD
REVISIONS	DIST	COUNTY	HEET NO.	
4-98 3-03 6-20	5-00 2-10 12-22	8-00 2-12		BEXAR

STORMWATER POLLUTION PREVENTION PLAN (SWP3):

This SWP3 has been developed in accordance with the TPDES Construction General Permit TXR150000 (CGP). The Texas Department of Transportation (TxDOT) ensures that project specifications include adequate best management practices (BMPs) for this project.

For all projects with soil disturbing activity and for projects that have Environmental, Permits, Issues, and Commitments (EPICs) dependent on stormwater controls and water quality measures TxDOT will maintain a SWP3 with all pertinent records, correspondence, environmental documents, etc. at the project field office, Area Office, or electronically.

This SWP3 is consistent with requirements specified in applicable stormwater plans and the projects environmental permits, issues, and commitments (EPICs). A copy of the CGP is included in Attachment 2.12 of the SWP3 binder.

1.0 SITE/PROJECT DESCRIPTION

1.1 PROJECT CONTROL SECTION JOB (CSJ):

1.2 PROJECT LIMITS:

From: FM 1346 AT ABBOTT RD INTERSECTION
.86 MI NORTH OF ABBOTT RD & FM1346 INTERSECTION
To: ON ABBOTT ROAD

1.3 PROJECT COORDINATES:

BEGIN: (Lat) 29°25'20.61"N, (Long) 98°15'5.41"W

END: (Lat) 29°25' 59.11" N, (Long) 98°14' 40.26" W

1.4 TOTAL PROJECT AREA (Acres): 2.52 ACRES

1.5 TOTAL AREA TO BE DISTURBED (Acres): 1.73 ACRES

1.6 NATURE OF CONSTRUCTION ACTIVITY:

ROADWAY WIDENING/ RECONSTRUCTION, CULVERT

EXTENSION FOR TURN LANES

1.7 MAJOR SOIL TYPES:

Soil Type	Description
MIGUEL-FINE	PERMEABLE LOAMY
WILCO-FINE	PERMEABLE SANDY
WILCO-FINE	PERMEABLE SANDY
HEIDEN-CLAY	IMPERMEABLE CLAYEY
HEIDEN-FERRIS	MODERATELY PERMEABLE CLAYEY
MIGUEL-FINE	PERMEABLE LOAMY
FLORESVILLE-FINE	PERMEABLE SANDY LOAM

1.8 PROJECT SPECIFIC LOCATIONS (PSLs):

PSLs must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. PSLs may be identified during preconstruction meetings or during the construction process. Please choose from the options below:

- PSLs determined during preconstruction meeting
- PSLs determined during construction
- No PSLs planned for construction

Type	Sheet #s

1.10 POTENTIAL POLLUTANTS AND SOURCES:

- Sediment laden stormwater from stormwater conveyance over disturbed area
- Fuels, oils, and lubricants from construction vehicles, equipment, and storage
- Solvents, paints, adhesives, etc. from various construction activities
- Transported soils from offsite vehicle tracking
- Construction debris and waste from various construction activities
- Contaminated water from excavation or dewatering pump-out water
- Sanitary waste from onsite restroom facilities
- Trash from various construction activities/receptacles
- Long-term stockpiles of material and waste
- Discharges from concrete washout activities, runoff from concrete cutting activities, and other concrete related activities.

Other: _____

Other: _____

Other: _____

1.11 RECEIVING WATERS:

Receiving waters must be depicted on the Environmental Layout Sheets in Attachment 1.2 of this SWP3. Include Segment # for receiving waters.

Tributaries	Classified Waterbody

* Add (*) for impaired waterbodies with pollutant in ().

1.12 ROLES AND RESPONSIBILITIES:

- Development of plans and specifications
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Perform SWP3 inspections
- Maintain SWP3 records and update to reflect daily operations
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____

Other: _____

Other: _____

1.13 ROLES AND RESPONSIBILITIES: CONTRACTOR

- Day To Day Operational Control
- Submit Notice of Intent (NOI) to TCEQ (≥5 acres)
- Post Construction Site Notice
- Submit NOI/CSN to local MS4
- Maintain schedule of major construction activities
- Install, maintain and modify BMPs
- Complete and submit Notice of Termination to TCEQ
- Maintain SWP3 records for 3 years
- Other: _____

Other: _____

Other: _____

1.14 LOCAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) OPERATOR COORDINATION:


MS4 Entity

STORMWATER POLLUTION PREVENTION PLAN (SWP3)





Sheet 1 of 2

FED. RD. DIV. NO.	PROJECT NO.	SHEET NO.
	-	77
STATE	STATE DIST.	COUNTY
TEXAS	-	BEXAR
CONT.	SECT.	JOB
-	-	-
HIGHWAY NO.		ABBOT RD



TEMPORARY SEDIMENT CONTROL FENCE



HINGE JOINT KNOT WOVEN MESH (OPTION) DETAIL

Galvanized hinge joint knot woven mesh (12.5 GA.SWG Min.) requires a minimum of five horizontal wires spaced at a maximum of 12 inches apart and all vertical wires spaced at a maximum of 12 inches apart.


SEDIMENT CONTROL FENCE USAGE GUIDELINES

A sediment control fence may be constructed near the downstream perimeter of a disturbed area along a contour to intercept sediment from overland runoff. A 2 year storm frequency may be used to calculate the flow rate to be filtered.

Sediment control fence should be sized to filter a maximum flow through rate of 100 GPM/FT². Sediment control fence is not recommended to control erosion from a drainage area larger than 2 acres.


LEGEND

Sediment Control Fence





GENERAL NOTES

1. Vertical tracking is required on projects where soil distributing activities have occurred unless otherwise approved.
2. Perform vertical tracking on slopes to temporarily stabilize soil.
3. Provide equipment with a track undercarriage capable of producing linear soil impressions measuring a minimum of 12" in length by 2" to 4" in width by 1/2" to 2" in depth.
4. Do not exceed 12" between track impressions.
5. Install continuous linear track impressions where the minimum 12" length impressions are perpendicular to the slope or direction of water flow.




TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES FENCE & VERTICAL TRACKING				Design Division Standard
FILE: ec116	DN: TxDOT	CK: KM	DW: VP	DN/CK: LS
© TxDOT: JULY 2016	CONT	SECT	JOB	HIGHWAY
REVISIONS	-	-	-	ABBOT RD
DIST	COUNTY		SHEET NO.	
	-		BEXAR	79




FILTER DAM AT SEDIMENT TRAP

RFD1 OR RFD2



PROFILE



SECTION C-C

ROCK FILTER DAM USAGE GUIDELINES

Rock Filter Dams should be constructed downstream from disturbed areas to intercept sediment from overland runoff and/or concentrated flow. The dams should be sized to filter a maximum flow through rate of 60 GPM/FT² of cross sectional area. A 2 year storm frequency may be used to calculate the flow rate.


Type 1 (18" high with no wire mesh) (3" to 6" aggregate): Type 1 may be used at the toe of slopes, around inlets, in small ditches, and at dike or swale outlets. This type of dam is recommended to control erosion from a drainage area of 5 acres or less. Type 1 may not be used in concentrated high velocity flows (approximately 8 Ft/Sec or more) in which aggregate wash out may occur. Sandbags may be used at the embedded foundation (4" deep min.) for better filtering efficiency of low flows if called for on the plans or directed by the Engineer.

Type 2 (18" high with wire mesh) (3" to 6" aggregate): Type 2 may be used in ditches and at dike or swale outlets.

Type 3 (36" high with wire mesh) (4" to 8" aggregate): Type 3 may be used in stream flow and should be secured to the stream bed.

Type 4 (Sack gabions) (3" to 6" aggregate): Type 4 May be used in ditches and smaller channels to form an erosion control dam.

Type 5: Provide rock filter dams as shown on plans.



FILTER DAM AT CHANNEL SECTIONS

RFD1 OR RFD2 OR RFD3


GENERAL NOTES

- If shown on the plans or directed by the Engineer, filter dams should be placed near the toe of slopes where erosion is anticipated, upstream and/or downstream at drainage structures, and in roadway ditches and channels to collect sediment.
- Materials (aggregate, wire mesh, sandbags, etc.) shall be as indicated by the specification for "Rock Filter Dams for Erosion and Sedimentation Control".
- The rock filter dam dimensions shall be as indicated on the SW3P plans.
- Side slopes should be 2:1 or flatter. Dams within the safety zone shall have sideslopes of 6:1 or flatter.
- Maintain a minimum of 1' between top of rock filter dam weir and top of embankment for filter dams at sediment traps.
- Filter dams should be embedded a minimum of 4" into existing ground.
- The sediment trap for ponding of sediment laden runoff shall be of the dimensions shown on the plans.
- Rock filter dam types 2 & 3 shall be secured with 20 gauge galvanized woven wire mesh with 1" diameter hexagonal openings. The aggregate shall be placed on the mesh to the height & slopes specified. The mesh shall be folded at the upstream side over the aggregate and tightly secured to itself on the downstream side using wire ties or hog rings. For in stream use, the mesh should be secured or staked to the stream bed prior to aggregate placement.
- Sack Gabions should be staked down with $\frac{3}{4}$ " dia. rebar stakes, and have a double-twisted hexagonal weave with a nominal mesh opening of $2\frac{1}{2}$ " x $3\frac{1}{4}$ "
- Flow outlet should be onto a stabilized area (vegetation, rock, etc.).
- The guidelines shown hereon are suggestions only and may be modified by the Engineer.


PLAN SHEET LEGEND

Type 1 Rock Filter Dam RFD1
Type 2 Rock Filter Dam RFD2
Type 3 Rock Filter Dam RFD3
Type 4 Rock Filter Dam RFD4

Texas Department of Transportation		Design Division Standard
TEMPORARY EROSION, SEDIMENT AND WATER POLLUTION CONTROL MEASURES		
ROCK FILTER DAMS		
EC (2) - 16		
FILE: ec216	DN: TxDOT	CK: KM
© TxDOT: JULY 2016	CONT	SECT
REVISIONS	JOB	HIGHWAY
-	-	-
DIST	COUNTY	Sheet No.
-	BEXAR	80




PLAN VIEW




CONSTRUCTION EXIT (TYPE 1)
ROCK CONSTRUCTION (LONG TERM)

GENERAL NOTES (TYPE 1)

1. The length of the type 1 construction exit shall be as indicated on the plans, but not less than 50'.
2. The coarse aggregate should be open graded with a size of 4" to 8".
3. The approach transitions should be no steeper than 6:1 and constructed as directed by the Engineer.
4. The construction exit foundation course shall be flexible base, bituminous concrete, portland cement concrete or other materials approved by the Engineer.
5. The construction exit shall be graded to allow drainage to a sediment trapping device.
6. The guidelines shown hereon are suggestions only and may be modified by the Engineer.
7. Construct exits with a width of at least 14 ft. for one-way and 20 ft. for two-way traffic for the full width of the exit, or as directed by the engineer.




PLAN VIEW



CONSTRUCTION EXIT (TYPE 2)
TIMBER CONSTRUCTION (LONG TERM)

GENERAL NOTES (TYPE 2)




1. The length of the type 2 construction exit shall be as indicated on the plans, but not less than 50'.
2. The treated timber planks shall be attached to the railroad ties with 1/2"x 6" min. lag bolts. Other fasteners may be used as approved by the Engineer.
3. The treated timber planks shall be #2 grade min., and should be free from large and loose knots.
4. The approach transitions shall be no steeper than 6:1 and constructed as directed by the Engineer.
5. The construction exit foundation course shall be flexible base, bituminous concrete, portland cement concrete or other material as approved by the Engineer.
6. The construction exit should be graded to allow drainage to a sediment trapping device.
7. The guidelines shown hereon are suggestions only and may be modified by the Engineer.
8. Construct exits with a width of at least 14 ft. for one-way and 20 ft. for two-way traffic for the full width of the exit, or as directed by the engineer.






SECTION A-A
CONSTRUCTION EXIT (TYPE 3)
SHORT TERM

GENERAL NOTES (TYPE 3)

1. The length of the type 3 construction exit shall be as shown on the plans, or as directed by the Engineer.
2. The type 3 construction exit may be constructed from open graded crushed stone with a size of two to four inches spread a min. of 4" thick to the limits shown on the plans.
3. The treated timber planks shall be #2 grade min., and should be free from large and loose knots.
4. The guidelines shown hereon are suggestions only and may be modified by the Engineer.












Legacy Engineering Group, PLLC
 7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
 TPE Firm Registration No. 20623

SHEET 2 OF 10

CONT	SECT	JOB	HIGHWAY	DIST	COUNTY	SHEET NO.
XXX	XX	XXX	ABBOTT RD	XXX	BEXAR	83














 **LEGACY**
ENGINEERING GROUP
Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

SHEET 4 OF 10

CONT	SECT	JOB	HIGHWAY	DIST	COUNTY	SHEET NO.
XXX	XX	XXX	ABBOTT RD	XXX	BEXAR	85










Legacy Engineering Group, PLLC
 7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
 TPE Firm Registration No. 20623

SHEET 7 OF 10



CONT	SECT	JOB	HIGHWAY	DIST	COUNTY	SHEET NO.
XXX	XX	XXX	ABBOTT RD	XXX	BEXAR	88





Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

SHEET 8 OF 10

CONT	SECT	JOB	HIGHWAY	DIST	COUNTY	SHEET NO.
XXX	XX	XXX	ABBOTT RD	XXX	BEXAR	89





Legacy Engineering Group, PLLC
7800 W Interstate 10, Ste. 830, San Antonio, Texas 78230, 210.660.1960
TBPE Firm Registration No. 20623

SHEET 10 OF 10

CONT	SECT	JOB	HIGHWAY	DIST	COUNTY	SHEET NO.
XXX	XX	XXX	ABBOTT RD	XXX	BEXAR	91