



Date: April 26, 2023, 4:45 PM - User ID: clodner
File: P:\24\82\13\Design\Civil\DW248213.dwg


THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016, CAPCO, Digital Globe, Texas Orthomography Program, USDA Farm Service Agency.




INDEX MAP
NOT-TO-SCALE




WATER/DRAIN CROSSING DETAIL "A"
NOT TO SCALE




WATER/DRAIN CROSSING DETAIL "A1"
NOT TO SCALE




WATER/DRAIN CROSSING DETAIL "A2"
NOT TO SCALE



TYPICAL SANITARY
SEWER/WATER CROSSING DETAIL
NOT-TO-SCALE



LOCATION MAP
NOT-TO-SCALE



WATER LEGEND

PROJECT LIMITS	---
UNDERGROUND FIBER OPTIC	---
OVERHEAD ELECTRICAL	---
ASBESTOS CEMENT PIPE	---
EXISTING WATER	---
EXISTING SEWER	---
PROPOSED SEWER	---
PROPOSED WATER	---
PROPOSED 3/4" SINGLE SERVICE WITH 5/8" METER	---
PROPOSED 1" DUAL SERVICE WITH 5/8" METER	---
3/4" SINGLE IRRIGATION SERVICE WITH 5/8" METER	---
JOINT RESTRAINT	---
VEHICULAR NON-ACCESS EASEMENT	---
CLEAR VISION EASEMENT	---
EXISTING TREES TO REMAIN UNDISTURBED	---
EXISTING TREES TO BE REMOVED	---

FIRE FLOW NOTE:

IN AN EFFORT TO MEET THE CITY OF SAN ANTONIO'S FIRE FLOW REQUIREMENTS FOR THE PROPOSED RESIDENTIAL DEVELOPMENT, THE PUBLIC WATER MAIN SYSTEM HAS BEEN DESIGNED FOR A MINIMUM FIRE FLOW DEMAND OF 1500 GPM AT 25 PSI RESIDUAL PRESSURE. THE FIRE FLOW REQUIREMENTS FOR INDIVIDUAL STRUCTURES WILL BE REVIEWED DURING THE BUILDING PERMIT PROCESS IN ACCORDANCE WITH THE PROCEDURES SET FORTH BY THE CITY OF SAN ANTONIO DIRECTOR OF DEVELOPMENT SERVICES DEPARTMENT AND THE SAN ANTONIO FIRE DEPARTMENT FIRE MARSHAL.

GENERAL NOTES:

- FIRE HYDRANT SHALL BE LOCATED BEHIND SIDEWALK IN ACCORDANCE WITH THE FIRE HYDRANT INSTALLATION DETAIL (SEE SHEET C4.04-C4.06).
- CONTRACTOR TO FIELD VERIFY EXACT LOCATIONS OF ALL EXISTING UTILITIES HORIZONTALLY AND VERTICALLY PRIOR TO CONSTRUCTION.
- ALL VALVES SHALL READ "OPEN RIGHT".
- ALL FIRE HYDRANTS SHALL BE PAINTED APPROPRIATE ECSUD COLORS.
- FIRE HYDRANTS AND VALVE BOXES TO BE RAISED TO THE PROPOSED TOP OF PAVEMENT OR GROUND ELEVATION.
- ALL WATER PIPE TO BE C-900, DR-18, CLASS 150 UNLESS OTHERWISE NOTED.
- PER TCEQ TAC 217.53(d)(7)(B), WASTEWATER MAIN ENCASEMENT AT W/W/CULVERT CROSSING IS REQUIRED. ENCASEMENT TO FOLLOW TCEQ TAC 217.53 (d)(7)(D).
- PER TCEQ TAC 290.44(e)(4)(B)(i), IF EXISTING WASTEWATER MAIN AT W/W/CULVERT CROSSING IS DISTURBED OR SHOWS SIGNS OF LEAKING DURING CONSTRUCTION THE EXISTING MAIN MAY REQUIRE ENCASEMENT AND REPLACEMENT WITH PRESSURE-RATED PIPE.

TRENCH EXCAVATION SAFETY PROTECTION:

CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/ GEOTECHNICAL/ SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND /OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH AS A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE PRESENCE AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

JOINT RESTRAINT NOTE:



CONTRACTOR SHALL INSTALL RETAINER GLANDS AT ALL FITTINGS AND PROVIDE JOINT RESTRAINING HARNESSES OR FIELD LOCK GASKETS AT ALL JOINTS WITHIN THE LENGTH SHOWN. CONTRACTOR SHALL INSURE THAT ALL TEES, BENDS, VALVES, ETC. HAVE A MINIMUM OF 5 FT OF PIPE WITH NO JOINTS ON EACH SIDE OF THE FITTING. JOINT RESTRAINTS AND RETAINER GLANDS SHALL BE CALCULATED BY EAST CENTRAL SPECIAL UTILITY DISTRICT (ECSUD) APPROVED PROGRAMS. THERE WILL BE NO SEPARATE PAY ITEM FOR RETAINER GLANDS AND OTHER JOINT RESTRAINING HARNESSES AND GASKETS, BUT SHALL BE SUBSIDIARY TO THE UNIT COST PER LINEAL FOOT OF PIPE INSTALLED.

ROW PERMIT NOTE:

A BEXAR COUNTY PERMIT MUST BE OBTAINED BEFORE WORKING IN BEXAR COUNTY RIGHTS-OF-WAY.


THE CONTRACTOR SHALL BE RESPONSIBLE FOR MEETING 98% COMPACTION ON ALL TRENCH BACKFILL AND PAYING FOR THE TESTS TO BE PERFORMED BY A THIRD PARTY. COMPACTION TESTS WILL BE DONE AT ONE LOCATION POINT RANDOMLY SELECTED OR AS INDICATED BY ECSUD INSPECTOR/TEST ADMINISTER, PER EACH 12-INCH LOOSE LIFT PER 400 LINEAL FEET AT A MINIMUM. THIS PROJECT WILL NOT BE ACCEPTED AND FINALIZED BY ECSUD WITHOUT THIS REQUIREMENT BEING MET AND VERIFIED BY PROVIDING ALL NECESSARY DOCUMENTED TEST RESULTS.

NO.	REVISION	DATE



STONE GARDEN - UNIT 4A BEXAR COUNTY, TEXAS OVERALL WATER DISTRIBUTION PLAN

PLAT NO.	24-11800158
JOB NO.	12482-13
DATE	DECEMBER 2024
DESIGNER	CL
CHECKED	DW
DRAWN	JR
SHEET	C4.00



DATE	
NO.	
REVISION	

Dan Wright
Dan Wright


PAPE-DAWSON ENGINEERS

2000 NW LOOP 410 | SAN ANTONIO, TX 78213 | 210.375.9000
TEXAS ENGINEERING FIRM #470 | TEXAS SURVEYING FIRM #1008800

STONE GARDEN - UNIT 4A
BEXAR COUNTY, TEXAS




OVERALL WATER DISTRIBUTION PLAN

PLAT NO.	24-11800158
JOB NO.	12482-13
DATE	DECEMBER 2024
DESIGNER	CL
CHECKED	DW
DRAWN	JR
SHEET	C4.01



THIS DOCUMENT HAS BEEN PRODUCED FROM MATERIAL THAT WAS STORED AND/OR TRANSMITTED ELECTRONICALLY AND MAY HAVE BEEN INADVERTENTLY ALTERED. RELY ONLY ON FINAL HARDCOPY MATERIALS BEARING THE CONSULTANT'S ORIGINAL SIGNATURE AND SEAL. AERIAL IMAGERY PROVIDED BY GOOGLE® UNLESS OTHERWISE NOTED. Imagery © 2016 CAPCD/Digital Globe, Texas OrthoImagery Program, USDA Farm Service Agency.

Date: April 26, 2023, 4:47 PM - User ID: cldhnr
File: P:\24\82\13\Design\Civil\DW248213.dwg



FIRE FLOW NOTE:
IN AN EFFORT TO MEET THE CITY OF SAN ANTONIO'S FIRE FLOW REQUIREMENTS FOR THE PROPOSED RESIDENTIAL DEVELOPMENT, THE PUBLIC WATER MAIN SYSTEM HAS BEEN DESIGNED FOR A MINIMUM FIRE FLOW DEMAND OF 1500 GPM AT 25 PSI RESIDUAL PRESSURE. THE FIRE FLOW REQUIREMENTS FOR INDIVIDUAL STRUCTURES WILL BE REVIEWED DURING THE BUILDING PERMIT PROCESS IN ACCORDANCE WITH THE PROCEDURES SET FORTH BY THE CITY OF SAN ANTONIO DIRECTOR OF DEVELOPMENT SERVICES DEPARTMENT AND THE SAN ANTONIO FIRE DEPARTMENT FIRE MARSHAL.

GENERAL NOTES:
1. FIRE HYDRANT SHALL BE LOCATED BEHIND SIDEWALK IN ACCORDANCE WITH THE FIRE HYDRANT INSTALLATION DETAIL (SEE SHEET C4.04-C4.06)
2. CONTRACTOR TO FIELD VERIFY EXACT LOCATIONS OF ALL EXISTING UTILITIES HORIZONTALLY AND VERTICALLY PRIOR TO CONSTRUCTION.
3. ALL VALVES SHALL READ "OPEN RIGHT"
4. ALL FIRE HYDRANTS SHALL BE PAINTED APPROPRIATE ECSD COLORS.
5. FIRE HYDRANTS AND VALVE BOXES TO BE RAISED TO THE PROPOSED TOP OF PAVEMENT OR GROUND ELEVATION.
6. ALL WATER PIPE TO BE C-900, DR-18, CLASS 150 UNLESS OTHERWISE NOTED.
7. PER TCEQ TAC 217.53(d)(7)(B), WASTEWATER MAIN ENCASEMENT AT W/WW/CULVERT CROSSING IS REQUIRED. ENCASEMENT TO FOLLOW TCEQ TAC 217.53 (d)(7)(D).
8. PER TCEQ TAC 290.44(e)(4)(B)(i), IF EXISTING WASTEWATER MAIN AT W/WW/CULVERT CROSSING IS DISTURBED OR SHOWS SIGNS OF LEAKING DURING CONSTRUCTION THE EXISTING MAIN MAY REQUIRE ENCASEMENT AND REPLACEMENT WITH PRESSURE-RATED PIPE.

TRENCH EXCAVATION SAFETY PROTECTION:
CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR STRUCTURAL DESIGN/ GEOTECHNICAL/ SAFETY/EQUIPMENT CONSULTANT, IF ANY, SHALL REVIEW THESE PLANS AND ANY AVAILABLE GEOTECHNICAL INFORMATION AND THE ANTICIPATED INSTALLATION SITES WITHIN THE PROJECT WORK AREA IN ORDER TO IMPLEMENT CONTRACTOR'S TRENCH EXCAVATION SAFETY PROTECTION SYSTEMS, PROGRAMS AND/OR PROCEDURES FOR THE PROJECT DESCRIBED IN THE CONTRACT DOCUMENTS. THE CONTRACTOR'S IMPLEMENTATION OF THESE SYSTEMS, PROGRAMS AND/OR PROCEDURES SHALL PROVIDE FOR ADEQUATE TRENCH EXCAVATION SAFETY PROTECTION THAT COMPLY WITH A MINIMUM, OSHA STANDARDS FOR TRENCH EXCAVATIONS. SPECIFICALLY, CONTRACTOR AND/OR CONTRACTOR'S INDEPENDENTLY RETAINED EMPLOYEE OR SAFETY CONSULTANT SHALL IMPLEMENT A TRENCH SAFETY PROGRAM IN ACCORDANCE WITH OSHA STANDARDS GOVERNING THE DESIGN, CONSTRUCTION AND ACTIVITIES OF INDIVIDUALS WORKING IN AND AROUND TRENCH EXCAVATION.

JOINT RESTRAINT NOTE:
CONTRACTOR SHALL INSTALL RETAINER GLANDS AT ALL FITTINGS AND PROVIDE JOINT RESTRAINING HARNESSES OR FIELD LOCK GASKETS AT ALL JOINTS WITHIN THE LENGTH SHOWN. CONTRACTOR SHALL INSURE THAT ALL TEES, BENDS, VALVES, ETC. HAVE A MINIMUM OF 5 FT OF PIPE WITH NO JOINTS ON EACH SIDE OF THE FITTING. JOINT RESTRAINTS AND RETAINER GLANDS SHALL BE CALCULATED BY EAST CENTRAL SPECIAL UTILITY DISTRICT (ECSD) APPROVED PROGRAMS. THERE WILL BE NO SEPARATE PAY ITEM FOR RETAINER GLANDS AND OTHER JOINT RESTRAINING HARNESSES AND GASKETS, BUT SHALL BE SUBSIDIARY TO THE UNIT COST PER LINEAL FOOT OF PIPE INSTALLED.

ROW PERMIT NOTE:
A BEXAR COUNTY PERMIT MUST BE OBTAINED BEFORE WORKING IN BEXAR COUNTY RIGHTS-OF-WAY.
THE CONTRACTOR SHALL BE RESPONSIBLE FOR MEETING 98% COMPACTION ON ALL TRENCH BACKFILL AND PAYING FOR THE TESTS TO BE PERFORMED BY A THIRD PARTY. COMPACTION TESTS WILL BE DONE AT ONE LOCATION POINT RANDOMLY SELECTED OR AS INDICATED BY ECSD INSPECTOR/TEST ADMINISTER, PER EACH 12-INCH LOOSE LOFT PER 400 LINEAL FEET AT A MINIMUM. THIS PROJECT WILL NOT BE ACCEPTED AND FINALIZED BY ECSD WITHOUT THIS REQUIREMENT. BEING MET AND VERIFIED BY PROVIDING ALL NECESSARY DOCUMENTED TEST RESULTS.

DATE
NO. REVISION

**PAPE-DAWSON
ENGINEERS**
2000 NW LOOP 410 | SAN ANTONIO, TX 78213 | 210.375.9000
TEXAS ENGINEERING FIRM #470 | TEXAS SURVEYING FIRM #1008800

PLAT NO. 24-11800158
JOB NO. 12482-13
DATE DECEMBER 2024
DESIGNER CL
CHECKED DW DRAWN JR
SHEET C4.03

STONE GARDEN - UNIT 4A
BEXAR COUNTY, TEXAS
OVERALL WATER DISTRIBUTION PLAN